EVRide ? People, fleet & rentals

Identity, station inventory, reservations and handovers

users

7 columns

COLUMN	TYPE	KEYS / RELATIONSHIP
id	BIGINT	PK
name	VARCHAR(100)	?
email	VARCHAR(100)	UQ
password	VARCHAR(255)	?
role	VARCHAR(20)	?
status	VARCHAR(20)	?
created_at	TIMESTAMPTZ	?

stations

9 columns

COLUMN	TYPE	KEYS / RELATIONSHIP
id	BIGINT	PK
name	VARCHAR(120)	?
address	TEXT	?
latitude	NUMERIC(9, 6)	?
longitude	NUMERIC(9, 6)	?
capacity	INTEGER	?
opens_at	TIME WITHOUT TIME ZONE	NULL
closes_at	TIME WITHOUT TIME ZONE	NULL
status	VARCHAR(20)	?

vehicles

9 columns

COLUMN	TYPE	KEYS / RELATIONSHIP
id	BIGINT	PK
current_station_id	BIGINT	FK?stations.id P1 ? NULL
name	VARCHAR(100)	?
type	VARCHAR(50)	?
battery_percent	INTEGER	?
status	VARCHAR(20)	?
daily_price	NUMERIC(12, 2)	?
deposit_amount	NUMERIC(12, 2)	?
created_at	TIMESTAMPTZ	?

user_documents

8 columns

COLUMN	TYPE	KEYS / RELATIONSHIP
id	BIGINT	PK
user_id	BIGINT	FK?users.id P1
document_type	VARCHAR(30)	?
document_number	VARCHAR(50)	?
image_front_url	TEXT	?
image_back_url	TEXT	NULL
verified_status	VARCHAR(20)	?
created_at	TIMESTAMPTZ	?

wallets

6 columns

COLUMN	TYPE	KEYS / RELATIONSHIP
id	BIGINT	PK
user_id	BIGINT	FK?users.id P1 ? UQ
balance	NUMERIC(12, 2)	?
status	VARCHAR(20)	?
created_at	TIMESTAMPTZ	?
updated_at	TIMESTAMPTZ	?

rentals

11 columns

COLUMN	TYPE	KEYS / RELATIONSHIP
id	BIGINT	PK
customer_id	BIGINT	FK?users.id P1
vehicle_id	BIGINT	FK?vehicles.id P1
pickup_station_id	BIGINT	FK?stations.id P1
actual_return_station_id	BIGINT	FK?stations.id P1 ? NULL
expires_at	TIMESTAMPTZ	?
actual_start_time	TIMESTAMPTZ	NULL
actual_end_time	TIMESTAMPTZ	NULL
status	VARCHAR(20)	?
total_price	NUMERIC(12, 2)	NULL
created_at	TIMESTAMPTZ	?

handovers

8 columns

COLUMN	TYPE	KEYS / RELATIONSHIP
id	BIGINT	PK
rental_id	BIGINT	FK?rentals.id P1
staff_id	BIGINT	FK?users.id P1
kind	VARCHAR(10)	?
time	TIMESTAMPTZ	?
battery_percent	INTEGER	?
note	TEXT	NULL
created_at	TIMESTAMPTZ	?

rental_reviews

5 columns

COLUMN	TYPE	KEYS / RELATIONSHIP
id	BIGINT	PK
rental_id	BIGINT	FK?rentals.id P1 ? UQ
rating	INTEGER	?
comment	TEXT	NULL
created_at	TIMESTAMPTZ	?

RELATIONSHIPS

Solid arrows connect tables on this page. FK labels name the exact target and its page.
Page 4 lists every relationship explicitly, including links between pages.

EVRide ? Pricing, promotions & settlement

Financial records and the rental terms snapshot

invoices

5 columns

COLUMN	TYPE	KEYS / RELATIONSHIP
id	BIGINT	PK
rental_id	BIGINT	FK?rentals.id P1 ? UQ
total_amount	NUMERIC(12, 2)	?
status	VARCHAR(20)	?
created_at	TIMESTAMPTZ	?

transactions

9 columns

COLUMN	TYPE	KEYS / RELATIONSHIP
id	BIGINT	PK
rental_id	BIGINT	FK?rentals.id P1
invoice_id	BIGINT	FK?invoices.id P2 ? NULL
actor_id	BIGINT	FK?users.id P1
idempotency_record_id	BIGINT	FK?idempotency_records.id P3 ? NULL
amount	NUMERIC(12, 2)	?
kind	VARCHAR(20)	?
status	VARCHAR(20)	?
created_at	TIMESTAMPTZ	?

wallet_transactions

11 columns

COLUMN	TYPE	KEYS / RELATIONSHIP
id	BIGINT	PK
wallet_id	BIGINT	FK?wallets.id P1
rental_id	BIGINT	FK?rentals.id P1 ? NULL
transaction_id	BIGINT	FK?transactions.id P2 ? UQ ? NULL
idempotency_record_id	BIGINT	FK?idempotency_records.id P3 ? NULL
amount	NUMERIC(12, 2)	?
type	VARCHAR(30)	?
balance_before	NUMERIC(12, 2)	?
balance_after	NUMERIC(12, 2)	?
status	VARCHAR(20)	?
created_at	TIMESTAMPTZ	?

promotions

10 columns

COLUMN	TYPE	KEYS / RELATIONSHIP
id	BIGINT	PK
code	VARCHAR(50)	UQ
description	TEXT	NULL
discount_percent	INTEGER	NULL
max_discount_amount	NUMERIC(12, 2)	NULL
min_rental_amount	NUMERIC(12, 2)	NULL
start_date	TIMESTAMPTZ	?
end_date	TIMESTAMPTZ	?
status	VARCHAR(20)	?
created_at	TIMESTAMPTZ	?

user_promotions

5 columns

COLUMN	TYPE	KEYS / RELATIONSHIP
id	BIGINT	PK
user_id	BIGINT	FK?users.id P1
promotion_id	BIGINT	FK?promotions.id P2
is_used	BOOLEAN	?
used_at	TIMESTAMPTZ	NULL

rental_pricing_snapshots

14 columns

COLUMN	TYPE	KEYS / RELATIONSHIP
id	BIGINT	PK
rental_id	BIGINT	FK?rentals.id P1 ? UQ
vehicle_name	VARCHAR(100)	?
vehicle_type	VARCHAR(50)	?
daily_price	NUMERIC(12, 2)	?
pricing_policy_version	VARCHAR(64)	?
pricing_policy_snapshot	JSONB	?
deposit_amount	NUMERIC(12, 2)	?
promotion_id	BIGINT	FK?promotions.id P2 ? NULL
promotion_code	VARCHAR(50)	NULL
discount_percent	INTEGER	NULL
max_discount_amount	NUMERIC(12, 2)	NULL
discount_amount	NUMERIC(12, 2)	?
created_at	TIMESTAMPTZ	?

RELATIONSHIPS

Solid arrows connect tables on this page. FK labels name the exact target and its page.
Page 4 lists every relationship explicitly, including links between pages.

EVRide ? Reliability, audit & tracking

Durable request replay, audit trail and operational support data

support_tickets

8 columns

COLUMN	TYPE	KEYS / RELATIONSHIP
id	BIGINT	PK
rental_id	BIGINT	FK?rentals.id P1
created_by	BIGINT	FK?users.id P1
assigned_to	BIGINT	FK?users.id P1 ? NULL
title	VARCHAR(200)	?
description	TEXT	?
status	VARCHAR(20)	?
created_at	TIMESTAMPTZ	?

gps_points

5 columns

COLUMN	TYPE	KEYS / RELATIONSHIP
id	BIGINT	PK
rental_id	BIGINT	FK?rentals.id P1
latitude	NUMERIC(9, 6)	?
longitude	NUMERIC(9, 6)	?
recorded_at	TIMESTAMPTZ	?

idempotency_records

12 columns

COLUMN	TYPE	KEYS / RELATIONSHIP
id	BIGINT	PK
actor_id	BIGINT	FK?users.id P1
http_method	VARCHAR(10)	?
request_path	VARCHAR(500)	?
idempotency_key	VARCHAR(128)	?
request_hash	VARCHAR(64)	?
state	VARCHAR(20)	?
response_status	INTEGER	NULL
response_body	JSONB	NULL
created_at	TIMESTAMPTZ	?
expires_at	TIMESTAMPTZ	?
completed_at	TIMESTAMPTZ	NULL

audit_logs

9 columns

COLUMN	TYPE	KEYS / RELATIONSHIP
id	BIGINT	PK
actor_id	BIGINT	FK?users.id P1 ? NULL
action	VARCHAR(100)	?
resource_type	VARCHAR(100)	?
resource_id	VARCHAR(100)	NULL
request_id	VARCHAR(64)	NULL
before_data	JSONB	NULL
after_data	JSONB	NULL
created_at	TIMESTAMPTZ	?

RELATIONSHIPS

Solid arrows connect tables on this page. FK labels name the exact target and its page.
Page 4 lists every relationship explicitly, including links between pages.

EVRide ? Complete relationship index

All 29 foreign-key relationships from ORM metadata ? source and target page shown

FOREIGN KEY LINKS ? 1

user_documents.user_id	P1	
? users.id	P1	
wallets.user_id	P1	
? users.id	P1	
vehicles.current_station_id	P1	
? stations.id	P1	
rentals.actual_return_station_id	P1	
? stations.id	P1	
rentals.customer_id	P1	
? users.id	P1	
rentals.pickup_station_id	P1	
? stations.id	P1	
rentals.vehicle_id	P1	
? vehicles.id	P1	
handovers.rental_id	P1	
? rentals.id	P1	
handovers.staff_id	P1	
? users.id	P1	
rental_reviews.rental_id	P1	
? rentals.id	P1	

FOREIGN KEY LINKS ? 2

invoices.rental_id	P1	
? rentals.id	P2	
transactions.actor_id	P1	
? users.id	P2	
transactions.idempotency_record_id	P3	
? idempotency_records.id	P2	
transactions.invoice_id	P2	
? invoices.id	P2	
transactions.rental_id	P1	
? rentals.id	P2	
wallet_transactions.idempotency_record_id	P3	
? idempotency_records.id	P2	
wallet_transactions.rental_id	P1	
? rentals.id	P2	
wallet_transactions.transaction_id	P2	
? transactions.id	P2	
wallet_transactions.wallet_id	P1	
? wallets.id	P2	
user_promotions.promotion_id	P2	
? promotions.id	P2	

FOREIGN KEY LINKS ? 3

user_promotions.user_id	P1	
? users.id	P2	
support_tickets.assigned_to	P1	
? users.id	P3	
support_tickets.created_by	P1	
? users.id	P3	
support_tickets.rental_id	P1	
? rentals.id	P3	
gps_points.rental_id	P1	
? rentals.id	P3	
idempotency_records.actor_id	P1	
? users.id	P3	
rental_pricing_snapshots.promotion_id	P2	
? promotions.id	P2	
rental_pricing_snapshots.rental_id	P1	
? rentals.id	P2	
audit_logs.actor_id	P1	
? users.id	P3	

P1 People, fleet & rentals ? P2 Pricing, promotions & settlement ? P3 Reliability, audit & tracking

Arrows follow SQLAlchemy foreign-key declarations; every reference includes the target table.column.