EVRide | Entity Relationship Diagram

PostgreSQL ? 15 tables ? Reservation expiry: created_at + 30 minutes ? Source: database.sql

users — 7 columns

id	BIGINT	PK
name	VARCHAR(100)	
email	VARCHAR(100)	UQ
password	VARCHAR(255)	
role	VARCHAR(20)	
status	VARCHAR(20)	
created_at	TIMESTAMPTZ	

user_documents — 8 columns

id	BIGINT	PK
user_id	BIGINT	FK users.id
document_type	VARCHAR(30)	
document_number	VARCHAR(50)	
image_front_url	TEXT	
image_back_url	TEXT	NULL
verified_status	VARCHAR(20)	
created_at	TIMESTAMPTZ	

stations — 9 columns

id	BIGINT	PK
name	VARCHAR(120)	
address	TEXT	
latitude	NUMERIC(9,6)	
longitude	NUMERIC(9,6)	
capacity	INT	
opens_at	TIME	NULL
closes_at	TIME	NULL
status	VARCHAR(20)	

vehicles — 9 columns

id	BIGINT	PK
current_station_id	BIGINT	FK stations.id / NULL
name	VARCHAR(100)	
type	VARCHAR(50)	
battery_percent	INT	
status	VARCHAR(20)	
daily_price	NUMERIC(12,2)	
deposit_amount	NUMERIC(12,2)	
created_at	TIMESTAMPTZ	

wallets — 6 columns

id	BIGINT	PK
user_id	BIGINT	FK users.id / UQ
balance	NUMERIC(12,2)	
status	VARCHAR(20)	
created_at	TIMESTAMPTZ	
updated_at	TIMESTAMPTZ	

rentals — 11 columns

id	BIGINT	PK
customer_id	BIGINT	FK users.id
vehicle_id	BIGINT	FK vehicles.id
pickup_station_id	BIGINT	FK stations.id
actual_return_station_id	BIGINT	FK stations.id / NULL
expires_at	TIMESTAMPTZ	
actual_start_time	TIMESTAMPTZ	NULL
actual_end_time	TIMESTAMPTZ	NULL
status	VARCHAR(20)	
total_price	NUMERIC(12,2)	NULL
created_at	TIMESTAMPTZ	

handovers — 8 columns

id	BIGINT	PK
rental_id	BIGINT	FK rentals.id
staff_id	BIGINT	FK users.id
kind	VARCHAR(10)	
time	TIMESTAMPTZ	
battery_percent	INT	
note	TEXT	NULL
created_at	TIMESTAMPTZ	

rental_reviews — 5 columns

id	BIGINT	PK
rental_id	BIGINT	FK rentals.id / UQ
rating	INT	
comment	TEXT	NULL
created_at	TIMESTAMPTZ	

promotions — 10 columns

id	BIGINT	PK
code	VARCHAR(50)	UQ
description	TEXT	NULL
discount_percent	INT	NULL
max_discount_amount	NUMERIC(12,2)	NULL
min_rental_amount	NUMERIC(12,2)	NULL
start_date	TIMESTAMPTZ	
end_date	TIMESTAMPTZ	
status	VARCHAR(20)	
created_at	TIMESTAMPTZ	

user_promotions — 5 columns

id	BIGINT	PK
user_id	BIGINT	FK users.id
promotion_id	BIGINT	FK promotions.id
is_used	BOOLEAN	
used_at	TIMESTAMPTZ	NULL

invoices — 5 columns

id	BIGINT	PK
rental_id	BIGINT	FK rentals.id / UQ
total_amount	NUMERIC(12,2)	
status	VARCHAR(20)	
created_at	TIMESTAMPTZ	

transactions — 8 columns

id	BIGINT	PK
rental_id	BIGINT	FK rentals.id
invoice_id	BIGINT	FK invoices.id / NULL
actor_id	BIGINT	FK users.id
amount	NUMERIC(12,2)	
kind	VARCHAR(20)	
status	VARCHAR(20)	
created_at	TIMESTAMPTZ	

wallet_transactions — 9 columns

id	BIGINT	PK
wallet_id	BIGINT	FK wallets.id
rental_id	BIGINT	FK rentals.id / NULL
amount	NUMERIC(12,2)	
type	VARCHAR(30)	
balance_before	NUMERIC(12,2)	
balance_after	NUMERIC(12,2)	
status	VARCHAR(20)	
created_at	TIMESTAMPTZ	

support_tickets — 8 columns

id	BIGINT	PK
rental_id	BIGINT	FK rentals.id
created_by	BIGINT	FK users.id
assigned_to	BIGINT	FK users.id / NULL
title	VARCHAR(200)	
description	TEXT	
status	VARCHAR(20)	
created_at	TIMESTAMPTZ	

gps_points — 5 columns

id	BIGINT	PK
rental_id	BIGINT	FK rentals.id
latitude	NUMERIC(9,6)	
longitude	NUMERIC(9,6)	
recorded_at	TIMESTAMPTZ	

PK primary key ? FK foreign key (arrows point to referenced table) ? UQ unique ? NULL nullable