

Vim

Verbs

- **d** delete (keep visual mode)
- **c** change (move to in insert mode)
- **>** ident
- **v** visally select
- **control + v** vertical visal selection
- **y** yank

Noun

- **b** back
- **i** inner
- **2j** two lines down
- **"** quotes
- **p** paragraph
- **s** sentence
- ex.: **dip** delete inner paragraph, inner make vim remembe the object type
- **w** move forward
- **b** move backward
- **e** move end of word
- **f** find a character forward
- **F** find a character backward
- **t** find a character forward and stop before
- **T** find a character backward and stop before
- **;** next searched item
- **\$** move to the end of a line
- **0** move to the beginning of a line
- **^** fist non-blank character of line
- **{}** move between paragraph
- **()** move between sentence
- **g;** last edited place
- **gg** beginning of file
- **G** end of file
- **H** jump to top of screen
- **M** jump to middle of screen
- **L** jump to middle of screen
- **zz** posiciona o cursor no meio da tela
- **z.** posiciona o cursor no meio da tela
- **zt** posiciona o cursor no início da tela (top)
- **zb** posiciona o cursor no fim da tela (bottom)
- **control d** down half screen
- **control u** up half screen
- **control f** down all screen
- **control b** down all screen

Registers

- **@** ou **"** in normal mode
- **control r** in insert mode

Macros

- **q[letter]** enter recording mode
- **q** finished the macro
- **@[letter]** is the address the recorded macro
- **10@w** execute the macro 10 times

Windows

- **ctrl-w +** mair verticalmente
- **ctrl-w -** menor verticalmente
- **ctrl-w <** mais a esquerda
- **ctrl-w >** mais a direita
- **ctrl-w ctrl-x** inverter as janelas entre direita e esquerda, cima e baixo
- **ctrl-w ctrl-r** inverter as janelas entre direita e esquerda, cima e baixo
- **ctrl-w k** posiciona as janelas horizontalmente divididas
- **ctrl-w h** posicionada as janelas ver verticalmente

Fuzzy Finder fzf

- **;** file here
- **;**h file home
- **;**w file ~/Wiki
- **;**b buffers
- **;**l lines
- **;**L LinesB
- **control x** resultado em buffer horizontal
- **control v** resultado em buffer vertical
- **control t** resultado em tab

Search

- **/** search top do down
- **?** search down do top
- **:vimgrep palavra-buscada *.qmd**
- **:vimgrep /palavra_buscada/g *.qmd** adiciona resultados para quickfix
- **:vimgrep palavra_buscada %** busca no arquivo atual
- **:vimgrep /foo/ foo.txt bar.txt gar.txt** buscar em vários arquivos
- **:vimgrep /palavra_buscada/j *.Rmd** don't jump to the first match
- **:vimgrep /palavra_buscada/ 'find . -type f'**
- **:control r** insere a última query buscada

Others

- **:Tabularize /,** arquivos separados por vírgula
- **:Tabularize \t** arquivos separados por tab
- **:Goyo** no distraction

Plugins

jalvesaq/Nvim-R

- Start/Close
 - \rf Start R (default)
 - \rq Close R (no save)
 - :RStop Stop (interrupt) R
- Send
 - \aa File
 - \bb Block (cur)
 - \bd Block (cur, down)
 - \cc Chunk (cur)
 - \cd Chunk (cur, down)
 - \ch Chunk (from first to here)
 - \ff Function (cur)
 - \fd Function (cur and down)
 - \ss Selection
 - \sd Selection (and down)
 - \m{motion} Send motion region
 - \pp Paragraph
 - \pd Paragraph (and down)
 - \l Line
 - \d Line (and down)
 - \q Line (and new one)
 - \r<Left> Left part of line (cur)
 - \r<Right> Right part of line (cur)
 - \o Line (evaluate and insert the output as comment)
 - \su All lines above the current one
- Command
 - \rh Help
 - \rl List space
 - \rr Clear console
 - \rm Remove objects and clear console
 - \rp Print (cur)
 - \rn Names (cur)
 - \rt Structure (cur)
 - \qr Quarto render (cur file)
 - \qp Quarto preview (cur file)
 - \qs Quarto stop preview (all files)
- Edit
 - \gn Go (next R chunk)
 - \gN Go (previous R chunk)
- Object Browser
 - \ro Open/Close
 - \r= Expand (all lists)
 - \r- Collapse (all lists)
 - Enter Toggle (cur)

vimcmdline: Python and Julia

- \s to start the interpreter.
- space to send the current line to the interpreter.
- \space to send the current line to the interpreter and keep the cursor.
- \q to send the quit command to the interpreter.
- space to send a selection of text to the interpreter.
- \p to send from the line to the end of paragraph.
- \b to send block of code between the two closest marks.
- \f to send the entire file to the interpreter.
- \m to send the text in the following motion to the interpreter. For example
- \miw would send the selected word.

tpope/vim-commentary

- gc{motion} Comment or uncomment lines that {motion} moves over.
- ex:
 - gc4j comentar da 4 linhas abaixo
 - gcip comentar o parágrafo
 - :4,8Commentary comentar das linhas 4 a 8

tpope/vim-surround

- c chance
- d delete
- y you surround

"Hello *world!"	ds"	Hello world!
(123+4*56)/2	ds)	123+456/2
<div>Yo!*</div>	dst	Yo!
"Hello *world!"	cs"'	'Hello world!'
"Hello *world!"	cs"<q>	<q>Hello world!</q>
(123+4*56)/2	cs)]	[123+456]/2
(123+4*56)/2	cs)[[123+456]/2
<div>Yo!*</div>	cst<p>	<p>Yo!</p>
Hello w*orld!	ysiw)	Hello (world)!
Hello w*orld!	yssB	{Hello world!}

Obs.: * é a posição do cursor na sentença

tpope/vim-unimpaired quickfix

-]q is :cnext
- [q is :cprevious
-]a is :next
- [b is :bprevious

neoclide/coc.nvim

- ;y yank
- ;x explorer
- ;a Show all diagnostics
- ;e Manage extensions.
- ;c Show commands.
- ;p Resume latest coc list.

Git

- `stsewd/fzf-checkout.vim`
 - `gB` branches
 - * `enter` checkout
 - * `alt-enter` tack
 - * `control b` create
 - * `control d` delete
 - * `control e` merge
 - * `control r` rebase
 - `gC` commit history
 - `gT` tags
- `tpope/vim-fugitive`
 - `:Git <commando>`
 - `:G <commando>`
 - ex.: `:G init | :G add . | :G commit | :G remove --cached`
- `:G <enter>` Stage alternativas
 - `s` Stage (add) the file or hunk under the cursor.
 - `u` Unstage (reset) the file or hunk under the cursor.
 - `-` Stage or unstage the file or hunk under the cursor.
 - `U` Unstage everything.
 - `X` Discard the change under the cursor. This uses `checkout` or `clean`.
 - `=` Toggle an inline diff of the file under the cursor.
 - `>` Insert an inline diff of the file under the cursor.
 - `<` Remove the inline diff of the file under the cursor.
 - `gI` Open `.git/info/exclude` in a split and add the file under the cursor. Use a count to open `.gitignore`.
- `:G <enter>` Commit maps
 - `cc` Create a commit.
 - `ca` Amend the last commit and edit the message.
 - `ce` Amend the last commit without editing the message.
 - `cw` Reword the last commit.
 - `cvc` Create a commit with `-v`.
 - `cva` Amend the last commit with `-v`
 - `c?` Show this help.
- `:G <enter>` Diff maps
 - `dd` Perform a `|:Gdiffsplit|` on the file under the cursor.
 - `dv` Perform a `|:Gvdiffsplit|` on the file under the cursor.
 - `ds` Perform a `|:Ghdiffsplit|` on the file under the cursor.
 - `dh`
 - `dq` Close all but one diff buffer, and `|:diffoff|!` the last one.
 - `d?` Show this help
- Comandos especiais:
 - `:Gwrite`
 - `:Gread`
 - `:GRemove`
 - `:GDelete`
 - `:GMove`
 - `:GRename`
 - `:GBrowse`
 - `:Gclog`
 - `:Gdiffsplit`
 - `:Ghdiffsplit`
 - `:Gvdiffsplit`
 - `:Gdiffsplit`
 - `:Git blame`
 - `:Git merge`
 - `:Git_mergetool`

i3wm

Navigation

- **super** **u** focus parent
- **super** **d** focus child
- **super** **f** fullscreen toggle

Change container layout (stacked, tabbed, default)

- **super** **w** tabbed
- **super** **e** stacking
- **super** **r** toggle split

SetNext container as: split[h|v], stab, stack

- **super** **-** horizontal
- **super** **** vertical
- **super** **shift t** tabbed
- **super** **shift s** stacking

Float

- **super** **m** floating toggle
- **super** **n** focus mode__toggle

Action

- **alt** **[h,j,l,l]** move focused window
- **shift alt** **[0-9]** move focused window
- **super** **control** **[l,h]** the whole workspace to the next output
- **super** **;** **r** (resize) “Normal:Resize: [h|j|k|l|H|J|K|L]”
- **super** **;** **m** (move) “Normal:Resize: [h|j|k|l|H|J|K|L]”

Fuzzy Finder in Terminal

- **zahtura** ****<TAB>**
- **nvim** ****<TAB>**
- **nvim** **~/Downloads**<TAB>** **ou**
- **nvim** **control t**
- **control r** history
- **cd** ****<TAB>** chage directory
- **alt c** chage directory
- Options:
 - **ctrl-b** backward-kill-word
 - **ctrl-g** top
 - **ctrl-u** page-up
 - **ctrl-d** page-down
 - **ctrl-f** toggle-all
 - **ctrl-q** clear-query
 - **ctrl-s** clear-selection
 - **ctrl-o** jump
 - **ctrl-c** cancel
 - **ctrl-y** yank
 - **ctrl-p** toggle-preview
 - **ctrl-t** toggle-all
 - **ctrl-z** deselect-all
 - **tab:toggle** select and down
 - **shift-tab** select and up