

DEVELOPMENT

5.1 Technical System Implementation Parameters

Development was executed within an isolated ServiceNow environment using **Workflow Studio**. The step-by-step logic configurations are established through three primary pipeline stages:

Stage 1: Process Trigger Interface

The workflow engine binds natively to a standard Service Catalog Trigger. This establishes an active, lightweight data listener on the Requested Item table (sc_req_item), mapping catalog inputs directly into live execution memory containers (data pills) at initialization.

Stage 2: Ask For Approval Action Configuration

A core platform approval block is appended to the flow canvas, creating a unique relational link to the runtime parent item identifier. Input conditions are hard-coded to enforce the following governance rules:

- **Approval Rules:** Set to require **Anyone to Approve** from the dynamically generated routing list.
- **Approver Target Mapping:** Dot-walks the reference field path to extract the supervisor ID:

Trigger → Requested Item Record → Requested For → Manager

Stage 3: Conditional Evaluation Fork

An internal system evaluation block intercepts the runtime state returned from the approval action. If the authorization variable resolves strictly to **Approved**, the engine triggers the success branch and advances toward fulfillment.

5.2 Else Branch Configuration & Rejection Custom HTML Engineering

If the manager updates the record state to **Rejected**, the evaluation engine diverts execution into the negative Else logic block to handle task cancellation, state rollback, and user notification parsing.

Stage 4: Parent Record Status Update

An *Update Record* action is injected to modify the current `sc_req_item` database entry, shifting core variables to prevent downstream task leaks:

- **Approval Field:** Changed to *Rejected*
- **Ticket Stage:** Updated to *Closed Incomplete*

Stage 5: Send Email Custom Layout Injection

The *Send Email* action bypasses unformatted plain-text outputs by leveraging raw, inline-styled HTML blocks directly inside the body canvas. The layout is engineered within Workflow Studio as follows:

HTML

```
<h2 style="text-align: center; color: #0f172a;">Your request was rejected</h2>
```

```
<hr style="border: 0; border-top: 1px solid #e2e8f0;" />
```

```
<p>Hi
```

```
<strong>{{Trigger.request_item.requested_for.first_name}}</strong>  
,</p>
```

<p>{{Trigger.request_item.number}} was rejected by your manager, and this request has been canceled.</p>

<p style="text-align: center;">

View Request

</p>

<h3 style="color: #0369a1;">About this request</h3>

<p>

Requested item number:
{{Trigger.request_item.number}}

Short description:
{{Trigger.request_item.short_description}}

Rejection Comments:
{{Step2.approval_history_comments}}

</p>

<p>Thank you,
Fulfillment Team</p>

5.3 Developer Sandbox Environment Note

i System Property Guardrail

Outbound email routing is disabled globally by default via system properties in non-production environments to prevent accidental

spamming. Inbound/Outbound email transactions were safely verified by querying the system logs (sys_email.list), confirming that the records generated successfully with an operational status of **send-ready**.