

Angular Directives Examples

1 ngIf Example

TypeScript

```
show = false;

toggle() {
  this.show = !this.show;
}
```

HTML

```
<button (click)="toggle()">
  Toggle
</button>

<div *ngIf="show">
  Hello Angular
</div>
```

Explanation

- `*ngIf` is used for conditional rendering.
- If `show = true`, the div is displayed.
- If `show = false`, the div is removed from the DOM.
- `toggle()` changes the boolean value using:

```
this.show = !this.show;
```

2 ngFor with Index Example

TypeScript

```
students = ['Ronit', 'Alex', 'Sam'];
```

HTML

```
<div *ngFor="let student of students;  
          let i = index">  
  
    {{ i + 1 }} - {{ student }}  
  
</div>
```

Explanation

- `*ngFor` is used to loop through arrays.
- `student` stores the current item.
- `index` gives the current position.
- `i + 1` is used because index starts from 0.

Output

```
1 - Ronit  
2 - Alex  
3 - Sam
```

3 ngStyle Example

TypeScript

```
isError = true;
```

HTML

```
<p [ngStyle]="{  
  'color': isError ? 'red' : 'green'  
}">  
  Status Message  
</p>
```

Explanation

- ngStyle is used for dynamic inline styling.
- The ternary operator is used:

```
condition ? trueValue : falseValue
```

- If `isError = true`, text color becomes red.
- Otherwise, it becomes green.

4 ngClass Example

CSS

```
.red-text {  
  color: red;  
}  
  
.bold {  
  font-weight: bold;  
}
```

TypeScript

```
isError = true;  
isBold = true;
```

HTML

```
<p [ngClass]="{  
  'red-text': isError,  
  'bold': isBold  
  Error Message  
</p>
```

Explanation

- ngClass is used to add/remove CSS classes dynamically.
- If isError = true, class red-text is added.
- If isBold = true, class bold is added.

5 Difference Between ngStyle and ngClass

Feature	ngStyle	ngClass
Works With	CSS Properties	CSS Classes
Used For	Inline Styling	Reusable Styling
CSS File Needed	No	Yes
Best For	Small Dynamic Styles	Multiple Styles/Themes