

1. User & Authentication Models

User

The central entity for all platform interactions.

- **Core Fields:** id, email, password, username, avatarUrl.
- **Status Fields:** role (ADMIN, USER, VISITOR), banned, createdAt, updatedAt.
- **Relationships:** * Belongs to one favoriteTeam.
 - Has many followers and following (via the Follow model).
 - Has many posts, threads, polls, pollVotes, reports, and appeals.

RefreshToken

Manages secure authentication sessions. Stored refresh token data is used to verify the authenticity of tokens provided by the client.

- **Fields:** id, token (unique), expiresAt, createdAt.
- **Relationships:** Belongs to a User (cascades on delete).

Follow

Keeping track with the follower and following relationships happened between users.

- **Fields:** date.
- **Relationships:** Connects a follower (User) to a following (User). Uses a composite primary key @@id([followerId, followingId]) to prevent duplicate follows.

Appeal

Allows banned users to request account reinstatement. Decision of appeal is made from Admin.

- **Fields:** id, status (APPROVED, IN_PROGRESS, DENIED), content.
- **Relationships:** Belongs to a User.

2. Sports Data Models

Team

Represents a Premier League club and includes comprehensive info of each team, the teams are loaded in the setup script, as well as a forum associated to the team.

- **Fields:** id, name, logoUrl, venue, seasonYear.
- **Relationships:** Has many fans (Users). Plays in many homeMatches and awayMatches. Optionally has one dedicated Forum.

Match

Represents a scheduled football fixture, the matches are loaded in the setup script.

- **Fields:** id, date, scoreTeam1, scoreTeam2, matchday, stage, completed, winnerName.
- **Relationships:** * Links to two Teams: homeTeam and awayTeam.
 - Has a one-to-one relationship with a discussionThread (the automated match thread).

SportsData

A utility table to cache external API responses.

- **Fields:** id, jsonData, updatedAt.

AiDigest

Stores AI-generated daily summaries of platform and sports activity.

- **Fields:** id, digest, createdAt.
-

3. Forum & Discussion Models & Polls

Forum

Containers for threads, forums are created during data set up.

- **Fields:** id, type (GENERAL, MATCH, TEAM), teamName.
- **Relationships:** Optionally belongs to a specific Team. Has many threads. Uses a composite unique key @@unique([type, teamName]).

Thread

Individual discussion topics created within forums or auto-generated for matches. Each team also contains forum id, which is used to distinguish a team thread and a general thread, we use the forum id.

- **Fields:** id, title, visibility, createdAt, homeTeamSentiment, awayTeamSentiment, aiAvgScore, reportCount.
- **Relationships:** * Belongs to an author (User) and a forum (Forum).
 - Has many tags (ThreadTag) and posts.
 - Has one mainPost (the OP).
 - Can act as the specific matchDiscussionFor a Match.

ThreadTag

Defines thread tags to categorize content and provide users with a clear overview of the topic.

- **Fields:** id, name.
- **Relationships:** Belongs to a Thread.

Post

Posts represent individual comments within a thread. To maintain a version history, a recursive pointer links each post to its subsequent update. Updates are restricted to the most recent version of a post to prevent branching and ensure a linear update path.

Fields: id, content, visibility, createdAt, updatedAt, reportCount, aiFlagged, aiMaxScore, aiScores.

- **Relationships:** Belongs to an author (User) and a thread (Thread).
- **Structural Relationships:**
 - **Tree Structure (Replies):** Uses replyingToId to link to a parent Post, enabling nested comments.
 - **Linked List (Versioning):** Uses previousVersionId and nextVersionId to maintain a chronological edit history without destroying original data.

Poll & PollOption

Integrated within threads, polls provide enhanced interactivity compared to standard posts. Each user is restricted to a single vote, and results update dynamically based on the real-time count for each option.

- **Poll Fields:** id, pollDescription, deadline, visibility, createdAt, reportCount, aiFlaggedfields, aiMaxScore, aiScores.
- **Relationships:** A Poll belongs to an author and a thread, and contains many PollOption records.

PollVote

Records user participation in polls.

- **Fields:** id, optionIndex, createdAt.
 - **Relationships:** Links a User to a Poll. Uses @@unique([pollId, userId]) to enforce a "one vote per user" rule.
-

4. Moderation Models

Report

Records the reports submitted by users or administrators. Reports can be targeted at threads, posts, or polls. Upon administrative approval, the target entity is flagged as invisible to the public and locked to prevent further edits.

- **Fields:** id, reason, status (PENDING, DISMISSED, APPROVED), createdAt, userId
- **Relationships:** Created by a User. Can target either a post, thread, or poll (optional foreign keys).