

```
// Name: Connor Marler
// Instructor: Gerry Howser
// Date: 10/13/2022
// Project 2 Merge Sort Analysis
```

```
//Source: https://slaystudy.com/c-program-to-implement-merge-sort-using-templates/
```

```
#include<iostream>
//#include<vector>
#include <chrono>
#include <cassert>
```

```
using namespace std;
```

```
//Purpose: template function to merge 2 componenets of the array, arr
//PreCondition: takes in an templated array and integer start and end points
reflecting the specific subarray
//PostCondition: the result is written back to the original array
//Invariant:(indexOfMergedArray == left) && (indexOfSubArrayOne == 0) &&
(indexOfSubArrayTwo == 0))
```

```
template<typename T>
```

```
void Merge(T array[], int const left, int const right)
{
```

```
    auto mid = (left + right) / 2;
    auto const subArrayOne = mid - left + 1;
    auto const subArrayTwo = right - mid;
```

```
    // Create temp arrays
```

```
    auto *leftArray = new int[subArrayOne],
        *rightArray = new int[subArrayTwo];
```

```
    // Copy data to temp arrays leftArray[] and rightArray[]
```

```
    for (auto i = 0; i < subArrayOne; i++)
```

```
        leftArray[i] = array[left + i];
```

```
    for (auto j = 0; j < subArrayTwo; j++)
```

```
        rightArray[j] = array[mid + 1 + j];
```

```
    auto indexOfSubArrayOne
```

```
        = 0, // Initial index of first sub-array
```

```
    indexOfSubArrayTwo
```

```
        = 0; // Initial index of second sub-array
```

```
    int indexOfMergedArray
```

```
        = left; // Initial index of merged array
```

```
    // Merge the temp arrays back into array[left..right]
```

```
    assert((indexOfMergedArray == left) && (indexOfSubArrayOne == 0) &&
(indexOfSubArrayTwo == 0));
```

```
    while (indexOfSubArrayOne < subArrayOne && indexOfSubArrayTwo < subArrayTwo)
```

```
    {
```

```
        if (leftArray[indexOfSubArrayOne] <= rightArray[indexOfSubArrayTwo])
```

```
        {
```

```
            array[indexOfMergedArray] = leftArray[indexOfSubArrayOne];
```

```
            indexOfSubArrayOne++;
```

```
        }
```

```
        else {
```

```
            array[indexOfMergedArray] = rightArray[indexOfSubArrayTwo];
```

```
            indexOfSubArrayTwo++;
```

```
        }
```

```

        indexOfMergedArray++;
    }
    // Copy the remaining elements of
    // left[], if there are any
    while (indexOfSubArrayOne < subArrayOne)
    {
        array[indexOfMergedArray] = leftArray[indexOfSubArrayOne];
        indexOfSubArrayOne++;
        indexOfMergedArray++;
    }
    // Copy the remaining elements of
    // right[], if there are any
    while (indexOfSubArrayTwo < subArrayTwo)
    {
        array[indexOfMergedArray] = rightArray[indexOfSubArrayTwo];
        indexOfSubArrayTwo++;
        indexOfMergedArray++;
    }
    delete[] leftArray;
    delete[] rightArray;
}

```

```

//Purpose: template function to perform merge sort on array, arr
//PreCondition: takes in a templated array and integer start and end points
//reflecting the length of the array
//PostCondition: the list is now sorted in ascending orders
template<typename T>
void MergeSort(T arr[], int start, int end)
{
    if (start < end)
    {
        int mid = (start + end) / 2;
        MergeSort(arr, start, mid); // merge sort the elements in range [start, mid]
        MergeSort(arr, mid + 1, end); // merge sort the elements in range [mid+1, end]
        Merge(arr, start, end); // merge the above 2 componenets
    }
}

```

```

//Purpose: Template function to print array
//PreCondition: takes in an array and a value of the size of the array
//PostCondition: outputs the array givens
template<typename T>
void PrintArray(T arr[], int n)
{
    for (int i = 0; i < n; ++i)
        cout << arr[i] << " ";
    cout << "\n\n";
}

```

```

//Purpose: take in an array and fill it with a predetermined element set
//PreCondition: must receive arr[size] and a string value determining how to fill
the set
//PostCondition: must fill arr[size] with the values in the appropriate as
determined by preSortOrder
void populateArray(int *arr, const int size, const string preSortOrder)
{

```

```

// This if else tree could also be re-written as a switch case
if(preSortOrder == "assPreSortOrder")
{
    for(int i = 0; i <= size; i++)
    {
        arr[i] = i + 1;
    }
}
else if(preSortOrder == "decPreSortOrder")
{
    for(int j = 0; j <= size; j++)
    {
        arr[j] = size - j;
    }
}
else if(preSortOrder == "randPreSortOrder")
{
    for(int k = 0; k <= size; k++)
    {
        arr[k] = rand() % size + 1;
    }
}
else // error handling
{
    cout << "ERROR: Something broke. Please quit and try again." << endl;
}
}

int main()
{
    // These are what we will use for the time measurement
    using chrono::high_resolution_clock;
    using chrono::duration_cast;
    using chrono::duration;
    using chrono::nanoseconds;

    srand (time(NULL));
    const int SIZE = 500;
    string preSortOrder;
    int innerLoop = 1000;
    int outerLoop = 10;
    int averageTime = 0;
    int time = 0;

    int mainArray[SIZE]; // This the hard, original copy of the array
    int workingArray[SIZE]; // This is the copy used to work with and innerLoop
    through

    cout << "MERGE SORT AVG TIMES" << endl;
    for(int i = 0; i <= 2; i ++) // loops through each case
    {
        if(i == 0)
        {
            preSortOrder = "assPreSortOrder";
            cout << endl << "Ascending Order Time:" << endl;
        }
    }
}

```

```

else if(i == 1)
{
    preSortOrder = "decPreSortOrder";
    cout << endl << "Descending Order Time:" << endl;
}
else if(i == 2)
{
    preSortOrder = "randPreSortOrder";
    cout << endl << "Random Order Time:" << endl;
}

populateArray(mainArray, SIZE, preSortOrder);
averageTime = 0;

for(int k = 0; k < outerLoop; k++) // takes 10 data point
{
    averageTime = 0;
    for(int j = 0; j < innerLoop; j++) // perform the sort 1000 times and take an
average for one data point
    {
        for (int a = 0; a < SIZE; a++) // This copies over the original array onto
a working copy
        {
            workingArray[a] = mainArray[a];
        }
        //cout << "Before Sort" << endl;
        //PrintArray(workingArray, SIZE);
        auto time1 = high_resolution_clock::now(); // take initial time
        MergeSort(workingArray, 0, SIZE - 1); // do the sort
        auto time2 = high_resolution_clock::now(); // time the after time
        //cout << "After Sort" << endl;
        //PrintArray(workingArray, SIZE);
        auto nanoSeconds = duration_cast<nanoseconds>(time2 - time1); // find the
difference of the times
        time = nanoSeconds.count(); // convert to an int
        averageTime += time;
    }
    averageTime /= innerLoop;
    cout << "Trial # " << k + 1 << ": " << averageTime << " ns" << endl;
}
}
}

```