product/full.mk

product/full_base_telephony.mk

board/generic/device.mk

full_base.mk   telephony.mk

.   .

.   .

.   .

```
PRODUCT_PROPERTY_OVERRIDES := \
    ro.ril.hspxa=1
    ro.ril.gprsclass=10
    ro.dbd.qemu=1
PRDOUCT_COPY_FILES := \
    apns_conf.xml
    vold.conf
    media_profiles.xml
    media_codecs.xml
```

Note This can be used interchangeably with current generic_x86.
generic_x86 only adds some bios support for the X86 emulator

product/full.mk

product/full_base_telephony.mk

board/generic/device.mk

full_base.mk

telephony.mk

```
PRODUCT_PACKAGES += \
        Mms \
        rild
```

locales_full,mk

generic_no_telephony.mk

frameworks/base/data/
sounds/AllAudio.mk
…
…

external/svox/pico/lang
/all_pico_languages.mk
…
…

languages_full.mk

```
PRODUCT_LOCALES += \
        …
        …
        ...
```

product/full.mk

product/full_base_telephony.mk

board/generic/device.mk

full_base.mk

telephony.mk

locales_full,mk

generic_no_telephony.mk

frameworks/base/data/
sounds/AllAudio.mk

external/svox/pico/lang
/all_pico_languages.mk

frameworks/base/
data/fonts.mk

external/*-fonts
/fonts.mk

frameworks/base/
data/keyboards.mk

product/core

product/base

product/embedded

PROUCT_PACKAGES ...
PRODCUT_COPY_FILES...
PRODUCT_PROPERTY_OVERRIDES
         ...
         ...
         ...