```
Protocol Length Info
No.
      Time
                      Source
                                            Destination
    22 3.203055
                     IntelCor_7e:a1:58
                                           Broadcast
                                                                  ARP
                                                                          42
                                                                                 Who has 192.168.1.1? Tell 192.168.1.10
Frame 22: 42 bytes on wire (336 bits), 42 bytes captured (336 bits) on interface \Device\NPF_{812FDBC9-E528-45AD-944A-928C627E97AF}, id 0
   Interface id: 0 (\Device\NPF_{812FDBC9-E528-45AD-944A-928C627E97AF})
       Interface name: \Device\NPF_{812FDBC9-E528-45AD-944A-928C627E97AF}
       Interface description: Wi-Fi
   Encapsulation type: Ethernet (1)
   Arrival Time: Apr 25, 2021 01:01:28.767263000 Eastern Daylight Time
   [Time shift for this packet: 0.000000000 seconds]
   Epoch Time: 1619326888.767263000 seconds
   [Time delta from previous captured frame: 0.030745000 seconds]
   [Time delta from previous displayed frame: 0.030745000 seconds]
   [Time since reference or first frame: 3.203055000 seconds]
   Frame Number: 22
   Frame Length: 42 bytes (336 bits)
   Capture Length: 42 bytes (336 bits)
   [Frame is marked: False]
   [Frame is ignored: False]
   [Protocols in frame: eth:ethertype:arp]
   [Coloring Rule Name: ARP]
   [Coloring Rule String: arp]
Ethernet II, Src: IntelCor_7e:a1:58 <mark>(d0:ab:d5:7e:a1:58)</mark>, Dst: Broadcast <mark>(ff:ff:ff:ff:ff:ff</mark>)
   Destination: Broadcast (ff:ff:ff:ff:ff)
       Address: Broadcast (ff:ff:ff:ff:ff)
       .... .1. .... .... = LG bit: Locally administered address (this is NOT the factory default)
       .... 1 .... = IG bit: Group address (multicast/broadcast)
   Source: IntelCor_7e:a1:58 (d0:ab:d5:7e:a1:58)
       Address: IntelCor_7e:a1:58 (d0:ab:d5:7e:a1:58)
       .... ..0. .... = LG bit: Globally unique address (factory default)
   .....0 .... = IG bit: Individual address (unicast)

Type: ARP (0x0806)
Address Resolution Protocol (request)
   Hardware type: Ethernet (1)
   Protocol type: IPv4 (0x0800)
   Hardware size: 6
   Protocol size: 4
   Opcode: request (1)
   Sender MAC address: IntelCor_7e:a1:58 (d0:ab:d5:7e:a1:58)
   Sender IP address: 192.168.1.10
   Target MAC address: 00:00:00_00:00:00 (00:00:00:00:00:00)
```

Target IP address: 192.168.1.1