


Got it — I have the full Showside context loaded. You're post-Phase 4, with Phase 5 (upload flow UI) and Phase 6 (SEO/polish) still ahead, plus a design pass planned.

What are we working on?



You said: one extra thought i had would be about not only categorizing the media based on the song - but also other categories like 'the venue' 'the vibe' 'the VIP roofd...

one extra thought i had would be about not only categorizing the media based on the song - but also other categories like 'the venue' 'the vibe' 'the VIP roofdeck' 'the pit' etc etc so the app would classify media uploads beyond just the performance or the game highlights, and include more 'lifestyle' content as well which would encourage users to upload a broader variety of the pics and videos they took while at the event, not just of songs or plays... that make sense?

May 25



Claude responded: Yeah, that makes a lot of sense — and it's actually a smart expansion of the core concept.

Yeah, that makes a lot of sense — and it's actually a smart expansion of the core concept.

Right now the mental model is **setlist-to-clip** (song → footage). But a live event experience is way more than the performance itself. The journey *is* the content:

- Tailgate / pregame
- The walk-up / venue exterior
- Finding your seats
- The pit / floor energy
- VIP areas / rooftop / club level
- Halftime / intermission
- The crowd reacting to a big moment
- Post-show / parking lot

This matters for a few reasons:


It lowers the upload barrier. Someone who only shot crowd footage or a bar scene outside the stadium felt like their content "didn't qualify." Now it does. You get more uploads per event.

It makes the virtual attendance experience richer. A teenager in London doesn't just want to see the setlist — she wants to *feel* what it was like to be there. The chaos of the pit, the vibe of the VIP deck, the crowd losing it. That's atmosphere, not just performance.

It creates a second browse axis. Right now you'd filter by song. With location/vibe categories, you'd filter by *experience type* — "show me all the pit footage" or "what was the venue like?"

Implementation-wise it fits cleanly into what you already have — just expanding the tag taxonomy beyond songs to include **location/vibe tags** as a parallel category on the media row. Could be as simple as a second optional tag type: `tag_type: 'song' | 'location' | 'vibe'`.

Want to think through the taxonomy (what the actual categories would be) or jump to how it fits the schema?



You said: yes exactly.

yes exactly. taxonomy

May 25



Claude responded: Let's think about this in layers — what type of event it is matters because the categories differ between a concert, a sports game, a festival, etc.

Let's think about this in **layers** — what type of event it is matters because the categories differ between a concert, a sports game, a festival, etc. But there's probably a **universal core** that applies everywhere, plus **event-type overlays**.

Universal Core Tags

These apply to any live event:

Location/Space

- Entrance / arrival
- Main floor / general admission

- Seated section
- Standing area
- Concourse / hallways
- Concessions / food & drink
- Merch stand
- Restrooms (*probably skip this one*)
- Parking lot / tailgate
- Outside the venue
- VIP area
- Press area / photo pit

Moment Type

- Crowd reaction
- Waiting / before the show
- Intermission / halftime / break
- Post-show / exit
- Surprise moment
- Fan interaction
- Artist/player interaction with crowd

Vibe

- Chaos / energy
- Emotional moment
- Funny / chaotic
- Peaceful / quiet
- Atmosphere / aesthetic

Event-Type Overlays

Concert

- Specific song (*existing*)
- Opening act
- Soundcheck
- Encore
- Pit
- Barrier / front row
- Stage setup / production
- Light show / visuals
- Meet & greet

Sports

- Specific play (*equivalent of song*)
- Pregame warmups
- Player intro
- Big play reaction
- Halftime show

- Postgame
- Tailgate
- Student section / supporter section
- Walk-up / team arrival

Festival

- Campsite
- Between sets
- Second stage
- Food vendors
- Art installations
- Sunset / overnight
- Multiple-day arc

How It Sits in the Schema

Each media row gets an optional array of tags. A tag has:

```
tag_type: 'song' | 'location' | 'vibe' | 'moment'
tag_value: string (e.g. 'pit', 'crowd_reaction', 'encore')
tag_label: string (e.g. 'The Pit', 'Crowd Reaction', 'Encore')
```

Entity type on the **entities** table (**concert** / **sports** / **festival**) drives which tag options surface during upload — so a sports uploader never sees "encore" and a concert uploader never sees "tailgate warmups."


What Shows Up on the Front End

On the event page, instead of just a **Songs** filter row, you get two rows:

- **Moments** — song/play chips (existing)
- **Vibes** — pit / VIP / crowd / pregame / etc.

Or collapsed into a single filter bar with both types mixed, sorted by clip count.

Want to pressure-test the taxonomy more, or does this feel right enough to think about how it integrates into the upload flow UI (Phase 5)?



You said: feels like enough for now.

feels like enough for now. do you think AI would be able to auto-categorize the media itself? the

user flow would be that much easier if all someone had to do was click upload > select their 20 media from the event and click upload and then bam it would shortly be auto-categorized...possible?

May 25



Claude responded: Yes — and it's actually very doable with current AI capabilities.

Yes — and it's actually very doable with current AI capabilities. Let me break down what's realistic:

What AI Can Auto-Classify Today

Images — high confidence Vision models (GPT-4o, Claude, Gemini) are genuinely good at:

- Crowd vs stage vs venue exterior vs concessions
- Pit vs seated vs VIP aesthetic
- Pregame/tailgate vs in-show vs postgame
- Energy/vibe reading (chaos, emotional, chill)
- Sports vs concert context

You'd send the image + a prompt like "classify this concert photo from the following categories: [list]" and get reliable results. This is production-ready now.

Video — good with a frame sample You don't need to analyze the full video. Extract 3-5 keyframes, run them through vision classification, combine with audio signals. That gets you most of the way there.

Audio (for songs) — ACRCLOUD Already in your V2 plan. Fingerprinting handles song ID. The vibe/location tags are vision's job anyway.

Confidence Levels by Category

Category	AI Confidence	Notes
Stage vs crowd vs venue	Very high	Visual is obvious
Pit vs seated vs VIP	High	Density + angle tells the story
Pregame vs during vs postgame	Medium-high	Needs context clues
Emotional moment	Medium	Facial expressions, body language
Specific song (V2)	High	ACRCLOUD handles this

"Funny/chaotic"

Lower

Needs more nuance

The Architecture

Upload complete



Queue classification job (async, non-blocking)



Images → Vision API (Claude/GPT-4o) → tag array

Videos → Extract frames → Vision API → tag array



Write tags to DB



UI updates (tags appear on media card)

Key point: **async and non-blocking**. User uploads, sees their media immediately as untagged, tags populate within 5-15 seconds. No friction added to upload flow at all.

What This Means for UX

The upload flow becomes exactly what you described:

- 1 Select files
- 2 Tap upload
- 3 Done

No tagging screen at all in the happy path. Tags just appear. You could optionally let users **correct** a tag after the fact — a light edit affordance — but it's not required.

The only thing you might still ask manually: **which event is this from** — but that's already solved by the event picker at the start of the upload flow.


Cost

Vision API calls are cheap. At GPT-4o pricing, classifying one image is roughly **\$0.001–0.003**. Even at 1M uploads a month that's \$1-3k — trivial at scale, nearly free at V1 volume.

Verdict

This is a **V1.5 feature** not a V2 pipe dream. The upload flow ships clean in Phase 5, and you layer auto-classification on top as a background job shortly after. The schema you already have (tag_type / tag_value array) supports it with no changes.

Want to spec out the classification prompt + category list that would actually get sent to the vision API?



You said: my brain is spinning - there's so many applications for this beyond just events/concerts, i think - it could apply to things the the grand canyon, the empire s...

my brain is spinning - there's so many applications for this beyond just events/concerts, i think - it could apply to things the the grand canyon, the empire state building, on and on - basically any place/event where people are taking pics and video... but want to make sure I start in a logical place/use case first. do you think concerts is the right place to start? what other use cases make the most sense to start with?

May 25



Claude responded: Your instinct to focus is right — trying to be "fan media for everything" at launch is a trap.

Your instinct to focus is right — trying to be "fan media for everything" at launch is a trap. Let me think through this honestly.

Why Concerts First Is Correct

A few things make concerts the ideal beachhead:

Demand signal is already proven. Fan-shot concert clips on YouTube get 10M+ views organically. People are already doing this behavior — just unorganized across TikTok/Instagram/YouTube.

The pain is acute and emotional. Being priced out of a show you wanted to attend is a specific, felt frustration. The Morgan Wallen teenager in London is a real person with a real problem. That emotional hook drives word of mouth.

Upload motivation is high. Concert attendees are *proud* of their footage. They want to share it. The social currency of "I was there" is strong.

Defined entity structure. Artist → Tour → Show is clean. You know exactly what the taxonomy looks like before you build.

Community already exists. Fan communities around artists are passionate, organized, and vocal. One Reddit post in r/MorganWallen or r/Beyonce could drive hundreds of uploads.

The Broader Landscape

Here's how other use cases stack up honestly:

Use Case	Upload Motivation	Viewer Demand	Entity Structure	Verdict
Concerts	Very high	Very high	Clean	✅ Start here
Sports games	High	High	Clean	Strong second
Festivals	High	High	Messier (multi-artist)	Phase 2
Theme parks	Medium	Medium	Clean	Interesting but niche
Grand Canyon / landmarks	Low	Medium	Simple but shallow	Tourist trap — see below
Protests / cultural moments	High	High	Unpredictable	Moderation nightmare
Weddings / private events	Medium	Low	Private — different product	Different business
Restaurants / venues	Low	Low	Yelp already owns this	No

Sports Is the Obvious Second

Everything that makes concerts work applies to sports:

- Same priced-out audience (playoff tickets, sold-out games)
- Same "I was there" upload pride
- Tailgate culture = even more lifestyle content
- Team → Season → Game mirrors Artist → Tour → Show perfectly
- Passionate existing fan communities

The main difference: sports has **highlight clip rights issues** at the professional level. NFL/NBA are aggressive about IP. You'd want to start with college sports or be careful about how you position professional game clips. Fan-shot footage from the stands is legally grayer than broadcast replays — but worth thinking through.

The Tourist/Landmark Case — Interesting But Different

Grand Canyon, Empire State Building, etc. — the instinct is right that the product *could* work there. But a few things make it a worse starting point:

- **Upload motivation is lower.** People share landmark photos but don't feel the same pride/community around it.
- **No existing fan community to seed.** You can't post in a subreddit to kickstart uploads.
- **The "virtual attendance" hook is weaker.** Nobody feels priced out of the Grand Canyon the same way they feel priced out of a Taylor Swift show.
- **It's closer to Google Street View / Flickr territory.** Harder to differentiate.

That said — **it's the same infrastructure.** If Showside works for concerts, expanding to landmarks is a config change not a rebuild.


The Honest Answer

Concerts first. Sports second. Everything else is a future config.

The underlying product is really: *organized, community-uploaded media for any shared experience people attend in person.* Concerts just happen to have the strongest combination of emotional pain point + existing fan behavior + clean data structure + seeding opportunity.

Start there, prove the virtual attendance session hypothesis, then expand.

What's pulling at your brain — are you worried concerts is too narrow, or is something else calling to you?



**You said: nothing - just thinking through it all - i agree
concerts is right starting point.**

nothing - just thinking through it all - i agree concerts is right starting point. i worry about getting people to upload to SS instead of/in addition to instagram/tiktok but thats just going to be the nature of it, i think...

May 25



**Claude responded: Yeah, that tension is real — but I think
it's actually more manageable than it feels.**

Yeah, that tension is real — but I think it's actually more manageable than it feels. Here's why:

The Core Insight

Instagram and TikTok are **broadcast platforms** — you post *to your followers*. Showside is an **archive platform** — you post *to the show*.

Those aren't competing motivations. They're sequential. Post the highlight to TikTok for clout, then upload the full 3-minute clip to Showside because it belongs there permanently. Same person, same night, different jobs.

The framing that unlocks this: **Showside is where the show lives forever. TikTok is where you go viral today.**

What You're Actually Competing With

You're not really competing with TikTok for attention. You're competing with **doing nothing** — the 47 clips sitting in someone's camera roll that never got posted anywhere because they weren't "good enough" for Instagram. That's your actual addressable content pool. It's enormous.

What Works In Your Favor

No performance anxiety. On Instagram every post is a referendum on your personal brand. On Showside nobody cares if your clip is shaky — it's fan footage, that's the point. Lower bar = more uploads.

The event as context. When someone uploads to Showside they're contributing to *the show's record* not their personal feed. That's a different and lower-pressure motivation.

The QR code at the venue. You already have this in the schema. A QR code at the show that says "*Upload your footage here*" catches people in the moment before they even think about Instagram.


Cross-posting is fine. You don't need exclusivity. If someone uploads to both TikTok and Showside, you win. You got the content. Their TikTok post might even drive viewers to Showside.

The One Thing That Would Really Move the Needle

If even one artist or team **officially acknowledges Showside** — a tweet, a story, a mention — the upload behavior follows immediately. Fan communities are extremely responsive to signals from the artist. That's probably the single highest-leverage distribution move in V1.

The upload motivation problem is real but it's a **marketing and positioning problem**, not a product problem. The product just needs to make uploading fast and frictionless — which is exactly what Phase 5 is. The rest is distribution strategy you can tackle post-launch.

What's next — ready to get back into building?



You said: wow - that was amazing framing - i love it, thanks.

wow - that was amazing framing - i love it, thanks. when you say 'artist or team officially acknowledges Showside' - how exactly are you thinking that would happen? ex. between songs at the show the artist shouts out 'make sure you upload all these videos to Showside, I want to see this shit from your view tomorrow!' - something like that?? what else are you thinking there?

May 25



Claude responded: Yes exactly that — and that's actually the highest-leverage version because it hits 20,000 people simultaneously in the most emotionally activated moment of th...

Yes exactly that — and that's actually the highest-leverage version because it hits 20,000 people simultaneously in the most emotionally activated moment of their night. But there's a whole ladder of acknowledgment:

The Acknowledgment Ladder

Level 1 — Passive (no relationship needed)

- Fan accounts repost content sourced from Showside, credit the platform
- Music journalists reference Showside clips in reviews
- Reddit/Discord communities organically adopt it as "where we post show footage"

This happens on its own if the product is good enough. No outreach required.

Level 2 — Social (light relationship)

- Artist reposts a Showside clip on their Instagram stories
- Tour manager tweets "the pit footage on Showside from last night 🔥"
- Artist's fan club officially recommends uploading there

This is one good clip going viral on the platform away from happening organically. An artist's social team is constantly hunting for fan content — if your platform is where the best clips live, they'll find it.

Level 3 — Active endorsement (real relationship)

- Artist posts "upload your footage to Showside" in their pre-show email to fan club
- QR code appears on the official venue screen during set change
- Tour merch table has a Showside card/flyer
- Artist's website links to their Showside page

Level 4 — The shoutout (your example)

- Between songs: "*Yo upload all this to Showside, I want to see the show from your angle tomorrow*"
- This is the nuclear option — immediate mass behavior change in the room

How You Actually Get There

The path isn't cold outreach to artists. It's:

Step 1 — Build the artist's page without asking permission. Morgan Wallen's Showside page exists whether Morgan Wallen knows about it or not. It looks incredible because fans already uploaded. That page *is* the pitch.

Step 2 — The content does the outreach. Artist's social team finds a clip of a surprise moment from last Tuesday's show. It's on Showside. They repost it. That's level 2 happening organically.

Step 3 — You reach the team not the artist. You never cold email Morgan Wallen. You find his tour manager or social media manager — real humans with real jobs who are actively looking for fan content — and you show them the page. The pitch is "*your fans are already here, we just organized it.*"

Step 4 — You offer them something. Not money. Access. An artist dashboard where they can see all fan uploads from their shows, download clips, see what songs got filmed most. That's genuinely useful to a social media team. Now Showside has a reason to be in their workflow permanently.


The Flywheel

One mid-size artist endorses it → their fanbase floods uploads → the page looks incredible → a bigger artist's team sees it → repeat.

You don't need Taylor Swift in month one. You need one artist with a passionate enough fanbase

to seed the content, and the flywheel starts.

The artist dashboard idea is interesting too — it's essentially a free B2B layer that sits on top of the consumer product and creates the relationship you need. Worth keeping in mind for post-V1.



You said: ok - thinking ahead again - how do i monetize this eventually?

ok - thinking ahead again - how do i monetize this eventually?

May 25



Claude responded: Good thing to think about now even if you don't build any of it yet — because the monetization model should inform some product decisions early.

Good thing to think about now even if you don't build any of it yet — because the monetization model should inform some product decisions early.

The Core Asset You're Building

Before getting to revenue streams — what you actually have is:

- **Verified, located, timestamped fan media** attached to specific events
- **Audience intent data** — people actively seeking to experience specific artists/events
- **A captive moment** — someone deep in a 30-minute virtual attendance session is highly engaged

That's a valuable asset. The monetization follows from it.

Revenue Streams, Ranked by Fit

1. Artist/Team Dashboard — SaaS The one I mentioned above. Charge artists, managers, or labels for:

- Access to all fan uploads from their shows
- Download rights for social use
- Analytics (most filmed songs, crowd energy heatmaps, etc.)
- Verified clip licensing for official use

This is B2B, recurring, and high margin. A label paying \$500/month to have access to fan footage across a 40-city tour is an easy sell. This is probably your **first real revenue stream** because it doesn't require massive consumer scale.

2. Licensing Fan footage has real commercial value:

- Artist uses a fan clip in their official music video
- ESPN uses crowd footage in a highlight package
- Netflix documentary about a tour uses fan POV clips
- Advertiser wants authentic live event footage

You sit in the middle as the marketplace. Take a cut. The uploader gets a small payment, you get a percentage. This is **long term** but potentially very high value per transaction.

3. Ticketing Affiliate Someone watches 30 minutes of Beyoncé footage on Showside and then sees "*She's playing Miami in March — tickets from \$180*" with an affiliate link to Ticketmaster/StubHub. That person is the highest-intent concert buyer on the internet right now. Affiliate commissions on ticket sales are meaningful. This is **easy to implement early** and requires no advertiser relationships.

4. Promoted Placement Artists or promoters pay to have their entity page featured, or to have their upcoming show surfaced to users browsing similar artists. Not traditional ads — more like **native promotion** that fits the experience. "*Fans of this artist also uploaded footage from...*" could be organic or paid.

5. Consumer Subscription — Showside Pro Light premium tier for heavy users:

- Download clips for offline viewing
- Early access to uploads from sold-out shows
- Ad-free experience
- Exclusive "virtual front row" curated cuts

Honestly this is **lower priority** — consumer subscriptions are hard and you need significant scale first.

6. Brand Partnerships A beer brand sponsors the "pit footage" category. A camera brand sponsors the upload experience. A credit card sponsors VIP content. These are real dollars but require a sales team and meaningful traffic — **later stage**.

The Honest Prioritization

Stream	When	Why
Artist dashboard SaaS	Post-traction, pre-scale	Doesn't need millions of users
Ticketing affiliate	Early — V1.5	Easy to implement, high intent audience


Licensing marketplace	Medium term	Needs content volume first
Promoted placement	Medium term	Needs traffic first
Brand partnerships	Late	Needs sales infrastructure
Consumer subscription	Late	Needs scale and habit formation

The Strategic Insight

Most UGC platforms monetize the **audience** (ads). Showside has a more interesting opportunity to monetize the **content itself** — because the content has verified provenance (real event, real date, real location) which makes it licensable and commercially valuable in a way that a random TikTok isn't.

That's the angle that makes this genuinely differentiated as a business, not just as a product.

Want to keep thinking through this or get back into the build?



You said: how can we maybe gameify this a bit to drive even more uploads - ie.

how can we maybe gameify this a bit to drive even more uploads - ie. if you upload a video of a full song it gets featured higher on the page, most liked video gets a badge/points, etc etc - brainstorm this for me.

May 25



Claude responded: Love this direction — gamification done right makes uploading feel like contributing to something, not just posting content.

Love this direction — gamification done right makes uploading feel like contributing to something, not just posting content. Here's a full brainstorm:

The Core Principle

The best gamification for Showside isn't points for points sake — it's **status within the fan community**. A Morgan Wallen superfan cares deeply about being recognized as someone who was there and contributed. Lean into that identity.

Uploader Reputation System

Showside Score — a running score per user built from:

- Videos uploaded (base points)
- Full song captured (bonus points)
- Likes received on uploads
- How many events contributed to
- How early you uploaded after the show

Displayed as a subtle badge on your profile. Not gamey numbers — more like a **tier system**:

-  **Attendee** — uploaded once
-  **Regular** — 5+ uploads across shows
-  **Superfan** — 20+ uploads, high likes
-  **Legend** — top contributor for a specific artist

The Legend tier is the one people chase. "I'm the #1 Morgan Wallen uploader on Showside" is a real identity for a certain type of fan.

Content Quality Incentives

Full song bonus Video over 2.5 minutes gets a "Full Song" badge on the card and surfaces higher in the setlist view. You mentioned this — it's smart because it directly improves the virtual attendance experience.

First upload bonus First person to upload from a specific show gets a "First There" badge permanently on that media. Early upload behavior is incredibly valuable — you want footage up before the buzz dies.

Coverage completeness If uploads collectively cover every song in a setlist, the event page gets a "**Full Show Captured**" banner. This creates collaborative pressure — fans see which songs are missing and go hunting in their camera roll.

Rarity badge If only 1-2 people filmed a specific moment — a surprise guest, a rarely played deep cut — that clip gets a "**Rare Moment**" badge. Scarcity = perceived value.

Social / Competitive Mechanics

Show leaderboard Each event page has a top contributors list — "Most uploaded from this

show." Small but visible. Creates friendly competition among fans who attended the same night.

Artist leaderboard Across all shows for an artist — who has contributed the most to this artist's archive. This is the one superfans will actually care about deeply.

Streak system Uploaded from 3 shows in a row? You're on a streak. Displayed on profile. Encourages repeat behavior across the touring season.

City champion Top uploader from each city gets a subtle geo badge. "Chicago's top contributor" means something to a local fan community.

Discovery / Curation Incentives

Community picks Top liked clip of each show gets automatically featured in the hero position on the event page. The uploader gets notified — *"Your clip was voted the best moment from last night's show."* That notification is incredibly motivating.

Setlist MVP Most liked clip for each song on the setlist gets a small crown. Visible to everyone browsing that song's clips. Creates competition per song not just per show.

Editor's picks Manual curation by Showside (or eventually community moderators) — a human selects the best clip of the week across all shows. Featured on the homepage. The uploader gets a permanent "Editor's Pick" badge on that clip.

Upload Completion Mechanics

Progress bar on event page "This show is 60% captured" — based on setlist songs with at least one clip. Fans see the gap and fill it.

Missing songs prompt *"Nobody has uploaded Wallen's 'Sand In My Boots' from this show yet — do you have it?"* Sent as a notification to people who uploaded from that event. Direct call to action.

Collective milestone celebrations When a show hits 100 uploads, everyone who contributed gets a notification — *"The Nashville show just hit 100 uploads — you're one of the fans who made it happen."* Belonging, not just points.

Lightweight Profile / Identity Layer

Not a full social network — but enough to make contribution feel visible:

- Public profile page showing your shows attended, uploads, badges earned
- Shareable — *"Check out my Showside archive"* — which is also a distribution mechanic
- Favorite artist stats — *"You've uploaded from 7 Morgan Wallen shows"*

This is the thing that converts a one-time uploader into a habitual contributor. Identity investment.

What NOT to Do

- **Don't make it feel like work.** Points systems that feel like chores kill motivation. Everything should feel like recognition, not obligation.
- **Don't over-engineer V1.** The first version of gamification is probably just: Full Song badge + First There badge + show leaderboard. That's enough to test if it moves behavior.
- **Don't reward quantity over quality.** If uploading 50 blurry photos scores more than one incredible video you've broken the incentive structure.


V1 Gamification Shortlist

If you had to pick 3 things to ship first:

- 1 **"Full Song" badge** — directly improves content quality, easy to implement
- 2 **"First There" badge** — drives early upload behavior, just a timestamp check
- 3 **Show leaderboard** — visible on event page, creates community competition without requiring accounts

Everything else is V2 and beyond.

Want to think about how any of these integrate into the schema or upload flow?



You said: looking across apps in the App Store that are in the same similar realm it seems like most of the apps are for individuals to track their concert attendance pe...



looking across apps in the App Store that are in the same similar realm it seems like most of the apps are for individuals to track their concert attendance personally. It would be cool if we could add in that feature as well to allow people to track their own attendance at these concerts as that

seems to be something that a lot of concertgoers like doing

May 25



Claude responded: Great research — and you're right, that's a clear pattern across all 7 of these apps.

Great research — and you're right, that's a clear pattern across all 7 of these apps. Let me break down what you're seeing:

What These Apps Are

Every single one is a **personal diary/tracker** — built for the attendee to log their own history:

- **Concerts Remembered** — rate, remember, relive your shows
- **Live Music Archive** — log shows you've attended (Grateful Dead/jam band focused)
- **Encore: Concert Diary** — "every show, one place", personal stats
- **Momento: Live Events** — sports + music attendance tracker, personal timeline
- **Concert Memory Archive** — write stories about shows you attended
- **NEXFES** — concert journal and log
- **RAVR** — ranked personal concert archive

None of them are community platforms. None have fan-uploaded media that non-attendees can browse. They're all **inward-facing** — about *your* history, not *the show's* history.

The Opportunity This Reveals

These apps exist because **concert attendance tracking is a genuine behavior** people want. The demand is proven by 7 separate apps in the same category.

But every single one stops at the personal level. None of them answer the question: *what if your personal archive connected to a shared community archive of the same show?*

That's the gap Showside fills — and adding a personal tracking layer on top makes it dramatically stickier.

How It Fits Into Showside

The personal tracking feature isn't a detour — it's actually a **perfect acquisition funnel**:

User logs "I attended this show"



They see the community uploads from that show



They remember they have footage on their phone



They upload it

The tracker creates the emotional connection to the show that converts a passive user into an uploader. It's the missing top of the funnel.

What The Feature Looks Like

Core — dead simple:

- "I was there" button on any event page
- Show gets added to your personal attended list
- Profile shows your show count, artists seen, cities visited

Stats layer (what makes it addictive):

- Total shows attended
- Unique artists seen
- Venues visited
- Streak — shows attended this year
- First show ever logged
- Most seen artist

The shareable card — this is the distribution mechanic:

- Auto-generated graphic: "I've seen Morgan Wallen 7 times across 5 cities"
- Share to Instagram story — drives new users back to Showside
- Annual wrapped moment — "Your 2025 in shows"

Convergence with uploads:

- Your attended shows show which ones you've uploaded from vs haven't
- Gentle nudge: "You attended this show — do you have footage?"

How It Differentiates From These Apps

Every app you found is **attendee-only**. Your tracker on Showside has something none of them have:

When you log "I was there" — you land on a page full of community footage from that exact show. Your personal memory connects to a shared archive. The show exists beyond your phone.

That's the feature none of these 7 apps can offer. The tracker isn't the product — it's the **on-ramp**

to the community.

Schema Impact

Minimal. You basically already have it:

```
attended_events table
- user_id
- event_id
- attended_at (timestamp)
- seat_section (optional)
- notes (optional)
```

Or even simpler — a boolean flag on the existing relationship between users and events. The stats are all derived queries from that single table.

V1 Shortlist For This Feature

- 1 "I was there" button on event page — one tap, logged
 - 2 Profile page showing attended shows count + list
 - 3 Shareable stat card — this is the growth mechanic worth prioritizing
- Everything else (wrapped, streaks, notes) is V2.

Want to think about how the profile page looks, or get back into the build?



You said: "Full Song" badge would be great to add to v1

"Full Song" badge would be great to add to v1

May 25



Claude responded: Easy call — it's one of the highest-signal badges because it directly improves the viewing experience and rewards the behavior you most want.

Easy call — it's one of the highest-signal badges because it directly improves the viewing experience and rewards the behavior you most want.

Here's exactly what it needs:

Logic

When a video is uploaded, check duration on the Mux webhook response. Mux returns `duration` in seconds on the `video.asset.ready` event.

`duration >= 150 seconds (2.5 min) → badge = true`

You could tune that threshold — 2 minutes might be more inclusive, 3 minutes more strict. 2.5 feels right for "this is a real song capture not a 30-second clip."

Schema

One column addition to the `media` table:

sql

```
ALTER TABLE media ADD COLUMN is_full_song BOOLEAN DEFAULT FALSE;
```

Set it in the Mux webhook handler alongside the existing status flip:

typescript

```
if (duration >= 150) {  
  updates.is_full_song = true;  
}
```


Display

- Small badge on the video card — "Full Song" or just a 🎵 icon with a label
- In the setlist/song filter view — full song clips surface first within that song's results
- Subtle — it shouldn't dominate the card, just signal quality to browsers

That's It

One DB column, ~3 lines of logic in the webhook handler, one badge component in the UI. Probably 30 minutes of work inside Claude Code.

Want to knock it out now or keep it on the list for Phase 5/6?



You said: and lets add a simple profile page also to v1.

and lets add a simple profile page also to v1. give me the instructions i should give to claude code to build these out. also, i think we were last at the phase 5 build - lets continue with that also

May 25



Claude responded: Here's everything you need to give Claude Code — broken into clear tasks:

Here's everything you need to give Claude Code — broken into clear tasks:

Task 1 — Full Song Badge

Add a "Full Song" badge to videos that capture a complete song.

Schema change:

- Add `is\_full\_song BOOLEAN DEFAULT FALSE` to the media table
- Create migration: supabase/migrations/[timestamp]_add_full_song_badge.sql

Webhook update:

- In the Mux webhook handler (app/api/mux-webhook/route.ts), when handling the video.asset.ready event, check the duration field from the Mux payload
- If duration >= 150 seconds, set is_full_song = true when updating the media row to status = 'active'

UI:

- Add a small "Full Song" badge to video cards where is_full_song = true
- Use a music note icon (Heroicons) + "Full Song" label
- Style: small pill, subtle — doesn't overpower the card
- In the song/setlist filter view on the event page, sort full song videos first within results

Task 2 — Profile Page

Build a simple user profile page at /profile/[username] (and /profile/me for the logged-in user).

Database:

- Add `username TEXT UNIQUE` and `bio TEXT` columns to the users table
- Add `attended\_events` table:

```
CREATE TABLE attended_events (  
  id UUID PRIMARY KEY DEFAULT gen_random_uuid(),  
  user_id UUID REFERENCES users(id) ON DELETE CASCADE,  
  event_id UUID REFERENCES events(id) ON DELETE CASCADE,  
  attended_at TIMESTAMPTZ DEFAULT NOW(),  
  UNIQUE(user_id, event_id)  
);
```
- Enable RLS: users can insert/delete their own rows, all rows are publicly readable

API routes needed:

- POST /api/attendance-toggle — toggle attended status for an event (same pattern as like-toggle: check exists → insert or delete)

UI — Profile page sections:

1. Header: avatar (initials fallback), display name, username, bio, join date, edit button (own profile only)
2. Stats row: [X Shows] [X Artists] [X Uploads] [X Likes received]
3. Shows Attended grid: event cards with artist name, venue, date — most recent first, max 12 shown then "View all"
4. Uploads grid: their media uploads, same card style as event page

Event page addition:

- Add "I Was There" button on each event page
- Authenticated: toggles attendance, updates count
- Unauthenticated: prompts soft sign-up (same pattern as post-upload account prompt)
- Show attendee count: "247 fans were here"

Profile is publicly viewable. Edit only for own profile.
Use existing Supabase auth session for ownership checks.
Dark theme consistent with rest of app.

Task 3 — Phase 5 Upload Flow

Technical notes:

- All uploads are anonymous (no auth required) — use existing session token
- Use existing API routes exactly as built — don't modify them
- Show upload speed / estimated time remaining if possible
- Handle errors per-file: failed files shown in red with retry button
- Mobile-first: all tap targets minimum 44px, thumb-friendly layout
- Accessible from: event page Upload tab, homepage CTA, direct URL /upload

How To Feed These To Claude Code

Give them **one task at a time** in this order:

- 1 Task 1 (Full Song Badge) — smallest, good warm-up, touches the webhook you need working anyway
- 2 Task 2 (Profile Page) — medium complexity, sets up the attendance infrastructure
- 3 Task 3 (Phase 5 Upload Flow) — biggest, save for last so the DB and auth patterns are solid first


For each task, paste the block above and add:

Project is at ~/Projects/showside.

Use existing patterns and components already in the codebase.

After building, tell me what to test and how.

Want me to also draft the Phase 6 instructions while you're getting these underway?



You said: this was for task 2 response.

this was for task 2 response. i already completed task 1

Sizable spec. Note before I start: users.username and users.bio already exist from migration 0001_init.sql, so the migration is mostly the new attended_events table + RLS + a few updates to existing tables/triggers. Building this end-to-end: Created a file, ran a command, used 8 tools Migration on your clipboard (74 lines) — paste/run in the Supabase SQL editor while I keep building. Continuing with auth helpers, API routes, pages, and event-page integration: Created 13 files, ran a command, read a file, edited a file, used 10 tools Typecheck and verify: Ran 2 commands, used 2 tools Typecheck clean (the outer tsc exit: was empty because the shell intercepted PIPESTATUS — confirmed via re-run). Checking if the dev server is still up: Ran 3 commands Confirmed — "0 fans were here" rendered correctly (React inserted HTML-comment text-node separators that hid it from my grep). The event page even handles the missing-table case gracefully (count ?? 0), so nothing 500s. Updated todos Profile + attendance feature

complete. All 7 tasks (23–29) done, typecheck clean, smoke tests green. Layer Status Migration 0005_attendance.sql (clipboard) ⌚ Needs to be applied in Supabase SQL editor before the toggle endpoint and real counts work lib/auth.ts — getCurrentUser / getCurrentProfile ✓
POST /api/attendance/toggle ✓ (401 anon, toggle for authed, returns fresh count) POST /api/auth/{signup,signin,signout} ✓ Signup uses admin createUser + email_confirm: true so dev signups skip the email-verification roundtrip /signup, /signin pages + client forms ✓ Honor ? next=; signup honors ?attend=<eventId> for the soft-signup-then-attend path /profile/[username] ✓ Header (avatar/initials, display name, @handle, bio, join date, Edit + Sign out for own), 4-stat row (Shows / Artists / Uploads / Likes received), Shows-attended grid (max 12 + "View all"), Uploads grid /profile/me ✓ Redirects to /signin?next=/profile/me (anon) or /profile/<username> (authed) components/attendance-button.tsx ✓ Filled "I was there" pill (white) flips to outlined emerald check when toggled. Anon click → /signup?next=<event>&attend=<eventId> (soft signup) components/sign-out-button.tsx ✓ Event page integration ✓ Attendance button + "X fans were here" count rendered under the stat strip
Smoke tests: Route Result /signup ✓ 200 /signin ✓ 200 /profile/me (anon) ✓ 307 → /signin?next=/profile/me /profile/no-such-user ✓ 404 Event page (no migration yet) ✓ 200, button renders, count shows 0 Things to know: Schema note. users.username and users.bio already existed from 0001_init.sql. The migration's add column if not exists lines are no-ops on the current schema but keep it portable to a fresh DB. The real work in the migration is the attended_events table + RLS + a users.show_count trigger so the profile stat stays accurate. Dev-mode signup is instant. I went with admin.createUser({ email_confirm: true }) + an immediate signInWithPassword so you don't need email infrastructure to test. For production you'd switch to supabase.auth.signUp(...) and wire up Supabase's email templates. Soft signup carries intent forward. Click "I was there" while signed out → URL becomes /signup?next=<event>&attend=<eventId>. After the signup completes, the form calls /api/attendance/toggle with that event ID before redirecting back to the event page. You land back where you started, signed in, and already attending. Edit profile (/profile/me/edit) is not built yet — the button is there but links to a page that 404s. Easy follow-up if you want it. Once you apply the migration, try the full loop: /signup → make a user Land on /profile/<username> (Shows: 0) Go to an event page → "I was there" → page refresh shows 1 fan Back to /profile/me → Shows: 1 Say if you want me to build the profile-edit page next, or move on.

Show more

May 25



Claude responded: That's a clean build — Claude Code

handled it well.

That's a clean build — Claude Code handled it well. A few things to do before moving on:

Right Now — Apply The Migration

Go to Supabase SQL editor and run the migration it put on your clipboard (0005_attendance.sql). Nothing works correctly until that's done.

Then run the smoke test loop it suggested:

- 1 `/signup` → create a user
- 2 Go to an event page → tap "I was there"
- 3 Check `/profile/[username]` → Shows count should be 1

Quick Decisions Before Task 3

Two things Claude Code flagged that need a call:

Profile edit page — it built the button but the page 404s. Do you want it built before moving to the upload flow, or is it fine as a post-launch item? Functionally it's low priority for V1 since most early users will be anonymous uploaders, not profile builders.

Dev signup vs production signup — it used `email_confirm: true` so you can test without email infrastructure. That's fine for now, just remember to swap it before any real launch or beta.

When Ready — Task 3

Once migration is applied and smoke tests pass, paste the Task 3 block with:

Task 1 (Full Song badge) and Task 2 (Profile + Attendance) are complete.

Moving to Task 3 — the Phase 5 upload flow.


Project is at `~/Projects/showside`.

Use existing patterns and components already in the codebase.

After building, tell me what to test and how.

The upload flow is the most critical build in the whole project — it's the make-or-break UX moment. Take your time reviewing it when it's done before moving to Phase 6.

Want me to draft the Phase 6 instructions now so they're ready to go?



You said: task 3 result:

Sizable build. The user spec mentions section labels (Pit / Floor / Seated / VIP / Outside / Concourse) that aren't in my current section_tag CHECK constraint, so I'll extend the enum via a small migration (the API route's validation reads from SECTION_ORDER in lib/types.ts, so widening that constan

pasted

task 3 result:

May 25



Claude responded: Really clean build — the upload flow is the heart of the product and it sounds like Claude Code nailed the architecture.

Really clean build — the upload flow is the heart of the product and it sounds like Claude Code nailed the architecture.

Do This First

Apply migration 0006 in Supabase SQL editor, then run the test sequence in order:

- 1 **Happy path** — search → select event → pick files → section pill → watch progress → success screen → view show
- 2 **Deep link** — `/upload/[event-slug]` skips step 1
- 3 **Limits** — 21st file error, 500MB error
- 4 **"Can't find your event?"** — verify row appears in Supabase
- 5 **Video** — set up ngrok if you want the full webhook loop to test the Full Song badge end to end

The HEIC note is worth remembering for when you do real device testing — Safari on iPhone is the primary upload device for this whole product.

Where You Stand

Phase	Status
Phase 1 — Scaffold + schema	✓
Phase 2 — API routes	✓
Phase 3 — Admin panel	✓
Phase 4 — Public pages	✓
Phase 5 — Upload flow	✓
Full Song badge	✓
Profile + attendance	✓
Phase 6 — Polish	⌚
Design pass	⌚

Phase 6 Instructions — Ready To Go

Once you've tested and are happy with Phase 5, paste this:

Moving to Phase 6 — SEO polish, performance, and finishing touches.
Project is at ~/Projects/showside.

1. VIEW COUNT DEDUP

- Add a media_views table:

```
CREATE TABLE media_views (
  media_id UUID REFERENCES media(id) ON DELETE CASCADE,
  session_token TEXT NOT NULL,
  viewed_at TIMESTAMPTZ DEFAULT NOW(),
  UNIQUE(media_id, session_token)
);
```
- On fullscreen viewer open: POST /api/view — inserts row if not exists, increments media.view_count only on first view per session
- Same pattern as existing like-toggle

2. INFINITE SCROLL

- Event page Browse tab: currently loads all media at once
- Add cursor-based pagination: page size 24, load more on scroll to bottom (IntersectionObserver)
- Entity page fan highlights grid: same treatment if > 24 items
- Keep existing filter/sort working with pagination

3. FOOTER PAGES

Build simple dark-themed pages for:

- /about — what Showside is, the mission, "the show from everyone who was there"
- /dmca — standard DMCA takedown policy and contact form (saves to a dmca_requests table: url, description, contact_email, created_at)
- /privacy — standard privacy policy
- /terms — standard terms of service
- /contact — simple contact form (saves to contact_submissions table)

Add footer component to all public pages with links to these

4. PROFILE EDIT PAGE

Build /profile/me/edit (currently 404s):

- Edit display name, bio (textarea, 160 char limit)
- Avatar: initials only for V1, no image upload yet
- Save calls PATCH /api/profile
- Cancel returns to profile

5. LIGHTHOUSE / PERFORMANCE


- Add loading skeletons to entity page, event page, profile page (replace any layout shift with skeleton components)
- Ensure all images use next/image with proper width/height
- Add blur placeholder to media thumbnails
- Verify meta tags, OG images, canonical URLs on all public pages (JSON-LD structured data already exists from Phase 4 — just verify)
- Add /sitemap.xml dynamic generation if not already present

After each section tell me what to test.

One Thing Worth Noting

The profile edit page is the only loose end from Task 2 — it's in the Phase 6 instructions above so it gets cleaned up in the same pass as the rest of the polish work.

Ready to run the Phase 5 tests?



You said: it built the upload flow and it looks great - i tested uploading an actual file and it said it uploaded but i don't see it in the event uploads - was it actual...

it built the upload flow and it looks great - i tested uploading an actual file and it said it uploaded but i don't see it in the event uploads - was it actually supposed to be able to upload/hold real

files at this point, or are we still just building flow/structure UI?

May 25



Claude responded: It should be uploading real files at this point — the API routes were built and curl-tested back in Phase 2, and the upload flow is wired to those real endpoint...

It should be uploading real files at this point — the API routes were built and curl-tested back in Phase 2, and the upload flow is wired to those real endpoints. So something is breaking in the actual transfer, not the UI.

Let's diagnose it quickly.

Most Likely Culprits

1. Mux webhook not firing locally Videos stay at `status = 'uploading'` forever until the `video.asset.ready` webhook fires. Since you're on localhost, Mux can't reach you. So video uploads appear to succeed but never show up in Browse because they never flip to `active`.

Photos should show up immediately though — they don't need a webhook. If you uploaded a photo and it's not showing, that's a different issue.

Quick Diagnosis

Go to Supabase and run:

```
sql
SELECT id, status, media_type, created_at
FROM media
ORDER BY created_at DESC
LIMIT 10;
```

This tells you everything:

Result

No rows at all

Means

Upload isn't reaching the DB — API route issue

Rows with `status = 'uploading'`

Files are landing but webhook isn't firing (expected for video on localhost)


Rows with `status = 'active'`

Upload worked — check why they're not displaying

What Did You Upload?

- **Photo only** → should be visible immediately, something else is wrong
- **Video only** → expected behavior on localhost, needs ngrok to complete
- **Both** → photo should show, video shouldn't

Tell me what the Supabase query returns and what file type you tested and I can pinpoint exactly what to fix.




Claude responded: The column is named differently than expected.

The column is named differently than expected. Run this first to see the actual column names:

```
sql
SELECT column_name
FROM information_schema.columns
WHERE table_name = 'media'
ORDER BY ordinal_position;
```

That'll show you exactly what the media table columns are called. Paste the results back here and we'll know immediately whether it's a naming mismatch in the schema or something deeper.

My guess is the column is called `type` or `file_type` instead of `media_type` — but let's confirm before assuming anything.





May 25



Claude responded: Column is filetype not mediatype.

Column is `file_type` not `media_type`. Now run this to see what actually uploaded:

sql

```
SELECT id, status, file_type, created_at  
FROM media  
ORDER BY created_at DESC  
LIMIT 10;
```

This will tell us immediately if rows are being created at all, and what status they're stuck at.



May 25



Claude responded: Everything is working correctly.

Everything is working correctly. Here's exactly what you're seeing:

Photos — fully working  The 5 `active` photo rows from 15:20 are live and should be visible in the event page Browse tab right now. If you're not seeing them, that's a display bug worth checking.

Videos — stuck at `uploading` as expected  All 3 video rows are `status = 'uploading'` — this is the localhost/webhook issue we discussed. Mux has the actual video file, but it can't call back to your localhost to fire the `video.asset.ready` webhook, so the status never flips to `active`.

One removed row — something was moderated or deleted, ignore that.

Two Things To Do

1. Check why photos aren't showing in the UI

They're **active** in the DB so they should be rendering. Go to the event page Browse tab and check. If they're not there, give Claude Code this:


Photos are uploading successfully (status = active in DB) but not appearing in the event page Browse tab. Check the Browse tab query — it may be filtering by something that excludes these rows, or the storage_url may not be rendering correctly for R2 photos.

2. Fix videos for local testing with ngrok

ngrok http 3000

Copy the public URL it gives you, go to your Mux dashboard → Webhooks, set the endpoint to `https://[your-ngrok-url]/api/mux-webhook`. Then upload a video — the webhook will fire, status flips to **active**, and it appears in Browse.

The core upload pipeline is genuinely working. This is further along than it looks.



You said: to clarify, the morgan wallen photos we uploaded are showing fine - its just the test videos i just tried to upload i don't see yet - maybe they are just still...

to clarify, the morgan wallen photos we uploaded are showing fine - its just the test videos i just tried to upload i don't see yet - maybe they are just still being processed?

May 25



Claude responded: Yes exactly — that's completely normal

and expected.

Yes exactly — that's completely normal and expected. Nothing is broken.

The videos are sitting at `uploading` status because Mux processed the file fine but can't reach your localhost to fire the webhook. That's the only missing piece.

The full video flow is:

- Upload to Mux ✓
- Mux transcodes it ✓
- Mux fires webhook → your /api/mux-webhook ✗ (can't reach localhost)
- Status flips to 'active' ⌚ never happens without webhook
- Video appears in Browse ⌚ never happens without active status


Everything is working. You just need ngrok to complete the loop locally:

```
bash
ngrok http 3000
```

Paste the public URL into Mux dashboard → Webhooks → your endpoint becomes `https://abc123.ngrok.io/api/mux-webhook`. Upload a new test video and it'll go all the way through within 30-60 seconds.

The photos working perfectly is actually the more important proof — it confirms the whole upload pipeline, DB writes, R2 storage, and display are all solid. Videos are one webhook configuration away from working identically.

Ready to move to Phase 6, or do you want to get ngrok set up first?



You said: paste it where?

 paste it where?

May 25




Claude responded: You're in the right place.

You're in the right place. Click into the **Showside** environment, then look for **Webhooks** in the left sidebar.

The steps:

- 1 Click **Showside** environment
- 2 Find **Webhooks** in the left nav
- 3 Click **Add webhook** (or **Create webhook**)
- 4 Paste your ngrok URL as: `https://[your-ngrok-url]/api/mux-webhook`
- 5 Select the event: `video.asset.ready`
- 6 Save

But you need ngrok running first to get that URL. In your terminal:

```
bash
```

```
ngrok http 3000
```

It'll output something like:


```
Forwarding https://abc123.ngrok.io -> localhost:3000
```

That `https://abc123.ngrok.io` part is what you paste in — just add `/api/mux-webhook` to the end.

Do you have ngrok installed? If not:

```
bash
```

```
brew install ngrok
```



You said: i can see the three test videos i uploaded



i can see the three test videos i uploaded

May 25



Claude responded: All 3 videos are in Mux with status Ready — so Mux has them, transcoded them, everything worked perfectly on that end.

All 3 videos are in Mux with status **Ready** — so Mux has them, transcoded them, everything worked perfectly on that end.

The only missing piece is the webhook firing back to your app to flip them from **uploading** to **active** in your DB.


Look in the left sidebar — you should see **Webhooks** under the ENV section near the bottom. Click that and add your ngrok URL there.

But honestly — for right now this is enough proof that the full pipeline works. You could skip ngrok locally and just **deploy to Vercel first**. Once you're on a real URL:

- 1 Set the Mux webhook to your Vercel URL `/api/mux-webhook`
- 2 Upload a test video
- 3 It goes all the way through automatically — no ngrok needed

That might be the cleaner next step anyway since Phase 6 is mostly polish work that's easier to QA on a real deployment.

Your call — ngrok now to test locally, or deploy to Vercel and test everything on a real URL?



You said: huh?

huh? give me the steps to do

May 25



Claude responded: Sorry — here's exactly what to do:

Sorry — here's exactly what to do:

Step 1 — Run ngrok in terminal

```
bash
```

```
ngrok http 3000
```

You'll see output like:

```
Forwarding https://abc123.ngrok-free.app -> localhost:3000
```

Copy that `https://abc123.ngrok-free.app` URL.

Step 2 — Add webhook in Mux

In the Mux dashboard left sidebar, click **Webhooks** (under ENV section).

Then:

- 1 Click **Add webhook**
- 2 Paste: `https://abc123.ngrok-free.app/api/mux-webhook`
- 3 Save

Step 3 — Flip existing videos manually

The 3 videos already in Mux are Ready but your DB doesn't know it. Easiest fix — run this in Supabase SQL editor to manually activate them:

```
sql
```

```
UPDATE media
```

```
SET status = 'active'
```

```
WHERE file_type = 'video'
```

```
AND status = 'uploading'
```

```
AND created_at > '2026-05-25';
```


That'll make them appear in Browse right now without waiting for the webhook.

Step 4 — Test a new video upload

Upload one more test video through the upload flow. This time the webhook fires, status flips

automatically, and you see it appear in Browse within 30-60 seconds.

That confirms the full end-to-end loop is working.



Claude responded: ngrok isn't installed.

ngrok isn't installed. Install it first:

bash


brew **install** ngrok/ngrok/ngrok

Wait for it to finish, then run:

bash

ngrok http 3000

If you don't have Homebrew either it'll say `brew: command not found` — let me know if that happens.



Claude responded: ngrok installed but needs a free account.

ngrok installed but needs a free account. Quick:

- 1 Go to <https://dashboard.ngrok.com/signup> and create a free account
- 2 Once signed in, go to <https://dashboard.ngrok.com/get-started/your-authtoken> and

- copy your authtoken
- 3 Run this in terminal (paste your actual token):

bash


ngrok config add-authtoken YOUR_TOKEN_HERE

- 4 Then run:

bash

ngrok http 3000

Should work after that.



May 25

Claude responded: ngrok is running.

ngrok is running. Your public URL is:

<https://accurate-flatfoot-flavorful.ngrok-free.dev>


Now go to Mux dashboard:

- 1 Click **Webhooks** in the left sidebar
- 2 Click **Add webhook**
- 3 Paste this exact URL:

<https://accurate-flatfoot-flavorful.ngrok-free.dev/api/mux-webhook>

- 4 Save

Then come back here and we'll run the SQL to manually activate the 3 existing videos, and test a fresh upload end to end.



You said: done

done

May 25



Claude responded: Now run this SQL in Supabase to manually activate the 3 existing videos:

Now run this SQL in Supabase to manually activate the 3 existing videos:

sql

```
UPDATE media
SET status = 'active'
WHERE file_type = 'video'
AND status = 'uploading'
AND created_at > '2026-05-25';
```

Then go to the event page Browse tab — the 3 videos should appear immediately.

After that, upload one fresh test video through the upload flow and watch it go all the way through automatically within 30-60 seconds. That confirms the full webhook loop is working.



You said: done but page not loading



done but page not loading

May 25



Claude responded: Your Next.

Your Next.js dev server stopped running. Opening ngrok in that terminal window killed it.


Open a **new terminal window** and run:

```
bash
```

```
cd ~/Projects/showside
```

```
npm run dev
```

Then go back to `localhost:3000/morgan-wallen` and it should load again.



You said: great i see them, looks like they're still processing



great i see them, looks like they're still processing

May 25



Claude responded: This is all looking great.

This is all looking great. A few things to note:

Image 1 — event page looking solid

- 6 uploads, 4 videos, 2 photos showing correctly
- "I was there" button is working (1 fan was here — that's you)
- Fan highlights grid is rendering with the seed data photos looking cinematic
- The 4 video cards showing "pr..." are the manually activated videos — thumbnails still generating from Mux

Image 2 — "Video still processing" This means the SQL update flipped status to `active` but the `mux_playback_id` is still null — so the player has no ID to play. The webhook needs to fire to write that playback ID.

Run this in Supabase to check:

```
sql
```


```
SELECT id, status, mux_playback_id, mux_asset_id  
FROM media  
WHERE file_type = 'video'
```

```
ORDER BY created_at DESC
LIMIT 5;
```

If `mux_playback_id` is null on those rows, the webhook hasn't fired yet.

To trigger it — upload one brand new test video now through the upload flow. With ngrok running and the webhook configured, it should fire automatically and you'll see it appear in Browse within 60 seconds, fully playable.

The existing 3 videos may need their playback IDs backfilled manually from the Mux dashboard — we can do that after confirming the new upload works end to end.



Claude responded: As expected — all 4 videos have muxplaybackid = NULL because the webhook never fired for these.

As expected — all 4 videos have `mux_playback_id` = NULL because the webhook never fired for these. We need to backfill them from Mux.

Go to your Mux dashboard → Showside environment → Video Assets. You'll see the 3 videos from today. For each one click in and grab two values:

- **Asset ID** (looks like `abc123xyz`)
- **Playback ID** (looks like `def456uvw`)


Then run this in Supabase for each video, matching by the order they were uploaded. We'll do one at a time:

```
sql
UPDATE media
SET
  mux_asset_id = 'PASTE_ASSET_ID_HERE',
  mux_playback_id = 'PASTE_PLAYBACK_ID_HERE'
WHERE id = 'PASTE_MEDIA_ROW_ID_HERE';
```

The media row IDs are visible in your Supabase results:

- 058e68ac-a24a-40a2-8345-381adac04aeb
- c2670769-e780-472d-988d-f9ff6c39ff96
- bdfed390-607a-427b-888f-6bef1d129224
- 5a9b16a2-024e-4263-8d8f-fd5a0f64d8b8

Go grab those Mux IDs and paste them here — I'll write the exact SQL to run.



You said: give me a prompt to have claude code do this work

give me a prompt to have claude code do this work

May 25




In the Mux dashboard I can see 4 video assets that were uploaded but never had their webhook fire, so mux_playback_id and mux_asset_id are NULL in the media table for these rows:

- 058e68ac-a24a-40a2-8345-381adac04aeb
- c2670769-e780-472d-988d-f9ff6c39ff96
- bdfed390-607a-427b-888f-6bef1d129224
- 5a9b16a2-024e-4263-8d8f-fd5a0f64d8b8

Please write a small Node.js script I can run once from the terminal that:

1. Uses the Mux API to list all video assets in the Showside environment
2. For each asset, finds the matching media row in Supabase by mux_upload_id (which was saved when the upload was created)
3. Updates that row with the correct mux_asset_id and mux_playback_id
4. Prints a summary of what was updated

Use the existing Mux and Supabase credentials from .env.local.
Save the script as scripts/backfill-mux-ids.ts and give me the command to run it.





May 25



Claude responded: Looking good — Claude Code wrote the script and it's still running (spinning indicator at bottom).

Looking good — Claude Code wrote the script and it's still running (spinning indicator at bottom).

Wait for it to finish then share the output. You should see one line per asset showing whether it updated successfully or skipped. Expected result is 4 rows updated with proper `mux_playback_id` values.



You said: its done

its done

May 25




Claude responded: What did the output say?

What did the output say? Should look something like:

```
✓ 058e68ac: updated 1 row(s) · duration 8s · fullSong=false
✓ c2670769: updated 1 row(s) · duration 34s · fullSong=false
✓ bdfed390: updated 1 row(s) · duration 39s · fullSong=false
✓ 5a9b16a2: updated 1 row(s) · duration Xs · fullSong=false
```

Summary: 4 scanned · 4 updated · 0 errored

Paste the output or screenshot it and we'll know if the backfill worked. Then go refresh the event page — videos should be fully playable.



You said: where do i run that comand.

where do i run that comand...?

May 25



Claude responded: In your terminal — the one that's running the dev server is occupied, so open a third terminal window and run:

In your terminal — the one that's running the dev server is occupied, so open a **third terminal window** and run:


bash

cd ~/Projects/showside

npx tsx --env-file=.env.local scripts/backfill-mux-ids.ts

You should have 3 terminal windows open now:

- 1 **ngrok** running
- 2 **npm run dev** running
- 3 **This script** — runs once and exits




May 25



Claude responded: Type y and hit Enter to install tsx and proceed.


Type `y` and hit Enter to install `tsx` and proceed.



Claude responded: Perfect — 3 rows updated, 0 errors.

Perfect — 3 rows updated, 0 errors. Go refresh the event page now and all 3 videos should be fully playable.

The full pipeline is working. Now upload one fresh test video through the upload flow to confirm the webhook fires automatically end to end — that's the final proof that everything is wired up correctly for future uploads.



You said: it worked!

it worked! i see the videos on the frontend

May 25



Claude responded: The full stack is working end to end:

The full stack is working end to end:

-  Photos upload → R2 → appear immediately
-  Videos upload → Mux → webhook fires → appear in Browse
-  Playback working in the viewer
-  "I was there" attendance tracking
-  Full Song badge logic in webhook handler

-  Profile page
- That's a complete, functional V1 product. Every core user journey works.

What's Left


Item	Priority
Phase 6 — polish, infinite scroll, footer pages, view count dedup	High
Profile edit page	Medium
Design pass	High
Vercel deployment	When ready to share

Recommended Next Step

Before Phase 6 polish, I'd actually suggest **deploying to Vercel first**. Here's why:

- ngrok URL changes every time you restart it — annoying for ongoing video testing
- Once on Vercel you set a permanent Mux webhook URL and never think about it again
- You can share a real URL with anyone you want to test with
- Phase 6 work is easier to QA on a real deployment

Want the Vercel deployment instructions, or go straight into Phase 6?



You said: vercel

vercel

May 25



Claude responded: Here's exactly what to do:

Here's exactly what to do:

Step 1 — Push to GitHub first

In your terminal:

```
bash
cd ~/Projects/showside
git add .
git commit -m "V1 complete - phases 1-5"
git push
```

If you haven't set up a GitHub repo yet:

- 1 Go to **github.com/new**
- 2 Create a new private repo called **showside**
- 3 Then run:

```
bash
git remote add origin https://github.com/YOUR_USERNAME/showside.git
git push -u origin main
```

Step 2 — Deploy to Vercel

- 1 Go to **vercel.com** and sign in
- 2 Click **Add New Project**
- 3 Import your **showside** GitHub repo
- 4 Framework will auto-detect as **Next.js**
- 5 Before clicking Deploy — click **Environment Variables** and add every variable from your **.env.local** file

Your **.env.local** variables — add all of these:

```
NEXT_PUBLIC_SUPABASE_URL
NEXT_PUBLIC_SUPABASE_ANON_KEY
SUPABASE_SERVICE_ROLE_KEY
MUX_TOKEN_ID
MUX_TOKEN_SECRET
MUX_WEBHOOK_SECRET
CLOUDFLARE_R2_ACCESS_KEY_ID
CLOUDFLARE_R2_SECRET_ACCESS_KEY
CLOUDFLARE_R2_BUCKET_NAME
CLOUDFLARE_R2_ENDPOINT
NEXT_PUBLIC_R2_PUBLIC_URL
```

- 6 Click **Deploy**

Step 3 — Update Mux webhook URL

Once Vercel gives you your live URL (something like **showside.vercel.app**):

- 1 Go to Mux dashboard → Webhooks
- 2 Replace the ngrok URL with:


`https://showside.vercel.app/api/mux-webhook`

Step 4 — Update Supabase allowed URLs

- 1 Go to Supabase dashboard → Authentication → URL Configuration
- 2 Add your Vercel URL to **Allowed Redirect URLs**:

`https://showside.vercel.app/**`

That's it. Share your `.env.local` variable names if you're unsure which ones you have and I can help confirm the list.



You said: which terminal window - i have three open



which terminal window - i have three open

May 25




Claude responded: Use the bottom left one (the one running npm run dev) — it's already in the showside directory.

Use the **bottom left one** (the one running `npm run dev`) — it's already in the `showside` directory.

Just click on it and run:

```
bash
git add .
git commit -m "V1 complete - phases 1-5"
git push
```

If it says `no remote` or fails, let me know and we'll set up the GitHub repo first.



Claude responded: It's running but we need to wait and see the result.

It's running but we need to wait and see the result. Scroll down in that terminal window to see if it succeeded or errored.

What does it say below the `git push` line?



You said: nothing below that - maybe still running?

nothing below that - maybe still running?


May 25



Claude responded: It might be waiting for GitHub authentication.

It might be waiting for GitHub authentication. Give it 30 seconds — if nothing happens, press **Enter** once.

If it then shows an error like `remote: Repository not found` or `fatal: no remote`, that means no GitHub repo is set up yet. Let me know what appears and we'll go from there.



You said: i pressed enter and it just added a line - no response yet

i pressed enter and it just added a line - no response yet


May 25



Claude responded: It's probably hung waiting for credentials.

It's probably hung waiting for credentials. Press **Ctrl+C** to cancel it, then let me know what error shows up if any.

Then we'll set up GitHub properly first before trying to push again.



May 25



Claude responded: Good — cancelled cleanly.

Good — cancelled cleanly. No GitHub remote is set up yet. Let's check:

bash

`git remote -v`

Paste what it shows and we'll set up the GitHub repo from there.





May 25



Claude responded: No git repo initialized at all yet.

No git repo initialized at all yet. Let's set it all up:

Step 1 — Initialize git:

bash

cd ~/Projects/showside


git init

git add .

git commit -m "V1 complete - phases 1-5"

Then go to **github.com/new** and create a new private repo called **showside** — don't add any README or .gitignore, just create it empty.

Come back and tell me when it's created and I'll give you the next commands.



You said: i have a github account for roombox - can i use that account or need to set up a fresh one?

i have a github account for roombox - can i use that account or need to set up a fresh one?

May 25




Claude responded: You can absolutely use the RoomBox GitHub account — just create a new repo under that

account called `showside`.

You can absolutely use the RoomBox GitHub account — just create a new repo under that account called `showside`. No need for a separate account.

Go to github.com/new while logged into the RoomBox account, create a private repo called `showside`, leave it completely empty (no README, no `.gitignore`), and click Create.

Then come back and I'll give you the two commands to connect and push.



You said: ok i created a new repo in github

ok i created a new repo in github

May 25



Claude responded: What's the repo URL it showed you?

What's the repo URL it showed you? Should look like:

<https://github.com/roombox-stack/showside>

or similar. Paste it here and I'll give you the exact commands to run.



You said: `https://github.`

<https://github.com/roombox-stack/showside.git>

May 25



Claude responded: Run these three commands one at a time:

Run these three commands one at a time:

```
bash
cd ~/Projects/showside
git init
git add .
Then:
```

```
bash
git commit -m "V1 complete - phases 1-5"
Then:
```

```
bash
git remote add origin https://github.com/roombox-stack/showside.git
git branch -M main
git push -u origin main
```

It may ask for your GitHub username and password. For the password — GitHub no longer accepts your actual password, you need a **Personal Access Token**. If it prompts you:

- 1 Go to **github.com** → **Settings** → **Developer Settings** → **Personal Access Tokens** → **Tokens (classic)**
- 2 Generate new token with **repo** scope
- 3 Copy it and paste it as your password in the terminal

```
? ? ? ?
?
```

You said: run these in terminal?

run these in terminal?


May 25

```
? ?
? ?
```

Claude responded: Yes — in that same terminal window

(bottom left, the one that shows `showside %` at the prompt).

Yes — in that same terminal window (bottom left, the one that shows `showside %` at the prompt).



Claude responded: As expected — GitHub needs a Personal Access Token not your password.

As expected — GitHub needs a Personal Access Token not your password.

Go to: **github.com** → **click your profile photo** → **Settings** → **scroll to bottom** → **Developer settings** → **Personal access tokens** → **Tokens (classic)** → **Generate new token (classic)**

Settings:

- Note: `showside`
- Expiration: 90 days
- Check the **repo** scope checkbox


Click **Generate token**, copy it immediately (you only see it once).

Then run:

`bash`

`git push -u origin main`

When it asks for password — paste the token instead.





Claude responded: It's asking for username again.

It's asking for username again. Type:

roombox-stack

Hit Enter, then when it asks for password — paste your Personal Access Token (not your GitHub password).



May 25



Claude responded: Pushed successfully — 147 files, 3.

Pushed successfully — 147 files, 3.80 MiB up to GitHub.

Now go to **vercel.com** and:

- 1 Click **Add New Project**
- 2 Click **Import Git Repository**
- 3 Select `roombox-stack/showside`
- 4 Before clicking Deploy — click **Environment Variables** and add all your `.env.local` variables
- 5 Click **Deploy**

For the environment variables — open your `.env.local` file in the project and copy each one into Vercel. You can view it by running in terminal:

bash

cat ~/Projects/showside/.env.local

That'll print all the variables you need to add.





You said: did we already create a vercel account.

did we already create a vercel account...? i forget...


May 25



Claude responded: Not sure — check if you can log into vercel.

Not sure — check if you can log into **vercel.com** with your GitHub account (the roombox-stack one). Click **Log in with GitHub** and it'll either take you into an existing dashboard or create a new account automatically.

Either way works — Vercel + GitHub login is the smoothest path.



You said: i connected my github account - but not sure if it connected the showside env directly yet.



i connected my github account - but not sure if it connected the showside env directly yet...

May 25




Claude responded: You're in — Vercel account exists under "Matt P".

You're in — Vercel account exists under "Matt P". No projects yet which is perfect.

Click **Import Project** on the right side, then find and select the `roombox-stack/showside` repo. It'll ask you to connect the roombox-stack GitHub org — approve that and the

repo should appear.



You said: done

done

May 25



Claude responded: Now before you click Deploy you should see an Environment Variables section.

Now before you click Deploy you should see an **Environment Variables** section.


Run this in your terminal to see all your variables:

bash

`cat ~/Projects/showside/.env.local`

Then add each one into Vercel. Don't share the output here — those are secret keys. Just copy them from your terminal directly into Vercel.

Once all variables are added, click **Deploy**.



You said: where do i paste them into vercel?

where do i paste them into vercel?

May 25




Claude responded: On the deployment setup screen there

should be an Environment Variables section — it looks like a form with two fields: Name and Value.

On the deployment setup screen there should be an **Environment Variables** section — it looks like a form with two fields: **Name** and **Value**.

If you don't see it, look for a section that says "**Environment Variables**" or a small arrow/chevron to expand it — it's usually collapsed below the project name and framework settings.

Can you screenshot what you're seeing on the Vercel screen right now?




Claude responded: You're in the wrong place — this is the team-level settings.

You're in the wrong place — this is the team-level settings. You need to be inside the Showside project itself.

Click **Projects** in the left sidebar, then click on the **showside** project, then go to **Settings** → **Environment Variables** from within that project.

The env vars need to be set at the project level not the team level.



You said: hmm thats weird - not projects were found - but e just connected showside.

hmm thats weird - not projects were found - but e just connected showside...

May 25






Claude responded: You may have imported it but not fully deployed yet.

You may have imported it but not fully deployed yet. Go back to the main dashboard:

vercel.com/matt-p-s-projects

Click **Add New...** in the top right → **Project** → and look for the showside repo to import again. This time go all the way through the setup flow — that's where the Environment Variables section appears, right before you click Deploy.



You said: got it



got it

May 25



Claude responded: Perfect — you can see the Environment Variables section and there's an "Import .

Perfect — you can see the **Environment Variables** section and there's an **"Import .env"** button. That's the easiest way.

Click **"Import .env"** and it will let you paste the entire contents of your `.env.local` file at once — no need to add them one by one.

Go to your terminal, run:

```
bash
```

```
cat ~/Projects/showside/.env.local
```

Copy the entire output, then paste it into the Import .env dialog in Vercel.

Important: Make sure `.env.local` is NOT in your GitHub repo (it shouldn't be — it should be in `.gitignore`). You're pasting it directly into Vercel, not committing it.



You said: wait wheres my .

wait wheres my `.env` file located? whats the path

May 25



Claude responded: It's at:

It's at:


`/Users/mpocock/Projects/showside/.env.local`

Run this in terminal to print it:

bash

`cat ~/Projects/showside/.env.local`

Then copy the output and paste into the Vercel Import `.env` dialog.



May 25



Claude responded: The .

The `.env.local` file is hidden in Finder (files starting with `.` are hidden by default). That's why you don't see it.

Just use the terminal to print it — don't need to find it in Finder:

```
bash
```

```
cat ~/Projects/showside/.env.local
```

Run that in terminal, copy the output, paste into Vercel's Import .env dialog.



You said: i ran that but nothing came up

i ran that but nothing came up

May 25




Claude responded: Try this to check if it exists:

Try this to check if it exists:

```
bash
```

```
ls -la ~/Projects/showside | grep env
```

What does it show?



May 25



Claude responded: The env file contents are visible in your terminal — but don't share this screen with anyone, it contains your secret keys.

The env file contents are visible in your terminal — but **don't share this screen with anyone**, it contains your secret keys.

Now go to Vercel, click "**Import .env**" or "**paste the .env contents**" link, and paste everything from the terminal output starting from `# Supabase` all the way to `NEXT_PUBLIC_APP_URL=http://localhost:3000`.


One important change — update this one variable before deploying. The localhost URL won't work on Vercel. Change:

`NEXT_PUBLIC_APP_URL=http://localhost:3000`

to:

`NEXT_PUBLIC_APP_URL=https://showside.vercel.app`

Then click **Deploy**.



You said: paste it where?




paste it where?

May 25



Claude responded: Click the "Import .

Click the "**Import .env**" button at the bottom left. It will open a text box where you can paste all the contents at once.



You said: that button opens a file finder window not a text box

that button opens a file finder window not a text box


May 25



Claude responded: Got it — then click Cancel on that file finder window.

Got it — then click **Cancel** on that file finder window.

Instead click "**paste the .env contents**" — that blue link right next to the Import .env button. That one opens a text box where you can paste everything at once.



You said: even though it says paste i'm telling you there is no where to paste it - that blue link takes me to this page <https://vercel.com/docs/environment-variables>

even though it says paste i'm telling you there is no where to paste it - that blue link takes me to this page <https://vercel.com/docs/environment-variables>

May 25



Claude responded: Got it — skip the import shortcut then.

Got it — skip the import shortcut then. You'll need to add them one by one using the Key/Value fields.

Easiest way: open your `.env.local` in a text editor so you can see all the values clearly:

bash


[open](#) -a TextEdit ~/Projects/showside/.env.local

That'll open the file in TextEdit. Then for each variable, type the key name in the **Key** field and

the value in the **Value** field, click **Add More** to add the next one.

Variables to add:

```
1  NEXT_PUBLIC_SUPABASE_URL
2  NEXT_PUBLIC_SUPABASE_ANON_KEY
3  SUPABASE_SERVICE_ROLE_KEY
4  MUX_TOKEN_ID
5  MUX_TOKEN_SECRET
6  MUX_WEBHOOK_SECRET
7  R2_ACCOUNT_ID
8  R2_ACCESS_KEY_ID
9  R2_SECRET_ACCESS_KEY
10 R2_BUCKET_NAME
11 R2_PUBLIC_URL
12 ADMIN_KEY
13 NEXT_PUBLIC_APP_URL → value: https://showside.vercel.app
```



You said: can claude code do this?

can claude code do this?

May 25



Claude responded: No — Claude Code can't access Vercel's website.

No — Claude Code can't access Vercel's website. But there's a faster way using the Vercel CLI from terminal:

```
bash
npm i -g vercel
vercel login
vercel link
vercel env add
```

Actually even faster — run this single command that pushes all your env vars to Vercel at once:

```
bash
cd ~/Projects/showside
npx vercel env pull --yes
Actually the cleanest approach is:
```


```
bash
cd ~/Projects/showside
npx vercel link
```

It'll ask you to log in and link the project, then run:

```
bash
cat .env.local | while IFS='=' read -r key value; do
  [[ "$key" =~ ^#.*$ || -z "$key" ]] && continue
  echo "$value" | npx vercel env add "$key" production --force
done
```

This loops through every variable in `.env.local` and adds them to Vercel automatically.


Want to try this approach?



Claude responded: You're logged in to Vercel.

You're logged in to Vercel. It's asking about the Claude Code plugin — type N and hit Enter to skip that.

Then it'll continue and we can link the project and push the env vars.





May 25



Claude responded: Run:

Run:

bash

`npx vercel link`


It'll ask you a few questions — answer like this:

- Set up and deploy? **Y**
- Which scope? Select **Matt P's projects**
- Link to existing project? **Y**
- What's the name? **showside**

Then after it's linked run:

bash

`npx vercel env pull --yes`



May 25



Claude responded: It's asking Which team?

It's asking **Which team?** — **Matt P's projects** is already selected. Just hit **Enter** to confirm it.



You said: Link to existing project?


Link to existing project?

May 25



Claude responded: Type Y and hit Enter.

Type Y and hit Enter.



You said: In which directory is your code located?

In which directory is your code located?

May 25



Claude responded: Hit Enter to accept the default .

Hit **Enter** to accept the default . / — your code is in the current directory.



You said: Customize settings?

Customize settings?

May 25



Claude responded: Type N and hit Enter.

Type N and hit Enter.



You said: Do you want to change additional project settings?


Do you want to change additional project settings?

May 25



Claude responded: Type N and hit Enter.

Type N and hit Enter.



May 25



Claude responded: It tried to create a new project with the wrong name.


It tried to create a new project with the wrong name. The project doesn't exist in Vercel yet — you need to create it first through the website, then link to it.

Go back to the Vercel deploy screen in your browser and click **Deploy** — even without the env vars for now. It'll create the project, then we can add the env vars after through the CLI.

Or run this to deploy directly from terminal which will create the project properly:

bash

npx vercel --name showside



You said: 18:57:32.



18:57:32.309 Running build in Washington, D.C., USA (East) – iad1 18:57:32.310 Build machine configuration: 2 cores, 8 GB 18:57:32.426 Cloning github.com/roombox-stack/showside (Branch: main, Commit: 7bdb866) 18:57:32.427 Previous build caches not available. 18:57:32.798 Cloning completed: 372.000ms 18:57:33.128 Running "vercel build" 18:57:33.174 Vercel CLI 54.4.1 18:57:33.377 Installing dependencies... 18:57:35.926 npm warn deprecated rimraf@3.0.2: Rimraf versions prior to v4 are no longer supported 18:57:36.495 npm warn deprecated inflight@1.0.6: This module is not supported, and leaks memory. Do not use it. Check out lru-cache if you want a good and tested way to coalesce async requests by a key value, which is much more comprehensive and powerful. 18:57:37.475 npm warn deprecated @humanwhocodes/config-array@0.13.0: Use @eslint/config-array instead 18:57:37.568 npm warn deprecated @humanwhocodes/object-schema@2.0.3: Use @eslint/object-schema instead 18:57:37.650 npm warn deprecated glob@7.2.3: Old versions of glob are not supported, and contain widely publicized security vulnerabilities, which have been fixed in the current version. Please update. Support for old versions may be purchased (at exorbitant rates) by contacting i@izs.me 18:57:37.922 npm warn deprecated node-domexception@1.0.0: Use your platform's native DOMException instead 18:57:38.695 npm warn deprecated glob@10.3.10: Old versions of glob are not supported, and contain widely publicized security vulnerabilities, which have been fixed in the current version. Please update. Support for old versions may be purchased (at exorbitant rates) by contacting i@izs.me 18:57:40.400 npm warn deprecated eslint@8.57.1: This version is no longer supported. Please see <https://eslint.org/version-support> for other options. 18:57:44.122 18:57:44.123 added 508 packages in 11s 18:57:44.124 18:57:44.124 163 packages are looking for funding 18:57:44.125 run `npm fund` for details 18:57:44.175 Detected Next.js version: 14.2.35 18:57:44.181 Running "npm run build" 18:57:44.289 18:57:44.289 > showside@0.1.0 build 18:57:44.290 > next build 18:57:44.290 18:57:44.792 Attention: Next.js now collects completely anonymous telemetry regarding usage. 18:57:44.792 This information is used to shape Next.js' roadmap and prioritize features. 18:57:44.793 You can learn more, including how to opt-out if you'd not like to participate in this anonymous program, by visiting the following URL: 18:57:44.793 <https://nextjs.org/telemetry> 18:57:44.793 18:57:44.844 ▲ Next.js 14.2.35 18:57:44.845 18:57:44.865 Creating an optimized production build ... 18:58:04.869 ✓ Compiled successfully 18:58:04.870 Linting and checking validity of types ... 18:58:11.776 Collecting page data ... 18:58:13.568 Generating static pages (0/28) ...

Show more


May 25



Claude responded: Good news — it deployed and got pretty far.


Good news — it deployed and got pretty far. Scroll down in the build logs to see the actual error. Click on the **Build Logs** section to expand it and scroll to the bottom where the red error will be.

Or click **Deployment Summary** to see a condensed version of what failed.



Claude responded: The logs cut off at "Generating static pages (0/28)" — it likely failed because the env vars aren't set yet.

The logs cut off at "Generating static pages (0/28)" — it likely failed because the env vars aren't set yet. Click **Go to Project** then go to **Settings** → **Environment Variables** from within the project to add them there.



You said: i just connected the vercel connector to claude - give me a prompt for claude code to finish this process.

i just connected the vercel connector to claude - give me a prompt for claude code to finish this process...

May 25



I need to deploy Showside to Vercel. The project is already linked to GitHub at roombox-stack/showside and a deployment was attempted but failed because environment variables aren't set yet.

Please:

1. Use the Vercel MCP to add all environment variables from `.env.local` to the Vercel project called "showside" for the production environment
2. Then trigger a new deployment
3. Tell me the live URL when it's done

The project is at `~/Projects/showside` and the Vercel project name is "showside" under the "matt-p-s-projects" team.



You said: Now we have the real answer.

Now we have the real answer. It's not the email at all — it's a Vercel Hobby Plan limitation: "The deployment was blocked because the commit author did not have contributing access to the project on Vercel. The Hobby Plan does not support collaboration for private repositories. Please upgrade to Pro to add team members." Vercel treats your GitHub identity (`mpocock`) as a different user from your Vercel account (`mpocock-7264`) because they aren't formally linked under the same account. On the Hobby plan, only the project owner can push deploy-triggering commits to a private repo. That's why Vercel only let the very first deploy through (it was bootstrapping the project) and has blocked every commit since. Three ways forward, fastest first: Option A — Make the GitHub repo public (free, 30 seconds, fully reversible) Hobby plan removes the contributor restriction for public repos. Best path for a V1 demo.

- 1 Open <https://github.com/roombox-stack/showside/settings>
- 2 Scroll to the Danger Zone at the bottom → "Change visibility" → Make public
- 3 Tell me when done and I'll push another empty commit (or you can just click Redeploy in the Vercel dashboard — once the repo is public, the existing commit should unblock without a new push). Caveat: anyone can browse your source code. Your `.env.local` is gitignored, so secrets stay out. If you have any private notes in committed files, double-check first. Option B — Link your GitHub identity to your Vercel account (free, no repo changes) This might work if `mpocock-7264` was created without OAuth-linking to the `mpocock` GitHub login.
- 4 Open <https://vercel.com/account/login-connections> (or Settings → Login Connections in the dashboard)
- 5 Look for GitHub in the list. If it shows "Connect," connect it and authorize for `mpocock`.
- 6 If GitHub is already connected, this likely won't fix it — fall back to Option A or C. Option C — Upgrade to Pro (\$20/mo) The Pro plan supports collaborators on private

repos. Justifiable if Showside is going to be a real product, but overkill for first deploy. My recommendation: do Option A, push the deploy through, and we'll have a live URL in 60 seconds. You can flip the repo back to private the moment you upgrade or restructure ownership later. Say which path you want and I'll do my part.

Show more

May 25



Claude responded: Easiest call — Option A.

Easiest call — **Option A**. Make the repo public for now, get the live URL, worry about private repo settings later when it's a real product worth protecting.

Go to: github.com/roombox-stack/showside/settings

Scroll to the bottom → **Danger Zone** → **Change visibility** → **Make public** → confirm.

Then come back and we'll trigger a redeploy.



You said: write a detailed description of the showside platform as you understand it today - i want to use this as the Instructions for this Project

write a detailed description of the showside platform as you understand it today - i want to use this as the Instructions for this Project

May 25



Claude responded: Here's a comprehensive project description you can paste as the Claude Project instructions:

Here's a comprehensive project description you can paste as the Claude Project instructions:

Showside — Project Context & Build Log

What We're Building

Showside is a fan media platform for live events. Fans who attended upload photos and videos. Non-attendees virtually attend by browsing organized fan footage. Think YouTube Shorts meets a permanent concert archive.

Core concept: Experience-first, archive-second. A teenager in London who couldn't afford a Morgan Wallen ticket lands on his page and feels like she experienced the show within 30 seconds. The entity page leads with the best fan clips across all shows — not a list of tour dates.

Tagline: "The show, from everyone who was there."

Primary Audience

People who couldn't attend — priced out, wrong city, wrong country. Not just attendees logging history. The virtual attendance session (30+ minutes browsing a full show) is the core unproven hypothesis V1 needs to test.

Product Decisions Made

- Entity → Event hierarchy: Artist/team/brand page → specific show sub-page → media grid
- Entity page design: Experience-first. Hero with cinematic dark background + video thumbnails. Fan highlights grid (1 large + 4 small cards). Most filmed songs row. Recent shows (4 cards). Full archive collapsed behind a click.
- Video dominates over photos — virtual attendance needs video
- Anonymous uploads — no account required to upload. Account creation only prompted on success screen.
- Upload target: Under 60 seconds from opening page to upload complete on mobile
- Like toggle: Repeat call = unlike
- No audio fingerprinting in V1 — manual song tagging only, AI classification in V2
- No mobile app in V1 — mobile-first web only
- Mux for video (upload, transcode, HLS, thumbnails), Cloudflare R2 for photos
- Featured = cumulative view_count, no cron job needed
- Orphan media rows: status = 'uploading' on presign, flipped to 'active' on complete/webhook
- Media beyond song tagging: location/vibe tags (pit, floor, VIP, concourse, outside, etc.) to encourage lifestyle content uploads beyond just performance clips
- AI auto-classification of media planned for V1.5 — vision API classifies location/vibe tags async after upload, no friction added to upload flow

Tech Stack

- Framework: Next.js 14 (App Router, SSR)
- Database: Supabase (Postgres + auth + RLS)
- Video: Mux (direct upload, HLS playback, webhooks)
- Photos: Cloudflare R2 (presigned URLs)
- Deployment: Vercel (in progress)
- Styling: Tailwind CSS
- Language: TypeScript
- Repo: github.com/roombox-stack/showside
- Local: ~/Projects/showside
- Built with: Claude Code, Opus 4.7, Max effort

Database Schema

Six core tables: entities, events, media, users, likes, follows. Additional tables: attended_events, event_suggestions, media_views (Phase 6).

DB triggers maintain all counters (upload_count, like_count, follower_count, show_count) in-transaction. Anon likes use partial unique index on (media_id, session_token) where user_id is null.

Media status flow: uploading → active (photos on /complete, videos on Mux webhook).

Key media columns: id, event_id, entity_id, uploader_id, upload_session, file_type, storage_url, mux_asset_id, mux_upload_id, mux_playback_id, thumbnail_url, duration_sec, song_tag, section_tag, is_full_song, status, view_count, like_count.

Supabase project ID: iuxhlflulrpoppuwnrxg / Region: us-west-2

Migrations Applied

- 0001_init.sql — base schema
- 0002 through 0004 — RLS, triggers, indexes
- 0005_attendance.sql — attended_events table, show_count trigger
- 0006_upload_extras.sql — section_tag CHECK widened, event_suggestions table

Build Status

✅ Phase 1 — Next.js scaffold, Supabase schema + migrations + RLS + triggers, seed data, all lib clients (Supabase, Mux, R2, session), middleware

✅ Phase 2 — All 8 API routes built and curl-tested: photo-url, video-url, upload-complete, mux-webhook, like-toggle, search, QR, admin-login

✅ Phase 3 — Admin panel: dashboard (stats), entities CRUD, events CRUD + setlist paste, moderation queue, QR download

- ✅ Phase 4 — All public pages: home, entity page, event page (Watch/Browse/Upload tabs), full-screen viewer, search, sitemap.xml, robots.txt, JSON-LD structured data
- ✅ Phase 5 — Upload flow UI: event picker → file select → optional section tagging → direct upload → success screen with soft account prompt. Anonymous uploads working. Photos active immediately, videos active on Mux webhook.
- ✅ Full Song Badge — `is_full_song` boolean on media table, set in Mux webhook handler when `duration >= 150` seconds. Displayed as badge on video cards.
- ✅ Profile Page — `/profile/[username]` with stats (shows, artists, uploads, likes received), attended shows grid, uploads grid. "I was there" attendance button on event pages. Soft signup flow carries attendance intent forward.
- ⌚ Phase 6 — View count dedup, infinite scroll, footer pages (`/about`, `/dmca`, `/privacy`, `/terms`, `/contact`), profile edit page, Lighthouse > 80, loading skeletons, performance polish
- ⌚ Design Pass — Full UI redesign after functionality complete. Dark cinematic aesthetic, experience-first not archive-first.
- ⌚ Vercel Deployment — In progress. Repo at `roombox-stack/showside`. Env vars configured. Hobby plan / public repo.

API Routes

- POST `/api/photo-url` — presigns R2 upload URL
- POST `/api/video-url` — creates Mux direct upload URL
- POST `/api/upload-complete` — flips photo status to active, writes metadata
- POST `/api/mux-webhook` — handles `video.asset.ready`, flips video to active, sets playback ID, sets `is_full_song`
- POST `/api/like-toggle` — toggles like, works anon (session) or authed
- GET `/api/search` — searches entities and events
- GET `/api/qr/[eventSlug]` — returns QR code for event upload URL
- POST `/api/admin-login` — validates `ADMIN_KEY`
- POST `/api/attendance/toggle` — toggles `attended_events` row
- POST `/api/event-suggestions` — saves suggested events from upload flow
- POST `/api/auth/signup`, `/signin`, `/signout` — auth endpoints

Gamification (Planned V1/V2)

V1 shipped: Full Song badge (`duration >= 150s`)

V1.5 planned:

- "First There" badge — first upload from a specific show
- Show leaderboard — top contributors per event
- Artist leaderboard — top contributors across all shows for an artist
- "I Was There" attendance tracking (✅ built)
- Coverage completeness — "Full Show Captured" banner when all setlist songs have clips
- Rarity badge — rare moments with only 1-2 clips
- Community picks — most liked clip auto-featured in hero position
- Shareable stat cards — "I've seen Morgan Wallen 7 times"
- Annual wrapped

Monetization Strategy (Future)

- 1 Artist/Team Dashboard SaaS — labels/managers pay for access to fan footage analytics and download rights
- 2 Ticketing affiliate — high-intent audience browsing show footage, affiliate links to Ticketmaster/StubHub
- 3 Licensing marketplace — fan footage has commercial value for documentaries, music videos, broadcasts
- 4 Promoted placement — artists/promoters pay for featured placement
- 5 Brand partnerships — sponsors for content categories (pit footage, VIP content)
- 6 Consumer subscription — Showside Pro (download, ad-free, early access)

Content Taxonomy

Media is tagged along two axes:

Songs/Plays (V1 manual, V2 ACRCLOUD audio fingerprinting)

- Any song from the setlist or play from the game

Location/Vibe tags (V1 manual in upload flow, V1.5 AI auto-classified):

- Universal: Entrance/arrival, Main floor/GA, Seated section, Concourse, Concessions, Merch stand, Outside the venue, VIP area, Parking lot/tailgate, Crowd reaction, Waiting/before show, Intermission/halftime, Post-show, Surprise moment, Fan interaction
- Concert-specific: Pit, Barrier/front row, Opening act, Soundcheck, Encore, Stage setup, Light show, Meet & greet
- Sports-specific: Pregame warmups, Player intro, Big play reaction, Halftime show, Postgame, Tailgate, Student section
- Festival-specific: Campsite, Between sets, Second stage, Art installations, Sunset/overnight

Competitive Landscape

- CrowdAlbum — acquired by Spotify 2016, shut down. Aggregated social posts, never tested native upload.
- Concert Archives — closest existing product. Live since 2013, built for attendees logging history not virtual attendance.

- FanVids / Aftershow.io / SureShot / Happaning — all B2B/artist-controlled.
- Concerts Remembered, Encore, RAVR, Memento, NEXFES — all personal concert diary/tracker apps. Attendee-only, no community archive.


The gap: Consumer-first, community-owned, virtual attendance experience. Nobody owns it.

Key Insights

- 56% of concert attendees share media on social during shows (Nielsen)
- Concert ticket prices up 50% since 2019 — avg top-100 tour ticket \$136 in 2024
- 151M people attended Live Nation events in 2024
- Fan-shot concert clips on YouTube regularly get 10M+ views
- Instagram/TikTok are broadcast platforms (post to your followers). Showside is an archive platform (post to the show). Not competing motivations — sequential.
- The 47 clips sitting in someone's camera roll that never got posted anywhere are the real addressable content pool.
- One artist shoutout at a show or social team repost is the highest-leverage distribution moment.
- Artist dashboard (B2B layer) is the relationship-building tool that gets Showside into artist workflows permanently.

Environment

- NEXT_PUBLIC_SUPABASE_URL
- NEXT_PUBLIC_SUPABASE_ANON_KEY
- SUPABASE_SERVICE_ROLE_KEY
- MUX_TOKEN_ID
- MUX_TOKEN_SECRET
- MUX_WEBHOOK_SECRET
- R2_ACCOUNT_ID
- R2_ACCESS_KEY_ID
- R2_SECRET_ACCESS_KEY
- R2_BUCKET_NAME
- R2_PUBLIC_URL
- ADMIN_KEY
- NEXT_PUBLIC_APP_URL



You said: no ones going to 'find' my public github right?

no ones going to 'find' my public github right?

May 25





Claude responded: Correct — nobody is going to randomly find it.


Correct — nobody is going to randomly find it. GitHub has millions of public repos. Nobody is browsing for yours.

The only real risks with a public repo are:

- 1 **Someone searches for your exact secrets** — not a risk because your `.env.local` is gitignored and never committed. Your API keys, Supabase credentials, Mux tokens, R2 keys are all safe.
- 2 **A competitor reads your code** — theoretical risk but at this stage you have no competitors watching you, and code is not the moat anyway. The moat is content, community, and distribution.
- 3 **Someone finds a security vulnerability** — more relevant later, not now.

For a V1 getting its first deployment, public repo is completely fine. Flip it private when you're on Vercel Pro and have real users worth protecting.

Go make it public and let's get the live URL.



You said: should i start a new chat in claude code to continue to phase 6?

should i start a new chat in claude code to continue to phase 6? will it lose the previous context?

May 25



Claude responded: Yes start a new Claude Code session — but no it won't lose context if you feed it the right information.

Yes start a new Claude Code session — but no it won't lose context if you feed it the right

information.

Claude Code doesn't retain memory between sessions. But you now have two things that replace that:

- 1 **The project instructions you just created** — paste that into the new Claude Code session at the start and it has full context of everything built so far.
- 2 **The codebase itself** — Claude Code reads the actual files, so it can see exactly what's been built regardless of conversation history.

How to start the new session:

Open Claude Code and paste this at the top:

Continuing Showside development. Full project context is in the instructions above. Phases 1-5 are complete including Full Song badge and Profile/Attendance features.

We are now starting Phase 6. Here are the instructions:

[paste the Phase 6 instructions block from earlier in our conversation]


Project is at ~/Projects/showside.

Use existing patterns and components already in the codebase.

After each section tell me what to test and how.

That's all it needs. The codebase does the rest.

Also — once you get the Vercel deployment working, add the live URL to your project instructions so future Claude Code sessions know the production URL.



You said: do i still need to use opus 4.

do i still need to use opus 4.7 max? its eating my tokens so fast...!

May 25



Claude responded: Good question — here's the honest

breakdown:

Good question — here's the honest breakdown:

Opus 4.7 Max effort was the right call for the complex architecture phases (1-4) where it was making hundreds of decisions about schema design, API patterns, RLS policies, and component structure simultaneously.

For Phase 6 the work is simpler — polish, infinite scroll, footer pages, loading skeletons. These are more mechanical tasks.


You could reasonably drop to:

- **Sonnet 4.5** — much cheaper, still very capable for polish work
- **Regular effort** instead of Max — saves tokens significantly

The risk is small. If Sonnet gets confused or produces lower quality output on a specific task you can always bump back up for that one task.

My suggestion: **start Phase 6 on Sonnet at normal effort**. If it struggles with something specific — like a complex pagination implementation or a tricky component — switch to Opus for that task only.

The big expensive brain was worth it to get the architecture right. The finishing work doesn't need it.



You said: its running - can i stop it and change the model?

its running - can i stop it and change the model?

May 25



Claude responded: Yes — you can stop it mid-task and switch models.

Yes — you can stop it mid-task and switch models. Claude Code lets you change the model between messages.

But if it's already running and making file changes, let it finish the current task first before

stopping. Interrupting mid-write can leave files in a broken state.

Watch for a natural stopping point — when it finishes a section and says something like "here's what to test" — then switch the model before giving it the next instruction.



You said: i cut it off at 6.

i cut it off at 6.3 for now

What's live in this deploy (Phase 6.1–6.3):

- `/api/view` — view count dedup (session-aware, no double-counting on reload)
- `/api/events/[slug]/media` — paginated media endpoint for Browse tab
- `BrowseGrid` — infinite scroll on event page Browse tab (24 per page, `IntersectionObserver`)
- `HighlightsGrid` — client-side show-more on entity highlights (24 at a time)
- `/about`, `/privacy`, `/terms`, `/contact`, `/dmca` — all footer pages with working forms
- `Footer` component on every public page Two DB migrations still need applying in Supabase SQL editor before the new features are fully live:
 - `supabase/migrations/0007_media_views.sql` — creates `media_views` table + trigger
 - `supabase/migrations/0008_footer_tables.sql` — creates `dmca_requests`
 - `contact_submissions` tables

Show more

May 25



Claude responded: Good stopping point.

Good stopping point. Clean progress.

Do this now before anything else:

Apply both migrations in Supabase SQL editor:

- 1 Open supabase/migrations/0007_media_views.sql — copy and run it
- 2 Open supabase/migrations/0008_footer_tables.sql — copy and run it

Then commit and push what's built:

```
bash
```

```
cd ~/Projects/showside
```

```
git add .
```

```
git commit -m "Phase 6.1-6.3 - view dedup, infinite scroll, footer pages"
```


```
git push
```

That'll trigger a Vercel redeploy automatically once the repo is public and linked.

Updated build status:

Item	Status
Phase 6.1 — View count dedup	✓
Phase 6.2 — Infinite scroll	✓
Phase 6.3 — Footer pages	✓
Phase 6.4 — Profile edit page	⌚
Phase 6.5 — Lighthouse/performance	⌚
Design pass	⌚
Vercel live URL	⌚

Did Vercel deploy successfully after making the repo public? Do you have a live URL yet?



Claude responded: You pasted the filename instead of the

file contents.


You pasted the filename instead of the file contents. You need to open the file and copy the SQL inside it.

Run this in terminal to print the contents:

```
bash
```

```
cat ~/Projects/showside/supabase/migrations/0007_media_views.sql
```

Copy the output and paste that into the Supabase SQL editor, then click Run.




Claude responded: Good — now select all that SQL output (everything from -- Phase 6.

Good — now select all that SQL output (everything from -- Phase 6.1 view-count dedup. down to grant select, insert on public.media_views to service_role;), copy it, paste into Supabase SQL editor and click Run.

Then do the same for the second migration:

```
bash
```


```
cat ~/Projects/showside/supabase/migrations/0008_footer_tables.sql
```



Claude responded: The first line Phase 6.

The first line `Phase 6.1 view-count dedup.` is missing the `--` comment prefix — it's trying to execute it as SQL.

Just delete line 1 (`Phase 6.1 view-count dedup.`) in the editor so it starts from line 2 (`--`), then click Run.



May 25

Claude responded: Same issue — delete line 1 (Phase 6.

Same issue — delete line 1 (`Phase 6.3 footer pages.`) so it starts from line 2 (`-- Stores DMCA...`), then click Run.

Both migration files have the same problem — the first line is missing the `--` comment prefix. Just delete line 1 in each and it'll work.



You said: • - How do I actually launch the website on the new domain?

• - How do I actually launch the website on the new domain? Where will it be hosted? What if I need to make changes to the pages? explain to me how the backend of the site will work

May 26



Claude responded: Great questions — let me explain the

whole picture clearly.

Great questions — let me explain the whole picture clearly.

Where The Site Is Hosted

Vercel hosts the website. It's a cloud platform that runs your Next.js app. When someone visits your URL, Vercel serves the pages.

Your current setup:

- Code lives on **GitHub** (roombox-stack/showside)
- Vercel watches that GitHub repo
- Every time you push code changes to GitHub, Vercel automatically rebuilds and redeploys the site in about 60 seconds

You never manually "upload" files anywhere. The flow is always:

You make changes locally → push to GitHub → Vercel auto-deploys

How To Get A Real Domain

Right now Vercel gives you a free URL like `showside.vercel.app`. To use a real domain like `showside.com`:

- 1 **Buy the domain** — go to Namecheap, Google Domains, or Cloudflare and buy `showside.com` (or whatever name you choose)
- 2 **Point it to Vercel** — in Vercel dashboard → your project → Settings → Domains → add your domain
- 3 Vercel gives you DNS records to copy into your domain registrar
- 4 Takes 10-30 minutes to propagate
- 5 Done — `showside.com` is live

Cost: ~\$10-15/year for the domain. Vercel hosting is free on the Hobby plan.

How To Make Changes

Two paths depending on what you're changing:

Content changes (adding events, uploading seed media, editing entity pages):

- Use the **Admin panel** at `yoursite.com/admin`
- Add new entities, events, setlists through the UI
- No code changes needed

Feature/design changes (new pages, UI updates, functionality):

- Open Claude Code
- Make the changes
- Run in terminal:

```
bash
```

```
git add .
```

```
git commit -m "describe what you changed"
```

```
git push
```

- Vercel picks it up automatically and redeploys in ~60 seconds

The Full Backend Picture

User visits showside.com



Vercel serves the Next.js app



Page loads, fetches data from Supabase (your database)



Media files (photos) served from Cloudflare R2 (your storage)



Videos streamed from Mux (your video platform)

The four services running your backend:

Service	What It Does	Cost
Vercel	Hosts and runs the website	Free (Hobby)
Supabase	Database — stores all events, users, media metadata	Free up to 500MB
Cloudflare R2	Stores photo files	~\$0.015/GB/month
Mux	Stores and streams videos	~\$0.015/min of video stored


What Happens When Someone Uploads

- 1 User selects files on your site
- 2 Site asks Vercel (your app) for upload permission
- 3 Vercel gives a direct upload URL to R2 (photos) or Mux (videos)
- 4 File goes directly from user's phone to R2/Mux — never touches Vercel
- 5 Vercel records the upload in Supabase
- 6 For videos: Mux processes it, then calls your Vercel webhook when ready
- 7 File is now live on the event page

What You Need To Do To "Launch"

- 1 ☒ Get Vercel deployment working (in progress)
- 2 Buy a domain (~\$12)
- 3 Point domain to Vercel (10 min)
- 4 Update `NEXT_PUBLIC_APP_URL` in Vercel env vars to your real domain
- 5 Update Mux webhook URL to your real domain
- 6 Update Supabase allowed URLs to your real domain
- 7 Tell people about it

That's the entire launch checklist. Everything else is already built.



You said: how scalable is this setup?

how scalable is this setup? what if 3 months from now the site is getting 100's of video uploads a week... just curious how stable/scalable this stack is

May 26



Claude responded: Really good question to think about now even though it's not an immediate concern.

Really good question to think about now even though it's not an immediate concern.

The Short Answer

Your stack is genuinely well-chosen for scale. Each component was built by companies whose entire business is handling massive scale. You're not running anything yourself that could fall over.

Each Component Under Load

Vercel — essentially infinitely scalable Vercel runs on serverless functions. When traffic spikes, it automatically spins up more instances. There's no server that gets overwhelmed. Netflix-scale companies run on this architecture. Hundreds of uploads a week is nothing — you'd

need millions of concurrent users before Vercel became a concern.

Mux — built for exactly this Mux's entire product is high-volume video. They handle encoding, storage, and streaming for companies like Robinhood, PBS, and Patreon. Hundreds of videos a week is a rounding error for them. Their HLS adaptive streaming automatically adjusts quality based on viewer connection speed. This scales to millions of concurrent viewers without you touching anything.

Cloudflare R2 — scales automatically R2 is Cloudflare's object storage. Cloudflare runs on 300+ data points globally. Photos get served from the edge closest to the viewer. Hundreds of uploads a week, millions of views — no configuration needed, it just handles it.

Supabase — scales well to a point This is the one component that needs the most attention as you grow. The free tier handles up to 500MB database and 2GB bandwidth. At hundreds of uploads a week you'll likely hit limits within a few months. The fix is simple — upgrade to Supabase Pro (\$25/month) which gives you 8GB database and 250GB bandwidth. That handles serious scale.

The Real Scaling Conversation

The architectural decisions that matter most at scale are already made correctly in your codebase:

Direct uploads — files go from user's device straight to Mux/R2, never through your server. This is the right call. If uploads went through Vercel, a spike in uploads would overwhelm your serverless functions. They don't — so it doesn't matter.

Database triggers for counters — all your like counts, view counts, upload counts are maintained by DB triggers not application code. This prevents race conditions under high concurrency.

RLS policies — Supabase Row Level Security means the database enforces access rules, not your app code. Scales cleanly.

CDN delivery — photos are on Cloudflare's CDN, videos on Mux's CDN. Content is served from the edge, not a single origin server.

What Would Actually Break First

If Showside suddenly went viral:

- 1 **Supabase free tier** — hit first, fixed by upgrading to Pro for \$25/month
- 2 **Mux costs** — at scale video storage and streaming costs real money. 1000 videos averaging 3 minutes each = ~\$0.045/min stored = ~\$45/month just for storage, plus streaming costs per viewer. Still manageable, just worth knowing.
- 3 **Vercel Hobby plan** — has some limits on execution time and bandwidth. Upgrade to Pro (\$20/month) if you hit them.

Total cost to handle serious early traction: ~\$50-100/month. That's nothing.

The Real Ceiling

This exact stack — Next.js on Vercel, Postgres on Supabase, Mux for video, Cloudflare for storage — could handle:

- 10,000 uploads per day
- 1 million page views per month
- 100,000 concurrent video viewers

...without any architectural changes. Just upgrade the paid tiers as revenue justifies it.


The only thing that would require a real architectural rethink is if you hit 10M+ monthly active users — and at that point you'd have the resources to hire engineers to solve it.

Bottom Line

You picked a stack that punches way above its weight. The three things to watch as you grow:

- 1 Supabase tier — upgrade to Pro when you approach 500MB
- 2 Mux costs — monitor monthly, it scales with content volume
- 3 Vercel tier — upgrade to Pro if you add team members or hit bandwidth limits

Everything else scales automatically with zero action from you.



You said: i'm really only used to managing wordpress or shopify websites, so this type of setup is kinda foreign to me

i'm really only used to managing wordpress or shopify websites, so this type of setup is kinda foreign to me

May 26



Claude responded: Totally understandable — this is a fundamentally different type of setup.

Totally understandable — this is a fundamentally different type of setup. Let me translate it into

familiar terms.

The WordPress/Shopify Mental Model vs Showside

WordPress — you log into a dashboard, install plugins, edit pages visually, and the hosting company runs a server with your files on it.

Shopify — fully managed, you log in, change things through a UI, Shopify handles everything else.

Showside — closer to a custom-built web app than either of those. There's no visual page editor. The "dashboard" is your admin panel for content, but design and feature changes require code.

The Key Differences

	WordPress/Shopify	Showside
Change a page design	Click and drag	Edit code, push to GitHub
Add a new feature	Install a plugin	Build it with Claude Code
Database	Managed for you invisibly	Supabase — you can see and query it
Hosting	One company handles everything	Split across Vercel + Supabase + Mux + R2
Updates	Click "Update" button	Push code to GitHub
Goes down	Call hosting support	Check Vercel/Supabase dashboards

What You Can Do Without Touching Code

Through your **Admin panel** (`yoursite.com/admin`):

- Add new artists/teams/entities
- Add new events with dates, venues, setlists
- Moderate uploaded content
- Download QR codes for events

Through **Supabase dashboard**:

- View all uploaded content
- Run SQL queries to see data
- Manually fix data issues

Everything else requires code changes via Claude Code.

The Good News

This is where Claude Code changes the equation completely for you.

In WordPress you'd hire a developer or buy a plugin. With Showside you just describe what you want to Claude Code in plain English and it writes the code, same as it built the whole product. You don't need to understand the code — you just need to be able to describe what you want and run `git push`.

Think of Claude Code as your on-demand developer. The barrier to making changes is describing what you want clearly, not knowing how to code.

The Mental Model That Helps

Think of it like this:

- **GitHub** = your filing cabinet. All the code lives there.
- **Vercel** = your store's physical location. It takes what's in the filing cabinet and makes it a live website.
- **Supabase** = your back office filing system. All the data — users, events, uploads — lives here.
- **Mux** = your video storage warehouse. All videos live here and get shipped to viewers on demand.
- **Cloudflare R2** = your photo storage warehouse. Same idea for images.
- **Claude Code** = your developer. Tells you exactly what changes to make and how to deploy them.

When something goes wrong — which will happen — the debugging process is:

- 1 Check Vercel dashboard for errors
- 2 Check Supabase for data issues
- 3 Ask Claude Code to fix it

What You Should Get Comfortable With

Just three things and you'll be able to manage this confidently:

1. The three terminal commands

```
bash
git add .
git commit -m "what I changed"
git push
```

You'll type these constantly. They're how you ship any change.

2. The Supabase SQL editor Just for running simple queries like `SELECT * FROM media ORDER BY created_at DESC LIMIT 10` to see what's in your database. You've already done this several times today.

3. The Vercel dashboard Just for checking if a deployment succeeded or failed. You look at the build logs when something breaks.

That's genuinely it. Everything else is either Claude Code's job or happens automatically.



You said: this is the entity design i'd like to go with - build in claude design.



this is the entity design i'd like to go with - build in claude design. how do we translate this over to claude code to rebuild the design in this manner/structure?

May 26



Claude responded: That design is stunning — dark, cinematic, content-forward exactly as we discussed.

That design is stunning — dark, cinematic, content-forward exactly as we discussed. The "most filmed songs" section with the color palette bars is a particularly nice touch.

Here's how to translate it into Claude Code:

Step 1 — Get The HTML/CSS Out of Claude Design

In Claude Design, look for an **Export** option or click on `index.html` in the file panel (image 2). You want the raw HTML/CSS that represents this design.

If you can export or copy the HTML — do that first. That gives Claude Code the exact markup to work from.

Step 2 — Screenshot Every Section

Take clean screenshots of each distinct section:

- 1 Hero (dark background + video grid + artist name + stats)
- 2 Fan highlights section (filter pills + large card + 4 small cards)
- 3 Most filmed songs (5-column grid with color bars)
- 4 Recent shows (4 cards)
- 5 Archive/footer section
- 6 Nav bar

The more precise the screenshots, the better Claude Code can match them.

Step 3 — Give Claude Code This Prompt

I have a new design for the Showside entity page that I want to implement. I'm attaching screenshots of each section. Please rebuild `app/[entitySlug]/page.tsx` and its components to match this design exactly.

Design notes:

- Dark background throughout (#0a0a0a or similar near-black)
- Red/crimson accent color for badges, highlights, active states
- Artist name is massive, left-aligned, overlaid on dark hero
- Hero right side: 3x2 grid of video thumbnails with play buttons and duration pills
- Stats strip below hero: Videos / Photos / Shows Covered / Total Clip Views / Since [year]
- Fan highlights section header: "The best moments, by the people who were there." with filter pills (All time best / Crowd energy / Stage moments / Acoustic / Pit / Most recent)
- Highlights grid: one large hero card (left, tall) + 4 smaller cards (2x2 right)
- Each card shows: thumbnail, play button, duration pill, song tag, venue/city, like count, uploader handle
- Most filmed songs section: 5-column horizontal grid, each column shows song name, clip count, and a row of 4 color-sampled thumbnail squares
- Recent shows: 4 cards in a row, each with thumbnail, venue name, date, city, clip count, video count
- Archive bar at bottom: dark band with "All X shows · Y clips · since YEAR" and "Browse the archive →" button
- Typography: bold condensed sans-serif for headings, clean sans for body
- All section headers prefixed with // like: // FAN HIGHLIGHTS,

// MOST FILMED SONGS, // RECENT SHOWS

Keep all existing data fetching logic — only change the visual presentation layer. The backend queries stay exactly the same.

[attach your screenshots here]

Step 4 — Iterate Section By Section

Don't try to do the whole page in one pass. Do it in order:


- 1 Hero section first — get that right
- 2 Fan highlights grid
- 3 Most filmed songs
- 4 Recent shows + archive bar
- 5 Nav bar last

Each section review — screenshot your localhost, compare to the design, tell Claude Code what's off.

One Important Note

The color palette bars in the "most filmed songs" section — those are auto-generated from thumbnail color sampling in the design mockup. For V1 you can fake this with placeholder colored squares or a gradient, and build the real color extraction in V1.5. Don't let that one feature block the whole design pass.

Can you export the HTML from Claude Design, or do you just have the screenshots?



You said: i can download the full html it looks like but it will come with multiple page mockups - not just the one entity page.



i can download the full html it looks like but it will come with multiple page mockups - not just the one entity page... not sure how i can separate that out

May 26





Claude responded: Download the full HTML file — that's fine.

Download the full HTML file — that's fine. Claude Code can extract just the entity page section from it even if it contains multiple mockups.

Here's the prompt to give Claude Code:

I'm attaching an HTML file exported from Claude Design. It contains multiple page mockups for the Showside redesign.

Please:

1. Open the file and identify the Morgan Wallen entity page mockup (it will be the one with the dark hero, artist name large on left, video grid on right, fan highlights section, most filmed songs, recent shows)
2. Extract the CSS design tokens — colors, typography, spacing, border radius, shadow styles
3. Rebuild `app/[entitySlug]/page.tsx` to match that design exactly, keeping all existing data fetching logic intact
4. Create any new components needed in `components/` following the existing naming patterns

Design priorities in order:


- Hero section with dark background, large artist name, 2x3 video grid
- Fan highlights grid (1 large + 4 small cards with filter pills)
- Most filmed songs (5 columns with color swatches — use placeholder colored squares for V1, real color extraction later)
- Recent shows 4-card row
- Archive bar at bottom
- Nav styling

Do NOT change:

- Any API routes
- Any data fetching (`getEntity`, `getEvents`, `getMedia` queries)
- The URL structure
- Any database logic

After building, tell me what to check at `localhost:3000/morgan-wallen`

Download the HTML first, then drag it into the Claude Code chat along with that prompt.



You said: which model should i select for this

which model should i select for this

May 26




Claude responded: For a design implementation task like this — use Sonnet at normal effort.

For a design implementation task like this — use **Sonnet** at normal effort.

It's reading an HTML file and translating it into React/Tailwind components. That's pattern matching work, not complex architecture. Sonnet handles it well and uses a fraction of the tokens.

If it struggles with a specific section or produces something that looks way off, you can bump to Opus for that one fix. But start with Sonnet.



You said: it was asking for all types of access - itunes, desktop etc etc -

it was asking for all types of access - itunes, desktop etc etc -

It's a multi-file React app. Let me find all the source files: RanFind all design files The HTML references external JSX files — it needs to be served, not just opened. Let me load the Chrome tools and render it: Ran 2 commands, used a tool The companion JSX files aren't exported alongside the HTML. Let me check if the other HTML files in Downloads are the self-contained versions: RanCompare the three HTML files The file needs its companion JSX files to render. Let me spin up a local server to serve it, then screenshot it in Chrome — the browser might have cached the scripts from a previous session: Ran 4 commands, used 5 tools The React app is blank — the JSX companion files are missing. But I can see a "C-" tab already open in Chrome which is likely the design loaded from somewhere. Let me check where those source files might live: Ran 2 commands The files are all 404. But that "C-" tab in Chrome is a previously loaded cached version of the design. Let me check Chrome's cache for the JSX files: Ran 2 commands Let me

check Chrome history to find what URL that "C-" tab loaded from: RanQuery Chrome history for C-Roll or Claude Design URLs

Show more

May 26



Claude responded: Stop Claude Code there — it's going down a rabbit hole trying to render the HTML file through Chrome which it doesn't need to do.

Stop Claude Code there — it's going down a rabbit hole trying to render the HTML file through Chrome which it doesn't need to do.

The simpler approach is to just give it the screenshots directly. Claude Code doesn't need to render the design file — it just needs to see what the design looks like.

Cancel the current task and start fresh with this prompt:


I want to redesign the entity page (app/[entitySlug]/page.tsx) to match a new design. I'm attaching screenshots of the design I want to match.

Please rebuild the entity page visually to match these screenshots exactly. Keep all existing data fetching logic completely unchanged — only change the visual/component layer.

[attach the screenshots from our earlier conversation showing the full entity page mockup]

Then attach the screenshots you shared with me earlier — the full entity page mockup (Image 1 from your previous message showing the complete Morgan Wallen page design).

Screenshots are actually better than the HTML file for this purpose — Claude Code can see exactly what it needs to build without trying to parse or render a complex React app.



You said: ok it ran:

ok it ran:

What changed (visual layer only — zero data fetching changes): Nav

- Upload button is now red (`bg-croll`) instead of the outlined smoke button
- Nav links updated to Browse / Artists / Sports / Events
- Slimmer (h-14 vs h-16), lighter weight feel with `bg-ink/90` and `border-white/5` Entity page (`/morgan-wallen` or any entity slug) Hero section
- Concert photo background at 25% opacity with a left-side dark gradient so the text always reads clearly
- Artist name now uses Archivo Black (`font-display`) at ~6.5rem, tight line height — huge and cinematic
- Red // In Showside • N Shows • N Clips breadcrumb in monospace above the name
- Genre + Verified as pill badges with `border-white/15` (subtle outline, no colored backgrounds)
- Two outline CTA buttons: "► Watch latest show" links to most recent event, "Follow • N" shows follower count
- Hero grid thumbnails are now portrait aspect (4:5) with hover scale and play icon reveal on hover Stats strip
- Horizontal scroll row with pipe dividers: CLIPS | PHOTOS | SHOWS COVERED | CONTRIBUTORS | SINCE
- Each chip has a tiny monospace label above a bold number Fan Highlights
- // FAN HIGHLIGHTS in red monospace above the Bricolage Grotesque heading
- Filter pills: active = white background + ink text, inactive = subtle dark with border
- "The best moments, by the people who were there." heading copy Most Filmed Songs
- // MOST FILMED SONGS eyebrow, heading with show count
- 5-column grid (mobile: 1-col), each card: large faded rank number, song title + clip count, 6 color swatches as palette placeholder Recent Shows
- // RECENT SHOWS eyebrow, 4-card grid
- Most recent card gets a red "Last Show" badge (top-left)
- "All N Shows →" link when there are more than 4 Archive section
- Full-width `bg-smoke/40` section at bottom
- // SHOWSIDE ARCHIVE eyebrow + large "All N shows • N clips • since YEAR" heading
- Year-grouped event list always shown inline

Show more

May 26






Claude responded: Looks like a solid build.

Looks like a solid build. Go check it at `localhost:3000/morgan-wallen` and compare it against your design screenshots.

Key things to eyeball:

- 1 **Hero** — does the artist name feel massive and cinematic? Is the background photo showing correctly?
- 2 **Video grid** — portrait thumbnails, play button on hover?
- 3 **Fan highlights** — 1 large + 4 small card layout correct?
- 4 **Most filmed songs** — 5 columns with color swatches?
- 5 **Recent shows** — 4 cards, "Last Show" badge on most recent?
- 6 **Typography** — is Archivo Black loading for the headings?

Screenshot what you see and share it here — we can compare against the target design and identify what needs tweaking.



You said: its close but the hero background image is either too dark or positioned incorrectly - i can barely see it - thoughts?



its close but the hero background image is either too dark or positioned incorrectly - i can barely see it - thoughts? maybe the overlay is too dark...

May 26



Claude responded: Looking good overall — the typography and layout are very close to the target.

Looking good overall — the typography and layout are very close to the target. The background image issue is exactly what you said — the overlay opacity is too aggressive.


Give Claude Code this targeted fix:

On the entity page hero, the background concert photo is barely visible.
Please adjust:

1. Increase the background image opacity from 25% to about 40-50%
2. The gradient overlay on the left side is too heavy — lighten it so the image bleeds through more on the right side especially
3. The image should feel like it's glowing behind the content, not completely suppressed
4. Reference the design: the right side of the hero should show the concert photo quite clearly, with the dark gradient only on the left third where the text sits

The target feel is cinematic — like a movie poster where the image is rich and visible but the text still reads clearly over it.

That's a one-minute fix — just CSS opacity and gradient values. Should make a big difference.



You said: Deployed.



Deployed. Here's what changed: Image opacity: `opacity-25` → `opacity-55` — the photo is now over twice as visible. Left-to-right gradient: was `from-ink via-ink/90 to-ink/50` (heavy across the whole width) → now `from-ink from-[5%] via-ink/75 via-[38%] to-ink/10`

- The solid black burns off quickly at the 5% mark
- By 38% it's already at 75% transparent — roughly the center column
- The right side (where the hero grid sits) gets only a faint 10% tint, so the concert photo comes through nearly unobstructed Bottom vignette: was `from-ink` (full black at bottom) → now `from-ink/50 via-transparent via-[30%]` — a softer darkening that only affects the very bottom edge, not the whole lower half. The result should feel like a film poster — the concert crowd visible and rich on the right, the dark zone only where the artist name and CTAs need contrast on the left.

Show more


May 26



Claude responded: That's looking really good — much more cinematic now.

That's looking really good — much more cinematic now. The crowd is visible on the right, text reads clearly on the left, the gradient feels natural.

Scroll down and screenshot the rest of the page — fan highlights, most filmed songs, recent shows sections. Want to see how those are looking before calling the hero done.



You said: i dig it.



i dig it. i also changed the primary accent color to an ember.


May 26



Claude responded: That ember/orange accent looks great — warmer and more energetic than the red, fits the concert vibe perfectly.

That ember/orange accent looks great — warmer and more energetic than the red, fits the concert vibe perfectly. The hero is looking really cinematic now.

Scroll down and screenshot the sections below — fan highlights, most filmed songs, recent shows. Want to see the full page before we decide what to tweak next.



You said: while i like the black bg, i worry it may be a little too dark - thoughts?

while i like the black bg, i worry it may be a little too dark - thoughts?

May 26



Claude responded: It's a valid instinct.

It's a valid instinct. Pure black (#000) can feel flat and heavy — like a void rather than a venue.

The design reference you built in Claude actually uses a very dark **charcoal/ink** rather than true black — something like #0a0a0a or #0d0d0d. The difference is subtle but meaningful. It gives the dark areas a bit more depth and makes the content pop more.

A few options to consider:

Option 1 — Warm dark charcoal #0d0b0a — has a very slight warm brown undertone that complements the ember accent and concert photography perfectly. Feels like being in a dark venue rather than a void.


Option 2 — Cool dark slate #0a0c0f — slight blue undertone, feels more cinematic/filmic. Common in streaming platforms like HBO Max.

Option 3 — Lighter dark #141414 or #161616 — noticeably less heavy, more like YouTube's dark mode. Content breathes more.

My honest recommendation: **Option 1, warm charcoal #0d0b0a.**

It pairs with the ember accent naturally, makes the concert photos feel warmer and more immersive, and lifts the page off pure black without losing the cinematic feel.

One line change in your Tailwind config. Want to give Claude Code that tweak, or scroll down and show me the rest of the page first?



You said: where are uploaded images being stored?

where are uploaded images being stored? mux?

May 26



Claude responded: Photos and videos go to different places:

Photos and videos go to different places:

Photos → **Cloudflare R2** Your R2 bucket called `showside-media`. Served via your public CDN URL (`R2_PUBLIC_URL`). Free egress, global CDN delivery.

Videos → **Mux** Uploaded directly to Mux, transcoded, stored on Mux's infrastructure, streamed via HLS. You can see them all in your Mux dashboard under the Showside environment — you were just there earlier today.

Where The Seed/Demo Images Come From

The concert photos you see in the hero background and thumbnail grids right now — those are likely either:

- 1 **Hardcoded URLs** in the seed data pointing to public concert photos Claude Code found or made up during seeding
- 2 **Placeholder images** from a service like Unsplash or similar


Run this in Supabase to check:

```
sql
SELECT storage_url, thumbnail_url
FROM media
LIMIT 5;
```

And check your entities table:

```
sql
SELECT name, image_url, hero_image_url
FROM entities;
```

That'll show you exactly where those images are pointing. If they're external URLs they'll work fine for now but could break if those sources go away — worth noting for when you add real content.



You said: do you think we'll be able to have attendees who

had backstage passes to a concert upload their media?

do you think we'll be able to have attendees who had backstage passes to a concert upload their media? or are there legal restrictions on that type of thing?

May 26



Claude responded: Great question — and the answer is nuanced.

Great question — and the answer is nuanced.

The Short Answer

Yes, backstage content is actually some of the most valuable content you could have — and it's generally fine with some caveats.

What's Legally Fine

Fan-shot content from anywhere they had legitimate access to is generally theirs to share:

- Backstage if they had a backstage pass
- Meet & greet photos
- Side stage if they were credentialed
- Pre-show soundcheck if they had early entry
- VIP areas, hospitality areas
- Parking lot, tailgate, outside the venue

If you were allowed to be there and you took the photo/video yourself, you own that content and can share it. This is the same legal footing as any fan photo from the floor pit.

Where It Gets More Complex

Artist portrait rights — if a fan takes a close-up photo of the artist backstage, technically the artist has some rights around commercial use of their likeness. Fan sharing on a community platform is generally considered fair use/editorial. Selling or licensing that photo is where it gets complicated.

Venue restrictions — some venues explicitly prohibit photography in certain areas (backstage,

production areas) in their ticketing terms. If someone violated venue rules to get the content, that's a terms of service issue between them and the venue — not really your problem as the platform hosting it, similar to how YouTube isn't liable for content that violates a venue's photography policy.

Professional camera restrictions — many venues ban professional cameras but allow phone cameras. Most backstage passes have similar language. Again this is between the attendee and the venue.

Confidential/private areas — if someone snuck into a genuinely private area (artist's personal dressing room without permission) that's a different matter. But legitimate backstage pass holders are explicitly allowed to be there.

How Platforms Handle This

YouTube, TikTok, Instagram — they all host backstage fan content constantly and don't proactively police it. They respond to takedown requests when rights holders complain.

Your DMCA page (which you just built in Phase 6.3) is exactly the right mechanism. If an artist or venue objects to specific content, they submit a DMCA request and you remove it. You're not liable for hosting it in good faith before receiving notice.

The Opportunity


Backstage content is actually a huge differentiator for Showside. Nobody else has it organized. A fan with a meet & greet photo or a backstage clip has nowhere to put it that's contextually relevant to the show. Right now it goes on Instagram and gets lost.

On Showside it lives on the event page tagged as "Meet & Greet" or "Backstage" — permanent, findable, part of the show's record.

The Taxonomy Already Supports It

Looking back at the content taxonomy we built — "Meet & greet" is already in the concert-specific tags. You're already set up for this. No product changes needed.

The only thing worth adding to your terms of service is a line that uploaders confirm they had legitimate access to the location where they captured their content. That shifts liability to the uploader, which is standard for any UGC platform.



You said: sorry, where are uploaded images being stored again?

sorry, where are uploaded images being stored again? i need to set hero images for a few blank entities we have as placeholders

May 27



Claude responded: Photos uploaded by fans → Cloudflare R2

Photos uploaded by fans → Cloudflare R2

Entity hero images (the background on the Morgan Wallen page) → these are stored as URLs in the `entities` table in Supabase, in columns like `image_url` and `hero_image_url`. They're not uploaded through the fan upload flow — they're just URLs pointing to images.

How To Set Hero Images For Your Entities

Easiest approach — use the Admin panel:

Go to `localhost:3000/admin` → Entities → click Edit on the entity → there should be fields for image URL and hero image URL.

If the admin panel doesn't have those fields, do it directly in Supabase:


```
sql
UPDATE entities
SET
  hero_image_url = 'https://your-image-url-here.jpg',
  image_url = 'https://your-thumbnail-url-here.jpg'
WHERE slug = 'taylor-swift';
```

Where To Get The Images

For placeholder/seed entities you have a few options:

- 1 **Upload to R2 directly** via Cloudflare dashboard and use the public URL
- 2 **Use any public image URL** temporarily — Unsplash has free concert/sports photos
- 3 **Upload to Supabase storage** if you want everything in one place

What entities are missing hero images? I can help you find appropriate placeholder images or set up the SQL to update them.



You said: we never added the ability to tag the videos with the song data - lets start with giving the admin the ability to manually tag videos with songs from the event...

we never added the ability to tag the videos with the song data - lets start with giving the admin the ability to manually tag videos with songs from the event's uploaded set list - or manually type it in if the set list is not available

May 27



Claude responded: Good call — this is important for the virtual attendance experience.

Good call — this is important for the virtual attendance experience. Here's the prompt for Claude Code:

Add the ability for admins to tag uploaded media with song/play data.

CONTEXT:

- The media table already has a `song\_tag` column (text)
- The events table already has a `setlist` column (text array of song names)
- This is admin-only for now — fan-side song tagging comes later

WHAT TO BUILD:

1. Admin moderation queue enhancement

- In the existing admin moderation queue (app/admin/moderation or wherever media is listed), add a song tag field to each media item:
- If the event has a setlist, show a dropdown populated with songs

from that event's setlist

- If no setlist exists OR admin wants to type something custom, show a text input instead
- A small "tag" icon button next to each media item opens an inline edit row
- Saving calls PATCH /api/admin/media/[id] to update song_tag
- Show current song_tag value if already set

2. New API route: PATCH /api/admin/media/[id]

- Requires admin auth (check ADMIN_KEY cookie same as other admin routes)
- Accepts: { song_tag: string | null }
- Updates media row
- Returns updated media row

3. Bulk tagging shortcut

On the event detail page in admin, add a "Tag Media" section:

- Shows all media for that event in a list
- Each row: thumbnail, file type, current song_tag, dropdown/input to set song tag
- "Save all" button updates all changed rows in one pass
- Dropdown is pre-populated from the event's setlist if available

4. Display on frontend

Media cards that have a song_tag set should show it as a small pill on the thumbnail — already may be partially built, just verify it shows up correctly

Use existing admin auth patterns, existing Tailwind dark theme styling, and existing admin layout components.

After building tell me what to test.



You said: Shipped as 9541131.

Shipped as 9541131. Quick map of what's new:

- PATCH /api/admin/media/[id] — accepts { song_tag: string | null }, validates ≤ 120 chars, returns the updated row. Auth handled by existing middleware.ts.
- Server actions in app/admin/(shell)/media/actions.ts: setSongTag(id, value) and bulkSetSongTags([{id, song_tag}]). Both used internally by the editors.

- `<SongTagEditor />` — collapsed view shows current tag as a yellow pill (or "no song tag") with a tag-icon button. Click → reveals a setlist dropdown (if a setlist exists) plus a free-text input + Save / Clear / Cancel. Used on:
 - `/admin/moderation` cards
 - `/admin/media` Event/Entity column
- `<BulkSongTagger />` on `/admin/events/[id]`: new "Tag media" section under the form/QR grid. Lists all non-removed media with thumbnail, dropdown + freetext, dirty/saved indicators (● amber for unsaved, ✓ emerald for saved), and a "Save all (N)" button that only sends the diff.
- Frontend song tag pill was already wired on the event browse mosaic tiles and on `<MediaCard>` — no changes needed there. What to test
- API: with the admin cookie set, `curl -X PATCH https://showside.vercel.app/api/admin/media/<id> -H "content-type: application/json" -d '{"song_tag":"7 Summers"}'`. Then again with `'{"song_tag":null}'` to clear. Confirm 200 + returned row reflects the new value.
- Moderation queue: hit `/admin/moderation` (likely empty since V1 auto-approves). If you have any pending items, the new tag editor renders below the section/caption — click the tag icon, pick a song from the dropdown, hit Save. The pill should update without a full page reload.
- Media list: `/admin/media` → in any row's Event/Entity column you'll see "no song tag" with a tag icon. Open editor. With a setlist on that event, the dropdown is populated; without one, it's text-input only. Save and confirm the pill renders. Refresh — value persists.
- Bulk tagger: open `/admin/events/<id>` for an event that has setlist + media (e.g. Santigold ZeyZey Miami). Scroll to the new "Tag media" section. Change a few rows — counter at the top reads "N unsaved". Click "Save all (N)" — pending → saved (✓), counter resets, "Saved." message briefly shows.
- Frontend: visit the public event page (`/santigold/santigold-zeyzey-miami-miami-2026-05-23`) → confirm the tagged clips show the song name pill bottom-left on the mosaic. Click a song in the setlist rail → confirm the mosaic now filters to only those tagged clips.
- Edge cases:
 - Setting empty/whitespace tag → saves as `null` (pill disappears).
 - Long text > 120 chars → API returns 400.
 - Event with no setlist → editor shows text-input only (no dropdown). Confirm it still saves.
 - Logged-out user hitting the PATCH endpoint → 401 from middleware.

Show more

May 27





Claude responded: Clean build.

Clean build. Go test the bulk tagger first since that's the most useful workflow:


- 1 Go to `localhost:3000/admin/events/[id]` for the Morgan Wallen AT&T Stadium event
- 2 Scroll to the new "Tag media" section
- 3 You should see all uploaded media with a dropdown populated from the setlist
- 4 Tag a few clips with song names
- 5 Hit "Save all"
- 6 Then go to the public event page and verify the song pills appear on the media cards and the setlist filter actually filters correctly

That's the core loop — admin tags → public display → filter works.

The moderation queue test can wait since you said V1 auto-approves so it's likely empty.

One thing worth checking after: go to the Morgan Wallen entity page and see if the "Most Filmed Songs" section now shows accurate clip counts based on the tags you just set. That section should update automatically since it's querying `song_tag` counts from the media table.

How does the bulk tagger UI feel? Is the dropdown populated with the right songs?



Claude responded: Easy fix — you've hit the Mux free tier 10 asset limit.

Easy fix — you've hit the Mux free tier 10 asset limit.

Two options:

Option 1 — Delete test videos (free, 2 minutes) Go to Mux dashboard → Showside environment → Video → Assets → delete the test uploads you don't need. You only have 3 real ones worth keeping. Get back under 10 and uploads work again immediately.

Option 2 — Upgrade Mux to Pay-as-you-go (recommended) Pay-as-you-go removes the cap entirely. At your current volume it'll cost literally a few cents a month. This is the right move before any real users start uploading.


Go to Mux dashboard → Settings → Billing → upgrade to pay-as-you-go. No monthly fee — you only pay for what you use:

- ~\$0.015 per minute of video stored
- ~\$0.015 per GB streamed

For a V1 with light usage that's under \$5/month.

I'd do both — upgrade Mux now so you never hit a cap again, then delete the obvious test duplicates to keep things clean.

The pay-as-you-go upgrade takes 2 minutes and unblocks video uploads permanently. Worth doing before you go any further with testing.



You said: in theory, what are we using the 'verified' badge for?



in theory, what are we using the 'verified' badge for? also, are we thinking about adding a 'claimed' badge?

May 27



Claude responded: Good questions — let me think through both.

Good questions — let me think through both.

Verified Badge

Right now it's just seeded as `true` on all entities with no real logic behind it. The intention was always:

Verified = this entity page is confirmed to be about the real artist/team

Not that the artist themselves is involved — just that Showside has confirmed it's a legitimate page for that entity and not a duplicate or fake. You'd set this manually in the admin panel.

Think of it like Wikipedia's "this article is about the real person" — not an endorsement, just confirmation of identity.

Claimed Badge — Yes, Absolutely Add This

Claimed is a different and more meaningful signal:

Claimed = the artist, team, or their official representative has taken ownership of this page

What claiming unlocks:

- Artist can set their official hero image and bio
- They can pin specific clips to the top
- They get access to the artist dashboard (future monetization layer)
- Their uploads get a special "Official" tag
- They can respond to fan content

The distinction matters to users:

- **Verified** — this page is real
- **Claimed** — the artist is actually here

How The Badge System Should Work

Badge	Means	Set By
✓ Verified	Confirmed real entity	Showside admin
 Claimed	Artist/team controls page	Artist after outreach

Claimed implies verified — you can't be claimed without being verified first.

Schema

You already have `verified` boolean on entities. Just add:

```
sql
ALTER TABLE entities ADD COLUMN claimed BOOLEAN DEFAULT FALSE;
ALTER TABLE entities ADD COLUMN claimed_at TIMESTAMPTZ;
ALTER TABLE entities ADD COLUMN claimed_by TEXT; -- email or org name
```

V1 Reality

For V1 neither badge has real workflow behind it — they're both just admin-toggled booleans. The claimed workflow (artist submits request → you verify → you flip the flag) is a V2 feature when you actually have artists to claim pages.

But adding the `claimed` column and badge display now costs nothing and sets up the monetization narrative correctly from day one. When you pitch to an artist's team, showing them a "Claim this page" button is more compelling than explaining it's coming later.

Want to add the claimed badge to the schema and display it on entity pages?



You said: btw - the name of this app/site is now "c-roll" not showside anymore

btw - the name of this app/site is now "c-roll" not showside anymore

May 27



Claude responded: Got it — C-Roll it is.

Got it — C-Roll it is. Love it actually — plays on B-roll footage, implies the crowd/fan angle, easy to say and remember.

A few things to update across the codebase when you're ready:

Code/config changes:

- `package.json` — name field
- `next.config.js` — any references
- Page metadata/titles — the `<title>` tags and OG titles across all pages
- Nav logo — currently says "SHOWSIDE" or "c•roll" based on your last screenshot actually already showing "C-ROLL" which looks great
- `NEXT_PUBLIC_APP_URL` references
- Any hardcoded "Showside" strings in copy (about page, footer, etc.)
- JSON-LD structured data (sitemap, robots.txt)

External services:

- Supabase project name (cosmetic only, doesn't affect function)
- Mux environment name (cosmetic only)
- Vercel project name (cosmetic only)
- GitHub repo name — can rename from `showside` to `c-roll` in GitHub settings, then update your git remote

Give Claude Code this:

Rename the app from "Showside" to "C-Roll" throughout the codebase.


Find and replace all instances of "Showside" and "showside" with

"C-Roll" and "c-roll" respectively in:

- All page titles and metadata
- Nav/header components
- Footer components
- About/legal pages
- JSON-LD structured data
- Any user-facing copy strings

Do NOT rename database tables, column names, or environment variable names — those stay as-is.

Also update your Claude Project instructions with the new name when you get a chance.



You said: the title 'all clips' is not really correct - that title represents all the clips that have been tagged with a song title, not all total clips.



the title 'all clips' is not really correct - that title represents all the clips that have been tagged with a song title, not all total clips. whats a better title we can use there for the top of the set list?

May 27



Claude responded: You're right — "All clips" is misleading there since it's showing 8 tagged clips not all 10.

You're right — "All clips" is misleading there since it's showing 8 tagged clips not all 10.

Better options:

Most accurate:

- **By song** — describes what the list below actually is
- **Setlist** — clean, immediately understood
- **Browse by song** — descriptive

More editorial:


- **Step through the show** — you actually already have // STEP THROUGH THE SHOW as the section header above it, so this would be redundant
- **The setlist** — adds "the" for a bit more personality

My recommendation: "Setlist"

Simple, accurate, immediately understood. The number next to it (8) then makes sense as "8 songs have clips" rather than implying it's all clips.

The section header // STEP THROUGH THE SHOW above it gives the context, and "Setlist" as the first item label is clean and honest.

One word change for Claude Code — want to bundle it with any other small fixes?



You said: we need to build the 'Artists' page/tab.



we need to build the 'Artists' page/tab. what do you think should go on that page?

May 27



Claude responded: Love that nav — the yellow dot in "c·roll" is a nice touch.

Love that nav — the yellow dot in "c·roll" is a nice touch.

For the Artists page, think of it as the **discovery layer** for the music side of the platform. Here's what I'd put on it:

What The Artists Page Should Be

It's essentially a **browse/directory page** for all music entities on C-Roll. The goal is to help someone find an artist they care about, or discover one they didn't know had content here.

Page Structure

Hero/Header — simple and clean

- Page title: "Artists on C-Roll" or just "Artists"
- Subtitle: "Fan footage from [X] artists across [Y] shows"
- Search bar — type to filter the grid instantly

Filter Pills

- All / Most clips / Most followed / Recently active / A-Z
- Genre filters: Country / Pop / Hip-Hop / Rock / Indie / Electronic / R&B

Artist Grid The main content — cards for each artist entity:

- Hero/background image
- Artist name
- Genre badge
- Key stats: X shows · Y clips
- "Since [year]"
- Verified/Claimed badge if applicable

Cards link to the entity page.

Featured Section (top of grid)

- 2-3 "Featured Artists" shown larger at the top — manually curated by you in admin
- Rest of the grid below in uniform size

What Makes It Useful

- **Search** is the most important feature — someone lands here looking for a specific artist
- **"Recently active"** sort surfaces artists with fresh uploads — signals the platform is alive
- **Clip count** on each card is social proof — artists with more clips feel more worth clicking


V1 Shortlist

Keep it simple for now:

- 1 Search/filter bar
- 2 Genre filter pills
- 3 Artist grid with cards showing name, image, genre, show count, clip count

4 Sort by: Most clips / Most recent / A-Z
That's a complete, useful page. The featured section and advanced filters are V2.

Want the Claude Code prompt for this?



You said: maybe we just keep it the exact same structure as the Browse page for now - its a v1 - we just need a working page there



maybe we just keep it the exact same structure as the Browse page for now - its a v1 - we just need a working page there

May 27



Claude responded: That Browse page actually looks really good — clean grid, artist cards with images, follow buttons, clip counts, type badges (ARTIST / TEAM / EVENT).

That Browse page actually looks really good — clean grid, artist cards with images, follow buttons, clip counts, type badges (ARTIST / TEAM / EVENT).

Honestly you're right — for V1 the Artists page can just be the Browse page filtered to music entities only. One line of logic change, not a new page build.

Give Claude Code this:

The /artists route currently has no page. Instead of building something new, just create app/artists/page.tsx that renders the exact same component as the Browse page but pre-filtered to only show entities where type = 'music' or category = 'music' (whatever the correct field is in the schema).

Same layout, same cards, same sorting — just music artists only, no

sports teams or events.

Update the nav "Artists" link to point to /artists.

Do the same for /sports — pre-filtered to sports entities only.

That gives you three working nav links (Browse = everything, Artists = music only, Sports = sports only) with zero new UI to build. Events can wait or follow the same pattern.

Two pages, maybe 20 lines of code total.