

2b. Write a HTML program, to explain the working of tables by preparing a timetable.

(Note: Use <caption> tag to set the caption to the table & also use cell spacing, cell padding,

border, rowspan, colspan etc.).

Program:

```
<!DOCTYPE html>
```

```
<html>
```

```
  <head> <title>Time Table</title> </head>
```

```
  <body>
```

```
    <table border="1">
```

```
      <tr>
```

```
        <th>Day/Periods</th>
```

```
      <th>1          <p>9:30-10:20</p> </th>
```

```
        <th>2 <p>10:20-11:10</p> </th>
```

```
        <th>3 <p>11:10-12:00</p> </th>
```

```
        <th>4 <p>12:00-12:50</p> </th>
```

```
        <th> <p><br>12:50-1:50</p> </th>
```

```
        <th>5 <p>1:50-2:40</p> </th>
```

```
        <th>6 <p>2:40-3:30</p> </th>
```

```
        <th>7 <p>3:30-4:10</p> </th>
```

```
      </tr>
```

```
      <tr>
```

```
        <th>Monday</th>
```

```
        <td>DBMS</td>
```

```
        <td>P&S</td>
```

```
        <td>OS</td>
```

```
        <td>DT</td>
```

```
        <td rowspan="6"> <center><b>L <br> U <br> N <br> C <br> H </b></center></td>
```

```
        <td>SE</td>
```

```
        <td>DBMS</td>
```

```

        <td>OS</td>
    </tr>
    <tr>
        <th>Tuesday</th>
        <td>P&S</td>
        <td>DBMS</td>
        <td>MEFA</td>
        <td>DT</td>
        <td>SE</td>
        <td>P&S</td>
        <td>MEFA</td>
    </tr>
    <tr>
        <th>Wednesday</th>
        <td>DBMS</td>
        <td>MEFA</td>
        <td>P&S</td>
        <td>SE</td>
        <td colspan="3">
            <center>
                DT LAB
            </center>
        </td>
    </tr>
    <tr>
        <th>Thursday</th>
        <td>OS</td>
        <td colspan="3">
            <center>

```

DBMS LAB

</center>

</td>

<td>DBMS</td>

<td>MEFA</td>

<td>P&S</td>

</tr>

<tr>

<th>Friday</th>

<td>SE</td>

<td colspan="3">

<center>

OS LAB

</center>

</td>

<td>OS</td>

<td>MEFA</td>

<td>SE</td>

</tr>

<tr>

<th>Saturday</th>

<td>OS</td>

<td>SE</td>

<td>OS</td>

<td>DBMS</td>

<td colspan="3">

<center>

SOC LAB

</center>

</td>

</tr>

</table>

</body>

</html>

7a. a. Write a program using document object properties and methods.

Program:

```
<html>

<head><title>DOM Properties & Methods</title>

  <style>
    body {
      font-family: Arial, sans-serif;
      text-align: center;
      margin: 50px;
    }
    button {
      margin: 5px;
      padding: 10px;
      font-size: 16px;
    }
  </style>
</head>

<body>

  <h1 id="heading">JavaScript DOM Example</h1>
  <button onclick="changeTitle()">Change Page Title</button>
  <button onclick="changeBgColor()">Change Background Color</button>
  <button onclick="addNewParagraph()">Add Paragraph</button>
  <p id="message"></p>
  <script>
    function changeTitle() {
      document.title = "New Page Title!";
      document.getElementById("message").innerText = "Title changed
successfully!";
    }
    function changeBgColor() {
      document.body.style.backgroundColor = getRandomColor();
```

```
        document.getElementById("message").innerText = "Background color
changed!";
    }
    function addNewParagraph() {
        let newPara = document.createElement("p");
        newPara.innerText = "This is a dynamically added paragraph!";
        document.body.appendChild(newPara);
    }
    function getRandomColor() {
        let letters = "0123456789ABCDEF";
        let color = "#";
        for (let i = 0; i < 6; i++) {
            color += letters[Math.floor(Math.random() * 16)];
        }
        return color;
    }
</script>
</body>
</html>
```

7h. h. Write a program to explain user-defined object by using properties, methods, accessors, constructors and display.

Program:

```
<html>
<head>
    <title>User-Defined Object Example</title>
</head>
```

```
<body>
  <h1>User-Defined Object in JavaScript</h1>
  <p><strong>Car Details:</strong></p>
  <p id="carDetails"></p>
  <button onclick="showCarDetails()">Show Car</button>
  <button onclick="updateCarModel()">Update Model</button>
  <button onclick="updateCarYear()">Update Year</button>
  <p id="message"></p>
  <script>
    class Car {
      constructor(brand, model, year) {
        this.brand = brand;
        this.model = model;
        this.year = year;
      }
      get getModel() {
        return this.model;
      }
      set setModel(newModel) {
        this.model = newModel;
      }
      get getYear() {
        return this.year;
      }
      set setYear(newYear) {
        this.year = newYear;
      }
    }

    displayCar() {
      return `Brand: ${this.brand}, Model: ${this.model}, Year: ${this.year}`;
    }
  }
</script>

```

```
}  
  
let myCar = new Car("Toyota", "Corolla", 2022);  
  
function updateDisplay(result) {  
    document.getElementById("message").innerText = result;  
}  
  
function showCarDetails() {  
    document.getElementById("carDetails").innerText = myCar.displayCar();  
}  
  
function updateCarModel() {  
    myCar.setModel = "Camry";  
    updateDisplay("Car model updated to: " + myCar.getModel);  
    showCarDetails();  
}  
  
function updateCarYear() {  
    myCar.setYear = 2025;  
    updateDisplay("Car year updated to: " + myCar.getYear);  
    showCarDetails();  
}  
  
</script>  
</body>  
</html>
```