
SIM5218

WCDMA/HSDPA/ HSUPA/A-GPS Module





WCDMA/HSDPA(7.2Mbps)/HSUPA(5.76Mbps) /A-GPS Module – SIM5218

With High speed HSDPA /HSUPA functionality and strong capability in extension, SIM5218 is ideal for a wide arrange of products including USB Modems, gateways, routers, PDAs, Video Phone, tracking solutions, security solutions with Video and many more.

Advanced Features:

- Tri-Band UMTS 2100/1900/850MHz or 2100/1900/900MHz
- Quad-Band GSM, 850/900/1800/1900 MHz
- HSDPA 7.2Mbps
- HSUPA 5.76Mbps
- A-GPS or Stand-alone GPS positioning
- USB 2.0 High speed and UART support
- Integrated TCP/UDP/IP protocol stack
- Video call with Camera interface
- Embedded SIM card (option)
- WCDMA Diversity
- WCDMA Equalizer



WCDMA/HSDPA/HSUPA Module

General features:

- HSDPA 7.2Mbps
- HSUPA 2.0Mbps
- UMTS/HSDPA/HSDPA 850/1900/2100MHz
- Quad-Band GSM 850/900/1800/1900MHz
- GPRS multi-slot class 12
- EDGE multi-slot Class 12
- UMTS/HSDPA 3GPP release 5
- UMTS/HSUPA 3GPP release 6
- GSM 3GPP release 99
- Output power

UMTS 2100/1900/850: 0.25W

GSM850/GSM900: 2W DCS1800/PCS1900: 1W

- Control Via AT Commands
- Supply voltage range: 3.4V~ 4.2V
- Temperature range

Normal operation:-15 $^{\circ}$ C to +55 $^{\circ}$ C

Restricted operation :-20 $^{\circ}$ C to +70 $^{\circ}$ C Storage temperature :-40 $^{\circ}$ C to +85 $^{\circ}$ C

 \bullet Dimension: 58 imes 26 imes 4.5 mm

• Weight: TBD

Spec for A-GPS/Stand alone GPS:

•A-GPS mode: MS-Based, Ms- Assisted

Spec for Data transfer:

•HSDPA:

Max. 7.2Mbps(DL)

UE Category: 4, 6, 8, 12

•HSUPA

Max. 5.76Mbps(UL)

•WCDMA:

Max.384Kbps(DL), Max.384Kbps(UL)

•EDGE Class:

Max. 236.8Kbps(DL),Max.118Kbps(UL)

•GPRS

Max. 85.6Kbps(DL), Max.42.8Kbps(UL)

•CSD:

GSM Data rate 14.4Kbps WCDMA date rate 57.6Kbps

Distributed by:

Spec for SMS:

- Point to point MO and MT
- Text and PDU mode

Spec for Voice:

- Voice Codec HR, FR, EFR, AMR
- DTMF

Spec for CSD:

Support in GSM and WCDMA

Spec for network Identity and Time Zone (NITZ):

Support in GSM and WCDMA

Spec for video call:

- DTMF on H245
- Support standard WCDMA Video call (CS 64Kbps)

Other features:

- USB Driver for Microsoft Windows 2000/XP/Vista
- USB Driver for Linux 2.6.16
- Firmware update via USB

Interfaces:

- Embedded SIM card (option)
- USB2.0
- UART
- SIM card
- Audio: 2 Microphone, 3 speaker
- Video (Camera)
- GPIO
- I2C
- Min-SD card

More about SIM5218 Please contact:

Tel: 86-21-32523300
Fax: 86-21-32523020
Email: simcom@sim.com

Http:// www.sim.com/wm



TEXIM EUROPE

Partner in Electronic Components & Supply Chain Solutions



The Netherlands

Elektrostraat 17 NL-7483 PG Haaksbergen Tel: +31 (0)53 573 33 33 Fax: +31 (0)53 573 33 30

info@texim-europe.com



Belgium

Gentsesteenweg 1154-C22 Chaussée de Gand 1154-C22 B-1082 Brussel / Bruxelles Tel: +32 (0)2 462 01 00

Fax: +32 (0)2 462 01 99 info@texim-europe.com



Germany

Justus-von-Liebig-Ring 7-9 D-25451 Quickborn

Tel: +49 (0)4106 627 07-0 Fax: +49 (0)4106 627 07-20 info@texim-europe.com



Austria

Pyrkergasse 6/1 A-1190 Wien

Tel: +43 (0)1 369 09 09 - 0 Fax: +43 (0)1 369 09 10 info@texim-europe.com



Denmark

Fuglegaardsvaenget 25 DK-2820 Gentofte

Tel: +45 88 20 26 30 Fax: +45 88 20 26 39 info@texim-europe.com



United Kingdom

St. Mary's House, Church Lane Carlton Le Moorland Lincoln LN5 9HS

Tel: +44 (0)1522 789 555 Fax: +44 (0)845 299 22 26 info@texim-europe.com



Germany

Martin-Kollar-Strasse 9 D-81829 München

Tel: +49 (0)89 436 086-0 Fax: +49 (0)89 436 086-19 info@texim-europe.com



Elektrostraat 17

Tel: +31 (0)53 573 33 33 info@texim-europe.com www.texim-europe.com

