

# Announcements

- 🏆 **MILESTONE 2** due next Wednesday, Jan 24 at 6 PM SHARP
- 🏙️ **HACKATHON** TONIGHT 7 PM - 1 AM in 32-082 YAY
  - There will be food and drinks! 🍕 🥤
  - Nick will also give a mini lecture on how to get started on your project!
- 😄 **Homework 3: Setting up Render** required for deployment
  - Let us know if you didn't receive an email with a Render code
- 🎥 **Lecture recordings** are up at [weblab.is/recordings](https://weblab.is/recordings)
- 💖 **Subject Evaluations** are open Monday-Friday next week!
  - Special stickers for ppl who fill out their subject evals 👉 👈  
(take a screenshot of your completion page heh)

# State Management

Mark Tabor and Jay Hilton

# State in React

- `useState(initialValue) -> (state, setState)`
  - After `setState` called, components using state re-render

# State in React

- `useState(initialValue) -> (state, setState)`
  - After `setState` called, components using state re-render
- How do we get other components to use / update state?

# State in React

- `useState(initialValue) -> (state, setState)`
  - After `setState` called, components using state re-render
- How do we get other components to use / update state?
  - Pass state and `setState` as props!

# State in React

- `useState(initialValue) -> (state, setState)`
  - After `setState` called, components using state re-render
- How do we get other components to use / update state?
  - Pass state and `setState` as props!
- What if the component that needs the state is deep in the tree?

# State in React

- `useState(initialValue) -> (state, setState)`
  - After `setState` called, components using state re-render
- How do we get other components to use / update state?
  - Pass state and `setState` as props!
- What if the component that needs the state is deep in the tree?
  - Have to pass it through many components
  - We're sad...

# State in React

- `useState(initialValue) -> (state, setState)`
  - After `setState` called, components using state re-render
- How do we get other components to use / update state?
  - Pass state and `setState` as props!
- What if the component that needs the state is deep in the tree?
  - Have to pass it through many components
  - We're sad...
- Is there a better way?



# A Concrete Example

```
9   import React, { useState } from 'react';
10
11   const ParentComponent = () => {
12     const [name, setName] = useState('Alice');
13     setName('Ben');
14
15     return (
16       <div>
17         <ChildComponent name={name} />
18       </div>
19     );
20   };
21
22   const ChildComponent = ({ name }) => (
23     <div>
24       <h2>User Details</h2>
25       <p>Name: {name}</p>
26     </div>
27   );
28
29   export default ParentComponent;
```

Import useState


Create State and setState

setName to 'Ben'

Pass state as prop

ChildComponent has user as state and renders

# A Concrete Example



# Contexts to the Rescue!

- Create a context C
- Can use context C in any descendant of C.Provider

# Contexts to the Rescue!

- Create a context C
- Can use context C in any descendant of C.Provider
- How do I change C?

# Contexts to the Rescue!

- Create a context C
- Can use context C in any descendant of C.Provider
- How do I change C?
  - useState!

# Contexts to the Rescue!

- Create a context C
- Can use context C in any descendant of C.Provider
- How do I change C?
  - useState!
- How do I pass around the setter for C?

# Contexts to the Rescue!

- Create a context C
- Can use context C in any descendant of C.Provider
- How do I change C?
  - useState!
- How do I pass around the setter for C?
- useState hook as context too?

# Contexts to the Rescue!

- Create a context C
- Can use context C in any descendant of C.Provider
- How do I change C?
  - useState!
- How do I pass around the setter for C?
- useState hook as context too?
  - How do I know where C is changed?
  - Centralized updates would be nice for debugging



# Contexts to the Rescue!

- Create a context C
- Can use context C in any descendant of C.Provider
- How do I change C?
  - useState!
- How do I pass around the setter for C?
- useState hook as context too?
  - How do I know where C is changed?
  - Centralized updates would be nice for debugging


*This is a form of  
dependency injection,  
if you've heard of it.*

*If not, that's okay too!*

# Examples


# useContext Example 1

- Here's a component tree:



# useContext Example 1


- Here's a component tree:



- What is the value of the variable `x` in A? What about D?

# useContext Example 1


- Here's a component tree:



- What is the value of the variable **x** in A? What about D?
  - Answer: 5

# useContext Example 1


- Here's a component tree:



- What is the value of the variable **x** in A? What about D?
  - Answer: 5
- What about in F?

# useContext Example 1


- Here's a component tree:



- What is the value of the variable **x** in A? What about D?
  - Answer: 5
- What about in F?
  - We don't know!

## useContext Example 2


- Now you try!
- Here's a different component tree!






## useContext Example 2

- Now you try!
- Here's a different component tree!
- What's the value of the variable **user** in B?




## useContext Example 2

- Now you try!
- Here's a different component tree!
- What's the value of the variable **user** in B?
  - Answer: We don't know!




## useContext Example 2

- Now you try!
- Here's a different component tree!
- What's the value of the variable **user** in B?
  - Answer: We don't know!
- What about in C?



## useContext Example 2

- Now you try!
- Here's a different component tree!
- What's the value of the variable **user** in B?
  - Answer: We don't know!
- What about in C?
  - Answer: 'Ben'




# Many Contexts

- Can we have multiple contexts?


# Many Contexts

- Can we have multiple contexts?
- Maybe something like:




# Many Contexts

- Can we have multiple contexts?
- Maybe something like:



# Many Contexts


- Can we have multiple contexts?
- Maybe something like:
- TODO: (MAYBE MORE TEXT ABOUT IT?)






# useContext / useReducer Example 1

- Here's a component tree:



# useContext / useReducer Example 1


- Here's a component tree:



- What is the value of the variable **x** in A? What about D?

# useContext / useReducer Example 1


- Here's a component tree:



- What is the value of the variable **x** in A? What about D?
  - Answer: 5

# useContext / useReducer Example 1


- Here's a component tree:



- What is the value of the variable **x** in A? What about D?
  - Answer: 5
- What about in F?

# useContext / useReducer Example 1


- Here's a component tree:



- What is the value of the variable **x** in A? What about D?
  - Answer: 5
- What about in F?
  - We don't know!


## useContext / useReducer Example 2

- Now you try!
- Here's a different component tree!




## useContext / useReducer Example 2

- Now you try!
- Here's a different component tree!
- What's the value of the variable **user** in B?



## useContext / useReducer Example 2


- Now you try!
- Here's a different component tree!
- What's the value of the variable **user** in B?
  - Answer: We don't know!






## useContext / useReducer Example 2

- Now you try!
- Here's a different component tree!
- What's the value of the variable **user** in B?
  - Answer: We don't know!
- What about in C?



## useContext / useReducer Example 2

- Now you try!
- Here's a different component tree!
- What's the value of the variable **user** in B?
  - Answer: We don't know!
- What about in C?
  - Answer: 'Ben'




# Many Contexts

- Can we have multiple contexts?


# Many Contexts

- Can we have multiple contexts?
- Maybe something like:




# Many Contexts

- Can we have multiple contexts?
- Maybe something like:



# Many Contexts

- Can we have multiple contexts?
- Maybe something like:
- TODO: (MAYBE MORE TEXT ABOUT IT?)



Questions?

# State Machines



# Background: State Machines

- Initial state
- $\text{next}(\text{state}, \text{action}) \rightarrow \text{newState}$ 
  - Transition function
- Examples?

# Background: State Machines

- Initial state
- $\text{next}(\text{state}, \text{action}) \rightarrow \text{newState}$ 
  - Transition function
- Examples?
  - Washing machine: off, rinsing clothes, done
  - Garage door: closed, opening, open, closing
  - Oven: off, warming up, on (at some temperature), cooling down

# Background: State Machines

- Initial state
- $\text{next}(\text{state}, \text{action}) \rightarrow \text{newState}$ 
  - Transition function
- Examples?
  - Washing machine: off, rinsing clothes, done


# Background: State Machines

- Initial state
- `next(state, action) -> newState`
  - Transition function
- Examples?
  - Washing machine: off, rinsing clothes, done
  - Garage door: closed, opening, open, closing


# Background: State Machines

- Initial state
- $\text{next}(\text{state}, \text{action}) \rightarrow \text{newState}$ 
  - Transition function
- Examples?
  - Washing machine: off, rinsing clothes, done
  - Garage door: closed, opening, open, closing
  - Oven: off, warming up, on (at some temperature), cooling down

# Background: State Machine Diagrams



# Background: State Machine Diagrams



# Reducers



# ~~Contexts~~ Reducers to the Rescue!

- Reducer:  $f(\text{state}, \text{action}) \rightarrow \text{newState}$ 
  - Some initial state
  - Don't mutate state, just return the new state
    - Mutating makes it hard to see the past state
    - Seeing past state is nice for logging and debugging

# ~~Contexts~~ Reducers to the Rescue!

- Reducer:  $f(\text{state}, \text{action}) \rightarrow \text{newState}$ 
  - Some initial state
  - Don't mutate state, just return the new state
- Reducers are just state machines!
  - They often name the transition function `dispatch`

# ~~Contexts~~ Reducers to the Rescue!

- Reducer:  $f(\text{state}, \text{action}) \rightarrow \text{newState}$ 
  - Some initial state
  - Don't mutate state, just return the new state
- Reducers are just state machines!
  - They often name the transition function `dispatch`
- How do we call `dispatch`?

# ~~Contexts~~ Reducers to the Rescue!

- Reducer:  $f(\text{state}, \text{action}) \rightarrow \text{newState}$ 
  - Some initial state
  - Don't mutate state, just return the new state
- Reducers are just state machines!
  - They often name the transition function `dispatch`
- How do we call `dispatch`?
  - Import it! It's just like a function

# ~~Contexts~~ Reducers to the Rescue!

- Reducer:  $f(\text{state}, \text{action}) \rightarrow \text{newState}$ 
  - Some initial state
  - Don't mutate state, just return the new state
- Reducers are just state machines!
  - They often name the transition function `dispatch`
- How do we call `dispatch`?
  - Import it! It's just like a function
- Why might this be better?

# ~~Contexts~~ Reducers to the Rescue!

- Reducer:  $f(\text{state}, \text{action}) \rightarrow \text{newState}$ 
  - Some initial state
  - Don't mutate state, just return the new state
- Reducers are just state machines!
  - They often name the transition function `dispatch`
- How do we call `dispatch`?
  - Import it! It's just like a function

# ~~Contexts~~ Reducers to the Rescue!

- Why might this be better?

# ~~Contexts~~ Reducers to the Rescue!

- Why might this be better?
  - We can keep the update logic in one place!
  - Only worry about dispatching the right actions
  - Atomic updates: an action happens all at once if it's not async



# ~~Contexts~~ Reducers to the Rescue!

- Why might this be better?
  - We can keep the update logic in one place!
  - Only worry about dispatching the right actions
  - Atomic updates: an action happens all at once if it's not async
- Why are they named that?
  - Similar to `Array.reduce`
    - `Array.reduce((previousState, newItem) => { const nextState = f(previousState, newItem); return nextState });`
    - The function we use as a reducer is like the function we pass to `Array.reduce`

Questions?

# Some Example Reducer Code

\*don't worry if the code is small, we'll talk about each part in detail

```
const ShoppingList = () => {
  // Make a ref for the current value of our input form.
  const inputRef = useRef()
  // A reducer for the items in a shopping list. This might be useful
  // if our shopping cart changed in many places.
  const [items, dispatch] = useReducer((state, action) => {
    switch (action.type) {
      case 'add':
        return [
          ...state,
          {
            id: state.length,
            name: action.name,
          },
        ]
      case 'remove':
        // Keep every item except the one we want to remove
        return state.filter((_, index) => index !== action.index)
      default:
        return state
    }
  }, [])

  function handleSubmit(e) {
    // On submission, don't reload the page. Additionally, send
    // an add event to the reducer to add the item to the list.
    e.preventDefault()
    dispatch({
      type: 'add',
      name: inputRef.current.value,
    })
    inputRef.current.value = ''
  }

  // Render the list as a bulleted list of items with their names and
  // an x button that sends a remove event to the reducer when clicked.
  return (
    <div>
      <form onSubmit={handleSubmit}>
        <input ref={inputRef} />
      </form>
      <ul>
        {items.map((item, index) => (
          <li key={item.id}>
            {item.name}
            <button onClick={() => dispatch({ type: 'remove', index })}>
              X
            </button>
          </li>
        ))}
      </ul>
    </div>
  )
}
```

# Some Example Reducer Code

- Here's what a reducer looks like!
- switch is like an if statement here
  - If the type is add, add the item
  - If the type is remove, remove the item
  - For anything else, leave the state unchanged
- The state can be read with items
- But how do we use this code?

```
const [items, dispatch] = useReducer((state, action) => {  
  switch (action.type) {  
    case 'add':  
      return [  
        ...state,  
        {  
          id: state.length,  
          name: action.name,  
        }  
      ]  
    case 'remove':  
      // keep every item except the one we want to remove  
      return state.filter((_, index) => index !== action.index)  
    default:  
      return state  
  }  
}, [])
```

# Some Example Reducer Code

- This function, when called, will dispatch an add event
- Adds current value stored in input box to the list
  - inputRef was created earlier

```
function handleSubmit(e) {  
  // On submission, don't reload the page. Additionally, send  
  // an add event to the reducer to add the item to the list.  
  e.preventDefault()  
  dispatch({  
    type: 'add',  
    name: inputRef.current.value,  
  })  
  inputRef.current.value = ''  
}
```

# Some Example Reducer Code

- When the form is submitted, call `handleSubmit`
  - Adds value in input box to list
- When the button next to an item is clicked, remove it from the list
  - Button has an x inside

```
// Render the list as a bulleted list of items with their names and
// an x button that sends a remove event to the reducer when clicked.
return (
  <>
    <form onSubmit={handleSubmit}>
      <input ref={inputRef} />
    </form>
    <ul>
      {items.map((item, index) => (
        <li key={item.id}>
          {item.name}
          <button onClick={() => dispatch({ type: 'remove', index })}>X</button>
        </li>
      ))}
    </ul>
  </>
)
```

# A Reducer Example

- { type: "add", name: "cheese" }
- [ {id: 0, name: "cheese"} ]

```
const [items, dispatch] = useReducer((state, action) => {  
  switch (action.type) {  
    case 'add':  
      return [  
        ...state,  
        {  
          id: state.length,  
          name: action.name,  
        },  
      ]  
    case 'remove':  
      // keep every item except the one we want to remove  
      return state.filter((_, index) => index !== action.index)  
    default:  
      return state  
  }  
}, [])
```

# A Reducer Example

- { type: "add", name: "cheese" }
- [ {id: 0, name: "cheese"} ]
- { type: "add", name: "bread" }

```
const [items, dispatch] = useReducer((state, action) => {  
  switch (action.type) {  
    case 'add':  
      return [  
        ...state,  
        {  
          id: state.length,  
          name: action.name,  
        },  
      ]  
    case 'remove':  
      // keep every item except the one we want to remove  
      return state.filter((_, index) => index !== action.index)  
    default:  
      return state  
  }  
}, [])
```



# A Reducer Example

- { type: "add", name: "cheese" }
- [ {id: 0, name: "cheese"} ]
- { type: "add", name: "bread" }
- [ {id: 0, name: "cheese"}, {id: 1, name: "bread"} ]

```
const [items, dispatch] = useReducer((state, action) => {
  switch (action.type) {
    case 'add':
      return [
        ...state,
        {
          id: state.length,
          name: action.name,
        },
      ]
    case 'remove':
      // keep every item except the one we want to remove
      return state.filter((_, index) => index !== action.index)
    default:
      return state
  }
}, [])
```

# A Reducer Example

- { type: "add", name: "cheese" }
- [ {id: 0, name: "cheese"} ]
- { type: "add", name: "bread" }
- [ {id: 0, name: "cheese"}, {id: 1, name: "bread"} ]
- { type: "remove", index: 0 }

```
const [items, dispatch] = useReducer((state, action) => {
  switch (action.type) {
    case 'add':
      return [
        ...state,
        {
          id: state.length,
          name: action.name,
        },
      ]
    case 'remove':
      // keep every item except the one we want to remove
      return state.filter((_, index) => index !== action.index)
    default:
      return state
  }
}, [])
```

# A Reducer Example

- { type: "add", name: "cheese" }
- [ {id: 0, name: "cheese"} ]
- { type: "add", name: "bread" }
- [ {id: 0, name: "cheese"}, {id: 1, name: "bread"} ]
- { type: "remove", index: 0 }
- [ {id: 1, name: "bread"} ]

```
const [items, dispatch] = useReducer((state, action) => {
  switch (action.type) {
    case 'add':
      return [
        ...state,
        {
          id: state.length,
          name: action.name,
        },
      ]
    case 'remove':
      // keep every item except the one we want to remove
      return state.filter((_, index) => index !== action.index)
    default:
      return state
  }
}, [])
```

Questions?

# But how can we share reducer values?

- useContext!
  - Share the value with useContext
- Export the dispatch function from one central place
  - Ex: dispatch.js
  - We can just import it then!

# State Management

- useContext / useReducer: simple state management
- Change state in a centralized file without explicitly passing it around
  - Dispatch actions to modify state

# State Management

- useContext / useReducer: simple state management
- Change state in a centralized file without explicitly passing it around
  - Dispatch actions to modify state
  - This is more *declarative*: we're saying what we want to do
    - Often more understandable

# State Management

- useContext / useReducer: simple state management
- Change state in a centralized file without explicitly passing it around
  - Dispatch actions to modify state
  - This is more *declarative*: we're saying what we want to do
    - Often more understandable
  - Easier to change how we handle updates if logic changes



# State Management

- Sneak peek: Redux!
  - More complex state management
  - Leverages immutability more

# State Management

- Sneak peek: Redux!
  - More complex state management
  - Leverages immutability more
    - Better tooling

# Redux

- Everything you just saw, and more:

# Redux

- Everything you just saw, and more:
  - Better dev tools!
    - Can see what actions are emitted, in the browser!

# Redux

- Everything you just saw, and more:
  - Better dev tools!
    - Can see what actions are emitted, in the browser!
  - Time travel debugging
    - Replay the actions emitted and watch state change!

# Redux

- Everything you just saw, and more:
  - Better dev tools!
    - Can see what actions are emitted, in the browser!
  - Time travel debugging
    - Replay the actions emitted and watch state change!
  - Can easily log actions to see what's going on in the app

# Redux

- Structurally a little different
  - Single global data structure that reducers are looked up in

# Redux

- Structurally a little different
  - Single global data structure that reducers are looked up in
  - But global variables are bad!



# Redux

- Structurally a little different
  - Single global data structure that reducers are looked up in
  - But global variables are bad!
  - Not so bad if we can very easily tell when they change

# Redux

- Structurally a little different
  - Single global data structure that reducers are looked up in
  - But global variables are bad!
  - Not so bad if we can very easily tell when they change
- Adds even more complexity than useContext/useReducer

# Which should I use?

- Should we use state management here? If so, which?

# Which should I use?

- Should we use state management here? If so, which?
- Example 1: Counter component (like in Catbook!)

# Which should I use?

- Should we use state management here? If so, which?
- Example 1: Counter component (like in Catbook!)
  - No State Management!

# Which should I use?

- Should we use state management here? If so, which?
- Example 1: Counter component (like in Catbook!)
  - No State Management!
- Example 2: Task management dashboard with a task list, task detail view, and a sidebar with filters

# Which should I use?

- Should we use state management here? If so, which?
- Example 1: Counter component (like in Catbook!)
  - No State Management!
- Example 2: Task management dashboard with a task list, task detail view, and a sidebar with filters
  - useContext/useReducer!

# Which should I use?

- Should we use state management here? If so, which?
- Example 1: Counter component (like in Catbook!)
  - No State Management!
- Example 2: Task management dashboard with a task list, task detail view, and a sidebar with filters
  - useContext/useReducer!
- Example 3: Large e-Commerce platform with a shopping cart, user authentication, and various product pages



# Which should I use?

- Should we use state management here? If so, which?
- Example 1: Counter component (like in Catbook!)
  - No State Management!
- Example 2: Task management dashboard with a task list, task detail view, and a sidebar with filters
  - useContext/useReducer!
- Example 3: Large e-Commerce platform with a shopping cart, user authentication, and various product pages
  - Redux!

# Wrap-up

- There's a lot more that we haven't said
  - Redux is complicated
  - Interesting performance optimizations
    - Re-render only when relevant state changes
- State management adds complexity
  - Can make code more maintainable and easier to understand
- Maybe it's a good idea for your project!
- Questions?