STANDARD ARRIVAL CHART-INSTRUMENT

ATIS 126.4 APP01 127.9(120.9) APP02 125.25(120.9) APP03 119.275(120.9) TWR 118.2(130.0)

ZBTJ TIANJIN/Binhai RNAV RWY34L/R (DUMAP AVBOX)

VAR6°W BEARINGS ARE MAGNETIC ALTITUDES, ELEVATIONS AND HEIGHTS IN METERS DME DISTANCES TL 3600 TA 3000 3300(QNH≥1031hPa) 2700(QNH≤979hPa) 1. RNAV 1 2. RADAR REQUIRED DME DISTANCES IN NAUTICAL MILES DISTANCES IN KM 3. GNSS, IRU REQUIRED ZB(P)001 Ν NOT TO SCALE ⚠ Outbound distance 10km O No aircraft is permitted to maneuver or circumnavigate CB in Prohibited Fly Over Area. TIANJIN APP AREA TIANJIN -112.1 TAJ CH 58X N39 06.6E117 21.5 TJ824 1500 <u>110°</u> TJ823 IAF AVBOX-5ZA, 7ZA TJ820 TJ830 1200 TJ840 3040 TJ821 TJ862 010° 1800 TJ841 TJ822 1500 AVBOX 900 2700 **DUMAP** 2400 IAF TJ830 TJ820 900 900 MAX205kt MAX205kt (for AVBOX-5ZA DUMAP-5ZA) (for AVBOX-7ZA) TJ84 1500 TJ840 TAJ TJ821 900 900 MAX205kt 900 (for DUMAP-7ZA) MSA 46km Changes: Add Prohibited Fly Over Area.