

STANDARD DEPARTURE CHART-INSTRUMENT

VAR4° W
ATIS 127.05
APP01 119.625(132.15)
APP02 120.25(132.15)
APP03 127.975(132.15)
TWR 118.875(118.2)

ZSWZ WENZHOU/Longwan
RNP RWY21

BEARINGS ARE MAGNETIC
ALTITUDES, ELEVATIONS
AND HEIGHTS IN METERS
DME DISTANCES IN
NAUTICAL MILES
DISTANCES IN KM

TL 3600
TA 3000
3300(QNH≥1031hPa)
2700(QNH≤979hPa)

SHENGZHOU
113.4 SHZ
CH 81X
N29 36.0E120 49.0

- GNSS REQUIRED
- RNP1



YUNHE
244 BZ
N28 06.1E119 33.7

WZ402
ALT by ATC

WZ421
2100
or by ATC

SHENGZHOU
113.4 SHZ
CH 81X
N29 36.0E120 49.0

WENZHOU
116.4 WNZ
CH 111X
N27 55.8E120 51.8

WZ401
5500
or by ATC
MAX 400kmH

BEGMO
9000
or by ATC

DONGSHAN
109.2 DST
CH 29X
N27 45.0E120 37.8

WZ411
294

WZ503
700

WZ508
099° 26

OKATO
6000
or by ATC


WZ406
5500
or by ATC
MAX 400kmH

Note:

- Turning is forbidden before DER.
- It is available to gain the ALT at WZ401 and WZ406 for holding pattern if cannot get the required ALT by ATC: BEG-62X, OKA-62X.

RUPOX

LIANJIANG
117.6 LJG
CH 123X
N26 13.2E119 32.9



Changes: Speed.