

RootFin (Brynex Test Environment) — Project Documentation


RootFin is a retail ERP / finance platform built by **Rootments** for a chain of stores (shoe / suit / wedding-wear retail). It covers daily cash & bank accounting (Day Book, closures, security deposits), purchasing, sales, inventory (items, groups, adjustments, transfers, store orders) and reporting.

This repository (`RootfinBrynexTestenv`) is the **test environment** of the project: a React SPA (`frontend/`) and a Node/Express API (`backend/`) that can talk to MongoDB, PostgreSQL, or both.

Table of Contents

1. [Architecture](#)
 2. [Repository Layout](#)
 3. [Tech Stack & Dependencies](#)
 4. [Getting Started](#)
 5. [Configuration](#)
 6. [Backend in Detail](#)
 7. [Frontend in Detail](#)
 8. [Domain Modules](#)
 9. [Roles, Access Control & Guards](#)
 10. [CI/CD & Deployment](#)
 11. [Maintenance Scripts](#)
 12. [Housekeeping Files & Known Issues](#)
 13. [Git Workflow](#)
-

1. Architecture



- **Frontend** is a client-routed SPA; session user is kept client-side (`currentuser`) and each route is guarded by role/store checks.

- **Backend** is a layered Express app. A `DB_TYPE` switch (`mongodb` | `postgresql` | `both`) selects which databases are connected at startup.
- **Mongoose models** (`backend/model/`) are the primary data layer; **Sequelize models** (`backend/models/sequelize/`) mirror a subset for the PostgreSQL migration (see §6.4).
- In-memory caching (`node-cache`) is used for heavy report endpoints.

2. Repository Layout

```

RootfinBrynexTestenv/
├─ README.md                ← this document
├─ package.json             root-level deps (cookie-parser, cors, express, mongoose,
nodemailer, react-*, vite)
├─ .github/workflows/
│   └─ deploy.yml           rsync + PM2 deploy to EC2 on push to master
│   └─ daily-commit-report.yml daily Conventional-Commits audit
├─ .vscode/settings.json    editor settings
├─ backend/
│   └─ server.js            app entry point
│   └─ swagger.js          Swagger UI at /api-docs
│   └─ .env                environment variables (not committed to docs)
│   └─ db/                 database.js (Mongo), postgresql.js (Sequelize)
│   └─ route/              Express routers (24 files)
│   └─ controllers/        request handlers (≈30 files)
│   └─ model/               Mongoose schemas (≈25 files)
│   └─ models/sequelize/   Sequelize models (11 files + index.js)
│   └─ utils/               stock engines, numbering, cache, e-mail
│   └─ utlis/               legacy helpers (parseBase64, nextInvoice) – note typo in
folder name
│   └─ scripts/             one-off DB maintenance / migration scripts
├─ frontend/
│   └─ index.html, vite.config.js, vercel.json, eslint.config.js
│   └─ public/              static assets
│   └─ src/
│       └─ main.jsx, App.jsx bootstrap + all routes
│       └─ api/api.js        API base URL
│       └─ components/       shared UI (Nav, Header, guards, uploads...)
│       └─ pages/            ≈100 page components
│       └─ hooks/            data-fetching & UX hooks
│       └─ utils/            cache, alerts, warehouse mapping, image upload
│       └─ config/           salesInventoryAccess.json (feature gating)
│       └─ data/             openingBalance.json
├─ production_changes.patch  patch captured when syncing production → test
└─ fix_home.cjs / fix_report.cjs / scratch.jsx  ad-hoc dev helpers

```

3. Tech Stack & Dependencies

Backend (backend/package.json , ES modules)

Package	Purpose
express 4	HTTP server
mongoose 8	MongoDB ODM
sequelize 6 + pg	PostgreSQL ORM / driver
bcrypt	password hashing
cookie-parser, cors, body-parser	HTTP middleware
dotenv, cross-env	env loading / cross-platform <code>NODE_ENV</code>
node-cache	in-memory report cache
nodemailer	reorder-alert & PO e-mails
node-fetch	outbound HTTP
swagger-jsdoc, swagger-ui-express	API docs
nodemon	dev auto-reload

Scripts: `npm start` (production, 2 GB heap), `npm run dev` (nodemon, development), `check-transfers`, `optimize:quick`, `optimize:full` (index creation), `test:stock`.

Frontend (frontend/package.json , Vite)

Package	Purpose
react 19, react-dom, react-router-dom 7	UI + routing
tailwindcss 4 (@tailwindcss/vite), daisyui 4	styling
react-select	searchable dropdowns
react-toastify	notifications
recharts	charts
lucide-react, react-icons	icons
jspdf, html2pdf.js, html2canvas-pro	PDF export (html2canvas-pro adds <code>oklch()</code> colour support)
react-to-print, react-csv	print / CSV export
html5-qrcode	barcode / QR scanning
react-helmet	document head

Scripts: `dev`, `build`, `lint`, `preview`.

Root package.json

Holds a duplicate set of shared libs (cookie-parser, cors, express 5, mongoose, nodemailer, react-csv, react-helmet, react-icons, vite). It is **not** the runtime manifest for either app; install inside `backend/` and `frontend/`.

4. Getting Started

Prerequisites: Node 18+, a MongoDB URI, (optional) PostgreSQL 13+.

```
git clone <repo-url> && cd RootfinBrynexTestenv

# Backend
cd backend
npm install
cp .env .env.local # then edit values (see §5)
npm run dev        # http://localhost:7000 (or PORT)

# Frontend (new terminal)
cd frontend
npm install
npm run dev        # http://localhost:3000
```

Then open `http://localhost:3000` . API docs: `http://localhost:<PORT>/api-docs` . Health: `GET /api/test` , DB state: `GET /api/db-status` .

Point the frontend at your local API by editing `frontend/src/api/api.js` (see §5.3).

5. Configuration

5.1 Backend environment variables (`backend/.env`)

`server.js` loads `.env.<NODE_ENV>` if that file exists, otherwise `.env` .

Variable	Used by	Description
<code>PORT</code>	<code>server.js</code>	listen port, default <code>7000</code>
<code>NODE_ENV</code>	everywhere	<code>development</code> (default) or <code>production</code>
<code>DB_TYPE</code>	<code>server.js</code>	<code>mongodb</code> (default), <code>postgresql</code> , or <code>both</code>
<code>MONGODB_URI</code>	<code>db/databases.js</code>	fallback Mongo connection string
<code>MONGODB_URI_PROD</code>	<code>db/databases.js</code>	used when <code>NODE_ENV=production</code>
<code>MONGODB_URI_DEV</code>	<code>db/databases.js</code>	used in non-production
<code>POSTGRES_DB_DEV</code> / <code>_USER_DEV</code> / <code>_PASSWORD_DEV</code> / <code>_HOST_DEV</code> / <code>_PORT_DEV</code>	<code>db/postgresql.js</code>	dev PG credentials (defaults: <code>rootfin_dev</code> , <code>postgres</code> , <code>postgres</code> , <code>localhost</code> , <code>5432</code>)
<code>POSTGRES_*_PROD</code> / <code>POSTGRES_URI_PROD</code> / <code>DATABASE_URL</code>	<code>db/postgresql.js</code>	production PG credentials or connection URI
<code>POSTGRES_URI_DEV</code>	<code>db/postgresql.js</code>	optional dev connection URI

Variable	Used by	Description
POSTGRES_LOGGING	db/postgre sql.js	true logs SQL
SYNC_DB	db/postgre sql.js	true runs <code>sequelize.sync()</code> on connect
e-mail settings	utils/emailS ervice.js	SMTP configuration for nodemailer

Values are supplied per environment and are never documented here.

Resilience features in `db/database.js` : environment-specific connection strings, protection against cross-environment connections, and `disconnected` / `reconnected` / `error` listeners.

Express middleware (`server.js`): JSON & urlencoded body limit **10 MB** (base64 attachments), `cookie-parser` , CORS with credentials.

CORS: an explicit origin allow-list (local dev and deployed frontends) is configured in `server.js` . Add new frontend origins there.

5.2 PostgreSQL pool / SSL

`db/postgresql.js` builds config per environment, supports a full URI with `dialectOptions` (SSL) and connection `pool` settings, and optionally syncs tables when `SYNC_DB=true` .

5.3 Frontend configuration

File	Purpose
<code>src/api/api.js</code>	exports <code>{ baseUrl }</code> , the API root used by every page. Set it to your local or deployed API (or switch to <code>import.meta.env.VITE_API_URL</code>).
<code>vite.config.js</code>	plugins <code>react()</code> and <code>tailwindcss()</code> ; dev server on port 3000 .
<code>vercel.json</code>	rewrites all paths to <code>/index.html</code> (SPA routing).
<code>eslint.config.js</code>	ESLint 9 flat config with react-hooks / react-refresh.
<code>src/config/salesInventoryAccess.json</code>	<code>allowedEmails</code> list — stores allowed to see Sales and Inventory menus (see §9). Case-insensitive; rebuild required in production.
<code>src/config/README.md</code>	how to add/remove stores from that list
<code>src/data/openingBalance.json</code>	opening balance seed data for stores

6. Backend in Detail

6.1 Startup flow (`server.js`)

1. Load env file → create Express app → `setupSwagger(app)` .
2. Apply body parsers, cookies, CORS, `OPTIONS *` preflight.

3. Mount routers (all under `/api` unless noted).
4. Utility endpoints: `GET /` (liveness text), `GET /api/test`, `GET /api/db-status` (reports Mongo `readyState` and PG authentication).
5. `app.listen` → connect DBs by `DB_TYPE`. PostgreSQL failure is non-fatal when Mongo is used; Mongo failure exits the process.

6.2 Routers → API surface

Router file	Base path(s)	Main endpoints
LoginRoute.js	/api (users)	POST /signin, POST /login, GET /getAllStores, GET /getAllUsers, PUT /updateUser/:id, DELETE /deleteUser/:id, POST /reset-password, POST /createPayment, GET /Getpayment, POST /saveCashBank, GET /getsaveCashBank, GET /pendingClosures, PUT /approveClosure/:id, GET /AdminColseView, GET /getTransactions, POST /syncTransaction, PUT /editTransaction/:id, GET /transaction/:id/attachment, GET /financialSummaryWithEdit
TwsRoutes.js	/api	GET /getEditedTransactions, GET /getsaveCashBank
DayBookRoutes.js	/api	GET /daybook, GET /daybook/range
ExpenseTargetRoutes.js	/api	POST/GET /expense-targets, GET /expense-targets/all
ShoeItemRoutes.js	/api	/shoe-sales/items, /:itemId, /:itemId/history
ItemGroupRoutes.js	/api	/shoe-sales/item-groups, /:id, /:id/items/:itemId/history, /:id/monthly-opening-stock
ManufacturerRoutes.js / BrandRoutes.js	/api	/shoe-sales/manufacturers[:id], /shoe-sales/brands[:id]
AddressRoutes.js	/api	/purchase/addresses[:id]
VendorRoutes.js	/api	/purchase/vendors[:id], /:vendorId/history
BillRoutes.js	/api	/purchase/bills[:id], /purchase/orders/:id/convert-to-bill, /purchase/receives/:id/convert-to-bill
VendorCreditRoutes.js	/api	/purchase/vendor-credits[:id], /next-number, /available, /apply-to-bill
PurchaseOrderRoutes.js	/api	/purchase/orders[:id], /number/:orderNumber, /next-number, POST /:id/send
PurchaseReceiveRoutes.js	/api	/purchase/receives[:id], /next-number, POST /:id/send

Router file	Base path(s)	Main endpoints
InventoryAdjustmentRoutes.js	/api	/inventory/adjustments[:id] , /next-reference , /stock/item
TransferOrderRoutes.js	/api	/inventory/transfer-orders[:id] , /:id/receive , /stock/item
StoreOrderRoutes.js	/api	/inventory/store-orders[:id] , /next-number
StoreRoutes.js	/api	/stores[:id] , /stores/loc/:locCode
SalesPersonRoutes.js	/api	/sales-persons[:id] , /loc/:locCode
SalesInvoiceRoutes.js	/api	/sales/invoices[:id] , POST /next-number
SalesReportRoutes.js	/api /reports/sales	/by-invoice , /summary , /by-item , /returns , /by-group
InventoryReportRoutes.js	/api /reports/inventory	/summary , /stock-summary , /valuation , /aging , /opening-stock , /stock-on-hand
ReorderAlertRoutes.js	/api	/reorder-alerts , /warehouse/:w , PUT /:id/notify , PUT /:id/resolve , DELETE /:id , POST /test-email
MergRoutes.js	/api	GET /mergedTransactions (currently commented out in server.js)

Other: /api-docs (Swagger UI), /api/test , /api/db-status .

6.3 Controllers (backend/controllers/)

Controller	Responsibility
LoginAndSignup.js	sign-up, login (bcrypt), user CRUD, password reset, store/user lists, payments
CloseController.js	cash/bank day closing, approval of pending closures, admin close view
DayBookController.js	Day Book per store/day and date ranges
TransactionController.js , TwsTransaction.js , TwsControllers.js , EditController.js	transaction sync, edit history, attachments, financial summary
ExpenseTargetController.js	monthly expense targets per store
ShoeItemController.js , ItemGroupController.js	items, groups, stock per warehouse, item history, monthly opening stock
ManufacturerController.js , BrandController.js	catalogue masters

Controller	Responsibility
VendorController.js , VendorHistoryController.js , AddressController.js	vendors, history log, addresses
PurchaseOrderController.js , PurchaseReceiveController.js , BillController.js , VendorCreditController.js	purchase cycle & numbering
InventoryAdjustmentController.js , TransferOrderController.js , StoreOrderController.js	stock movements
SalesInvoiceController.js , SalesPersonController.js	sales, returns, salespeople
SalesReportController.js , SalesByGroupController.js , InventoryReportController.js , OptimizedReportController.js	reports (cached)
StoreController.js	store master CRUD

6.4 Data layer

Mongoose models (backend/model/) User, Store, Transaction, TransactionHistory, Close (Closing.js), ExpenseTarget, Shoeltem, ItemGroup, ItemHistory, Manufacturer, Brand, Vendor, VendorHistory, VendorCredit, Address, PurchaseOrder, PurchaseReceive, Bill, InventoryAdjustment, TransferOrder, StoreOrder, SalesInvoice, SalesPerson, ReorderAlert, Counter (auto-number sequences).

Sequelize models (backend/models/sequelize/) — InventoryAdjustment, SalesInvoice, SalesPerson, Store, StoreOrder, Transaction, TransferOrder, User, Vendor, VendorCredit, VendorHistory, wired together in index.js .

6.5 Utilities (backend/utils/)

File	Role
stockManagement.js → improvedStockManagement.js → ultraEnhancedStockManagement.js	successive generations of the stock-update engine (per-warehouse quantity changes for sales, returns, receives, transfers, adjustments)
stockValidationSystem.js	validates stock consistency before/after operations
monthlyStockTracking.js	month-wise opening/closing stock
cashPropagation.js	carries closing cash/bank balances forward to later days
next*.js (SalesInvoice, PurchaseOrder, PurchaseReceive, CreditNote, StoreOrder, ItemGroup, InventoryAdjustment)	auto-increment document numbers via Counter
cacheManager.js	node-cache wrapper (TTL 300 s, generateCacheKey)
emailService.js , reorderNotification.js	nodemailer; low-stock reorder alerts
vendorHistoryLogger.js	vendor audit trail

6.6 Swagger

swagger.js builds a spec with swagger-jsdoc from JSDoc comments in route/*.js (e.g. in LoginRoute.js) and serves it at /api-docs .

7. Frontend in Detail

7.1 Bootstrapping

- `main.jsx` renders `<App />` in the router.
- `App.jsx` reads the logged-in user from client storage (`currentUser`), defines every `<Route>` , and wraps pages with guards.
- Unauthenticated users are redirected to `/login` ; authenticated users visiting `/login` are redirected to `/` .

7.2 Shared components (`src/components/`)

Component	Purpose
<code>Nav.jsx</code>	sidebar menu; applies role and <code>salesInventoryAccess</code> gating
<code>Header.jsx</code> , <code>Head.jsx</code>	top bar / document head
<code>DaybookGuard.jsx</code>	blocks pages until the previous day's Day Book is closed
<code>OptimizedTable.jsx</code>	paginated/virtualised data table
<code>AssignTargetModal.jsx</code>	set expense targets
<code>ImageUpload.jsx</code> , <code>SingleImageUpload.jsx</code> , <code>AttachmentDisplay.jsx</code>	base64 attachments
<code>LoadingScreen.jsx</code>	loading UI

7.3 Hooks (`src/hooks/`)

`useFetch` , `useOptimizedFetch` (cached fetching), `useFinancialData` , `useSidebar` , `useEnterToSave` , `usePreventNumberInputScroll` .

7.4 Utils (`src/utils/`)

`cache.js` (client cache), `customAlert.jsx` / `customConfirm.jsx` (styled dialogs), `imageUpload.js` , `warehouseMapping.js` (store ↔ warehouse names / location codes).

7.5 Page / route map (`src/pages/`)

Area	Routes	Pages
Auth	<code>/login</code>	Login
Home & Day Book	<code>/</code> , <code>/daybook</code> , <code>/datewisedaybook</code> , <code>/RentOutReport</code> , <code>/BookingReport</code>	Home, DayBook, Datewisedaybook, Booking
Accounts	<code>/income</code> , <code>/expenses</code> , <code>/Income&Expenses</code> , <code>/CashBankLedger</code> , <code>/securityReport</code> , <code>/Revenuereport</code>	Income, Expenses, SecurityReturn, SecurityPending, Security, Revenuereport, IncomeExpenseReport, BillWiseIncome

Area	Routes	Pages
Closing (admin)	<code>/CloseReport</code> , <code>/AdminClose</code> , <code>/PendingDaybookClosures</code>	CloseReport, AdminClose, PendingDaybookClosures
Store/ User admin	<code>/ManageStores</code> , <code>/manage-users/*</code>	ManageStores, AddNewStore, AddNewUser, ExistingUsers, EditUser, ResetUserPassword
Items	<code>/shoe-sales/items</code> , <code>/item-groups</code> , <code>/price-lists</code> , <code>/inactive-items</code> , <code>.../stocks</code>	ShoeSalesItems, ShoeSalesItemCreate/Detail/DetailFromGroup, ShoeSalesItemGroups/Create/Detail, ShoeSalesPriceLists/Create, InactiveItems, ItemStockManagement, StandaloneItemStockManagement
Inventory	<code>/inventory/adjustments</code> , <code>/packages</code> , <code>/transfer-orders</code> , <code>/store-orders</code> , <code>/reorder-alerts</code>	InventoryAdjustments/Create/Detail, InventoryPackages/Create, TransferOrders/Create/View, StoreOrders/Create/View, ReorderAlerts
Sales	<code>/sales/customers</code> , <code>/orders</code> , <code>/invoices/returns</code>	/new
Purchase	<code>/purchase/orders</code> , <code>/receives</code> , <code>/bills</code> , <code>/payments</code> , <code>/vendor-credits</code> , <code>/vendors</code> (each with <code>/new</code> , <code>/:id</code> , <code>/:id/edit</code>)	PurchaseOrders/Create/Detail, PurchaseReceives/Create/Detail, Bills, BillDetail, BillBooking, PaymentsMade, VendorCredits, VendorCreditDetail, PurchaseVendors/Create/Detail
Reports	<code>/reports/sales</code> , <code>/sales-by-invoice</code> , <code>/sales-by-group</code> , <code>/inventory</code> , <code>/income-expense</code>	SalesReport, SalesByInvoiceReport, SalesByGroupReport, InventoryReport, IncomeExpenseReport, OptimizedFinancialSummary

7.6 PDF / print

Day Book and report PDFs use `html2canvas-pro` + `jspdf` (fits to a single page; supports Tailwind 4 oklch colours). Print views use `react-to-print`.

7.7 Tests

`src/pages/__tests__` contains tests for transfer-order creation and warehouse filtering. No test runner script is defined in `package.json`.

8. Domain Modules

1. **Day Book & Closure** – each store records transactions (income, expense, payments, security deposits/returns, bookings). At day end the store submits a *cash/bank closing*; supervisors/admins approve in *Pending Daybook Closures*. `cashPropagation` carries balances forward. `DaybookGuard` forces yesterday to be closed first.
2. **Expense Targets** – per-store monthly targets (`AssignTargetModal`).
3. **Items & Groups** – items belong to item groups with per-warehouse stock, price lists, brands, manufacturers, history logs and monthly opening stock.
4. **Purchase cycle** – Vendor → Purchase Order → Purchase Receive (adds stock) → Bill → Payments Made; Vendor Credits applied to bills; vendor history log.
5. **Inventory control** – adjustments, inter-warehouse transfer orders (with receive step), store orders, reorder alerts with e-mail.

6. **Sales** – invoices (auto-numbered), returns, credit notes, salespeople per location, sales reports by invoice / item / group.
7. **Reporting** – inventory valuation, aging, stock-on-hand, opening stock; sales summaries; financial summary; results cached for 5 minutes.

9. Roles, Access Control & Guards

- `power: 'admin'` – full access: user/store management, close reports, stock-management pages, Purchase section.
- Head-office location users – may access `AdminClose`.
- `role: 'supervisor'` (and admin) – `PendingDaybookClosures`.
- **Cluster manager** (`isClusterManager`) – redirected to `/datewisedaybook` home; `ClusterGuard` limits income/expense pages.
- **Sales & Inventory visibility** – menu items appear only for emails in `frontend/src/config/salesInventoryAccess.json`.
- **DaybookGuard** – wraps most operational pages (requires previous-day close).

10. CI/CD & Deployment

Piece	Details
Frontend	Vercel; <code>vercel.json</code> rewrites to <code>index.html</code> .
Backend	Render and/or AWS EC2.
<code>.github/workflows/deploy.yml</code>	On push to <code>master</code> : checkout → configure SSH from repository secrets → <code>rsync</code> to the server → <code>npm install</code> → restart via PM2. Credentials are stored as GitHub Actions secrets.
<code>.github/workflows/daily-commit-report.yml</code>	scheduled; lists recent commits and flags those not matching Conventional Commits (<code>type(scope): summary</code>) in the run summary.

Production start: `NODE_ENV=production node --max-old-space-size=2048 server.js`.

11. Maintenance Scripts (`backend/scripts/` , run with `node`)

Script	Purpose
<code>check-database-connection.js</code>	verify DB connectivity
<code>create-indexes.js</code> , <code>quick-optimize.js</code> , <code>optimize-data-types.js</code>	index / performance tuning
<code>sync-stores-to-postgresql.js</code> , <code>migrate-vendors-to-postgresql.js</code> , <code>sync-vendor-history-table.js</code>	Mongo → PostgreSQL migration
<code>add-vendor-credit-columns.js</code> , <code>drop-invoiceno-unique-index.js</code>	schema fixes
<code>analyze-cash-closecash-issue.js</code> , <code>fix-cash-closecash-swap.js</code> , <code>MIGRATION_CASH_CLOSECASH_README.md</code>	repair swapped cash/closeCash values

Script	Purpose
<code>recalculate-close-balances.js</code>	rebuild closing balances
<code>fix-return-location-codes.js</code> , <code>test-return-query.js</code> , <code>check-transfer-orders.js</code> , <code>test-calc.js</code>	data fixes / diagnostics

Also in `backend/`: `query_closures.js`, `query_targets.js`, `check_palakkad.js`, `revoke_requests.cjs`, `test_db.js` (ad-hoc diagnostics).

12. Housekeeping Files & Known Issues

- **Dev helpers (safe to ignore / delete):** `fix_home.cjs`, `fix_report.cjs`, `scratch.jsx`, `production_changes.patch`, `frontend/fix_*.cjs`, `frontend/fix_*.py`, `frontend/patch_css.js`, `frontend/test-*.js`, `frontend/src/pages/fix*.cjs`, `pages/InactiveItems*.txt`.
- `frontend/src/pages/S极狐alesInvoiceCreate.jsx` has a corrupted filename (stray characters) — it is a stray duplicate of `SalesInvoiceCreate.jsx`.
- `backend/utlis/` (typo) and `backend/utlis/` coexist.
- `frontend/Readme.txt` and old README content describe an earlier plan (JWT, Plaid/Stripe) that is **not** implemented; this document supersedes it.
- The API URL is set directly in `api.js`; consider `VITE_API_URL`.
- `server.js` contains a large commented-out legacy version at the bottom.
- Backend uses Express 4; root `package.json` lists Express 5 (unused).

13. Git Workflow

- Default deploy branch: `master`; test environment branch carries local features merged with production fixes (see `production_changes.patch`).
- Use Conventional Commits (`feat:`, `fix:`, `docs:` ...) — audited daily by the commit-report workflow.

Contact (legacy README): Rootments — Project dev: Jishnu M. License: MIT — Rootments.