

Tweak Settings - Domains

Created by Anonymous, last modified by Doc User on Feb 09, 2017

For cPanel & WHM version 62

([Home](#) >> [Server Configuration](#) >> [Tweak Settings](#))

[Allow users to park subdomains of the server's hostname](#)
[Allow cPanel users to create subdomains across accounts](#)
[Allow WHM users to create subdomains across accounts](#)
[Allow Remote Domains](#)
[Allow resellers to create accounts with subdomains of the server's hostname.](#)
[Allow unregistered domains](#)
[Automatically add A entries for registered nameservers when creating a new zone](#)
[Prevent cPanel users from creating specific domains](#)
[Check zone syntax](#)
[Check zone owner](#)
[Enable DKIM on domains for newly created accounts](#)
[Enable SPF on domains for newly created accounts](#)
[DNS request management application](#)
[Proxy subdomains](#)
[Proxy subdomain creation](#)
[Thunderbird and Outlook autodiscover and autoconfig support \(enables proxy subdomain and SRV record creation\)](#)
[Preferred mail service to configure to use for Thunderbird and Outlook® autodiscover and autoconfig support](#)
[Host to publish in the SRV records for Outlook autodiscover support.](#)
[Overwrite custom A records used for proxy subdomains](#)
[Overwrite custom SRV records used by Outlook AutoDiscover support](#)
[Proxy subdomain override](#)
[Always use authoritative \(registered\) nameservers when creating a new DNS zone.](#)

[Additional documentation](#)

Allow users to park subdomains of the server's hostname

This setting allows users to park subdomains on your server's main domain.

For example, this setting has the following impact on the example.com server:

- If you select *On*, a cPanel user could successfully create the subdomain.example.com alias.
- If you select *Off*, a cPanel user would receive an error message if they attempt to create the subdomain.example.com alias.


This setting defaults to *Off*.

Allow cPanel users to create subdomains across accounts

This setting allows a user to create an addon domain or subdomain of a domain that another user owns.

For example, if the user bob owns the domain example.com, the user charlie can create the store.example.com subdomain.

This setting defaults to *Off*.


 **Warning:**
Do **not** enable this option. It can cause serious security issues.

Allow WHM users to create subdomains across accounts

This setting allows WHM users to create an addon domain or a subdomain of a domain that another user owns.

For example, if the user bob owns the domain example.com, the WHM user charlie can create an account for the store.example.com subdomain.


This setting defaults to *Off*.

 **Warning:**
Do **not** enable this option. It can cause serious security issues.

Allow Remote Domains

This setting allows users to create parked domains (aliases) and addon domains that resolve to other servers.

This setting defaults to *Off*.

 **Warning:**
Do **not** enable this option. It can cause serious security issues.

Allow resellers to create accounts with subdomains of the server's hostname.

This setting allows resellers to create accounts with subdomains of your server's main domain.

For example, if your main domain name is example.com, enable this setting to redirect user.example.com visitors to the reseller's website.

This setting defaults to *Off*.

Allow unregistered domains

This setting allows users to create domain names on the server that they do **not** register with a valid registrar.

This setting defaults to *Off*.

Automatically add A entries for registered nameservers when creating a new zone


This setting specifies whether the system automatically creates [A entries](#) for a new domain's registered nameservers when a user creates a domain.

This setting defaults to *On*.

Prevent cPanel users from creating specific domains

This setting prevents the creation of certain domains with domain names that the `/var/cpanel/commonddomains` file contains.

If you enable this setting, cPanel users **cannot** create (as an addon or parked domain) any domain that the `/var/cpanel/commonddomains` file or the `/usr/local/cpanel/etc/commonddomains` file contains.

 **Important:**
Do **not** edit the `/usr/local/cpanel/etc/commonddomains` file directly. If you do, the system **will overwrite** your changes whenever cPanel & WHM updates.

Check zone syntax

This setting allows you to have the system automatically check zone file syntax whenever a user saves or synchs DNS zone files.

This setting's value defaults to *On*.

Check zone owner

This setting allows you to have the system automatically check a DNS zone's owner whenever a user saves or synchs DNS zone files.


This setting defaults to *On*.

Enable DKIM on domains for newly created accounts

[DKIM \(DomainKeys Identified Mail\)](#) verifies a message's sender and integrity. It allows an email system to prove that a message is valid, **not** forged, and that it came from the specified domain.

This setting allows you to specify whether to enable DKIM for new accounts by default.

This setting defaults to *On*.


 **Note:**
The `/scripts/enable_spf_dkim_globally` script allows you to enable SPF and DKIM for existing accounts on the server, and create the appropriate DNS records for their domains. For more information, read our [The SPF and DKIM Global Settings Script](#) documentation.

Enable SPF on domains for newly created accounts

[SPF \(Sender Policy Framework\)](#) denies spammers the ability to send email when they forge your domain's name as the sender (spoofing). This authentication function adds IP addresses to a list of computers that you authorize to send mail from your domain name. It verifies that messages that your domain sends come from the listed sender, which reduces the amount of backscatter that you receive.

This setting allows you to specify whether to enable SPF for new accounts by default.

This setting defaults to *On*.

 **Note:**
The `/scripts/enable_spf_dkim_globally` script allows you to enable SPF and DKIM for existing accounts on the server, and create the appropriate DNS records for their domains. For more information, read our [The SPF and DKIM Global Settings Script](#) documentation.

DNS request management application

This setting specifies the application that the system uses to handle DNS management requests.

To specify a new application, enter the path to the application that you wish to use in the text box.

This setting defaults to *dnsadmin, auto-detect SSL*.

Proxy subdomains


This setting allows users to access cPanel & WHM services from standard HTTP ports, such as Port 80 and Port 443. This setting is useful if users **cannot** access the standard cPanel & WHM ports due to firewall restrictions.

If you enable this setting, the system automatically redirects visitors to the correct port when they access the following subdomains:

- `cpanel.example.com` redirects to the user's [cPanel Home Interface](#).
- `webmail.example.com` redirects to the user's *Webmail* interface.
- `webdisk.example.com` redirects to the user's Web Disk.
- `whm.example.com` redirects to the user's WHM interface.

 **Note:**
`example.com` represents the user's domain name.

This setting defaults to *On*.

 **Important:**

- The settings that you select in the [Redirection](#) section do **not** apply to proxy subdomains.
- When you enable this setting, it creates an entry in your Apache configuration file (`httpd.conf`). This feature also requires that you **do not** manually disable `mod_rewrite` and `mod_proxy` in the `httpd.conf` file.

Proxy subdomain creation

Proxy subdomains allow users to reach particular interfaces within cPanel or WHM when they enter a subdomain in a browser. For example, a user who enters `cpanel.example.com` reaches `example.com`'s cPanel *Home* Interface.

This setting allows WHM to automatically create DNS entries for the following subdomains for every user's account:

- cpanel.example.com
- webmail.example.com
- webdisk.example.com
- whm.example.com

Note:
example.com represents the user's domain name.

This setting defaults to *On*.

Important:
You **must** add DNS entries for these subdomains to work. Use the `/usr/local/cpanel/scripts/proxydomains` file to create DNS entries manually.

Thunderbird and Outlook autodiscover and autoconfig support (enables proxy subdomain and SRV record creation)

This setting automatically creates autodiscover and autoconfig proxy subdomains when you create a domain.

- autoconfig.example.com
- autodiscover.example.com

This setting also creates the autodiscover and autoconfig SRV records that local domains need for Outlook and Thunderbird email autoconfiguration.

This setting defaults to *On*.

Note:
If you turn off the *Proxy subdomains* option, the system disables this setting.

For more information about Autodiscover and AutoConfig, visit the [TechNet for Autodiscover](#) and [Mozilla's AutoConfig](#) websites.

Preferred mail service to configure to use for Thunderbird and Outlook® autodiscover and autoconfig support

This setting allows you to choose the email transfer method to use with Thunderbird and Outlook with Autodiscover and AutoConfig support.

This setting defaults to *imap*.

Notes:

- We recommend that you select IMAP and **not** POP3.
- You **must** enable the *Thunderbird and Outlook autodiscover and autoconfig support (enables proxy subdomain and SRV record creation)* option in order to configure this setting.

Host to publish in the SRV records for Outlook autodiscover support.

Microsoft Outlook®'s Autodiscover service searches DNS for an SRV record for an email inbox's domain that points to a particular server for Autodiscover. By default, this server is `cpanelmaildiscovery.cpanel.net`.

This setting allows system administrators to perform the following actions:

- Choose the host that the system publishes to the SRV records.
- Change the default host if they have an SSL-enabled host with an SSL certificate that a Certificate Authority signs.
- Use their own server for Outlook® Autodiscover. Enter that server's Fully Qualified Domain Name (FQDN) in the available text box.
- When you enable the *Host to publish in the SRV records for Outlook autodiscover support* feature, the system queries the server that you specify for the Autodiscover settings. You **must** have a custom XML file for this feature to function properly.

This setting defaults to `cpanelmaildiscovery.cpanel.net`.

Notes:

- For more information about how to use a custom XML file, visit [Mozilla's autoconfiguration page](#), or the [Exchange's Autodiscover page](#).
- You must enable the *Thunderbird and Outlook autodiscover and autoconfig support (enables proxy subdomain and SRV record creation)* option in order to configure this option.

For more information about Microsoft Outlook's Autodiscover feature, visit [Microsoft's Support](#) website.

Overwrite custom A records used for proxy subdomains

This setting allows the system to remove any existing custom [A records](#) that match proxy subdomains that you create or remove.

Note:
If you turn off the *Proxy subdomains* option, the system disables this setting.

This setting defaults to *Off*.

Overwrite custom SRV records used by Outlook AutoDiscover support

This setting allows the system to remove any existing custom SRV records whenever the user adds or removes Outlook Autodiscover support.

This setting defaults to *Off*.

Proxy subdomain override

This setting allows users to create cPanel, Webmail, Web Disk, and WHM subdomains that override automatically generated proxy subdomains.

For example, a user can direct visitors who access `cpanel.example.com` to a web page that the user configures, such as `mycontrolpanel.example.com`.

This setting defaults to *On*.

 **Note:**

Proxy subdomains allow you to enter a subdomain in your browser to reach particular cPanel & WHM interfaces. For example, enter `cpanel.example.com` to reach `example.com`'s cPanel interface.

Restrict document roots to public_html

This setting prevents the creation of addon domains and subdomains outside of a cPanel user's primary domain's document root (the `public_html` directory within the user's `/home` directory).

For example, if you enable this setting and then create the `example.com` addon domain, the system creates the `/home/username/public_html/example.com` directory rather than the `/home/username/example.com` directory.

This setting defaults to *On*.

Always use authoritative (registered) nameservers when creating a new DNS zone.

This setting allows the server to use a new domain's authoritative nameservers (the nameservers on record with the domain's registrar). The server does **not** use the nameservers that domain's creator specified.

This setting defaults to *Off*.


Additional documentation

Suggested documentation


For cPanel users


For WHM users

For developers


 [The proxydomains Script](#)


 [List Subdomains](#)

 [Tweak Settings - Domains](#)

 [Addon Domain Conversion List](#)

 [List Parked Domains](#)

 [Subdomains](#)

 [Redirects](#)

 [Addon Domains](#)

 [Aliases](#)

 [How to Modify your hosts File](#)

 [How to Set Email Send Limits](#)

 [The proxydomains Script](#)

 [List Subdomains](#)


 [Tweak Settings - Domains](#)

 [UAPI Functions - DomainInfo::single_domain_data](#)

 [cPanel API 2 Functions - SubDomain::listsubdomains](#)

 [cPanel API 2 Functions - Park::listparkeddomains](#)

 [cPanel API 2 Functions - Park::unpark](#)

 [cPanel API 2 Functions - AddonDomain::listaddondomains](#)

whm

domains

uidoc

whmserverconfiguration