

Guide d'installation AirBar Server (Windows, macOS, Linux)

Objectif: deployer et lancer le serveur AirBar avec Docker Compose sur les 3 OS.

1. Prerequis communs

- Acces administrateur (ou sudo sur Linux/macOS)
- Connexion Internet
- Docker Desktop (Windows/macOS) ou Docker Engine + Compose plugin (Linux)
- Git

Verification rapide:

Windows (PowerShell)

```
git --version  
docker --version  
docker compose version
```

macOS / Linux (bash)

```
git --version  
docker --version  
docker compose version
```

2. Installer les outils

Windows

1. Installer Git: <https://git-scm.com/download/win>
2. Installer Docker Desktop: <https://www.docker.com/products/docker-desktop/>
3. Ouvrir Docker Desktop et attendre Running.

macOS

1. Installer Git (souvent déjà présent):
 - `xcode-select --install` si nécessaire
2. Installer Docker Desktop: <https://www.docker.com/products/docker-desktop/>
3. Lancer Docker Desktop et attendre Running.

Linux (Ubuntu/Debian)

```
sudo apt update
sudo apt install -y ca-certificates curl gnupg git

# Docker Engine + Compose plugin
sudo install -m 0755 -d /etc/apt/keyrings
curl -fsSL https://download.docker.com/linux/ubuntu/gpg | sudo gpg --dearmor -o
/etc/apt/keyrings/docker.gpg
sudo chmod a+r /etc/apt/keyrings/docker.gpg

echo \
  "deb [arch=$(dpkg --print-architecture) signed-by=/etc/apt/keyrings/docker.gpg]
https://download.docker.com/linux/ubuntu \
  $(. /etc/os-release && echo $VERSION_CODENAME) stable" | sudo tee
/etc/apt/sources.list.d/docker.list > /dev/null

sudo apt update
sudo apt install -y docker-ce docker-ce-cli containerd.io docker-buildx-plugin
docker-compose-plugin

# Optionnel: éviter sudo pour docker
sudo usermod -aG docker $USER
# puis déconnecter/reconnecter la session
```

3. Récupérer le code

Windows (PowerShell)

```
cd C:\
mkdir airbar_production
cd airbar_production
git clone https://github.com/rorophil/airbar_backend.git
cd .\airbar_backend\airbar_backend_server
```

macOS / Linux (bash)

```
mkdir -p ~/airbar_production
cd ~/airbar_production
git clone https://github.com/rorophil/airbar_backend.git
cd airbar_backend/airbar_backend_server
```

4. Configurer les secrets (.env)

Dans le dossier `airbar_backend_server`, verifier/editer `.env`:

```
POSTGRES_PASSWORD=ChangeMePostgresPassword
REDIS_PASSWORD=ChangeMeRedisPassword
SERVERPOD_PASSWORD_SHARED=ChangeMeSharedKeyAtLeast32Chars
SERVERPOD_PASSWORD_SERVICE_SECRET=ChangeMeServiceSecretAtLeast32Chars
SERVERPOD_PASSWORD_JWT_REFRESH_PEPPER=ChangeMeJwtRefreshPepperAtLeast32Chars
SERVERPOD_PASSWORD_JWT_HMAC_SHA512_PRIVATE_KEY=ChangeMeJwtHmacSha512PrivateKeyAtLeast32Chars
SERVERPOD_PASSWORD_EMAIL_SECRET_HASH_PEPPER=ChangeMeEmailSecretHashPepperAtLeast32Chars
```

Recommandation: utiliser des valeurs aleatoires de 32+ caracteres en production.

5. Verifier la config production

Verifier `config/production.yaml`:

- `apiServer.publicHost` doit exister
- `database.host` doit etre `postgres`
- `redis.host` doit etre `redis`

6. Build et demarrage

Windows (PowerShell)

```
docker compose -f .\docker-compose.yaml up -d --build
docker compose -f .\docker-compose.yaml ps
```

macOS / Linux (bash)

```
docker compose -f ./docker-compose.yaml up -d --build
docker compose -f ./docker-compose.yaml ps
```

Attendu:

- postgres: Up (healthy)
- redis: Up (healthy)
- airbar_server: Up

7. Premier demarrage: appliquer les migrations

Windows (PowerShell)

```
docker compose -f .\docker-compose.yaml run --rm --entrypoint /bin/sh airbar_server
-c "./server --mode=production --server-id=prod-001 --logging=normal --
role=monolith --apply-migrations"
docker compose -f .\docker-compose.yaml up -d airbar_server
```

macOS / Linux (bash)

```
docker compose -f ./docker-compose.yaml run --rm --entrypoint /bin/sh airbar_server
-c "./server --mode=production --server-id=prod-001 --logging=normal --
```

```
role=monolith --apply-migrations"  
docker compose -f ./docker-compose.yaml up -d airbar_server
```

8. Verifier les logs

Windows (PowerShell)

```
docker compose -f .\docker-compose.yaml logs --tail 100 airbar_server
```

macOS / Linux (bash)

```
docker compose -f ./docker-compose.yaml logs --tail 100 airbar_server
```

9. Operations courantes

Redemarrer

Windows:

```
docker compose -f .\docker-compose.yaml restart
```

macOS/Linux:

```
docker compose -f ./docker-compose.yaml restart
```

Arreter

Windows:

```
docker compose -f .\docker-compose.yaml down
```

macOS/Linux:

```
docker compose -f ./docker-compose.yaml down
```

Reset complet (destructif, supprime les volumes)

Windows:

```
docker compose -f .\docker-compose.yaml down -v
```

macOS/Linux:

```
docker compose -f ./docker-compose.yaml down -v
```

10. Depannage rapide

docker compose non reconnu

- Windows/macOS: verifier Docker Desktop lance
- Linux: verifier installation du compose plugin

```
docker compose version
```

Missing password for ...

- verifier toutes les variables `SERVERPOD_PASSWORD_*` dans `.env`
- relancer build + up

relation ... does not exist

- migrations non appliquees
- relancer la commande d'application des migrations en mode production

backend en restart loop

- inspecter logs backend

Windows:

```
docker compose -f .\docker-compose.yaml logs --tail 200 airbar_server
```

macOS/Linux:

```
docker compose -f ./docker-compose.yaml logs --tail 200 airbar_server
```

11. Checklist finale

- Docker OK
- .env complet et securise
- postgres/redis healthy
- backend Up
- migrations appliquees
- logs sans crash

12. Mode express (10 commandes max)

Utiliser cette section si vous voulez aller au plus court.

Windows (PowerShell)

```
cd C:\
mkdir airbar_production
cd airbar_production
git clone https://github.com/rorophil/airbar_backend.git
cd .\airbar_backend\airbar_backend_server
docker compose -f .\docker-compose.yaml up -d --build
docker compose -f .\docker-compose.yaml run --rm airbar_server --apply-migrations
docker compose -f .\docker-compose.yaml up -d airbar_server
docker compose -f .\docker-compose.yaml ps
docker compose -f .\docker-compose.yaml logs --tail 100 airbar_server
```

macOS / Linux (bash)

```
mkdir -p ~/airbar_production
cd ~/airbar_production
git clone https://github.com/rorophil/airbar_backend.git
cd airbar_backend/airbar_backend_server
docker compose -f ./docker-compose.yaml up -d --build
docker compose -f ./docker-compose.yaml run --rm airbar_server --apply-migrations
docker compose -f ./docker-compose.yaml up -d airbar_server
docker compose -f ./docker-compose.yaml ps
docker compose -f ./docker-compose.yaml logs --tail 100 airbar_server
```