Sprint 14 go-live pack: the hosted demo

Your accounts, your keys. Every step here happens in your own Supabase, Vercel, Resend, Anthropic and Voyage accounts. No key, password or token goes into this file, the chat or the repository. Where a step needs one, it says where you keep it.

Branch `main`, after Sprint 14's security review is merged (it holds `vercel.json`, the hosted build check and the demo data). About 90 minutes, most of it waiting for DNS and deployments. Do the steps in order: later ones need values from earlier ones.

Two values you will note as you go (they are not secret): - **Project ref**: the Supabase project's ID (in its address, `https://<project-ref>.supabase.co`). - **App address**: the Vercel address, for example `https://rfi-respond.vercel.app`.

Before you start

- A **Resend** account (or another SMTP provider) with a sending domain you own verified. Resend shows the DNS records to add; verification can take a while, so start it first.
- The **Anthropic** and **Voyage** keys you use locally (in `supabase/functions/.env` on your PC).
- Docker Desktop is not needed for these steps.

Steps

1. Create the Supabase project

Flow

1. In the Supabase dashboard, choose **New project**: name `rfi-respond-demo`, region **London (eu-west-2)**, plan **Free**.
2. Generate a database password and save it in your password manager.

Expected outcome: the project is ready, and its address is `https://<project-ref>.supabase.co`.

Result: ☐ Done. Project ref:

2. Apply the migrations and deploy the functions

Flow (PowerShell in `C:\Code\rfi-responder`, on `main`)

1. `npx supabase login`
2. `npx supabase link --project-ref <project-ref>` and enter the database password when asked.
3. `npx supabase db push`, then answer `Y`.
4. `npx supabase functions deploy`

Expected outcome

- `db push` lists the migrations from `20260430145610` (the prototype's) to `20261102100000` and applies them all without an error.
- `functions deploy` deploys `embed`, `embed-entries`, `extract-questions` and `process-questions`.

Result: ☐ Done. Notes:

3. Set the function secrets

Flow

1. `npx supabase secrets set --env-file supabase/functions/.env`. This reads your keys from the file, so they never appear on the command line.
2. `npx supabase secrets list`

Expected outcome: the list shows `ANTHROPIC_API_KEY`, `VOYAGE_API_KEY`, `EMBEDDING_PROVIDER` and `EMBEDDING_MODEL`, with their values hidden. `APP_ORIGIN` comes in step 5.
Result: ☐ Done. Notes:

4. Deploy the app on Vercel

Flow

1. In Supabase, open **Project Settings**, then **API**, and copy the **Project URL** and the **anon** (or **publishable**) key. Never copy the `service_role` or secret key.
2. In Vercel, choose **Add New**, then **Project**, and import `rorymcclelland/RFI-responder`.
3. Under **Environment Variables**, add `VITE_SUPABASE_URL` (the Project URL) and `VITE_SUPABASE_ANON_KEY` (the anon key). Leave the build settings as `vercel.json` sets them.
4. Choose **Deploy**.

Expected outcome

- The build log shows `npm run build:hosted` passing, then the deployment is ready.
- Opening the app address shows the RFI Respond sign-in page.
- If the build stops with “The hosted build stopped”, the message names the variable to fix.

Result: ☐ Done. App address:

5. Point Supabase at the app

Flow

1. `npx supabase secrets set APP_ORIGIN=<app address>` (no trailing slash).
2. In Supabase, open **Authentication**, then **URL Configuration**. Set **Site URL** to the app address, and add `<app address>/**` under **Redirect URLs**.

Expected outcome: the secret is listed, and both addresses are saved.
Result: ☐ Done. Notes:

6. Sign-in settings and email

Flow

1. **Authentication**, then **Sign In / Providers**:
   - turn **Allow new users to sign up** off;
   - keep **Email** on, with **Confirm email** on.
2. In the same place, set **Password requirements**: minimum length `12`, **Letters and digits**. Leaked-password protection is greyed out on the Free plan (agreed, Q1).
3. **Authentication**, then **Emails**, then **SMTP Settings**: turn on custom SMTP.

- Host `smtp.resend.com`, port `465`, user `resend`.
- Password: a Resend API key with send access only (create it in Resend).
- Sender: an address on your verified domain, with the sender name `RFI Respond demo`.

Expected outcome: all settings saved; Supabase accepts the SMTP settings.
Result: ☐ Done. Notes:

7. Load the demo data

Flow

1. In Supabase, open the **SQL Editor** and start a new query.
2. Paste the whole of `supabase\demo-hosted.sql` and choose **Run**.
3. Run `select count(*) from kb_entries;` and `select name from opportunities;`

Expected outcome

- The first run reports success.
- There are 132 entries: 130 seeded and 2 learned by the demo's exported response.
- There are four responses, each marked "(fictional)".

Result: ☐ Done. Notes:

8. Your admin account

Flow

1. **Authentication**, then **Users**, then **Invite user**, with your own email address.
2. Open the email, follow the link, and set a password (12 characters or more, letters and digits). Save it in your password manager.
3. In the SQL Editor, replacing the address with yours: `update public.user_profiles set is_admin = true where id = (select id from auth.users where email = 'you@yourdomain');`
4. Sign out of the app and back in.

Expected outcome

- The email arrives from your sending domain.
- The link opens the app's **Welcome: choose a password** page.
- After signing in again you see **Governance** in the menu.

Result: ☐ Done. Notes:

9. Limits, in the app and at the providers

Flow

1. In the app, open **Governance**, then **Usage and limits**. Set:
   - **Monthly budget (£)** to `5`;
   - **Questions per person per day** to `50`;
   - **Word documents read by AI per person per day** to `5`.
2. In the Anthropic console, set a monthly spend limit for the key's workspace.

3. In the Voyage dashboard, set a usage limit, and switch on the zero-retention opt-out (`Organization`, then `Terms of Service`, the dashboard's labels).

Expected outcome: the governance page shows the new limits. Both provider limits are saved, and the Voyage opt-out is on.
Result: ☐ Done. Notes:

10. Invite the reviewers

Flow

1. For each reviewer: **Authentication**, then **Users**, then **Invite user**, with their address.
2. Tell them to expect the email, and that the demo holds synthetic data only.

Expected outcome: each appears under **Users** as invited; they are members, not admins.
Result: ☐ Done. Notes:

When the demo has been idle

On the Free plan Supabase pauses a project after a period without use. Before a demo, open the project in the dashboard and choose **Restore project** if it is paused. Wait until it is ready, then load the app once.

To reset the demo

Paste the whole of `supabase\demo-hosted-reset.sql` into the SQL Editor and run it. It removes every response and knowledge-base entry, including what reviewers added, and loads the demo again. Accounts, roles, limits, usage and the audit log are kept.

When you have finished

Reply "live", with the app address. I then check the hosted project's security advisors and the app's pages (with your permission, through the connected Supabase tools and the browser), and send the hosted test pack.