



ROS-Industrial Basic Developer's Training Class

October 2024



Southwest Research Institute







Session 3: Motion Control of Manipulators



Southwest Research Institute




Outline





- URDF
- TF
- Motion Planning in ROS









HowTo: Set Up a New Robot

- 1. Create a URDF
- 2. Create a Movelt! Package
- 3. Update Movelt! Package for ROS-I
- 4. Test on ROS-I Simulator
- 5. Test on "Real" Robot







URDF: Unified Robot Description Format








URDF: Overview



- URDF is an XML-formatted file containing:
 - Links: coordinate frames and associated geometry
 - Joints: connections between links
- Similar to DH-parameters (but way less painful)
- Can describe entire workspace, not just robots






URDF: Link



- A Link describes a physical or virtual object
 - Physical: robot link, workpiece, end-effector, ...
 - Virtual: TCP, robot base frame, ...
- Each link becomes a TF frame
- Can contain visual/collision geometry [optional]
- http://wiki.ros.org/urdf/XML/link



URDF Transforms

X/Y/Z Roll/Pitch/Yaw Meters Radians






URDF: Joint



- A Joint connects two Links
 - Defines a transform between parent and child frames
 - Types: fixed, free, linear, rotary
 - Denotes axis of movement (for linear / rotary)
 - Contains joint limits on position and velocity
- ROS-I conventions
 - X-axis front, Z-Axis up
 - Keep all frames similarly rotated when possible
- http://wiki.ros.org/urdf/XML/joint






URDF Tips



- create from datasheet or use <u>Solidworks Add-In</u>
- double-check joint-offsets for accuracy
- round near-zero offsets (if appropriate)
- use "base link" and "tool0"
- use simplified collision models
 - convex-hull or primitives









Verify the URDF



- It is critical to verify that your URDF matches the physical robot:
 - each joint moves as expected
 - joint-coupling issues are identified
 - min/max joint limits
 - joint directions (pos/neg)
 - correct zero-position, etc.
 - check forward kinematics













Exercise 3.0

Create a simple urdf







URDF: XACRO



- XACRO is an XML-based "macro language" for building URDFs
 - <Include> other XACROs, with parameters
 - Simple expressions: math, substitution
- Used to build complex URDFs
 - multi-robot workcells
 - reuse standard URDFs (e.g. robots, tooling)

```
<xacro:include filename="myRobot.xacro"/>
<xacro:myRobot prefix="left "/>
<xacro:myRobot prefix="right "/>
cproperty name="offset" value="1.3"/>
<joint name="world to left" type="fixed">
    <parent link="world"/>
   <child link="left base link"/>
   <origin xyz="${offset/\overline{2}} 0 0" rpy="0 0 0"/>
</joint>
```





Exercise 3.1



Exercise 3.1

Combine simple urdf with ur5 xacro









TF – Transforms in ROS






TF: Overview



- TF is a distributed framework to track coordinate frames
- Each frame is related to at least one other frame








TF: Time Sync



- TF tracks frame history
 - can be used to find transforms in the past!
 - essential for asynchronous / distributed system







TF: c++



- Each node using TF has its own TransformListener
 - listens to <u>all</u> TF messages, calculates relative transforms
 - Can try to transform in the past
 - > Can only look as far back as it has been running

```
tf2_ros::Buffer buffer(node->get_clock());
tf2_ros::TransformListener listener(buffer);

geometry_msgs::msg::TransformStamped transform;
transform = buffer.lookupTransform("target", "source", tf2::TimePointZero);

Result

Parent Frame
("reference") ("object")

Time
```

- Note confusing "target/source" naming convention
- Tf2::TimePointZero gives latest available transform



TF Timing



- When requesting a transform, you must specify a time:
 - Latest Received

```
lookupTransform("from", "to", tf2::TimePointZero)
```

Current Time (will probably fail)

```
lookupTransform("from", "to", now)
```

Current Time (wait for it to be available)

```
lookupTransform("from", "to", now, 50ms)
```








TF: Sources



- A robot_state_publisher provides TF data from a URDF
- Nodes can also publish TF data










Exercise 3.2







Motion Planning in ROS

(using Movelt)









Motion Planning in ROS












- Motion Types: limited, but well-defined. One motion task.
- Environment Model: none, or extremely limited





ROS Motion Planning





Motion Types: flexible, goal-driven, with constraints but minimal control over actual path


• Environment Model: yes (fixed CAD or sensor-driven)





Motion Planning Components










Movelt Components




consortium'



Movelt Nodes









Movelt! Package - Motivation



For each new robot model...

create a new Movelt! package

- Kinematics
 - physical configuration, lengths, etc.
- Movelt! configuration
 - plugins, default parameter values
 - self-collision testing
 - pre-defined poses
- Robot connection
 - FollowJointTrajectory Action name





Movelt! Package Contents



- A Movelt! Package...
 - includes all required nodes, config, launch files
 - motion planning, filtering, collision detection, etc.
 - is unique to each individual robot model
 - includes references to URDF robot data
 - uses a standard interface to robots
 - publish trajectory, listen to joint angles
 - can (optionally) include workcell geometry
 - e.g. for collision checking







Create a Movelt! Package



- Use the Movelt! Setup Assistant
 - can create a new package or edit an existing one






Update Movelt! Package



- Setup Assistant generates a generic package
 - missing config. data to connect to a specific robot
 - ROS-I robots use a standard interface*








Exercise 3.3




Param: base_frame

Exercise 3.3:

Create a Movelt! Package









Motion Planning using Movelt!

- 1. Motion Planning using Rviz
- 2. Motion Planning using C++





Motion Planning in RViz



Display Options

▶ Sc	Scene Geometry						
₹ Sc	ene Robot						
	Show Robot Visual	✓					
	Show Robot Collision						
'	Robot Alpha	1					
	Attached Body Color	150 ; 50; 150					
)	Links						
₹ Pl	anning Request						
	Planning Group	manipulator					
	Show Workspace						
	Query Start State						
	Query Goal State	✓					
	Interactive Marker Size	0					
	Start State Color	0; 255; 0					





Motion Planning in RViz



Planning Options

Context	Planning	Manipulation	Scene Objects	Stored Scenes	Stored States	Status	Joints	
Commands		Query	Query Options					
<u>P</u> lan <u>E</u> xecute			Planning Group: manipulator		s): 5.0 pts: 10			
Plan & Execute		Start Stat		Velocity Scaling Accel. Scaling:	0.10		\$	
Clear octomap		Goal State		Use Cartesia✓ Collision-awa				
Path Constraints None			Approx IK So External Con Replanning Sensor Positi	nm.				






Exercise 3.4



Exercise 3.4:

Motion Planning using RVIZ









Review



ROS

- **URDF**
- Movelt
- Path Planners
- RViz Planning

ROS-Industrial

- Robot Drivers
- Path Planners







Questions?



- ROS-I Architecture
- Setup Assistant
- Robot Launch Files
- RViz Planning

