

# Lab8 Completed

May 3, 2024

Rosa Chavez

```
[2]: # Save your input data file into your Project directory
fna.data <- "WisconsinCancer.csv"

# Complete the following code to input the data and store as wisc.df
wisc.df <- read.csv(fna.data, row.names=1)

wisc.df
```

		diagnosis	radius_mean	texture_mean	perimeter_mean	area_mean
		<chr>	<dbl>	<dbl>	<dbl>	<dbl>
A data.frame: 569 × 31	842302	M	17.990	10.38	122.80	1001.0
	842517	M	20.570	17.77	132.90	1326.0
	84300903	M	19.690	21.25	130.00	1203.0
	84348301	M	11.420	20.38	77.58	386.1
	84358402	M	20.290	14.34	135.10	1297.0
	843786	M	12.450	15.70	82.57	477.1
	844359	M	18.250	19.98	119.60	1040.0
	84458202	M	13.710	20.83	90.20	577.9
	844981	M	13.000	21.82	87.50	519.8
	84501001	M	12.460	24.04	83.97	475.9
	845636	M	16.020	23.24	102.70	797.8
	84610002	M	15.780	17.89	103.60	781.0
	846226	M	19.170	24.80	132.40	1123.0
	846381	M	15.850	23.95	103.70	782.7
	84667401	M	13.730	22.61	93.60	578.3
	84799002	M	14.540	27.54	96.73	658.8
	848406	M	14.680	20.13	94.74	684.5
	84862001	M	16.130	20.68	108.10	798.8
	849014	M	19.810	22.15	130.00	1260.0
	8510426	B	13.540	14.36	87.46	566.3
	8510653	B	13.080	15.71	85.63	520.0
	8510824	B	9.504	12.44	60.34	273.9
	8511133	M	15.340	14.26	102.50	704.4
	851509	M	21.160	23.04	137.20	1404.0
	852552	M	16.650	21.38	110.00	904.6
	852631	M	17.140	16.40	116.00	912.7
	852763	M	14.580	21.53	97.41	644.8
	852781	M	18.610	20.25	122.10	1094.0
	852973	M	15.300	25.27	102.40	732.4
	853201	M	17.570	15.05	115.00	955.1
	921362	B	7.691	25.44	48.34	170.4
	921385	B	11.540	14.44	74.65	402.9
	921386	B	14.470	24.99	95.81	656.4
	921644	B	14.740	25.42	94.70	668.6
	922296	B	13.210	28.06	84.88	538.4
	922297	B	13.870	20.70	89.77	584.8
	922576	B	13.620	23.23	87.19	573.2
	922577	B	10.320	16.35	65.31	324.9
	922840	B	10.260	16.58	65.85	320.8
	923169	B	9.683	19.34	61.05	285.7
	923465	B	10.820	24.21	68.89	361.6
	923748	B	10.860	21.48	68.51	360.5
	923780	B	11.130	22.44	71.49	378.4
	924084	B	12.770	29.43	81.35	507.9
	924342	B	9.333	21.94	59.01	264.0
	924632	B	12.880	28.92	82.50	514.3
	924934	B	10.290	27.61	65.67	321.4
	924964	B	10.160	19.59	64.73	311.7
	925236	B	9.423	27.88	59.26	271.3
	925277	B	14.590	22.68	96.39	657.1

```
[3]: # We can use -1 here to remove the first column
wisc.data <- wisc.df[,-1]
```

```
[4]: # Create diagnosis vector for later
diagnosis <- factor(wisc.df$diagnosis)
```

```
[5]: #Q1
nrow(wisc.data)
```

569

```
[6]: #Q2
sum(diagnosis == "M")
```

212

```
[7]: #Q3
length(grep("_mean", names(wisc.data)))
```

10

```
[8]: # Check column means and standard deviations
colMeans(wisc.data)

apply(wisc.data,2,sd)
```

```
radius\__mean 14.1272917398946 texture\__mean 19.2896485061512 perimeter\__mean
91.9690333919157 area\__mean 654.889103690686 smoothness\__mean 0.096360281195079
compactness\__mean 0.104340984182777 concavity\__mean 0.0887993158172232
concave.points\__mean 0.0489191458699472 symmetry\__mean 0.181161862917399
fractal\__dimension\__mean 0.0627976098418278 radius\__se 0.405172056239016
texture\__se 1.21685342706503 perimeter\__se 2.86605922671353 area\__se 40.337079086116
smoothness\__se 0.00704097891036907 compactness\__se 0.0254781388400703
concavity\__se 0.0318937163444639 concave.points\__se 0.0117961370826011
symmetry\__se 0.0205422987697715 fractal\__dimension\__se 0.00379490386643234
radius\__worst 16.2691898066784 texture\__worst 25.677223198594 perimeter\__worst
107.261212653779 area\__worst 880.583128295254 smoothness\__worst 0.132368594024605
compactness\__worst 0.254265043936731 concavity\__worst 0.272188483304042
concave.points\__worst 0.114606223198594 symmetry\__worst 0.290075571177505
fractal\__dimension\__worst 0.0839458172231985
```

```
radius\__mean 3.52404882621208 texture\__mean 4.30103576816695 perimeter\__mean
24.2989810387549 area\__mean 351.914129181653 smoothness\__mean 0.0140641281376736
compactness\__mean 0.0528127579325122 concavity\__mean 0.0797198087078935
concave.points\__mean 0.0388028448591536 symmetry\__mean 0.0274142813360357
fractal\__dimension\__mean 0.00706036279508446 radius\__se 0.277312732986104
texture\__se 0.551648392617202 perimeter\__se 2.02185455404211 area\__se
45.4910055161318 smoothness\__se 0.00300251794383907 compactness\__se
0.0179081793256774 concavity\__se 0.0301860603229884 concave.points\__se
0.00617028517404687 symmetry\__se 0.0082663715287984 fractal\__dimension\__se
```

```
0.00264607096708919 radius\___worst 4.83324158046932 texture\___worst 6.14625762303832
perimeter\___worst 33.6025422690364 area\___worst 569.356992669949 smoothness\___worst
0.0228324294048355 compactness\___worst 0.157336488913742 concavity\___worst
0.208624280608132 concave.points\___worst 0.0657323411959421 symmetry\___worst
0.0618674675375187 fractal\___dimension\___worst 0.018061267348894
```

```
[9]: # Perform PCA on wisc.data by completing the following code
wisc.pr <- prcomp(wisc.data, scale. = TRUE)
```

```
[10]: # Look at summary of results
summary(wisc.pr)
```

Importance of components:

	PC1	PC2	PC3	PC4	PC5	PC6	PC7
Standard deviation	3.6444	2.3857	1.67867	1.40735	1.28403	1.09880	0.82172
Proportion of Variance	0.4427	0.1897	0.09393	0.06602	0.05496	0.04025	0.02251
Cumulative Proportion	0.4427	0.6324	0.72636	0.79239	0.84734	0.88759	0.91010

	PC8	PC9	PC10	PC11	PC12	PC13	PC14
Standard deviation	0.69037	0.6457	0.59219	0.5421	0.51104	0.49128	0.39624
Proportion of Variance	0.01589	0.0139	0.01169	0.0098	0.00871	0.00805	0.00523
Cumulative Proportion	0.92598	0.9399	0.95157	0.9614	0.97007	0.97812	0.98335

	PC15	PC16	PC17	PC18	PC19	PC20	PC21
Standard deviation	0.30681	0.28260	0.24372	0.22939	0.22244	0.17652	0.1731
Proportion of Variance	0.00314	0.00266	0.00198	0.00175	0.00165	0.00104	0.0010
Cumulative Proportion	0.98649	0.98915	0.99113	0.99288	0.99453	0.99557	0.9966

	PC22	PC23	PC24	PC25	PC26	PC27	PC28
Standard deviation	0.16565	0.15602	0.1344	0.12442	0.09043	0.08307	0.03987
Proportion of Variance	0.00091	0.00081	0.0006	0.00052	0.00027	0.00023	0.00005
Cumulative Proportion	0.99749	0.99830	0.9989	0.99942	0.99969	0.99992	0.99997

	PC29	PC30
Standard deviation	0.02736	0.01153
Proportion of Variance	0.00002	0.00000
Cumulative Proportion	1.00000	1.00000

#Q4

$0.4427 \times 100 = 44.27\%$

```
[12]: #Q5
original_variance <- wisc.pr$sdev^2 / sum(wisc.pr$sdev^2)
proportion <- min(which(cumsum(original_variance) >= 0.7))
proportion
```

3


```
[13]: #Q6
original_variance <- wisc.pr$sdev^2 / sum(wisc.pr$sdev^2)
proportion2 <- min(which(cumsum(original_variance) >= 0.9))
proportion2
```

7


#Q7

Everything stands out the plot does not seem to be properly formatted and it is difficult to understand/interpret


```
[16]: biplot(wisc.pr)
```



```
[18]: # Scatter plot observations by components 1 and 2
plot(wisc.pr$x[,1:2], col = diagnosis ,
     xlab = "PC1", ylab = "PC2")
```



```
[19]: #Q8
      # Repeat for components 1 and 3
      plot(wisc.pr$x[,c(1,3)], col = diagnosis,
            xlab = "PC1", ylab = "PC3")
```




There is some difference in PC3 data in that they shifted down but PC1 seems to cover the same data

```
[20]: # Create a data frame from PCA results for plotting
df <- as.data.frame(wisc.pr$x)
df$diagnosis <- diagnosis

# Load the ggplot2 package
library(ggplot2)

# Make a scatter plot colored by diagnosis
ggplot(df) +
  aes(PC1, PC2, col=diagnosis) +
```

```
geom_point()
```



```
[21]: # Calculate variance of each component
```

```
pr.var <- wisc.pr$sdev^2
```

```
head(pr.var)
```

```
1. 13.2816076822579 2. 5.69135461320994 3. 2.81794897722942 4. 1.98064047464105
5. 1.64873054770388 6. 1.207356611965
```


```
[22]: # Variance explained by each principal component: pve
```

```
pve <- pr.var / sum(pr.var)
```


```
# Plot variance explained for each principal component
```



```
plot(pve, xlab = "Principal Component",
     ylab = "Proportion of Variance Explained",
     ylim = c(0, 1), type = "o")
```




```
[23]: # Alternative scree plot of the same data, note data driven y-axis
barplot(pve, ylab = "Percent of Variance Explained",
        names.arg=paste0("PC",1:length(pve)), las=2, axes = FALSE)
axis(2, at=pve, labels=round(pve,2)*100 )
```



```
[24]: ## ggplot based graph
install.packages("factoextra")
library(factoextra)
fviz_eig(wisc.pr, addlabels = TRUE)
```

The downloaded binary packages are in  
 /var/folders/vw/6c5wjngs433234dthdjypz800000gn/T//Rtmpt41afw/downloaded\_packages

Welcome! Want to learn more? See two factoextra-related books at  
<https://goo.gl/ve3WBa>



```
[25]: #Q9
wisc.pr$rotation["concave.points_mean", 1]
```

```
-0.26085375838574
```

```
[29]: #Q10
original_variance <- wisc.pr$sdev^2 / sum(wisc.pr$sdev^2)
proportion2 <- min(which(cumsum(original_variance) >= 0.8))
proportion2
```


```
5
```

```
[30]: data.scaled <- scale(wisc.data)
```

```
[31]: data.dist <- dist(data.scaled)
```

```
[33]: wisc.hclust <- hclust(data.dist, method="complete")
```

```
[34]: #Q11
plot(wisc.hclust)
abline(h=20, col="red", lty=2)
```



```
[35]: wisc.hclust.clusters <- cutree(wisc.hclust, k=4)
```

```
[36]: table(wisc.hclust.clusters, diagnosis)
```


diagnosis

```
wisc.hclust.clusters   B    M
                     1  12 165
                     2   2   5
                     3 343  40
                     4   0   2
```

```
[40]: #Q12
cluster_matches <- list()
for (k in 2:10) {
  k_clusters <- cutree(wisc.hclust, k)
  clusters_vs_diagnoses <- table(Cluster = k_clusters, Diagnosis = diagnosis)
  cluster_matches[[paste("k =", k)]] <- clusters_vs_diagnoses
}
cluster_matches[["k = 2"]]
```

```
      Diagnosis
Cluster  B    M
      1 357 210
      2   0   2
```

```
[42]: #Q13
wisc.pr.hclust <- hclust(dist(wisc.pr$x), method="complete")
plot(wisc.pr.hclust, sub="", xlab="", ylab="Height")
```



I will prefer to stay with the complete method, as it looks better than the rest and let's me determine clusters on average.

```
[43]: wisc.km <- kmeans(scale(wisc.data), centers=2, nstart=20)
```

```
[44]: table(wisc.km$cluster, diagnosis)
```

```
diagnosis
  B  M
1 14 175
2 343 37
```

Q14

It is not as good as hclust results.


```
[45]: grps <- cutree(wisc.pr.hclust, k=2)
      table(grps)
```

```
grps
  1  2
567  2
```


```
[46]: table(grps, diagnosis)
```

```
      diagnosis
grps    B    M
  1  357  210
  2    0    2
```

```
[47]: plot(wisc.pr$x[,1:2], col=grps)
```



```
[48]: plot(wisc.pr$x[,1:2], col=diagnosis)
```



```
[49]: g <- as.factor(grps)
      levels(g)
```


1. '1' 2. '2'

```
[50]: g <- relevel(g,2)
      levels(g)
```

1. '2' 2. '1'



```
[51]: # Plot using our re-ordered factor
plot(wisc.pr$x[,1:2], col=g)
```



```
[52]: library(rgl)
plot3d(wisc.pr$x[,1:3], xlab="PC 1", ylab="PC 2", zlab="PC 3", cex=1.5, size=1,
      type="s", col=grps)
```

Warning message in rgl.init(initValue, onlyNULL):

"RGL: unable to open X11 display"

Warning message:

"'rgl.init' failed, running with 'rgl.useNULL = TRUE'."

```
[54]: ## Use the distance along the first 7 PCs for clustering i.e. wisc.pr$x[, 1:7]
wisc.pr.hclust <- hclust(dist(wisc.pr$x[, 1:7]), method="ward.D2")
```

```
[55]: wisc.pr.hclust.clusters <- cutree(wisc.pr.hclust, k=2)
```

```
[57]: #Q15
# Compare to actual diagnoses
table(wisc.pr.hclust.clusters, diagnosis)
```

```

              diagnosis
wisc.pr.hclust.clusters  B   M
              1  28 188
              2 329  24
```

Fairly good

```
[56]: #Q16
table(wisc.km$cluster, diagnosis)
table(wisc.hclust.clusters, diagnosis)
```

```

      diagnosis
      B   M
1   14 175
2  343  37

              diagnosis
wisc.hclust.clusters  B   M
              1  12 165
              2   2   5
              3 343  40
              4   0   2
```

This is good except for cluster 3


Q17

Hierarchical Clustering shows best specificity and k-means shows best sensitivity

```
[58]: #url <- "new_samples.csv"
url <- "https://tinyurl.com/new-samples-CSV"
new <- read.csv(url)
npc <- predict(wisc.pr, newdata=new)
npc
```

	PC1	PC2	PC3	PC4	PC5	PC6	PC7
A matrix: 2 × 30 of type dbl	2.576616	-3.135913	1.3990492	-0.7631950	2.781648	-0.8150185	-0.395909
	-4.754928	-3.009033	-0.1660946	-0.6052952	-1.140698	-1.2189945	0.819303

```
[59]: plot(wisc.pr$x[,1:2], col=g)
points(npc[,1], npc[,2], col="blue", pch=16, cex=3)
text(npc[,1], npc[,2], c(1,2), col="white")
```



Q18

The patients that fall into the clusters with predominant malignant cases should be prioritized

[ ]: