

Peak WhatsApp Send API

Internal API Documentation — Peak-Mobile-LTD / data service

Endpoint	POST /api/v1/peak/whatsapp/send
Base URL	https://peakdata-1048592730476.europe-west4.run.app
Controller	controllers.PeaKWhatsAppMessage
Request model	models.PeaKWhatsappMessageRequest
Auth	Bearer token (global ValidateToken middleware)
Content-Type	application/json

1. Overview

This endpoint allows an organization to send an outbound WhatsApp message (free-text or template-based) to a recipient phone number, using that organization's own connected WhatsApp Business Account (WABA). The service looks up the organization's active WhatsApp account record, sends the message via the underlying WhatsApp provider, and stores a record of the message in the database.

The route is registered under the **/api/v1** prefix (basePath1 in the router configuration) and is served by the **peakdata** Cloud Run service in the **europa-west4** region.

2. Authentication

Every route in this service — including this one — passes through a global Gin middleware, `middlewares.ValidateToken()`, applied at the router level before any route-specific logic runs. A valid bearer token must be supplied on every request.

Authorization: Bearer <YOUR_TOKEN>

Note: because `ValidateToken()` is global, even routes with 'public' in their path (e.g. `/public/register`) still require a valid token — a missing/invalid token returns HTTP 401 before the request reaches the controller.

3. Endpoint

Request

POST /api/v1/peak/whatsapp/send
Host: peakdata-1048592730476.europa-west4.run.app
Content-Type: application/json
Authorization: Bearer <YOUR_TOKEN>

Request Body Fields

Field	Type	Required	Description
organization_external_id	string	Yes	External ID of the organization. Used to look up an active WhatsApp account (O
to	string	Yes	Recipient phone number (MSISDN), e.g. 254700000000.
message	string	Conditional	Free-text message body. Required if template_name is not provided.
template_name	string	Conditional	Name of a pre-approved WhatsApp template. Required if message is not provid
template_language	string	No	Language code for the template (e.g. en).
template_components	array	No	Template component parameters, if the template requires variables.

Validation Rules

- organization_external_id** must correspond to an organization with an active (`is_active = true`) WhatsApp account, or the API returns 404.
- Either **message** or **template_name** must be non-empty. If both are missing, the API returns 400.

4. Example Request

```
curl -X POST "https://peakdata-1048592730476.europe-west4.run.app/api/v1/peak/whatsapp/send" \
-H "Content-Type: application/json" \
-H "Authorization: Bearer YOUR_TOKEN_HERE" \
-d '{
  "organization_external_id": "YOUR_ORG_EXTERNAL_ID",
  "to": "2547000000000",
  "message": "Hello from Peak WhatsApp!"
}'
```

Template-based example (instead of a plain message):

```
curl -X POST "https://peakdata-1048592730476.europe-west4.run.app/api/v1/peak/whatsapp/send" \
-H "Content-Type: application/json" \
-H "Authorization: Bearer YOUR_TOKEN_HERE" \
-d '{
  "organization_external_id": "YOUR_ORG_EXTERNAL_ID",
  "to": "2547000000000",
  "template_name": "your_template_name",
  "template_language": "en",
  "template_components": []
}'
```

5. Responses

200 OK — Message Sent

```
{
  "status": "sent",
  "message_id": "wamid.HBgMMjU0NzAwMDAwMDAwFQIAERgSNjE3NEJBNUe0MzEzRjBBN0RBAA==",
  "from": "254704965946"
}
```

status — always "sent" on success. **message_id** — the provider-assigned WhatsApp message ID (wamid), useful for tracking delivery status. **from** — the organization's WhatsApp Business display phone number that sent the message.

200 OK — Sent, but record not saved

If the message is sent successfully but the internal database record fails to save, the API still returns 200 with a warning, since the message delivery itself succeeded:

```
{
  "status": "sent",
  "message_id": "wamid...",
  "warning": "message sent but record creation failed"
}
```

400 Bad Request

Returned when the JSON body fails to bind/parse (missing or malformed fields):

```
{ "error": "invalid payload" }
```

Returned when neither message nor template_name is supplied:

```
{ "error": "either message or template_name is required" }
```

401 Unauthorized

Returned by the global auth middleware when the Authorization header is missing or invalid. No request body is required to trigger this — it happens before the controller runs.

404 Not Found

Returned when no active WhatsApp account exists for the given organization_external_id:

```
{ "error": "active WhatsApp account not found for this organization" }
```

500 Internal Server Error

Returned if the underlying send call to the WhatsApp provider fails (e.g. provider-side rejection, network error, invalid recipient number format). The response includes the raw error message from the send operation.

6. How It Works Internally

- Request JSON is bound to `models.PeakWhatsappMessageRequest`.
- The handler validates that either **message** or **template_name** is present.
- It queries the `OrganizationWhatsAppAccount` table for a row matching the given `organization_external_id` with `is_active = true`.
- It calls `services.SendPeakWhatsAppMessage(...)`, passing the recipient, message/template details, and the organization's own API key and phone number ID — meaning each organization sends from its own WhatsApp Business number, not a shared one.
- On success, it writes a message record to the database for history/audit purposes via `createMessageRecord(...)`.
- It returns the provider's message ID and the sending organization's display phone number.

7. Notes & Gotchas

- This endpoint is distinct from `/api/v1/flowbot/send` (`controllers.SendFlowbotWhatsApp`), which sends via a shared Flowbot WhatsApp number rather than a per-organization account.
- The domain `partnersv1.pinbot.ai` is **not** this service — it is the external Pinbot WhatsApp Business API that this service calls out to internally. The correct host for calling this endpoint is the Cloud Run URL above.
- All routes in this service, including public-looking ones, sit behind the global token-validation middleware — there is no truly anonymous route.
- Each organization must have an active row in `OrganizationWhatsAppAccount` before this endpoint can be used on their behalf.

Generated from source review of the Peak-Mobile-LTD/data Go codebase.