

Steel & Pipe Supply Co.
Premier Plant Services LLC
Customer PO: 216287
Heat: 1100080943
Shipment: 0026050592

NUCOR

Mill Certification
07/18/2026

MTR#:2478686-4
Lot #:110008094362
8812 HWY 79 W
Jewett, TX 75846 US
903 626-4461
Fax: 903 626-6290

Sold To: STEEL & PIPE SUPPLY CO INC
PO BOX 1688
MANHATTAN, KS 66502 US

Ship To: CPU
4750 W MARSHALL AVE
LONGVIEW, TX 75604 US

Customer PO	4500626709	Sales Order #	11108838 - 4.1
Product Group	Hot Roll - Merchant Bar Quality	Product #	3007260
Grade	Nucor Multigrade	Lot #	110008094362
Size	5" x 3" x 0.375"	Heat #	1100080943
BOL #	BOL-2510697	Load #	2478686
Description	Hot Roll - Merchant Bar Quality Unequal Angle 5" x 3" x 3/8" Nucor Multigrade 40' 0" [480"] 6001-10000 lbs	Customer Part #	505003001240
Production Date	05/28/2026	Qty Shipped LBS	19600
Product Country Of Origin	United States	Qty Shipped EA	50
Original Item Description		Original Item Number	

I hereby certify that the material described herein has been manufactured in accordance with the specifications and standards listed above and that it satisfies those requirements.

Melt Country of Origin : United States

Melting Date: 05/27/2026

Roll Country of Origin : United States

Rolling Date: 05/28/2026

C (%)	Mn (%)	P (%)	S (%)	Si (%)	Ni (%)	Cr (%)	Mo (%)	Cu (%)	Ti (%)	V (%)	Nb (%)
0.13	1.00	0.017	0.021	0.223	0.10	0.24	0.04	0.28	0.000	0.030	0.002
Sn (%)											
0.010											

ASTM A529 S78.2 CE (%) : 0.42

Tensile testing

	Yield (PSI)	Tensile (PSI)	Elongation in 8" (%)
(1)	55900	74200	22.0
(2)	56800	74800	23.0

Comments:

NUCOR MULTIGRADE MEETS THE REQUIREMENTS OF: ASTM A36/A36M-19; A529/529M-05(2009) GR50(345); A572/572M-07 GR50(345); A709/709M-10 GR36(250) & GR50(345); CSA G40.21-04 GR44W(300W) & GR50W(350W); AASHTO M270/M270M-10 GR36(270) & GR50(345); ASME SA36/SA36M-07; MEETS REPORTING REQUIREMENTS OF EN10204 SEC 3.1

1. All manufacturing processes of the steel, including melting, casting & hot rolling, have been performed in U.S.A
2. Mercury not intentionally added at any point during manufacturing or testing of this material.

3. Welding or weld repair was not performed on this material.

4. This material conforms to the specifications described on this document and may not be reproduced, except in full, without written approval of Nucor Corporation.

5. Results reported E45 (Determination of inclusion), A370 & E8 (Tensile), E381, E340 (Macroetch), E18 (Rockwell Hardness HRB, HRC), E10 (Brinell Hardness), E112 (Grain size), A370 E23 (Charpy Impact), E415 (Optical Emission Spectrometry), E1019 (Determination of Nitrogen) if it is needed. are provided as interpretation of ASTM procedures.


Robert Fortson, Quality Supervisor