



CMC STEEL ALABAMA
101 S 50TH STREET
BIRMINGHAM AL 35212-3525

CERTIFIED MILL TEST REPORT
For additional copies call
800-637-3227

We hereby certify that the test results presented here
are accurate and conform to the reported grade specification

Marcus W. McCluney - CMC Steel AL

Quality Assurance Manager

1SERIES-BPS®

216299

HEAT NO.: 1107359	S	Steel Service Co - OK	S	Steel Service Co - OK	Delivery#: 86978357
SECTION: ANG 8 X 4x12 40"0" A36/52950	O		H		BOL#: 77337843
GRADE: ASTM A36-19/A529-19 Gr 50	L	24412 AMAH PKWY	I	24412 AMAH PKWY	CUST PO#: 9309
ROLL DATE: 08/11/2026	D	CLAREMORE OK	P	CLAREMORE OK	CUST P/N:
MELT DATE: 08/05/2026	T	US 74019-4304	T	US 74019-4304	DLVRY LBS / HEAT: 9408.000 LB
Cert. No.: 86978357 / 107359B523	O	9183416322	O	9183416322	DLVRY PCS / HEAT: 12 EA
		9183416390		9183416390	Prod LBS/HEAT: 166992 LB

Characteristic		Value	Characteristic		Value	Characteristic		Value
C	0.16%		Elongation test 1	26.6%	The Following is true of the material represented by this MTR: *Material is fully killed and is Hot Rolled Steel *100% melted, rolled, and manufactured in the USA *EN10204:2004 3.1 compliant *Contains no weld repair *Contains no Mercury contamination *Manufactured in accordance with the latest version of the plant quality manual *Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661, and the Build America, Buy America Act of 2021 *Warning: This product can expose you to chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov *THE RECORDING OF FALSE, FICTITIOUS OR FRAUDULENT STATEMENTS OR ENTRIES ON THIS DOCUMENT MAY BE PUNISHABLE AS A FELONY UNDER FEDERAL STATUTE			
Mn	0.66%		Elongation Gage Lgth test 1	8IN				
P	0.014%		Yield to tensile ratio test1	0.70				
S	0.024%		Yield Strength test 2	53.7ksi				
Si	0.18%		Tensile Strength test 2	75.5ksi				
Cu	0.37%		Elongation test 2	26.6%				
Cr	0.15%		Elongation Gage Lgth test 2	8IN				
Ni	0.15%		Yield to tensile ratio test2	0.71				
Mo	0.057%							
V	0.005%							
Cb	0.012%							
Sn	0.011%							
B	0.0003%							
Ti	0.001%							
N	0.0085%							
Carbon Eq A6	0.34%							
Carbon Eq A529	0.38%							
Yield Strength test 1	52.9ksi							
Tensile Strength test 1	75.1ksi							

1SERIES ALSO MEETS ASTM GRADE A36 REV 08, A572-21 GR 50, A709-36, A709-50, A992, AASHTO GRADE M270-36, M270-50, CSA G40.21-04 GRADE 44W, 50W, ASME SA-36 2008A ADDEND A.

REMARKS : ALSO MEETS ASTM GRADE A36 REV 08, A572-21 GR 50, A709-36, A709-50, A992, AASHTO GRADE M270-36, M270-50, CSA G40.21-04 GRADE 44W, 50W, ASME SA-36 2008A ADDEND A.