



CMC STEEL TEXAS
1 STEEL MILL DRIVE
SEGUIN TX 78155-7510

CERTIFIED MILL TEST REPORT
For additional copies call
800-227-6489

We hereby certify that the test results presented here
are accurate and conform to the reported grade specification

Thomas Brunts
Thomas Brunts

1SERIES-BPS®

Quality Assurance Manager

HEAT NO.:3149265 SECTION: FLAT 1/4x4 20"0" A36/52950 GRADE: ASTM A36-19/A529-19 GR 50 ROLL DATE: 07/22/2026 MELT DATE: 07/17/2026 Cert. No.: 86972210 / 149265A934		S O L D T O		Steel & Pipe Supply Co Inc 555 POYNTZ AVE MANHATTAN KS US 66502-6085 7855875182 7855872282		S H I P T O		Steel & Pipe Supply Co 1003 Fort Gibson Rd Catoosa OK US 74015-0000 9182666325		Delivery#: 86972210 BOL#: 77330793 CUST PO#: 4500627325 CUST PIN: 10840020 DLVRY LBS / HEAT: 40392.000 LB DLVRY PCS / HEAT: 594 EA Prod LBS/HEAT: 148104 LB			
Characteristic		Value		Characteristic				Value		Characteristic		Value	
C		0.10%		Tensile Strength test 2				76.1ksi		The Following is true of the material represented by this MTR: *Material is fully killed and is Hot Rolled Steel *100% milled, rolled, and manufactured in the USA *EN10204:2004 3.1 compliant *Contains no weld repair *Contains no Mercury contamination *Manufactured in accordance with the latest version of the plant quality manual *Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661, and the Build America, Buy America Act of 2021 *Warning: This product can expose you to chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov *THE RECORDING OF FALSE, FICTITIOUS OR FRAUDULENT STATEMENTS OR ENTRIES ON THIS DOCUMENT MAY BE PUNISHABLE AS A FELONY UNDER FEDERAL STATUTE			
Mn		0.79%		Elongation test 2				26.3%					
P		0.019%		Elongation Gage Lgth test 2				8IN					
S		0.021%											
Si		0.19%											
Cu		0.33%											
Cr		0.13%											
Ni		0.17%											
Mo		0.055%											
V		0.000%											
Cb		0.015%											
Sn		0.011%											
Al		0.002%											
Carbon Eq F1554		0.26%											
Carbon Eq A529		0.34%											
Yield Strength test 1		57.5ksi											
Tensile Strength test 1		75.4ksi											
Elongation test 1		28.6%											
Elongation Gage Lgth test 1		8IN											
Yield Strength test 2		57.3ksi											

1SERIES ALSO MEETS ASTM GRADE A36-19, A529-19 GR50, A709-24 GR36, A709-24 GR50, A992-22, AASHTO M270-23 GR50, M270-23 GR50, CSA G40.21-40

1SERIES ALSO MEETS ASTM GRADE A36-19, A529-19 GR50, A572-25 GR50, A709-24 GR36, A709-24 GR50, A992-22, AASHTO M270-23 GR36, M270-23 GR50, CSA G40.21-0

4 44W, 50W, ASME SA6

REMARKS : ALSO MEETS ASTM GRADE A36, A529-50, A572-50, A709-36, A709-50, A992, AASHTO M270-36, M270-50, CSA G40.21-04 44W, 50W
ALSO MEETS THE REQUIREMENTS OF ASME SA36