

Steel & Pipe Supply Co.
Premier Plant Services
Customer PO: 8643-215990
Heat: 1100082294
Shipment: 0026047713

NUCOR

Mill Certification
08/11/2026

MTR#: 2503435-4
Lot #: 110008229460
8812 HWY 79 W
Jewett, TX 75846 US
903 626-4461
Fax: 903 626-6290

Sold To: STEEL & PIPE SUPPLY CO INC
PO BOX 1888
MANHATTAN, KS 66502 US

Ship To: STEEL & PIPE
1050 FORT GIBSON RD
CATOOSA, OK 74015 US

Customer PO	4500627421	Sales Order #	11109406 - 2.1
Product Group	Hot Roll - Merchant Bar Quality	Product #	3016727
Grade	Nucor Multigrade	Lot #	110008229460
Size	0.375" x 3"	Heat #	1100082294
BOL #	BOL-2541230	Load #	2503435
Description	Hot Roll - Merchant Bar Quality Flat 3/8" x 3" Nucor Multigrade 20' 0" [240"] 4001-8000 lbs	Customer Part #	101230020
Production Date	07/14/2026	Qty Shipped LBS	4900
Product Country Of Origin	United States	Qty Shipped EA	64
Original Item Description		Original Item Number	

I hereby certify that the material described herein has been manufactured in accordance with the specifications and standards listed above and that it satisfies those requirements.

Melt Country of Origin : United States

Melting Date: 07/06/2026

Roll Country of Origin : United States

Rolling Date: 07/14/2026

C (%)	Mn (%)	P (%)	S (%)	Si (%)	Ni (%)	Cr (%)	Mo (%)	Cu (%)	Ti (%)	V (%)	Sn (%)
0.12	0.84	0.013	0.020	0.209	0.14	0.21	0.04	0.28	0.001	0.042	0.010

ASTM A529 S78.2 CE (%) : 0.38

Tensile testing

	Yield (PSI)	Tensile (PSI)	Elongation in 8" (%)
(1)	59100	73400	20.0
(2)	58500	72900	20.0

Comments:

NUCOR MULTIGRADE MEETS THE REQUIREMENTS OF: ASTM A36/A36M-14; A529/529M-05(2009) GR50(345); A572/572M-07 GR50(345); A709/709M-10 GR36(250) & GR50(345); CSA G40.21-04 GR44W(300W) & GR50W(350W); AASHTO M270/M270M-10 GR36(270) & GR50(345); ASME SA36/SA36M-07; MEETS REPORTING REQUIREMENTS OF EN10204 SEC 3.1

1. All manufacturing processes of the steel, including melting, casting & hot rolling, have been performed in U.S.A
2. Mercury not intentionally added at any point during manufacturing or testing of this material.
3. Welding or weld repair was not performed on this material.
4. This material conforms to the specifications described on this document and may not be reproduced, except in full, without written approval of Nucor Corporation.
5. Results reported E45 (Determination of inclusion), A370 & E8 (Tensile), E381, E340 (Macroetch), E18 (Rockwell Hardness HRB, HRC), E10 (Brinell Hardness), E112 (Grain size), A370 E23 (Charpy Impact), E415 (Optical Emission Spectrometry), E1019 (Determination of Nitrogen) if it is needed, are provided as interpretation of ASTM procedures.



Robert Fortson, Quality Supervisor