



CMC STEEL TEXAS
1 STEEL MILL DRIVE
SEGUIN TX 78155-7510

CERTIFIED MILL TEST REPORT
For additional copies call
800-227-6489

We hereby certify that the test results presented here
are accurate and conform to the reported grade specification

Thomas Brun

Thomas Brun

1SERIES-BPS®

Quality Assurance Manager

HEAT NO.:3148227 SECTION: FLAT 3/8x3 20" A36/52950 GRADE: ASTM A36-19/A529-19 GR 50 ROLL DATE: 06/13/2026 MELT DATE: 06/02/2026 Cert. No.: 86980960 / 148227A146		Steel & Pipe Supply Co Inc 555 POYNTZ AVE MANHATTAN KS US 66502-6085 7855875182 7855872282		Steel & Pipe Supply Co S H I P T O 1003 Fort Gibson Rd Catoosa OK US 74015-0000 9182666325		Delivery#: 86980960 BOL#: 77340851 CUST PO#: 4500626630 CUST P/N: 101230020 DLVRY LBS / HEAT: 36768.000 LB DLVRY PCS / HEAT: 480 EA Prod LBS/HEAT: 234396 LB	
Characteristic		Value		Characteristic		Value	
C	0.10%	Yield to tensile ratio test1		Yield to tensile ratio test1		0.75	
Mn	0.91%	Yield Strength test 2		Yield Strength test 2		56.9ksi	
P	0.009%	Tensile Strength test 2		Tensile Strength test 2		75.9ksi	
S	0.036%	Elongation test 2		Elongation test 2		27.7%	
Si	0.19%	Elongation Gage Lgth test 2		Elongation Gage Lgth test 2		8IN	
Cu	0.42%	Yield to tensile ratio test2		Yield to tensile ratio test2		0.75	
Cr	0.10%	The Following is true of the material represented by this MTR: *Material is fully killed and is Hot Rolled Steel *100% melted, rolled, and manufactured in the USA *EN10204:2004 3.1 compliant *Contains no weld repair *Contains no Mercury contamination *Manufactured in accordance with the latest version of the plant quality manual *Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 661, and the Build America, Buy America Act of 2021 *Warning: This product can expose you to chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov *THE RECORDING OF FALSE, FICTITIOUS OR FRAUDULENT STATEMENTS OR ENTRIES ON THIS DOCUMENT MAY BE PUNISHABLE AS A FELONY UNDER FEDERAL STATUTE					
Ni	0.15%						
Mo	0.036%						
V	0.000%						
Cb	0.016%						
Sn	0.012%						
Al	0.003%						
Carbon Eq F1554	0.28%						
Carbon Eq A529	0.35%						
Carbon Eq A992	0.32%						
Yield Strength test 1	56.0ksi						
Tensile Strength test 1	74.7ksi						
Elongation test 1	24.3%						
Elongation Gage Lgth test 1	8IN						
1SERIES ALSO MEETS ASTM GRADE A36-19, A529-19 GR50, A572-25 GR50, A709-24 GR36, A709-24 GR50, A992-22, AASHTO M270-23 GR36, M270-23 GR50, CSA G40.21-04 44W, 50W, ASME SA6							