

Steel & Pipe Supply Co.
Premier Plant Services
Customer PO: 9100-216344
Heat: 7060035
Shipment: 0026051153



CMC STEEL TENNESSEE
1919 Tennessee Avenue
Knoxville TN 37921-2686

CERTIFIED MILL TEST REPORT
For additional copies call
865-867-7366/888-870-0766

We hereby certify that the test results presented here
are accurate and conform to the reported grade specification

Serena Patton

Quality Assurance Manager

HEAT NO.:7060035 SECTION: REBAR 19MM (#6) 20'0" A615/A706-60 GRADE: ASTM A615&A706-25 GR60 DualGr ROLL DATE: 06/29/2026 MELT DATE: 06/29/2026 Cert. No.: 86898256 / 060035L182		S Adelphia Metals LLC O 411 MAIN ST E L NEW PRAGUE MN D US 56071-2237 T 9527587500 O		S CPU Knoxville H 2741 MYNDERSE AVE I KNOXVILLE TN P US 37921-2686 T 8655460102 O		Delivery#: 86898256 BOL#: 3468397 CUST PO#: 869702 CUST P/N: DLVRY LBS / HEAT: 17304.000 LB DLVRY PCS / HEAT: 576 EA					
Characteristic		Value		Characteristic		Value		Characteristic		Value	
C		0.29%		% Light Test 1		5.90%		The Following is true of the material represented by this MTR: *Material is fully killed and is Hot Rolled Steel *100% melted, rolled, and manufactured in the USA *EN10204-2004 3.1 compliant *Contains no weld repair *Contains no Mercury contamination *Manufactured in accordance with the latest version of the plant quality manual *Meets the "Buy America" requirements of 23 CFR635.410, 49 CFR 66, and the Build America, Buy America Act of 2021 *Warning: This product can expose you to chemicals which are known to the State of California to cause cancer, birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov . *THE RECORDING OF FALSE, FICTITIOUS OR FRAUDULENT STATEMENTS OR ENTRIES ON THIS DOCUMENT MAY BE PUNISHABLE AS A FELONY UNDER FEDERAL STATUTE			
Mn		1.26%		Elongation Gage Lgth 1(metri		200mm					
P		0.023%		Bend Test 1		Passed					
S		0.031%		Rebar Deformation Avg. Spaci		0.436IN					
Si		0.29%		Rebar Deformation Avg. Helgh		0.056IN					
Cu		0.44%		Rebar Deformation Max. Gap		0.114IN					
Cr		0.24%		Uniform Elongation test 1		11.0%					
Ni		0.09%		Deform radius/height ratio 1		1.77					
Mo		0.030%									
V		0.003%									
Sn		0.005%									
Carbon Eq A706		0.54%									
Yield Strength test 1		67.0ksi									
Yield Strength test 1 (metri		462MPa									
Tensile Strength test 1		96.9ksi									
Tensile Strength 1 (metric)		668MPa									
Elongation test 1		16.2%									
Elongation Gage Lgth test 1		8IN									
Tensile to Yield ratio test1		1.45									

REMARKS : MEETS SUPPLEMENTARY REQUIREMENTS OF CURRENT A706 REVISIONS AT THE TIME OF PRODUCTION. MEETS AASHTO M31 TYPE W. 100% MANUFACTURED IN THE USA
PLEASE EMAIL CMC_TN_QUALITY@CMC.COM WITH ANY FEEDBACK, QUESTIONS, OR CONCERNS.