

**** TEST REPORT ****

CERTIFICATE BHW-2026-80535058-82730000-01
 SHIPMENT NO :805-35058 PAGE 1
 DATE ISSUED :06/26/2026
 PURCHASE ORDER :18904/2
 MILL ORDER NO YH 827-30000
 COIL/LIFT ID :397566
 REF # :
 VEH. ID :CTRN 500154
 PRODUCING MILL :CLEVELAND-CLIFFS
 BURNS HARBOR LLC
 250 W US HWY 12, BURNS HARBOR, IN 46304 US

Cleveland-Cliffs Burns Harbor LLC
 250 West US Highway 12
 Burns Harbor, IN 46304-9745

**CLIFFS**

I certify that the test results shown are correct as contained in the records of
 Cleveland-Cliffs Burns Harbor LLC and in compliance with the requirements of
 this order.

Larry Crawford
 Division Manager, Quality Assurance

S
O
L
D
T
O
WILLBANKS METALS INC
 1155 NE 28TH ST
 FORT WORTH TX 76106-7241

WILLBANKS METALS INC
 THEIR SIDING
 1000 NE 28TH ST
 FORT WORTH TX 76106

S
H
I
P
T
O

SPECIFICATIONS OF THE STEEL:

HOT ROLL BLACK STRUCTURAL STEEL DRY COIL/MILL EDGE---ASTM/ASME FOR CONVERSI
 ON TO ASTM A36/ASME SA36

ORDER DESCRIPTION:
 .1770IN X 60 IN COIL
 CUST APPL:MISC PARTS

QTY (LBS) HEAT NO.
 1 46100 821T12250

3/16 x A36

TEST PARAMETER

|DIR| TEST RESULT |UOM

YIELD STRENGTH
 TENSILE STRENGTH
 TOTAL ELONGATION

T 44.5 KSI
 T 66.5 KSI
 T 2 31 IN--PCT

HEAT (WT.%) C	MN	P	S	SI	CU	NI	CR	MO	V	TI	AL	CB
821T12250 .16	.87	.014	.006	.009	.022	.01	.03	.003	.001	.002	0.042	.002
PB	CA	N	B	SN								
	.0002	.003	.0002	.002								

MELTED AND MANUFACTURED IN THE U.S.A.

All tests were performed by Cleveland-Cliffs Burns Harbor LLC Laboratories, unless otherwise specified (indicated by *) in accordance with the following: Chemical analysis per ASTM E415 and E1019; Tensile tests per ASTM E8, A370, E696 and E517; JIS Z211, EN 10130 and ISO 6892; Impact tests per ASTM E23, A370 and A674; Hardness tests per ASTM E18 and A370. Conformance to the specification limits is based on sample acceptance that the results are within the limits (measurement uncertainty is not taken into account). Crosshead speed control method used for all tensile tests. Test certificates are prepared in accordance with procedures outlined in DIN EN 10204 2005 Type 3.1.