

FACT SHEET



MULTISORB

This white non-woven fabric consisting of cellulose and polyester has been especially developed for automatic blanket cleaning within printpresses. Features as: low lint, balanced absorptive capacity, high tear-resistance and low lint secure excellent cleaning under wet conditions.

TECHNICAL DATA

Fabric weight	Avg. Thickness	Permeability 196 Pa
73 g/m ²	260 micron	660 (L/M ² /s)
Tensile strength MD	Tensile strength CD	Elongation MD
2750 N/M	860 N/M	17 %
Elongation CD	Trapezium Tear MD	Trapezium Tear CD
32 %	1590 cN	2260 cN
Ratio Wet/ Dry	Absorbtive Capacity	Water Drop test
50 %	500 %	1 second

The facts stated and the recommendations and suggestions herein are based upon experiment and information believed to be reliable. No guarantee is made of their accuracy however, and DIMPLE assumes no liability for product failure other than to supply replacement material for DIMPLE shown to be defective when delivered. Except as stated above, there are no warranties expressed or implied on merchantability fitness for use, or otherwise. DIMPLE shall not be liable for special , incidental and consequential damages. No statement containing herein shall be construed as an inducement to infringe existing patents or as an endorsement of products of specific manufacture.

DIMPLE BV + Gooiland 46 + 1948 RD Beverwijk + telefoon: 0251-316 302 + e-mail: info@dimple.nl + www.dimple.nl