

SQL Exercise 4

1. Display the minimum Status in the Supplier table.

Query-

```
select min(status) from supplier;
```

2. Display the maximum Weight in the Parts table.

Query-

```
select max(weight) from parts;
```

3. Display the average Weight of the Parts.

Query-

```
select avg(weight) from parts;
```

4. Display the total Quantity sold for part 'P1'.

Query-

```
select sum(Qty) as 'Quantity'
from parts
where `P#`='p1';
```

5. Display the total Quantity sold for each part.

Query-

```
select `P#`,sum(Qty) as 'quantity'
from parts
group by `p#`;
```

6. Display the average Quantity sold for each part.

Query-

```
select `P#`,avg(Qty) as 'quantity'
from parts
group by `p#`;
```

7. Display the maximum Quantity sold for each part, provided the maximum Quantity is greater than 800.

Query-

```
select `P#` , max(Qty) as "Quantity"
from parts
group by `P#`
having max(Qty)>800;
```

8. Display the Status and the count of Suppliers with that Status.

Query-

```
select status, count(status) from supplier
group by status;
```

9. Display the count of Projects going on in different cities.

Query-

```
select city ,count(city) as "Cities" from projects
group by city;
```

10. What is the difference between COUNT(Status) and COUNT(*) ?

Count(*)- Count all rows in the table and also count all null values and non-null values.

Count(Status)- count status column wise data and not count null values.

11. Display the Status and the Count of Suppliers with that Status in the following format as shown below:-

Status Count

Ten 1

Twenty 2

Thirty 3

Query-

```
SELECT
```

```
CASE
```

```
  WHEN Status = 10 THEN 'Ten'
```

```
  WHEN Status = 20 THEN 'Twenty'
```

```
  WHEN Status = 30 THEN 'Thirty'
```

```
  ELSE 'Other'
```

```
END AS Status,
```

```
COUNT(*) AS Count
```

```
FROM SUPPLIER
```

```
GROUP BY Status;
```