

## EXERCISE-9

### Sub queries

#### Objectives

After completing this lesson, you should be able to do the following:

- Define subqueries
- Describe the types of problems that subqueries can solve
- List the types of subqueries
- Write single-row and multiple-row subqueries

#### **Using a Subquery to Solve a Problem**

Who has a salary greater than Abel's?

#### **Main query:**

Which employees have salaries greater than Abel's salary?

#### **Subquery:**

What is Abel's salary?

#### **Subquery Syntax**

`SELECT select_list FROM table WHERE expr operator (SELECT select_list FROM table );`

- The subquery (inner query) executes once before the main query (outer query).
- The result of the subquery is used by the main query.

~~A subquery is a~~ **A subquery is a** SELECT statement that is embedded in a clause of another SELECT statement.

You can build powerful statements out of simple ones by using subqueries. They can be very useful when you need to select rows from a table with a condition that depends on the data in the table itself.

You can place the subquery in a number of SQL clauses, including the following:

- WHERE clause
- HAVING clause
- FROM clause

#### **In the syntax:**

*operator* includes a comparison condition such as >, =, or IN

**Note:** Comparison conditions fall into two classes: single-row operators

(>, =, >=, <, <=, <>) and multiple-row operators (IN, ANY, ALL). statement. The subquery generally executes first, and its output is used to complete the query condition for the main (or outer) query

#### **Using a Subquery**

`SELECT last_name FROM employees WHERE salary > (SELECT salary FROM employees WHERE last_name = 'Abel');`

---

---

inner query and uses this result to display all the employees who earn more than this amount.

### **Guidelines for Using Subqueries**

- Enclose subqueries in parentheses.
- Place subqueries on the right side of the comparison condition.
- The ORDER BY clause in the subquery is not needed unless you are performing Top-N analysis.
- Use single-row operators with single-row subqueries, and use multiple-row operators with multiple-row subqueries.

### **Types of Subqueries**

- 
- Single-row subqueries: Queries that return only one row from the inner SELECT statement.
  - Multiple-row subqueries: Queries that return more than one row from the inner SELECT statement.

#### **Single-Row Subqueries**

- 
- Return only one row
  - Use single-row comparison operators

### **Example**

Display the employees whose job ID is the same as that of employee 141:

```
SELECT last_name, job_id FROM employees WHERE job_id = (SELECT job_id FROM employees WHERE employee_id = 141);
```

Displays employees whose job ID is the same as that of employee 141 and whose salary is greater than that of employee 143.

```
SELECT last_name, job_id, salary FROM employees WHERE job_id = (SELECT job_id FROM employees WHERE employee_id = 141) AND salary > (SELECT salary FROM employees WHERE employee_id = 143);
```

#### **Using Group Functions in a Subquery**

---

Displays the employee last name, job ID, and salary of all employees whose salary is equal to the minimum salary. The MIN group function returns a single value (2500) to the outer query.

```
SELECT last_name, job_id, salary FROM employees WHERE salary = (SELECT MIN(salary) FROM employees);
```

#### **The HAVING Clause with Subqueries**

---

- The Oracle server returns results into the HAVING clause of the main query. Displays all the departments that have a minimum salary greater than that of department 50. `SELECT department_id, MIN(salary) FROM employees GROUP BY department_id HAVING MIN(salary) > (SELECT MIN(salary) FROM employees WHERE department_id = 50);`

**Example Find the job with the lowest average salary.**

---

```
SELECT job_id, AVG(salary) FROM employees GROUP BY job_id HAVING
AVG(salary) = (SELECT MIN(AVG(salary)) FROM employees GROUP BY job_id);
```

**What Is Wrong in this Statements?**

```
SELECT employee_id, last_name FROM employees WHERE salary =(SELECT
MIN(salary) FROM employees GROUP BY department_id); Will This Statement Return
Rows? SELECT last_name, job_id FROM employees WHERE job_id =(SELECT job_id
FROM employees WHERE last_name = 'Haas');
```

**Multiple-Row Subqueries**

- 
- Return more than one row
  - Use multiple-row comparison operators

**Example**

Find the employees who earn the same salary as the minimum salary for each department.  
`SELECT last_name, salary, department_id FROM employees WHERE salary IN (SELECT MIN(salary)`

`FROM employees GROUP BY department_id);`

Using the ANY Operator in Multiple-Row Subqueries

```
SELECT employee_id, last_name, job_id, salary FROM employees WHERE salary < ANY
(SELECT salary FROM employees WHERE job_id = 'IT_PROG') AND job_id <> 'IT_PROG';
```

programmer. The maximum salary that a programmer earns is \$9,000. < ANY means less than the maximum. >ANY means more than the minimum. =ANY is equivalent to IN.

### Using the ALL Operator in Multiple-Row Subqueries

---

```
SELECT employee_id, last_name, job_id, salary
FROM employees
WHERE salary < ALL (SELECT salary FROM employees WHERE job_id = 'IT_PROG')
AND job_id <> 'IT_PROG';
```

Displays employees whose salary is less than the salary of all employees with a job ID of IT\_PROG and whose job is not IT\_PROG.

□ ALL means more than the maximum, and <ALL means less than the minimum.

The NOT operator can be used with IN, ANY, and ALL operators.

### Null Values in a Subquery

```
SELECT emp.last_name FROM employees emp
WHERE emp.employee_id NOT IN (SELECT mgr.manager_id FROM employees mgr);
```

Notice that the null value as part of the results set of a subquery is not a problem if you use the IN operator. The IN operator is equivalent to =ANY. For example, to display the employees who have subordinates, use the following SQL statement:

```
SELECT emp.last_name
FROM employees emp
WHERE emp.employee_id IN (SELECT mgr.manager_id FROM employees mgr);
```

Display all employees who do not have any subordinates:


```
SELECT last_name FROM employees
WHERE employee_id NOT IN (SELECT manager_id FROM employees WHERE manager_id IS
NOT NULL);
```


### Find the Solution for the following:

---

1. The HR department needs a query that prompts the user for an employee last name. The query then displays the last name and hire date of any employee in the same department as the employee whose name they supply (excluding that employee). For example, if the user enters Zlotkey, find all employees who work with Zlotkey (excluding Zlotkey).

```
SELECT last_name, hire_date
FROM employees
WHERE department_id=(SELECT department_id FROM employees
WHERE last_name = 'Zlotkey')
AND last_name <> 'Zlotkey';
```







Download ▾

Execution time: 0.143 seconds

LAST_NAME	HIRE_DATE
No items to display.	

2. Create a report that displays the employee number, last name, and salary of all employees who earn more than the average salary. Sort the results in order of ascending salary.



```
SELECT employee_id, last_name, salary
FROM employees
WHERE salary > (SELECT AVG(salary)
FROM employees)
ORDER BY salary ASC;
```

  Download ▾ Execution time: 0.006 seconds

	EMPLOYEE_ID	LAST_NAME	SALARY
1	1002	Smith	8000
2	1001	Doe	12000

3. Write a query that displays the employee number and last name of all employees who work in a department with any employee whose last name contains a *u*.

```
SELECT employee_id, last_name
FROM employees
WHERE department_id IN ( SELECT department_id
FROM employees WHERE last_name LIKE '%u%');
```



  Download ▾ Execution time: 0.005 seconds

EMPLOYEE_ID	LAST_NAME
-------------	-----------

No items to display.

4. The HR department needs a report that displays the last name, department number, and job ID of all employees whose department location ID is 1700.


```
SELECT last_name, department_id, job_id
FROM employees
WHERE department_id IN ( SELECT department_id
FROM department WHERE location_id = 1700 );
```

  Download ▾ Execution time: 0.008 seconds

	LAST_NAME	DEPARTMENT_ID	JOB_ID
1	Doe	90	AD_PRES
2	Smith	60	IT_PROG
3	Brown	40	HR_REP
4	White	50	SA_REP

5. Create a report for HR that displays the last name and salary of every employee who reports to King.

```
SELECT last_name, salary
FROM employees
WHERE manager_id = ( SELECT employee_id
FROM employees WHERE last_name = 'King' );
```



  Download ▾ Execution time: 0.007 seconds

LAST_NAME	SALARY
-----------	--------

No items to display.

6. Create a report for HR that displays the department number, last name, and job ID for every employee in the Executive department.

```
SELECT department_id, last_name, job_id
FROM employees
WHERE department_id IN ( SELECT department_id
FROM department WHERE dept_name = 'Executive');
```



  Download ▾ Execution time: 0.006 seconds

DEPARTMENT_ID	LAST_NAME	JOB_ID
---------------	-----------	--------

No items to display.

7. Modify the query 3 to display the employee number, last name, and salary of all employees who earn more than the average salary and who work in a department with any employee whose last name contains a *u*.

```
SELECT employee_id, last_name, salary
FROM employees
WHERE salary > (SELECT AVG(salary) FROM employees)
AND department_id IN ( SELECT department_id
FROM employees WHERE last_name LIKE '%u%');
```

Download ▾ Execution time: 0.005 seconds

EMPLOYEE_ID	LAST_NAME	SALARY
No items to display.		

Evaluation Procedure	Marks awarded
Query(5)	
Execution (5)	
Viva(5)	
Total (15)	
Faculty Signature	