

Model	Year	MG	SG	Illustration	Restrictions	UPD	14:15	25.02.2010	PORSCHE PET PORSCHE		
9442	1988	6	03	603-00		248					

The diagram illustrates the assembly of a rear disc brake. Key components include the brake disc (1), brake pads (4), floating callipers (3), and various mounting hardware (5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19). A grease gun (20) is shown at the bottom left, indicating the application of grease to the calliper pins.

Pos	Part Number	Description	Remark	Qty	Model
		disc brake rear axle			944, 944S
1	944 352 041 02	brake disc	-86	2	
1	944 352 041 03	brake disc	87-	2	
2	N 033 167 1	countersunk-head screw M 6 X 12		2	
3	944 352 429 00	floating calliper without pad	/L	1	
3	944 352 430 00	floating calliper without pad	/R	1	
4	944 352 951 02	brake pad repair set without asbestos		1	
5	944 352 952 00	mounting parts		1	
6	944 612 211 01	warning contact	-86	2	
6	944 612 212 01	warning contact	87-	2	
7	999 651 203 40	cable holder		2	
8	* 928 352 935 00	expanding spring		2	
9	* 928 351 936 00	retaining pin		4	
10	944 352 963 00	safety seal		2	
11	* 928 352 941 00	gasket set		2	
12	901 352 977 10	bleeder valve		2	
13	901 351 927 10	dust boot		2	
14	944 352 954 00	guide spring	/R	1	
(14)	944 352 953 00	guide spring	/L	1	
15	900 082 077 02	hexagon-head bolt M 12 X 1,5 X 37		4	
16	N 012 232 1	spring washer		4	
17	964 352 801 00	protective plate		2	
18	999 072 005 09	hexagon-head bolt M 6 X 12		8	
19	N 012 226 5	spring washer B 8		8	

