Lab: Dictionaries, Lambda and LINQ

Problems for exercises and homework for the "Programming Fundamentals" course @ SoftUni.

Check your solutions here: https://judge.softuni.bg/Contests/174/Dictionaries-Lambda-and-LINQ-Lab.

Associative Arrays

1. Count Real Numbers

Read a list of real numbers and print them in ascending order along with their number of occurrences.

Examples

Input	Output
8 2.5 2.5 8 2.5	2.5 -> 3 8 -> 2

Input	Output
1.5 5 1.5 3	1.5 -> 2 3 -> 1 5 -> 1

Input	Output
-2 0.33 0.33 2	-2 -> 1 0.33 -> 2 2 -> 1

Hints

- Use **SortedDictionary<double**, int> named counts.
- Pass through each input number **num** and increase **counts[num]** (when **num** exists in the dictionary) or assign **counts[num] = 1** (when **num** does not exist in the dictionary).
- Pass through all numbers **num** in the dictionary (**counts.Keys**) and print the number **num** and its count of occurrences counts[num].

2. Odd Occurrences

Write a program that extracts from a given sequence of words all elements that present in it odd number of times (case-insensitive).

- Words are given in a single line, space separated.
- Print the result elements in lowercase, in their order of appearance.

Examples

Input	Output
Java C# PHP PHP JAVA C java	java, c#, c
3 5 5 hi pi HO Hi 5 ho 3 hi pi	5, hi
a a A SQL xx a xx a A a XX c	a, sql, xx, c

Hints

- Use a **dictionary** ($string \rightarrow int$) to count the occurrences of each word (just like in the previous problem).
- Pass through all key-value pairs in the dictionary and append to the results list all keys that have odd value.
- Print the results list.



















LINQ II.

3. Sum, Min, Max, Average

Write a program to read n integers and print their sum, min, max, first, last and average values.

Examples

Input	Output
5 12 20 -5 37 8	Sum = 72 Min = -5 Max = 37 Average = 14.4
4 50 20 25 40	Sum = 135 Min = 20 Max = 50 Average = 33.75

Hints

- Include the "System.Linq" namespace to enable aggregate functions.
- Read the input array **nums**[].
- Use nums.Min(), nums.Max(), etc.

4. Largest 3 Numbers

Read a list of real numbers and print largest 3 of them. If less than 3 numbers exit, print all of them.

Examples

Input	Output
10 30 15 20 50 5	50 30 20

Input	Output
20 30	30 20

Hints

You can use LINQ query like this: $nums.OrderByDescending(x \Rightarrow x).Take(3)$.

5. Short Words Sorted


Read a text, extract its words, find all short words (less than 5 characters) and print them alphabetically, in lowercase.

- Use the following separators: . , : ; () [] " ' \ / ! ? (space).
- Use case-insensitive matching.
- Remove duplicated words.

Examples

Input	Output
-------	--------




















2-3, and, c#, can, go, in, java, php, you

Hints

- To extract the words from the input text, **split** by the specified separators.
- Use a **LINQ expression**:
 - Filter by word length: Where(...)
 - Order by word: OrderBy(...)
 - Use distinct to avoid repeated words: Distinct().

6. Fold and Sum

Read an array of 4*k integers, fold it like shown below, and print the sum of the upper and lower rows (2*k integers):



Examples

Input	Output	Comments
5 2 3 6	7 9	5 6 + 2 3 = 7 9
1 2 3 4 5 6 7 8	5 5 13 13	2 1 8 7 + 3 4 5 6 = 5 5 13 13
4 3 -1 2 5 0 1 9 8 6 7 -2	1 8 4 -1 16 14	-1 3 4 -2 7 6 + 2 5 0 1 9 8 = 1 8 4 -1 16 14

Hints

Use a LINQ expression:

- Row 1, left part: take the **first k** numbers and **reverse**.
- Row 1, right part: **reverse** and take the **first k** numbers.
- Concatenate the left and the right part of row 1.
- Row 2: skip the **first k** numbers and take the next **2*k** numbers.
- Sum the arrays row1 and row2: var sum = row1. Select((x, index) => x + row2[index]).

















