

# Exercise: Dictionaries, Lambdas and Functional Programming

Problems for exercises and homework for the [“Python Fundamentals” course @ SoftUni](#).

You can check your solutions here: <https://judge.softuni.bg/Contests/945/>.

## 01. Odd Occurrences

Write a program that extracts from a given sequence of words all elements that present in it **odd number of times** (case-insensitive).

- Words are given in a single line, space separated.
- Print the result elements in lowercase, in their order of appearance.

### Examples

Input	Output
Java C# PHP PHP JAVA C java	java, c#, c
3 5 5 hi pi HO Hi 5 ho 3 hi pi	5, hi
a a A SQL xx a xx a A a XX c	a, SQL, xx, c

### Hints

- Use a **dictionary** (**string** → **int**) to count the occurrences of each word (just like in the previous problem).
- Pass through all **key-value pairs** in the dictionary and append to the results list all **keys** that have **odd value**.
- Print the results list.

## 02. Count Real Numbers

Read a **list of real numbers** and **print them in ascending order** along with their **number of occurrences**.

### Examples

Input	Output
8 2.5 2.5 8 2.5	2.5 -> 3 times 8 -> 2 times

Input	Output
1.5 5 1.5 3	1.5 -> 2 times 3 -> 1 times 5 -> 1 times

Input	Output
-2 0.33 0.33 2	-2 -> 1 times 0.33 -> 2 times 2 -> 1 times

### Hints

- Use **dictionary** (**key=nums**, **value=count**) named **counts**.
- Pass through each input number **num** and increase **counts[num]** (when **num** exists in the dictionary) or assign **counts[num] = 1** (when **num** does not exist in the dictionary).
- Pass through all numbers **num** in the dictionary (**counts.keys()**) and print the number **num** and its count of occurrences **counts[num]**.

## 03. Letter Repetition

You will be given a **single string**, containing **random ASCII character**. Your task is to **print every character**, and how **many times** it has been used in the **string**.

## Examples

Input	Output
aaabbaaabbccccc	a -> 6 b -> 5 c -> 3
The quick brown fox jumps over the lazy dog	T -> 1 h -> 2 e -> 3 -> 8 q -> 1 u -> 2 i -> 1 c -> 1 k -> 1 b -> 1 r -> 2 o -> 4 w -> 1 n -> 1 f -> 1 x -> 1 j -> 1 m -> 1 p -> 1 s -> 1 v -> 1 t -> 1 l -> 1 a -> 1 z -> 1 y -> 1 d -> 1 g -> 1

## 04. Dict-Ref

You have been tasked to create a referenced dictionary, or in other words a dictionary, which knows how to reference itself.

You will be given several input lines, in one of the following formats:

- {name} = {value}
- {name} = {secondName}

The **names** will always be **strings**, and the **values** will always be **integers**.

In case you are given a **name** and a **value**, you must store the **given name** and its **value**. If the name already **EXISTS**, you must **CHANGE** its **value** with the **given one**.

In case you are given a **name** and a **second name**, you must **store** the **given name** with the **same value** as the **value** of the **second name**. If the given **second name DOES NOT** exist, you must **IGNORE** that input.

When you receive the command “end”, you must print **all entries** with their **value**, by **order of input**, in the following format:

**{entry} === {value}**

## Examples

Input	Output
Cash = 500 Johny = 5 Cash = 200 Johnny = 200 Car = 150 Plane = 2000000 end	Cash === 200 Johny === 5 Johnny === 200 Car === 150 Plane === 2000000
Entry1 = 10000 Entry2 = 12345 Entry3 = 10101 Entry4 = Entry1 Entry2 = Entry3 Entry3 = Entry4 end	Entry1 === 10000 Entry2 === 10101 Entry3 === 10000 Entry4 === 10000

## 05. Mixed Phones

You will be given several phone entries, in the form of strings in format:

**{firstElement} : {secondElement}**

The first element is usually the person’s name, and the second one – his phone number. The phone number consists ONLY of digits, while the person’s name can consist of any ASCII characters.

Sometimes the phone operator gets distracted by the Minesweeper she plays all day, and gives you first the phone, and then the name. e.g. : **0888888888 : Pesho**. You must store them correctly, even in those cases.

When you receive the command “Over”, you are to **print all names** you’ve stored with their phones. The names must be printed in **alphabetical order**.

## Examples

Input	Output
14284124 : Alex Gosho : 088423123 Ivan : 412048192 123123123 : Nanyo Pesho : 150925812 Over	Alex -> 14284124 Gosho -> 88423123 Ivan -> 412048192 Nanyo -> 123123123 Pesho -> 150925812
Ivan : 13213456 GeorgeThe2nd : 131313 Johnny : 5556322312 Donald : 3212 Over	Donald -> 3212 GeorgeThe2nd -> 131313 Ivan -> 13213456 Johnny -> 5556322312

## 06. Exam Shopping

A supermarket has **products** which have **quantities**. Your task is to stock the shop before **Exam Sunday**. Until you receive the command "**shopping time**", add the various **products** to the shop's **inventory**, keeping track of their **quantity** (for inventory purposes). When you receive the aforementioned command, the students start pouring in before the exam and **buy** various **products**.

The format for **stocking** a product is: "**stock {product} {quantity}**".

The format for **buying** a product is: "**buy {product} {quantity}**".

If a student **tries** to buy a product, which **doesn't exist**, print "**{product} doesn't exist**". If it does exist, but it's **out of stock**, print "**{product} out of stock**". If a student tries buying **more** than the quantity of that product, sell them **all the quantity** of the product (the product is left out of stock, **don't** print anything).

When you receive the command "**exam time**", your task is to **print** the **remaining** inventory in the following format: "**{product} -> {quantity}**". If a product is out of stock, **do not** print it.

### Examples

Input	Output
stock Boca_Cola 10 stock Boca_Cola 10 stock Kay's 3 stock Kay's 2 shopping time buy Boca_Cola 5 buy Kay's 5 exam time	Boca_Cola -> 15
stock Lobster_Energy 20 stock Loreni 30 stock Loreni 30 stock Lobster_Energy 10 shopping time exam time	Lobster_Energy -> 30 Loreni -> 60
stock Boca_Cola 16 stock Kay's_Chips 33 stock Lobster_Energy 60 stock Boca_Cola 4 stock Loreni 15 stock Loreni 15 stock Loreni 15 stock Loreni 15 shopping time buy Boca_Bola 2 buy Lobster_Energy 20 buy Boca_Cola 1 buy Boba_Bola 12 exam time	Boca_Bola doesn't exist Boba_Bola doesn't exist Boca_Cola -> 19 Kay's_Chips -> 33 Lobster_Energy -> 40 Loreni -> 60

## 07. User Logins

Write a program that receives a **list** of **username-password pairs** in the format "**{username} -> {password}**". If there's already a user with that username, **replace their password**. After you receive the command "**login**", **login**

**requests** start coming in, using the **same format**. Your task is to print the status of user login, using different messages as per the conditions below:

- If the password matches with the user's password, print "{username}: logged in successfully".
- If the user doesn't exist, or the password doesn't match the user, print "{username}: login failed".

When you receive the command **"end"**, print the **count** of **unsuccessful** login attempts, using the format **"unsuccessful login attempts: {count}"**.

## Examples

Input	Output
ivan_ivanov -> java123 pesh0 -> qwerty stamat4e -> 111111 princess_penka -> MyPrince <b>login</b> pesh0 -> qwertt ivan_ivanov -> java123 stamat4e -> 111112 princess_penka -> MyPrince end	pesh0: login failed ivan_ivanov: logged in successfully stamat4e: login failed princess_penka: logged in successfully unsuccessful login attempts: 2
johnny_bravo05 -> woahMama <b>login</b> johnny_bravo06 -> woahMama johnny_bravo05 -> woahmama johnny_bravo05 -> WoahMama johnny_bravo05 -> wohMama johnny_bravo05 -> woahMama end	johnny_bravo06: login failed johnny_bravo05: login failed johnny_bravo05: login failed johnny_bravo05: login failed johnny_bravo05: logged in successfully unsuccessful login attempts: 4
walter_white58 -> iamthedanger krazy_8 -> ese jesseABQ -> bword <b>login</b> krazy_8 -> ese krazy_8 -> ese jesse -> bword jesseabq -> bword walter_white58 -> IAmTheDanger walter_white58 -> iamthedanger end	krazy_8: logged in successfully krazy_8: logged in successfully jesse: login failed jesseabq: login failed walter_white58: login failed walter_white58: logged in successfully unsuccessful login attempts: 3

## Hints

- **Parse the commands** by splitting by space. The first element is the username, while the third element is the password.
- Store the **user entries** in **dictionary** with key {username} and value {password}.

## 08. Filter Base

You have been tasked to sort out a database full of information about employees. You will be given several input lines containing information in one of the following formats:

- {name} -> {age}

- {name} -> {salary}
- {name} -> {position}

As you see you have 2 parameters. There can be only 3 cases of input:

If the second parameter is an **integer**, you must store it as **name** and **age**.

If the second parameter is a **floating-point number**, you must store it as **name** and **salary**.

If the second parameter is a **string**, you must store it as **name** and **position**.

You must read input lines, then parse and store the information from them, **until** you receive the command **“filter base”**. When you receive that command, the **input sequence of employee information** should **end**.

On the last line of input you will receive a string, which can either be **“Age”**, **“Salary”** or **“Position”**. Depending on the case, you must **print all entries** which **have been stored** as **name** and **age**, **name** and **salary**, or **name** and **position**.

In case, the given last line is **“Age”**, you must print every employee, stored with its **age** in the following format:

```
Name: {name1}
Age: {age1}
=====
Name: {name2}
. . .
```

In case, the given last line is **“Salary”**, you must print every employee, stored with its **salary** in the following format:

```
Name: {name1}
Salary: {salary1}
=====
Name: {name2}
. . .
```

In case, the given last line is **“Position”**, you must print every employee, stored with its **position** in the following format:

```
Name: {name1}
Position: {position1}
=====
Name: {name2}
. . .
```

**NOTE:** Every entry is **separated** with the **other**, with a **string of 20 character ‘=’**.

There is **NO** particular order of printing – the data must be printed in **order of input**.

## Examples

Input	Output
Isacc -> 34 Peter -> CEO Isacc -> 4500.054321 George -> Cleaner John -> Security	Name: Peter Position: CEO ===== Name: George Position: Cleaner

Nina -> Secretary filter base Position	===== Name: John Position: Security ===== Name: Nina Position: Secretary =====
Ivan -> Chistach Pesho -> Ohrana Pesho -> 1323.0456 Ivan -> 732.404 Georgi -> 21 Georgi -> 21.02 filter base Salary	Name: Pesho Salary: 1323.0456 ===== Name: Ivan Salary: 732.404 ===== Name: Georgi Salary: 21.02 =====

## Hints:

Use `int()`, `float()` and `try-except` structure to find out in **which case** are you and where to **store** the data.

## 09. Wardrobe

You just bought a new wardrobe. The weird thing about it is that it came prepackaged with a big box of clothes (just like those refrigerators, which ship with free beer inside them)! So, you'll need to find something to wear.

### Input

On the first line of the input, you will receive **n** – the **number of lines** of clothes, which came prepackaged for the wardrobe.

On the next **n** lines, you will receive the clothes for each color in the format:

- “{color} -> {item1},{item2},{item3}...”

If a color is added a **second** time, **add all items** from it and **count** the **duplicates**.

**Finally**, you will receive the **color** and **item** of the clothing, that you need to look for.

### Output

Go through all the **colors** of the clothes and print them in the following format:

```
{color} clothes:
* {item1} - {count}
* {item2} - {count}
* {item3} - {count}
...
* {itemN} - {count}
```

If the **color** lines up with the **clothing item**, print “(**found!**)” alongside the item. See the examples to better understand the output.

## Examples

Input	Output
4 Blue -> dress,jeans,hats Gold -> dress,t-shirt,boxers White -> briefs,tanktop Blue -> gloves Blue dress	Blue clothes: * dress - 1 (found!) * jeans - 1 * hats - 1 * gloves - 1 Gold clothes: * dress - 1 * t-shirt - 1 * boxers - 1 White clothes: * briefs - 1 * tanktop - 1

Input	Output
4 Red -> hat Red -> dress,t-shirt,boxers White -> briefs,tanktop Blue -> gloves White tanktop	Red clothes: * hat - 1 * dress - 1 * t-shirt - 1 * boxers - 1 White clothes: * briefs - 1 * tanktop - 1 (found!) Blue clothes: * gloves - 1

Input	Output
5 Blue -> shoes Blue -> shoes,shoes,shoes Blue -> shoes,shoes Blue -> shoes Blue -> shoes,shoes Red tanktop	Blue clothes: * shoes - 9

## 10. Shellbound

Vladi is a crab. Crabs are scared of almost anything, which is why they usually hide in their shells. Vladi is a rich crab though. He has acquired many outer shells, in different regions, in which he can hide – each with a different size.

However, it is really annoying to look after all your shells when they are so spread out. That is why Vladi decided to **merge all** shells in **each** region, so that he has **one big shell** for **every region**. He needs your help to do that.

You will be given several input lines containing a **string** and an **integer**, separated by a **space**. The **string** will represent the **region's name**, and the **integer** – the shell in the **given region**, **size**.

You must store all shells in their corresponding regions.

If the region **already exists**, add the **new shell** to it. Make sure you have **NO** duplicate shells (shells with **same size**).

Vladi doesn't like shells to have the same size.



When you receive the command “**Aggregate**”, you must stop reading input lines, and you must print **every region**, **all of the shells** in that region, and the **size** of the **giant shell** after you’ve merged them in the following format:

**{regionName} -> {shell 1, shell 2..., shell n...} ({giantShell})**

The giant shell size is calculated when you **subtract** the **average** of the shells from the **sum** of the shells.  
Or in other words: **(sum of shells) - ((sum of shells) / (count of shells))**.

## Constraints

- All numeric data will be represented with **integer** variables in **range** [0...1.000.000.000].

## Examples

Input	Output
Sofia 50 Sofia 20 Sofia 30 Varna 10 Varna 20 Aggregate	Sofia -> 50, 20, 30 (67) Varna -> 10, 20 (15)
Sofia 2 Sofia 1 Plovdiv 100 Plovdiv 50 Aggregate	Sofia -> 2, 1 (2) Plovdiv -> 100, 50 (75)