

Guide Template

A starter for single-document beginner-guide PDFs — exercising every styled element so the verify harness has surface area to check.

Welcome

This placeholder guide is shipped with `guide-template`. It exists for two reasons:

1. The build pipeline has something to render before you replace it with your own content.
2. Every styled element in `style.css` is exercised at least once, so the verify harness's per-pixel diff catches any future regression to those rules.

Edit `guide.md` to write your own guide. Run `make` to render the PDF. Run `make verify` to confirm a rebuilt PDF matches the committed `baseline.pdf`.

What this section is for

This is an `h2` heading. The verify harness will notice if its color, weight, or margin changes between renders.

And this is an `h3`

Used for subsections within a section. Smaller than `h2`, same family.

You can use **bold**, italic, and `inline code` in paragraphs. Lists work too:

- Unordered bullet one
- Unordered bullet two with `code`
- Unordered bullet three with **bold**

And ordered lists:

1. First step
2. Second step
3. Third step

Tables

Pipe tables get the template's table styling — blue header, alternating row tint, thin gray borders.

Element	Source markup	Renders as
Heading	# Title	<h1>
Callout	<div class="callout warn">	warning box
Exercise	<div class="exercise">	green-bordered box
Diagram	<pre class="diagram">	monospace panel

Fenced code blocks

```
$ make
$ make verify
$ make baseline
```

Code blocks render in a light gray panel with Courier-family monospace.

Blockquotes

A blockquote renders with a left border and slightly muted italic text. Use it for pull-quotes, source attributions, or short asides that don't warrant a full callout.

Callouts

The template knows three callout variants.

Warning Amber background, orange border, bold-orange "Warning" header. Use for genuinely dangerous operations.

Tip Green tint with a green left bar. Use for advisory content that isn't quite a warning.

A blue accent callout has no bold header — just a light-blue background with a blue left bar. Good for mental-model notes.

Exercise boxes

Exercises render in a green-bordered box with the title strip on top.

Exercise 1 — Hello world

Run `make` from this directory. Confirm `guide-template.pdf` appears at the repo root. You should see this exact text rendered in the green box.

ASCII diagrams

The `<pre class="diagram">` element renders ASCII art in a tan-bordered monospace panel, sized to its content.

```
guide.md --pandoc--> HTML --transforms?--> HTML' --WeasyPrint--> PDF
                                     |
                                     v
                                qpdf canonicalize
                                     |
                                     v
                                guide-template.pdf
```

Section after a forced page break

The `<div class="page-break"></div>` element forces a page break before this section. The verify harness checks page count as well as content, so this forced break is exercised by the page-count check too.

More content here

Any text you put on this page lives on its own physical page in the PDF, separated from the prior section by the forced break.

How verification works

`make verify` runs `verify_pdf.py` against the committed `baseline.pdf`. Three checks at zero tolerance:

1. **Page count** via `pdftinfo` — fails if the PDFs disagree on page count.
2. **Text content** via `pdftotext -layout` — fails on any text difference, with a first-50-lines unified-diff snippet.
3. **Per-page pixel** via `pdftoppm + ImageMagick compare -metric AE` — fails if any pixel differs.

When `verify` fails, per-page diff PNGs land in `verify-diff/page-NN.png` so you can see what changed.

If you change source intentionally, the workflow is: `edit` → `make` → eyeball the PDF → `make baseline` → `commit baseline.pdf` together with the source change in **one** commit. Splitting them causes the version stamp to disagree between commits and triggers spurious `verify` failures.