

Local development / run instructions — Switch It

Accurate setup instructions for this repository. **No secret values** are included.

Prerequisites

- Node.js (compatible with Next.js 16; use a current LTS)
- npm
- Git
- A Supabase project (cloud) **or** local Supabase CLI workflow you already use for this repo
- Optional: Supabase CLI (`npx supabase`) for `db push`

Clone

```
git clone https://github.com/rotemkap10/switch-it.git
cd switch-it
```

GitHub repository:

```
https://github.com/rotemkap10/switch-it
```

Install dependencies

```
npm install
```

Environment variables

Copy the example file (tracked in git; names only, no secrets):

```
cp .env.example .env.local
```

`.env.example` currently lists:

```
NEXT_PUBLIC_SUPABASE_URL=
NEXT_PUBLIC_SUPABASE_PUBLISHABLE_KEY=
NEXT_PUBLIC_MAPTILER_API_KEY=
NEXT_PUBLIC_CARIMAGES_API_KEY=
```

Also used by the app (set in `.env.local` as needed):

Name	Required for	Why
------	--------------	-----

NEXT_PUBLIC_SUPABASE_URL	Almost everything	Supabase project URL
NEXT_PUBLIC_SUPABASE_PUBLISHABLE_KEY	Almost everything	User-scoped Supabase key (RLS)
NEXT_PUBLIC_MAPTILER_API_KEY	Maps + geocoding	MapLibre style + MapTiler geocoding
NEXT_PUBLIC_CARIMAGES_API_KEY	Vehicle catalog images	Public CarImages JS-loader key (generic fallback if missing)
NEXT_PUBLIC_PWA_DEV=true	Optional	Enable service worker during local next dev

Never put `SUPABASE_SERVICE_ROLE_KEY` in a `NEXT_PUBLIC_` variable.

Do not commit `.env.local`.

Auth — Confirm email (required for new accounts)

Switch It expects Supabase Auth **Confirm email** to be enabled so new registrations must verify before entering the app.

Local (`supabase/config.toml`):

```
[auth.email]
enable_confirmations = true
```

After changing this, restart local Supabase (`npx supabase stop && npx supabase start`) so Auth picks it up. In-app Mailpit / Inbucket (or your local SMTP) receives confirmation messages.

Production (Supabase Dashboard — manual):

1. Authentication → Providers → Email → enable **Confirm email**.
2. Authentication → URL configuration:
 - **Site URL** = your production app origin (e.g. `https://switch-it-wine.vercel.app`)
 - **Redirect URLs** include the app origin wildcard if used (e.g. `https://switch-it-wine.vercel.app/**`) — that already covers `/auth/callback` and `/auth/reset-password` . Explicit `/auth/callback` entries are fine too for preview origins.
3. Optional: customize the **Confirm signup** email template; keep `{{ .ConfirmationURL }}` so users land on `/auth/callback` .
4. Optional: customize the **Reset password** email template the same way (`{{ .ConfirmationURL }}`). No extra redirect URL is required when the wildcard already covers the app.

Signup + existing emails: With Confirm email on, production Auth often returns a successful-looking `signUp` response for an address that already has an account (anti-enumeration). Local GoTrue sometimes returns `User already registered` instead. The app only shows the hard “already exists” message when that explicit error appears; otherwise it uses the neutral Check your email UI (“*Check your inbox for a verification link...*” + “*Already registered... Sign in instead.*”).

Forgot password: Login → `/forgot-password` → Supabase `resetPasswordForEmail` with `redirectTo = {origin}/auth/callback/recovery` . Supabase PKCE often drops extra query params

from `redirectTo` , so recovery uses a dedicated callback route instead of relying on `?next=` . After the email link, the recovery callback exchanges the PKCE code and always sends the user to `/auth/reset-password` . Neutral success copy never discloses whether the email exists.

No `npx supabase db push` is required for this Auth setting alone.

Auth — Password policy

Production Dashboard password policy should require:

- minimum **8** characters
- uppercase + lowercase + digit + symbol (`lower_upper_letters_digits_symbols`)

Local `supabase/config.toml` mirrors that (`minimum_password_length = 8` , `password_requirements = "lower_upper_letters_digits_symbols"`). The app validates the same rules for **Create Account** and **Set new password** (Forgot Password) via `src/lib/auth/password-policy.ts` ; **Supabase Auth remains the final enforcer**. Login does **not** apply this policy locally.

Restart local Supabase after changing password settings in `config.toml` .

Supabase setup / migrations

1. Create or link a Supabase project.
2. Apply migrations with your linked workflow, for example:

```
npx supabase db push
```

Migrations live in:

```
supabase/migrations/
```

Important: product timing/reclaim behavior depends on **latest** migrations being applied on the remote database.

Edge Functions under `supabase/functions/` include **handoff-seeker-location** , which is required for **web and native** live location (seekers POST GPS here). Deploy after migrations:

```
npx supabase functions deploy handoff-seeker-location
```

Without this function, publish/claim/complete still work, but the publisher will not receive a live seeker marker. Experimental push paths also live under `supabase/functions/` .

Development server

```
npm run dev
```

Open the local URL Next prints (typically `http://localhost:3000`).

Quality commands

From `package.json` :

```
npm run lint
npm run test:run
npm run build
```

Useful related scripts:

```
npm run test          # Vitest watch
npm run test:watch
npm run start          # production server after build
```

Production build (local verification)

```
npm run build
npm run start
```

Deployment notes (submission)

Assignment requires:

1. **Live Vercel URL:** <https://switch-it-wine.vercel.app>
2. **GitHub** repository: <https://github.com/rotemkap10/switch-it>
3. These local instructions
4. Short env explanation (table above)

A Next.js app on Vercel does **not** require a `vercel.json` for this assignment. Deploy with the standard Next.js Vercel integration and set the same `NEXT_PUBLIC_*` variables in the Vercel project.

After deploy, confirm:

- the linked **production Supabase** project is the one the app uses
- latest migrations are applied (`npx supabase db push`), including security hardening (`20260823100000` through `20260823120000`)
- Edge Function `handoff-seeker-location` is deployed (required for web live location)

Native / Capacitor (optional)

Not required for the core web course demo. See `native/README.md` if discussing the native pilot.

Repository references

- `package.json`
- `.env.example`
- `README.md` (Local setup / Environment variables)
- `supabase/migrations/`
- `next.config.ts`
- `src/lib/supabase/client.ts` , `src/lib/supabase/server.ts`