

EEE4113F Literature Review



Prepared by:

Robert Dugmore
Mathapelo Morobi
Ruviel Perumal
Thiyashan Pillay

Prepared for:

EEE4113F
Department of Electrical Engineering
University of Cape Town

March 17, 2024

Declaration

1. I know that plagiarism is wrong. Plagiarism is to use another's work and pretend that it is one's own.
2. I have used the IEEE convention for citation and referencing. Each contribution to, and quotation in, this report from the work(s) of other people has been attributed, and has been cited and referenced.
3. This report is my own work.
4. I have not allowed, and will not allow, anyone to copy my work with the intention of passing it off as their own work or part thereof.



Robert Dugmore



Mathapelo Morobi



Ruviel Perumal



Thiyashan Pillay

March 17, 2024

Date

Contents

1	Problem statement	1
2	Literature Review	2
2.1	Introduction	2
2.2	Starlings and the need to monitor nest environments	2
2.2.1	Current monitoring of Red-Winged starlings	2
2.2.2	Starlings and nesting	2
2.3	An overview of existing full camera trap systems	2
2.3.1	Existing camera trap modules and technologies	3
2.3.2	Challenges and limitations of consumer camera traps	3
2.4	Data transmission techniques	4
2.4.1	Comparison of wired and wireless data transmission	4
2.5	Computing hardware	5
2.5.1	Single board computers and microcontroller hardware	5
2.5.2	Software for computing hardware	6
2.6	Sensing hardware	6
2.6.1	Motion detection	6
2.7	Image or video capturing hardware	7
2.7.1	Choice of camera	7
2.7.2	Night or low-light visibility	8
2.8	Power supply	8
2.8.1	Power sources for sensors situated in an impractical setting	8
2.8.2	Battery powered supply	9
2.8.3	Solar-powered supply	9
2.8.4	Power-saving operations for sensors situated in an impractical setting	9
2.9	Camera trap deployment in urban settings	9
2.9.1	Survey Studies	9
2.9.2	Camera Trap Deployment Strategies	10
2.9.3	Maintenance Challenges and Solutions	10
2.9.4	Weather Resistance Strategies	10
2.9.5	Theft Prevention Measures	11
2.9.6	Impact on Parental Behavior	11
2.10	Conclusion	11
	Bibliography	12

Chapter 1

Problem statement

Sally, an academic researching starlings on UCT campus, requires remote visual surveillance of the birds for an extended period of time without human intervention and without risk of damage or theft of hardware.

Chapter 2

Literature Review

2.1 Introduction

This literature delves into previous research articles about wildlife monitoring and related fields to better understand the approach that needs to be taken to design an effective camera module. This review will look into existing solutions (both successes and failures). Data acquisition methods were also investigated. Integration of camera traps with IoT, sensing and power supply requirements were researched as well as looking into camera traps being situated in an urban setting with the risk of theft or damage from weather conditions.

2.2 Starlings and the need to monitor nest environments

2.2.1 Current monitoring of Red-Winged starlings

Verstraeten et al. explain that the ‘monitoring of birds has widespread potential in numerous applications in ecology, climatology, and avian related zoonosis/infections such as avian influenza.’ [1]. Researchers from the Fitzpatrick Institute of Ornithology indicated a desire for a remote-monitoring solution for Red-Winged starling nests [2]. Their existing solution is a GoPro camera on a pole, which they hold up to the nest to try and view what is happening [2]. This allows only limited amounts of data to be gathered, and disturbs the birds [2].

2.2.2 Starlings and nesting

According to Ricklefs [3], a starling bird can reach full body growth in approximately 20 days and an adult starling can reach a body mass of 79 grams. [3] further details that a newly hatched starling chick can weigh 5.27 grams and can be one of up to 18 chicks in brood in the starling nest.

2.3 An overview of existing full camera trap systems

This section details a review of existing solutions for camera trap systems in general. There are numerous studies conducted on how effective different solutions are in both wildlife research and related fields that require camera sensing systems.

2.3.1 Existing camera trap modules and technologies

Swann et al. [4] argue that while choosing from a selection of camera traps designed for generalised use cases may be complex, it becomes essential to refine a module designed for nest ecology researchers. Meek et al. [5], emphasise the key elements such as cost effectiveness, speed, space and weight saving, usability, and versatility as being critical in developing an efficient wildlife surveillance system.

Recent studies shed light on the ongoing research to improve camera trap systems used in wildlife research by addressing common problems associated with detection reliability, data recording, and remote communication capabilities, while also revealing challenges in battery longevity, weight, and cost-effectiveness. Nazir, Sajid, et al. [6] introduced the “WiseEye” camera trap solutions, which aimed to address the frustrations of existing camera systems. The “WiseEye” system, consisting of a Raspberry Pi and passive infrared sensors, promised and showed an improvement in detection reliability, reduced data cataloguing time, and remote communication capabilities. With this solution came many drawbacks such as lower power efficiency, weight, and cost. This indicates potential areas that can be simplified and optimised to suit nest ecology research. Rico-Guevara et al. [7] contributed by confirming the importance of having a PIR sensor in their study that involved capturing pictures of hummingbirds. They also had issues when it came to power consumption and weight. This is a recurring issue among existing designs. Green, Sian, et al. [8] explored the integration of artificial intelligence with existing camera trap solutions, in a bid to offer advancements in data processing and analysis. This brought upon issues such as increased power consumption and greater computational requirements that would only be fixed if the whole system is redesigned.

In a study regarding nest predation, Ribeiro-Silva et al. [9] again stress the importance of infrared cameras but warn against positioning them too far away from the nest to reduce overexposure of the captured footage.

Wireless data transmission and automation of tasks are emerging as important requirements in modern camera trap solutions, according to Glover-Kapfer et al. [10]. However, they make note of the fact that the availability of good camera traps, i.e., those that are relevant to the researchers’ requirements, is often dictated by the novelty task at hand, which may limit the available options for studies in nest ecology.

2.3.2 Challenges and limitations of consumer camera traps

Addressing operational challenges and efficiency issues in existing solutions is vital when it comes to designing effective wildlife surveillance solutions, as indicated by Ribeiro-Silva et al. [9], who identifies the various shortcomings in existing solutions and proposed strategies to improve them. In the pursuit of effective nest monitoring, [9] found that problems like insufficient storage, wind displacement, weather damage, and false detection of animals outside the intended field of view led to poor efficiency, loss of data, and missed predation lists. Suggested improvements from [9] include camera positioning, increased storage, regular inspection, and the use of more than one camera to progressively monitor activity around the nest.

[11] suggest that existing camera trap modules may not meet the standards that are expected for scientific research and conservation. [11] stresses the necessity of laying the groundwork to establish

hardware standards tailored to each study, challenging the feasibility of adopting off-the-shelf modules for diverse research tasks.

A Bushnell TrophyCam, which captures both videos and photos, was found to provide intuitive data for distinguishing between different birds within the same species by analysing their behaviour from short video intervals [10]. Challenges experienced involved low detection efficiencies with motion sensors and a need for managing the video lengths to optimise data storage [9].

Weingarth et al. [12] tested 6 different camera modules to evaluate their usefulness in capture and recapture sampling. They found that no digital camera is perfect for any application. The only camera that suited all the needs of the desired camera module for the project was the Bushnell TrailScout 119935, with infrared capabilities and decent imaging capabilities [12]. This study indicates that consumer camera trap modules can have shortcomings that limit their application in research. Any camera must be carefully selected based on the needs of the specific research.

2.4 Data transmission techniques

2.4.1 Comparison of wired and wireless data transmission

Regardless of the improvements made concerning wireless communication capabilities, wired communications have served as the industry standard for communication protocol. Huynh’s study on general communication protocols [13] sheds light on several advantages of wired communication protocols. These include the implementation of parallel data transfer methods, where the speed of transmission can be adjusted by the number of parallel cables, only if the transfer rate per cable is maintained and the cables are shielded to minimise the effect of cross-talk. [13] also made note of differential lines being used instead of single-ended lines, to improve data transmission speeds, lower the power consumption and reduce the electromagnetic interference, which is all pertinent to the scope of the design.

Gula et al. suggest that wired solutions may introduce problems concerning cable management and animal interference. [14] details how different coaxial cable thicknesses are required to transmit different data types over a set length without any additional amplification, which would result in a cluster of cables running between subsystems. [14] also noted concerns that animals, such as rats, would chew up the cables over time.

Wireless data transmission has become a promising alternative, given the challenges of wired data transmission. Adsumilli, C et al. mention that ‘error resilience and error concealment were the most important aspects of current research for successful realization of transmission and reception of image/video signals over bandwidth limited fading wireless networks/channels.’ [15]. The successful video coding standards used were H.263 and MPEG-4, which were implemented to achieve error control for both reception and transmission of video in error prone environments [15].

Li et al. [16] suggest that implementing a wireless communication system will present a more cost-effective solution for wildlife research. [16] further stipulates that deploying a wireless system will reduce the overhead that comes with maintenance when the connections get damaged.

[15] H.263 and MPEG-4 encoding standards, which were implemented to achieve error control for both

reception and transmission of video in error prone environments [15].

In exploring alternative wireless connectivity solutions for low-powered IoT devices, Peng, Y. et al. [?] put forward a solution that is suitable for long-range transmission of low-rate data only. The device in the study is known as PLoRa, which allows for long range data connectivity (wireless) without needing battery power. The design consists of a ‘low-power packet detection circuit with novel blind chirp modulation and harmonic cancellation techniques’ [?]. While this solution is unsuitable for video or image transmission, the device will allow the user to wirelessly obtain logs on the status of the module even when battery power has run out. [?] reported a maximum packet detection range of 50 m, making it a possible solution for smaller data transmission needs.

Conversations with the researchers looking to monitor Red-Winged Starlings indicated that WiFi-based communication may be hampered by a lack of WiFi connectivity at many of the red-winged starling nesting sites [2].

2.5 Computing hardware

2.5.1 Single board computers and microcontroller hardware

Single-board microcomputers can be a valuable tool for biological research. Jolles argues that ‘[T]he Raspberry Pi [is] a great research tool that can be used for almost anything. This can range from ... video recording of laboratory experiments, to long-term field measurement stations’ [17]. The wide versatility of a device like the Raspberry Pi makes it ideal for the implementation of customisable video monitoring solutions. Jolles [17] also argues that the small footprint of the Raspberry Pi aids in its use in research, and versatile options for the provision of power allow it to be used with minimal human intervention over long periods. These benefits align strongly with the needs of the project at hand, further emphasising the Raspberry Pi as a viable platform around which to base the project.

Data storage and retrieval have been identified as a key limitation in the application of camera traps to monitor Red-Winged starlings [2]. Prinz et al. [18] implemented a project for video surveillance of Acorn Woodpecker nests. They justify the Raspberry Pi as a useful resource owing to its small size and variety of storage and connectivity options. The particular project uses a WiFi connection to upload footage to cloud storage on Google Drive. They further identify that the onboard SD card has sufficient storage for around 3 days’ worth of footage, but also identify the strength of the Raspberry Pi in its ability to leverage 3G/4G connectivity or external flash drives and hard drives as alternative means of data storage. The variety of footage collection and/or storage options makes it likely that a suitable option can be found in the case of Red-Winged starlings.

[17] acknowledges the existence of other microcomputer systems, and argues that the use of these systems is hampered by a lack of hardware and software maintenance, alongside generally poorer user support compared to the widespread Raspberry Pi.

Microcontrollers, including options from ST Microelectronics, Espressif, and Atmel offer an alternative to full microcomputers. Camacho et al. [19] discuss a custom design based on the ATMEGA2650 microcontroller. They use a customised circuit design to allow for advanced power management, to limit power draw. [19] further describe difficulties with using commonly available prototyping boards, which

are not necessarily as capable of achieving power draw requirements as custom circuit designs. Cardoso et al. [20] implement a remote visual surveillance based on an ESP32 microcontroller, demonstrating a successful microcontroller-based implementation under slightly different circumstances to [19]. [17] also identifies that microcontrollers may have even less stringent power requirements than the Raspberry Pi and argues that simple, repetitive tasks are often better suited to microcontrollers. Microcontroller based solutions may offer more customisability and lower costs compared to microcomputer solutions such as the Raspberry Pi.

[17] also identifies that microcontrollers and microcomputers can be used in tandem in some instances. This would allow the benefits of both systems to be realised, such as allowing for exceptionally low power draw the majority of the time, but allowing for the advanced connectivity options of the Raspberry Pi when required.

Both microcontrollers and single-board microcomputers have varying prices, typically depending on processing power and available peripherals. Local market prices may make higher-end devices too costly to be viable, and microcontrollers are generally significantly cheaper than microcomputers.

2.5.2 Software for computing hardware

Raspberry Pi computers allow for ‘user-friendly programming capabilities’ [17], with an operating system based on Debian Linux, which allows for Python programming [18]. This allows for easy control of the Raspberry Pi’s GPIO pins. [19] note their appreciation of the ATMEGA2650’s integration with Arduino. ESP32 system can also be coded using the Arduino framework, and options from ST Microelectronics are typically coded in C. While some embedded software frameworks may be easier to use than others, most available options should not substantially hamper the development of the system.

2.6 Sensing hardware

2.6.1 Motion detection

Meek and Pittet [5] identify that ‘Motion detection is of prime importance for any camera trap to be effective’. Importantly, Rovero et al. [21] discuss that the camera field of view does not correspond directly to the detection zone. Motion detection is often a separate process from video or image recording, and must be thoroughly considered to make for a viable solution.

Meek and Pittet [5] identify that most commercial camera traps use passive infrared (PIR) sensors to detect the motion of wildlife, but are prone to false detections, resulting in images that do not feature any wildlife. The sensitivity of a PIR motion detector ‘depends on many factors, including the distance of the moving target, the temperature differential, the size of the animal, its speed and background light.’ [5]. Rovero et al. [21] add to this by identifying that PIR sensors can be triggered by pockets of hot air or vegetation. Meek et al. [22] support a similar conclusion, indicating that ‘Where the temperature differential between the background and target is low, some sensors may be incapable of detecting target animals right in front of the camera’. Yun [23] explains that they work based on the principle of pyroelectricity, where certain materials generate a voltage when exposed to changes in temperature. [24] details that PIR sensors have found extensive use across diverse fields,

particularly in the creation of intelligent settings like healthcare facilities, smart energy systems, and security setups. The prevalence of PIR-based motion detection seems to indicate that it is a workable and useful solution, but evidence shows that there are also difficulties associated with the technology.

Rico-Guevara and Mickley [7] chose to use PIR motion sensors because they ‘were cheap and easy to deploy, and successfully detected hummingbirds.’ Their study found that the detection of even the smallest species of hummingbirds was adequate for their application. They chose to combat the issue of false detections by intentionally positioning the sensors away from objects that could trigger unwanted detections and mitigated the consequently limited scope of individual sensors by triggering from multiple differently positioned sensors. A separate standalone trigger was also developed which included an adjustable sensitivity, allowing ‘fine tuning by optimizing the trade-off between increased sensitivity and false positives’ [7].

Welbourne et al [25] identify that the functioning of PIR sensors is often misunderstood, leading to ‘flawed inferences or expectations of camera performance.’ A thorough understanding of PIR sensors would help in the development of a robust and well-functioning solution.

Rovero et al. [21] discuss that older commercial camera traps from the 1980s were triggered by a break in an infrared beam. However, newer models come in a ‘self-contained package including sensors and camera.’ Hobbs et al. propose a solution for ‘amphibians, reptiles, small mammals, and large invertebrates’ [26] using similar technology. However, the solution at hand appears to be too large to viably be integrated into a bird nest, and the system requires the animals to walk over a threshold near the beam, which makes it difficult to apply to birds that fly.

Prinz et al. [18] use an alternative technique that detects changes in the pixels from the camera output. This was achieved using the open-source program motion-MMAL. This alternative technique minimises the hardware requirements of the system.

According to Amusa [24], there are three technologies are used in practice for motion detection; they are Passive InfraRed (PIR), ultrasonic and audio sensors. Ultrasonic and audio sensors do not appear to be widespread and are thus not thoroughly considered in this investigation.

2.7 Image or video capturing hardware

2.7.1 Choice of camera

[17] notes that the Raspberry Pi Foundation offers two cameras for the Raspberry Pi - the v2 and HQ cameras, both of which connect to the Raspberry Pi via its Camera Serial Interface. Both cameras deliver the same video performance of 1080p 30fps, though the HQ camera is capable of higher-resolution still image photography, at 4056×3040 pixels, as opposed to 3280×2464 pixels [17]. Additionally, a version of the v2 board for infrared photography is available, and the HQ board can be used for infrared photography by manually removing its infrared filter. [17]. Senthilkumar et al. [27] discuss the use of a similar Raspberry Pi NOIR camera. This is likely the first version of infrared enabled v2 board discussed by [17]. [27] that the board ‘[I]s able to deliver clear 5MP resolution image, or 1080p HD video recording at 30fps.’ [27], and further, discusses that the sensor’s lack of an infrared filter makes it ideal for infrared or low-light conditions. [18] sites [27] to justify the use of the same camera module in

the case of bird nest monitoring. Camera modules from the Raspberry Pi Foundation appear as an enticing option for monitoring of Red-Winged Starling nests, especially if paired with a Raspberry Pi.

Many third-party camera modules for the Raspberry Pi exist, with varying capabilities [17]. The local market includes numerous options, alongside many options for use with microcontrollers, at varying price points.

[7] use a mechanical system to trigger a camera unit that would normally be operated by hand. This allowed the researchers to capture high-speed footage in good quality [7]. However, top-range handheld cameras can be prohibitively expensive and may not be as robust as integrated electronic modules.

2.7.2 Night or low-light visibility

Aguiar-Silva et al. [28] motivate for the use of infrared sensors because of the prevalence of nocturnal predators that attack the nesting areas of birds. A low-light visibility system makes it easier to conduct thorough research on nest activity that may only happen in low-light conditions.

Rovero et al. [21] stipulate that camera trap modules sometimes have infrared or white LED flash, to enable camera visibility at night. Flash technology is not generally needed when daylight can provide the necessary visibility for photography.

According to Meek et al. [22], infrared flash tends to be less disruptive to wildlife than incandescent white flash, alongside exhibiting superior power efficiency and faster overall camera trap trigger speeds. However, [22] also explained that infrared flashes are ‘are often in grey-scale ... or may have a reddish-pink tinge.’, whereas white flashes allow for colour images, which is sometimes useful for research. [22] identifies that LED technologies for white flashes can mitigate concerns about power draw and trigger speed. At the time of publication of [22], only one commercial camera trap module used LED flash, but LED technology has since become much more accessible, making it a much more viable solution than it previously was.

Conversations with the researchers working with Red-Winged starlings [2] indicated that infrared flash may be useful for night-time visibility of nests, or for enhanced visibility of some nesting sites that are very sheltered from daylight.

2.8 Power supply

Power plays an integral part, by supplying the entire module with the necessary power to run efficiently and adequately. This section aims to determine the best possible approach to make the power submodule of the design as optimal as it can be.

2.8.1 Power sources for sensors situated in an impractical setting

Various power sources can be used, specifically when it comes to remote sensors for low powered consumption applications. Dewan et al. [29] explain that one of the main issues with deploying sensors in remote or impractical environments is the life span of these sensors which is largely dependent on the power supply it is connected to. With this in mind, we can look into the various power sources that could be suitable for the design that will follow.

2.8.2 Battery powered supply

Polleneli et al. [30] describe the success of using batteries to power their motherboard for their drone application. They further iterated that their design included ‘generating reliable and stable 3.3 V and 5 V DC voltage from two Panasonic 18650 batteries’ [30]. [30] also included fast charging. Camera trapping for Red-Winged starlings could utilise fast charging to make the power supply system more convenient for the researchers involved. Callebaut et al. [31] outline issues faced with batteries and their lifespans and how to lengthen their life. They further explained the different types of batteries and how the battery type can optimise the battery life. They stated, “Lithium Cobalt Oxide (LCO) and Lithium Polymer (LIPO) batteries are currently the most used rechargeable technologies” [31]. These batteries can be useful and go hand in hand with solar power supply.

2.8.3 Solar-powered supply

The popularity and extensive use of solar is explained through the statement, “Solar power is used for operating both ground and floating sensors; solar-powered sensors have been deployed in forests, on mountains, in deserts, on ocean surfaces, on islands, and in household and industrial buildings.” [29]. This supports the possibility of integrating solar power into the design to reduce the number of manual recharges of the battery required. Krejcar further supports the use of solar powered supply for remote sensors and explains that “It is possible to apply the solution from a lower voltage (lower sun intensity)” [32], this indicates that it will be able to charge the battery and operate on days that are not extremely sunny.

2.8.4 Power-saving operations for sensors situated in an impractical setting

Power consumption is an important aspect to think about when it comes to design and power-saving operations must be put into place to make the whole device more efficient. Some of these methods are to be studied and analysed below.

Harikrishnan and Sivagami [33] go into detail talking about how PIR sensors can be used to switch a system on and off depending on whether a sensor is giving a reading or not [5]. This design can be extremely useful in our design as it will switch the device on only when there is motion, hence reducing redundant recordings and saving power. Harsha and Kumar [34] further support this notion and show the justification for the use of power-saving through tests.

2.9 Camera trap deployment in urban settings

Camera traps are valuable tools for wildlife monitoring, but vandalism and theft pose significant challenges, resulting in financial losses, data losses and compromised data quality. Despite attempts to mitigate these risks by placing camera traps at greater heights, the impact on detection rates remains understudied [35], [36].

2.9.1 Survey Studies

Meek et al. [35] investigated the effect of camera trap height on predator detection in road-based surveys, monitoring stations were established with cameras positioned at both 0.9 m and 3 m above

ground level. Additionally, a pilot trial compared vertical and horizontal camera orientations for medium-sized mammal detection.

The results found from this study are as follows: Placement of cameras at greater heights significantly reduced detection rates for all species compared to lower placements. False triggers were more common at higher placements, decreasing data quality. Vertical camera placement also showed reduced detection rates, with overhanging limbs causing false triggers. Recommended deployment heights vary widely in existing literature, with limited empirical support and emphasis on the animal size and habitat. [35].

In summary, raising camera traps may seem like a solution to theft, but it compromises data quality and promotes false triggers [35]. Optimal camera trap height is critical for maximizing detection rates, and aligning with the size and passage of target animals. Further innovation is needed to address theft while preserving data integrity.

2.9.2 Camera Trap Deployment Strategies

Roland Kays et al. in [37] discuss the employment of Reconyx RC55 Camera traps known for their resilience in harsh rainforest conditions. Camera traps are strategically placed along trails or near water bodies to maximize animal detection. However, randomized deployments revealed biases in trap rates, with certain species exhibiting preferences for or avoidance of trail-side locations. Furthermore, challenging weather conditions, particularly during the rainy season, impact camera performance, necessitating mitigation strategies such as desiccant packets and preventative maintenance schedules [37].

2.9.3 Maintenance Challenges and Solutions

Despite advancements in camera design, maintenance remains a critical aspect of long-term monitoring projects and data quality [37]. Common issues include lens blurriness and circuitry failures due to humidity, prompting manufacturers to enhance sealants and coatings. Practices such as drying camera traps with dehumidifiers, inserting silica gel packets, and duct-taping seams minimize moisture infiltration, preventing equipment damage and malfunctions [10]. Regular inspection and servicing of components such as gaskets, contacts, and wires are essential, particularly in humid environments. Additionally, theft poses a potential threat to camera trap networks, underscoring the importance of discrete placement, visible flash mitigation, and security measures such as cable locks and informational signage. Furthermore, periodic inspections during site visits enable lens cleaning, hardware tightening, and battery replacement, ensuring uninterrupted data collection and equipment functionality.

2.9.4 Weather Resistance Strategies

Utilizing weather-resistant housings, such as the Pelican 1300 case, shields camera equipment from rain, dust, and moisture, prolonging its lifespan and functionality [37]. Incorporating natural materials and camouflage fabric helps obscure camera traps, minimizing wildlife disturbance and theft risk. Furthermore, the development of zinc rain covers and the application of black glue for waterproofing offer additional layers of protection against environmental elements [37], [10].

2.9.5 Theft Prevention Measures

Implementing security measures such as cable locks, padlocks, and GPS trackers like Apple AirTags deters theft and aids in equipment recovery. Discreet placement and camouflage techniques reduce the visibility of camera traps, minimizing the likelihood of detection and tampering. Additionally, strategic positioning of camera traps at elevated heights and on stable mounts mitigates theft risk while optimizing surveillance coverage [37].

2.9.6 Impact on Parental Behavior

Bolton et.al in [38] explores the crucial aspect of camera trap deployment and its potential to influence parental behaviour. Concerns have been raised regarding disturbances caused by camera installation, potentially affecting parental care and nest attendance. However, research findings indicate minimal disturbance to parent birds during camera installation, with installations typically completed within 15 minutes [38]. Furthermore, the use of long, camouflaged cables enables maintenance activities, such as battery and memory card replacement, without necessitating parental departure from nests. This suggests that camera traps can be utilized without significant disruption to parental behaviour, mitigating potential concerns surrounding disturbance [38].

2.10 Conclusion

In conclusion, the evolution of camera trap technology has significantly enhanced wildlife monitoring practices, providing researchers with versatile tools and methodologies to study animal behavior and ecological dynamics. The comparison between wired and wireless data transmission underscores the efficiency and adaptability of wireless solutions, offering seamless integration into diverse field environments. Moreover, advancements in computing hardware, such as single-board computers and microcontrollers, offer customizable platforms for data processing and management, further enhancing the versatility of camera trap systems. Motion detection, facilitated by passive infrared sensors (PIR), ensures accurate wildlife detection, while camera choices such as the v2 and HQ cameras offer high-resolution imaging capabilities crucial for detailed behavioral analysis. Strategies for night-time visibility through infrared and LED flash technologies, coupled with efficient power supply solutions like batteries and solar power, sustain prolonged deployments even in remote locations. Addressing challenges such as vandalism and theft in urban settings ensures uninterrupted data collection and equipment, while minimizing disturbance to wildlife and ecosystems. Overall, camera trap deployment remains pivotal in advancing our understanding of wildlife ecology and informing conservation efforts, highlighting the ongoing innovation and interdisciplinary collaboration driving the field forward.

Bibliography

- [1] W. W. Verstraeten, B. Vermeulen, J. Stuckens, S. Lhermitte, D. Van der Zande, M. Van Ranst, and P. Coppin, “Webcams for bird detection and monitoring: A demonstration study,” *Sensors*, vol. 10, no. 4, pp. 3480–3503, 2010. [Online]. Available: <https://www.mdpi.com/1424-8220/10/4/3480>
- [2] S. Hofmeyer and S. Cunningham, personal communication, Mar 2024.
- [3] R. E. Ricklefs, “Patterns of growth in birds,” *Ibis*, vol. 110, no. 4, pp. 419–451, 1968. [Online]. Available: <https://onlinelibrary.wiley.com/doi/abs/10.1111/j.1474-919X.1968.tb00058.x>
- [4] D. E. Swann, K. Kawanishi, and J. Palmer, *Evaluating Types and Features of Camera Traps in Ecological Studies: A Guide for Researchers*. Tokyo: Springer Japan, 2011, pp. 27–43. [Online]. Available: https://doi.org/10.1007/978-4-431-99495-4_3
- [5] P. Meek and P. A., “User-based design specifications for the ultimate camera trap for wildlife research,” *CSIRO Wildlife Research*, vol. 39, no. 8, 12 2012.
- [6] S. Nazir, S. Newey, R. Irvine, F. Verdicchio, P. Davidson, G. Fairhurst, and R. van der Wal, “WiseEye: Next generation expandable and programmable camera trap platform for wildlife research,” *PLOS ONE*, vol. 12, no. 1, p. e0169758, 01 2017.
- [7] A. Rico-Guevara and J. Mickley, “Bring your own camera to the trap: An inexpensive, versatile, and portable triggering system tested on wild hummingbirds,” *Ecology and Evolution*, vol. 7, no. 13, pp. 4592–4598, 2017. [Online]. Available: <https://onlinelibrary.wiley.com/doi/abs/10.1002/ece3.3040>
- [8] S. Green, J. Rees, P. Stephens, R. Hill, and A. Giordano, “Innovations in camera trapping technology and approaches: The integration of citizen science and artificial intelligence,” *Animals*, vol. 10, no. 1, p. 132, 01 2020.
- [9] L. Ribeiro-Silva, D. Perrella, C. Biagolini-Jr, P. Zima, A. Piratelli, M. Schlindwein, P. Galetti Jr, and M. Francisco, “Testing camera traps as a potential tool for detecting nest predation of birds in a tropical rainforest environment,” *Zoologia*, vol. 35, pp. 1–8, 05 2018.
- [10] P. Glover-Kapfer, C. Soto-Navarro, and O. Wearn, “Camera-trapping version 3.0: current constraints and future priorities for development,” *Remote Sensing in Ecology and Conservation*, vol. 5, no. 3, pp. 209–223, 01 2019.
- [11] J. Ahumada, E. Fegraus, T. Birch, N. Flores, R. Kays, T. O’Brien, J. Palmer, S. Schuttler, J. Zhao, W. Jetz, M. Kinnaird, S. Kulkarni, A. Lyet, D. Thau, M. Duong, R. Oliver, and A. Dancer, “Wildlife insights: A platform to maximize the potential of camera trap and other passive sensor wildlife data for the planet,” *Environmental Conservation*, vol. 47, no. 1, pp. 1–6, 09 2019.

- [12] K. Weingarth, F. Zimmermann, F. Knauer, and M. Heurich, “Evaluation of six digital camera models for the use in capture-recapture sampling of Eurasian lynx (*Lynx lynx*),” *Waldökologie, Landschaftsforschung und Naturschutz*, vol. 13, pp. 87–92, 2013.
- [13] A. Huynh, “Study of wired and wireless data transmissions,” Ph.D. dissertation, Linköping University Electronic Press, 2010.
- [14] R. Gula, J. Theuerkauf, S. Rouys, and A. Legault, “An audio/video surveillance system for wildlife,” *European Journal of Wildlife Research*, vol. 56, pp. 803–807, 10 2010.
- [15] C. Adsumilli and Y. H. Hu, “Adaptive wireless video communications: Challenges and approaches,” in *Proceedings of International Workshop on Packet Video*, 2002, pp. 1–11. [Online]. Available: https://www.researchgate.net/profile/Yu-Hen-Hu/publication/228462595_Adaptive_wireless_video_communications_Challenges_and_approaches/links/542eb0f70cf29bbc126f3dcd/Adaptive-wireless-video-communications-Challenges-and-approaches.pdf
- [16] N. Li, B. Yan, G. Chen, P. Govindaswamy, and J. Wang, “Design and implementation of a sensor-based wireless camera system for continuous monitoring in assistive environments,” *Personal and Ubiquitous Computing*, vol. 14, pp. 499–510, 09 2010.
- [17] J. W. Jolles, “Broad-scale applications of the Raspberry Pi: A review and guide for biologists,” *Methods in Ecology and Evolution*, vol. 12, no. 9, pp. 1562–1579, 2021. [Online]. Available: <https://besjournals.onlinelibrary.wiley.com/doi/abs/10.1111/2041-210X.13652>
- [18] A. C. B. Prinz, V. K. Taank, V. Voegeli, and E. L. Walters, “A novel nest-monitoring camera system using a Raspberry Pi micro-computer,” *Journal of Field Ornithology*, vol. 87, no. 4, pp. 427–435, 2016. [Online]. Available: <https://onlinelibrary.wiley.com/doi/abs/10.1111/jfo.12182>
- [19] L. Camacho, R. Baquerizo, J. Palomino, and M. Zarzosa, “Deployment of a set of camera trap networks for wildlife inventory in western Amazon rainforest,” *IEEE Sensors Journal*, vol. 17, no. 23, pp. 8000–8007, 2017.
- [20] B. Cardoso, C. Silva, J. Costa, and B. Ribeiro, “Internet of things meets computer vision to make an intelligent pest monitoring network,” *Applied Sciences*, vol. 12, no. 18, 2022. [Online]. Available: <https://www.mdpi.com/2076-3417/12/18/9397>
- [21] F. Rovero, F. Zimmermann, D. Berzi, and P. Meek, “Which camera trap type and how many do i need? a review of camera features and study designs for a range of wildlife research applications,” *Hystrix, the Italian Journal of Mammalogy*, vol. 24, no. 2, pp. 148–156, 2013. [Online]. Available: <https://doi.org/10.4404/hystrix-24.2-8789>
- [22] P. D. Meek, P. Fleming, and G. Ballard, *An introduction to camera trapping for wildlife surveys in Australia*. Invasive Animals Cooperative Research Centre Canberra, Australia, 2012.
- [23] J. Yun and M.-H. Song, “Detecting direction of movement using pyroelectric infrared sensors,” *Sensors Journal, IEEE*, vol. 14, pp. 1482–1489, 05 2014.

- [24] K. Amusa, A. Adewusi, O. Nuga, A. Olanipekun, and O. Adewale, "Pyro-electric infrared sensor-based intrusion detection and reporting system," *Afr J. of Comp & ICTs*, vol. 8, no. 1, pp. 91–98, 2015.
- [25] D. J. Welbourne, A. W. Claridge, D. J. Paull, and A. Lambert, "How do passive infrared triggered camera traps operate and why does it matter? breaking down common misconceptions," *Remote Sensing in Ecology and Conservation*, vol. 2, no. 2, pp. 77–83, 2016. [Online]. Available: <https://zslpublications.onlinelibrary.wiley.com/doi/abs/10.1002/rse2.20>
- [26] M. T. Hobbs and C. S. Brehme, "An improved camera trap for amphibians, reptiles, small mammals, and large invertebrates," *PLOS ONE*, vol. 12, no. 10, pp. 1–15, 10 2017. [Online]. Available: <https://doi.org/10.1371/journal.pone.0185026>
- [27] G. Senthilkumar, K. Gopalakrishnan, and V. S. Kumar, "Embedded image capturing system using Raspberry Pi system," *International Journal of Emerging Trends & Technology in Computer Science*, vol. 3, no. 2, pp. 213–215, 2014. [Online]. Available: <https://picture.iczhiku.com/resource/paper/wyidrGyFuiSGfbbx.pdf>
- [28] F. Aguiar-Silva, O. Jaudoin, T. Sanaiotti, G. H. Seixas, S. Duleba, and F. Martins, "Camera trapping at harpy eagle nests: Interspecies interactions under predation risk," *Journal of Raptor Research*, vol. 51, pp. 72–78, 03 2017.
- [29] A. Dewan, S. U. Ay, M. N. Karim, and H. Beyenal, "Alternative power sources for remote sensors: A review," *Journal of Power Sources*, vol. 245, pp. 129–143, 2014. [Online]. Available: <https://www.sciencedirect.com/science/article/pii/S0378775313010884>
- [30] T. Polonelli, Y. Qin, E. M. Yeatman, L. Benini, and D. Boyle, "A flexible, low-power platform for UAV-based data collection from remote sensors," *IEEE Access*, vol. 8, pp. 164 775–164 785, 2020.
- [31] G. Callebaut, G. Leenders, J. Van Mulders, G. Ottoy, L. De Strycker, and L. Van der Perre, "The art of designing remote IoT devices—technologies and strategies for a long battery life," *Sensors*, vol. 21, no. 3, 2021. [Online]. Available: <https://www.mdpi.com/1424-8220/21/3/913>
- [32] O. Krejcar and M. Mahdal, "Optimized solar energy power supply for remote wireless sensors based on IEEE 802.15.4 standard," Dec 2012. [Online]. Available: <https://www.hindawi.com/journals/ijp/2012/305102/>
- [33] R. Harikrishnan and P. Sivagami, "Intelligent power saving system using PIR sensors," in *2017 International conference of Electronics, Communication and Aerospace Technology (ICECA)*, vol. 2, 2017, pp. 573–577.
- [34] B. Harsha and N. Kumar G.N., "Home automated power saving system using PIR sensor," in *2020 Second International Conference on Inventive Research in Computing Applications (ICIRCA)*, 2020, pp. 1117–1121.
- [35] P. D. Meek, G. A. Ballard, and G. Falzon, "The higher you go the less you will know: placing camera traps high to avoid theft will affect detection," *Remote Sensing*

- in Ecology and Conservation*, vol. 2, no. 4, pp. 204–211, 2016. [Online]. Available: <https://zslpublications.onlinelibrary.wiley.com/doi/abs/10.1002/rse2.28>
- [36] P. D. Meek, G. A. Ballard, J. Sparkes, M. Robinson, B. Nesbitt, and P. J. S. Fleming, “Camera trap theft and vandalism: occurrence, cost, prevention and implications for wildlife research and management,” *Remote Sensing in Ecology and Conservation*, vol. 5, no. 2, pp. 160–168, 2019. [Online]. Available: <https://zslpublications.onlinelibrary.wiley.com/doi/abs/10.1002/rse2.96>
- [37] R. Kays, B. Kranstauber, P. Jansen, C. Carbone, M. Rowcliffe, T. Fountain, and S. Tilak, “Camera traps as sensor networks for monitoring animal communities,” in *2009 IEEE 34th Conference on Local Computer Networks*, 2009, pp. 811–818.
- [38] M. Bolton, N. Butcher, F. Sharpe, D. Stevens, and G. Fisher, “Remote monitoring of nests using digital camera technology,” *Journal of Field Ornithology*, vol. 78, no. 2, pp. 213–220, 2007. [Online]. Available: <https://onlinelibrary.wiley.com/doi/abs/10.1111/j.1557-9263.2007.00104.x>