


Stabilizing Training of Generative Adversarial Networks through Regularization

Kevin Roth Aurélien Lucchi Sebastian Nowozin Thomas Hofmann
Institute of Machine Learning, ETH Zürich, Switzerland
Microsoft Research, Cambridge, UK




GANs are exciting, but ...
they're also notoriously hard to train!

GAN objective [2]

$$\begin{aligned} & \min_G \max_{\varphi} \mathbf{E}_{\mathbb{P}}[\ln \varphi(x)] + \mathbf{E}_{p(z)}[\ln(1 - \varphi(G(z)))] \\ & = \min_G D_{\text{JS}}(\mathbb{P}||Q_\theta) \text{ for Bayes-optimal } \varphi^*(x) \end{aligned}$$

Problem: Dim. Mismatch
or $\text{supp}(\mathbb{P}) \cap \text{supp}(Q_\theta) = \emptyset$


Solution: Adding Noise
(Convolving Densities)



=> Undef. f-div. $D_f(\mathbb{P}||Q_\theta) = ???$

=> Regularizing Discriminator

Dimensionally Misspecified Submanifold Mixture



Unstable unregularized GAN vs. stable regularized GANs for different levels of γ .
The regularized GAN can essentially be trained indefinitely without collapse.

References

- [1] M. Arjovsky and L. Bottou. Towards principled methods for training generative adversarial networks. In *NIPS 2016 Workshop on Adversarial Training*. In review for ICLR, volume 2016, 2017.
- [2] C. M. Bishop. Training with noise is equivalent to tikhonov regularization. *Neural computation*, 7(1):108–116, 1995.
- [3] I. Goodfellow, J. Pouget-Abadie, M. Mirza, B. Xu, D. Warde-Farley, S. Ozair, A. Courville, and Y. Bengio. Generative Adversarial Networks. *NIPS*, 2014.
- [4] X. Nguyen, M. J. Wainwright, and M. I. Jordan. Estimating divergence functionals and the likelihood ratio by convex risk minimization. *IEEE Transactions on Information Theory*, 56(11):5847–5861, 2010.
- [5] S. Nowozin, B. Cseke, and R. Tomioka. f-GAN: Training generative neural samplers using variational divergence minimization. In *Advances in Neural Information Processing Systems*, pages 271–279, 2016.
- [6] C. K. Sønderby, J. Caballero, L. Theis, W. Shi, and F. Huszár. Amortised map inference for image super-resolution. *arXiv preprint arXiv:1610.04490*, 2016.

Training with Noise

From f -divergences to f -GAN objectives [4]

$$D_f(\mathbb{P}||\mathbb{Q}) \geq \sup_{\psi \in \Psi} [F(\mathbb{P}, \mathbb{Q}; \psi) := \mathbf{E}_{\mathbb{P}}[\psi] - \mathbf{E}_{\mathbb{Q}}[f^c \circ \psi]]$$

- Practitioner: Explicitly adding noise $\xi \sim \Lambda_\gamma \equiv \mathcal{N}(0, \gamma \mathbb{I})$ to $x \sim \mathbb{P}, Q$
- Theory: Convolving Distributions

$$\mathbf{E}_{\mathbb{P}} \mathbf{E}_{\Lambda} [h(\psi(x + \xi))] = \int h(\psi(x)) \int p(x - \xi) \lambda(\xi) d\xi dx = \mathbf{E}_{\mathbb{P} * \Lambda} [h \circ \psi]$$

=> Convolved f -GAN Objective

$$F(\mathbb{P} * \Lambda_\gamma, \mathbb{Q} * \Lambda_\gamma; \psi) = \mathbf{E}_{\mathbb{P} * \Lambda_\gamma} [\psi] - \mathbf{E}_{\mathbb{Q} * \Lambda_\gamma} [f^c \circ \psi]$$

Analytic Approximation

- For small noise variance γ we can Taylor expand ψ around $\xi = 0$ [1]:

$$\psi(x + \xi) = \psi(x) + [\nabla \psi(x)]^T \xi + \frac{1}{2} \xi^T [\nabla^2 \psi(x)] \xi + \mathcal{O}(\xi^3)$$

- Third-order approximation (in ξ) of F_γ via $F = F_0$ plus a correction, i.e.

$$F_\gamma(\mathbb{P}, \mathbb{Q}; \psi) = F(\mathbb{P}, \mathbb{Q}; \psi) + \frac{\gamma}{2} \{ \mathbf{E}_{\mathbb{P}}[\Delta \psi] - \mathbf{E}_{\mathbb{Q}}[\Delta(f^c \circ \psi)] \} + \mathcal{O}(\gamma^2)$$

- Interpretation: Laplace $\Delta = \text{Tr}(\nabla^2)$ measures how much ψ and $f^c \circ \psi$ differ from their local average

Efficient Gradient-Based Regularization

- Chain-rule: $\Delta(f^c \circ \psi) = (f^{c''} \circ \psi) \cdot \|\nabla \psi\|^2 + (f^{c'} \circ \psi) \Delta \psi$
- Property of optimal discriminant ψ^* [3]: $(f^{c'} \circ \psi^*) d\mathbb{Q} = d\mathbb{P}$

=> Convenient cancellation at $\psi = \psi^* + \mathcal{O}(\gamma)$ [1]:

$$\mathbf{E}_{\mathbb{P}}[\Delta \psi^*] - \mathbf{E}_{\mathbb{Q}}[\Delta(f^c \circ \psi^*)] = -\mathbf{E}_{\mathbb{Q}}[(f^{c''} \circ \psi^*) \cdot \|\nabla \psi^*\|^2]$$

=> Tractable regularization which avoids (i) detrimental sampling variance, (ii) explicitly convolving the distributions, and (iii) the computation of Laplacians

Regularized f -GAN

$$F_\gamma(\mathbb{P}, \mathbb{Q}; \psi) = F(\mathbb{P}, \mathbb{Q}; \psi) - \frac{\gamma}{2} \Omega_f(\mathbb{Q}; \psi), \quad \Omega_f(\mathbb{Q}; \psi) := \mathbf{E}_{\mathbb{Q}}[(f^{c''} \circ \psi) \cdot \|\nabla \psi\|^2]$$

$$\begin{aligned} F_{\text{JS}}(\mathbb{P}, \mathbb{Q}; \varphi) &= \mathbf{E}_{\mathbb{P}}[\ln(\varphi)] + \mathbf{E}_{\mathbb{Q}}[\ln(1 - \varphi)] - \frac{\gamma}{2} \Omega_{\text{JS}}(\mathbb{P}, \mathbb{Q}; \varphi) \\ \Omega_{\text{JS}}(\mathbb{P}, \mathbb{Q}; \varphi) &:= \mathbf{E}_{\mathbb{P}}[(1 - \varphi)^2 \|\nabla \varphi\|^2] + \mathbf{E}_{\mathbb{Q}}[\varphi^2 \|\nabla \varphi\|^2] \end{aligned}$$

- “soft Lipschitz” constraint, non-negative weighting function $f^{c''} \geq 0$
- lower variance compared to explicitly adding noise
- easy to implement & computationally cheap
- can train indefinitely without collapse!

Algorithm 1 Regularized f -GAN. Default values: $\gamma_0 = 2.0$, $\alpha = 0.01$ (with annealing), $\gamma = 0.1$ (without annealing), $n_\psi = 1$

```

Require: Initial noise variance  $\gamma_0$ , annealing decay factor  $\alpha$ , number of discriminator update steps  $n_\psi$  per generator iteration, minibatch size  $m$ , number of training iterations  $T$ 
Require: Initial discriminator parameters  $\omega_0$ , initial generator parameters  $\theta_0$ 
for  $t = 1, \dots, T$  do
     $\gamma \leftarrow \gamma_0 \cdot \alpha^{t/T}$  # annealing
    for  $1, \dots, n_\psi$  do
        Sample minibatch of real data  $\{x^{(1)}, \dots, x^{(m)}\} \sim \mathbb{P}$ .
        Sample minibatch of latent variables from prior  $\{z^{(1)}, \dots, z^{(m)}\} \sim p(z)$ .
         $\omega \leftarrow \omega + \nabla_\omega (F(\omega, \theta) - \frac{\gamma}{2} \Omega_f(\omega, \theta))$  # gradient ascent
    end for
    Sample minibatch of latent variables from prior  $\{z^{(1)}, \dots, z^{(m)}\} \sim p(z)$ .
     $\theta \leftarrow \theta - \nabla_\theta F(\omega, \theta)$  # gradient descent
end for

```

Cross-Testing Protocol

Regularized $\gamma = 0.1$

True Cond.	
Pos.	Neg.
0.9688	0.0002
0.0312	0.9998

Cross-testing: FP: 0.0

Unregularized

True Cond.	
Pos.	Neg.
1.0	0.0013
0.0	0.9987

Cross-testing: FP: 1.0

Cross-Testing:
Classify 10k samples generated by the regularized GAN with the discriminator of the unregularized GAN and vice versa.

=> Regularized GAN generalizes better!

Stability across Architectures



Sample Quality and Diversity



tf code → github.com/rothk

```

# ----- JS-Regularizer -----
# ----- JS-Regularizer -----
def Discriminator_Regularizer(self, D1, D1_logits, D1_arg, D2, D2_logits, D2_arg):
    grad_D1_logits = tf.gradients(D1_logits, D1_arg)[0]
    grad_D2_logits = tf.gradients(D2_logits, D2_arg)[0]
    grad_D1_logits_norm = tf.norm(tf.reshape(grad_D1_logits, [self.batch_size,-1]), axis=1, keep_dims=True)
    grad_D2_logits_norm = tf.norm(tf.reshape(grad_D2_logits, [self.batch_size,-1]), axis=1, keep_dims=True)
    reg_D1 = tf.multiply(tf.square(1.0-D1), tf.square(grad_D1_logits_norm))
    reg_D2 = tf.multiply(tf.square(D2), tf.square(grad_D2_logits_norm))
    return tf.reduce_mean(reg_D1 + reg_D2)

```