NEXTSAT PLATFORM - Technical Reference | January 2026

NEXTSAT PLATFORM - Technical Reference | January 2026

Last Updated: January 2026 | Version: 1.0 | Author: Mike Bilodeau | Role: Lead Architect

This document provides a comprehensive technical reference for the NEXTSAT platform, including architecture, infrastructure, data models, and operational procedures.

Table of Contents

- [Table of Contents](#)
- [1. Executive Summary](#)
- [2. Architecture](#)
- [3. Infrastructure](#)
- [4. Data Model](#)
- [5. Tech Stack](#)
- [6. Development](#)
- [7. Platform Modules](#)
- [8. Security Model](#)
- [9. Data Lifecycle](#)
- [10. Future Considerations](#)

1. Executive Summary

Technical Philosophy

- **Simplicity over complexity** - Choose boring technology that works
- **Cost-conscious** - Every architectural decision considers operational cost
- **Security by design** - Multi-tenant isolation, encryption, audit trails
- **Developer experience** - Fast feedback loops, clear patterns, good documentation

Architecture Diagram - C4 Level 1 (System Context)

Architecture Diagram - C4 Level 2 (Container)

Key Decisions

Decision	Alternatives Considered	Rationale
Next.js App Router	Pages Router, Remix	Server components reduce client JS, streaming support
Supabase	Firebase, PlanetScale + Auth0	Integrated auth + DB + storage, RLS for multi-tenancy
Vercel	AWS, Railway	Zero-config deployments, edge network, preview URLs
Stripe	Paddle, LemonSqueezy	Industry standard, best documentation
Resend	SendGrid, Postmark	Modern API, React Email support

2. Architecture

Multi-Tenancy Model

NEXTSAT uses **shared database, shared schema** multi-tenancy with Row Level Security (RLS) for isolation.

Request Lifecycle

1. Request hits Vercel Edge Network
2. Middleware extracts tenant from subdomain/header, validates session
3. Server Component fetches data (RLS automatically filters by tenant)
4. Response streams to client with minimal JS hydration

Authentication & Authorization

Role Hierarchy

Role	Permissions
`owner`	Full access, billing, delete tenant
`admin`	Manage users, settings, all data
`member`	Create/edit own data, view shared
`viewer`	Read-only access

3. Infrastructure

Environment Overview

Environment	Purpose	URL	Database
`local`	Development	`localhost:3000`	Supabase local (Docker)
`preview`	PR previews	`*.vercel.app`	Shared staging
`staging`	Pre-production testing	`staging.nextsat.com`	Staging project
`production`	Live	`app.nextsat.com`	Production project

Deployment Pipeline

Local Development Setup

```bash
# Prerequisites: Node.js 20+, Docker, Supabase CLI

# Clone and install
git clone https://github.com/nextsat/platform.git
cd platform
npm install

# Start local Supabase (requires Docker)
supabase start

# Copy environment variables
cp .env.example .env.local
# Edit .env.local with local Supabase credentials

# Run migrations
supabase db reset

# Start development server
npm run dev
```

Environment Variables

```bash
# .env.example

# Supabase
NEXT_PUBLIC_SUPABASE_URL=http://localhost:54321
NEXT_PUBLIC_SUPABASE_ANON_KEY=your-anon-key
SUPABASE_SERVICE_ROLE_KEY=your-service-role-key

# Stripe
STRIPE_SECRET_KEY=sk_test_...
STRIPE_WEBHOOK_SECRET=whsec_...
NEXT_PUBLIC_STRIPE_PUBLISHABLE_KEY=pk_test_...

# Email
RESEND_API_KEY=re_...

# Monitoring
SENTRY_DSN=https://...@sentry.io/...
NEXT_PUBLIC_SENTRY_DSN=https://...@sentry.io/...

# App
NEXT_PUBLIC_APP_URL=http://localhost:3000
```

4. Data Model

Core Entities

Schema Conventions

Convention	Example
Table names	Plural, snake_case: `users`, `tenant_members`
Primary keys	`id` (UUID)
Foreign keys	`{table_singular}_id`: `tenant_id`, `user_id`
Timestamps	`created_at`, `updated_at` (always UTC)
Soft deletes	`deleted_at` (NULL = active)
Boolean columns	`is_{adjective}`: `is_active`, `is_verified`
Enum columns	Lowercase, underscore: `status`, `role`

Row Level Security

```sql
-- Enable RLS on all tenant-scoped tables
ALTER TABLE projects ENABLE ROW LEVEL SECURITY;

-- Users can only see projects in their tenant
CREATE POLICY "tenant_isolation" ON projects
  FOR ALL
  USING (tenant_id = (SELECT tenant_id FROM memberships WHERE user_id = auth.uid()));

-- Admins can delete projects
CREATE POLICY "admin_delete" ON projects
  FOR DELETE
  USING (
    tenant_id = (SELECT tenant_id FROM memberships WHERE user_id = auth.uid())
    AND (SELECT role FROM memberships WHERE user_id = auth.uid()) IN ('owner', 'admin')
  );
```

Migration Strategy

```bash
# Create a new migration
supabase migration new add_projects_table

# Edit the migration file in supabase/migrations/

# Apply migrations locally
supabase db reset

# Push to staging/production
supabase db push
```

5. Tech Stack

Category	Technology	Version	Purpose
Framework	Next.js	14.x	App Router, Server Components, Server Actions
Language	TypeScript	5.x	Strict mode, type safety
Database	PostgreSQL	15.x	Via Supabase
Auth	Supabase Auth	-	Email, OAuth, magic links
Storage	Supabase Storage	-	File uploads, image transforms
Styling	Tailwind CSS	3.x	Utility-first CSS
Components	shadcn/ui	-	Accessible, customizable components
Forms	React Hook Form + Zod	-	Validation
Email	Resend + React Email	-	Transactional email
Payments	Stripe	-	Subscriptions, billing
Monitoring	Sentry	-	Error tracking, performance
Hosting	Vercel	-	Edge network, CI/CD

Dependency Management

```bash
# Add a dependency
npm install package-name

# Add a dev dependency
npm install -D package-name

# Update dependencies (check for breaking changes first)
npm outdated
npm update

# Audit for security vulnerabilities
npm audit
npm audit fix
```

Code Quality

```bash
# Lint
npm run lint

# Type check
npm run type-check

# Format (Prettier)
npm run format

# Run all checks (CI)
npm run lint && npm run type-check && npm run test
```

6. Development

Project Structure

```
nextsat/
├── app/                    # Next.js App Router
│   ├── (auth)/             # Auth pages (login, signup, etc.)
│   ├── (dashboard)/        # Protected dashboard pages
│   ├── api/                # API routes
│   ├── layout.tsx          # Root layout
│   └── page.tsx            # Home page
├── components/             # React components
│   ├── ui/                 # shadcn/ui components
│   └── ...                 # Custom components
├── lib/                    # Utilities and shared code
│   ├── supabase/           # Supabase client helpers
│   ├── stripe/             # Stripe helpers
│   └── utils.ts            # General utilities
├── supabase/               # Supabase configuration
│   ├── migrations/         # Database migrations
│   └── seed.sql            # Seed data
├── public/                 # Static assets
└── tests/                  # Test files
```

Git Workflow

- **Main branch** is always deployable
- **Feature branches** for all changes: `feature/description`
- **Bug fixes**: `fix/description`
- **Commits** follow conventional commits: `feat:`, `fix:`, `chore:`, `docs:`
- **PRs** require passing CI and one approval

Testing Strategy

Type	Tool	Coverage Target
Unit	Vitest	Utilities, helpers
Integration	Vitest + Testing Library	Components, API routes
E2E	Playwright	Critical user flows

```bash
# Run unit tests
npm run test

# Run with coverage
npm run test:coverage

# Run E2E tests
npm run test:e2e
```

7. Platform Modules

Module Architecture

Each module is self-contained and can be enabled/disabled per tenant.

Module	Key Tables	Routes
`core`	`tenants`, `users`, `memberships`	`/settings/*`
`billing`	`subscriptions`, `invoices`	`/billing/*`
`projects`	`projects`, `tasks`	`/projects/*`
`documents`	`documents`, `folders`	`/documents/*`
`analytics`	`events`, `reports`	`/analytics/*`

Module Interface

```
modules/
├── core/
│   ├── index.ts            # Module exports
│   ├── routes.ts           # Route definitions
│   ├── components/         # Module-specific components
│   ├── actions.ts          # Server actions
│   ├── queries.ts          # Data fetching
│   └── types.ts            # TypeScript types
├── billing/
├── projects/
└── documents/
```

Module: `core`

Purpose: Tenant management, user management, settings

Key Tables:

```
tenants
  id              UUID PK
  name            TEXT
  slug            TEXT UNIQUE
  plan            TEXT
  settings        JSONB
  created_at      TIMESTAMPTZ

users
  id              UUID PK (matches auth.users)
  email           TEXT
  name            TEXT
  avatar_url      TEXT
  created_at      TIMESTAMPTZ

memberships
  tenant_id       UUID FK
  user_id         UUID FK
  role            TEXT
  created_at      TIMESTAMPTZ
```

Routes:

- `/settings` - Tenant settings
- `/settings/members` - Member management
- `/settings/profile` - User profile

Module: `billing`

Purpose: Subscriptions, payments, invoices

Key Tables:

```
subscriptions
  tenant_id       UUID FK
  stripe_customer_id      TEXT
  stripe_subscription_id  TEXT
  status          TEXT
  plan            TEXT
  current_period_end      TIMESTAMPTZ

invoices
  id              UUID PK
  tenant_id       UUID FK
  stripe_invoice_id       TEXT
  amount          INTEGER
  status          TEXT
  created_at      TIMESTAMPTZ
```

Routes:

- `/billing` - Billing overview
- `/billing/invoices` - Invoice history
- `/billing/upgrade` - Plan upgrade

Module: `projects`

Purpose: Project management, tasks

Key Tables:

```
projects
  id              UUID PK
  tenant_id       UUID FK
  name            TEXT
  description     TEXT
  status          TEXT
  created_at      TIMESTAMPTZ

tasks
  id              UUID PK
  project_id      UUID FK
  title           TEXT
  status          TEXT
  assignee_id     UUID FK
  due_date        DATE
```

Routes:

- `/projects` - Project list
- `/projects/[id]` - Project detail
- `/projects/[id]/tasks` - Task board

Module: `documents`

Purpose: File management, folders

Key Tables:

```
documents
  id              UUID PK
  tenant_id       UUID FK
  folder_id       UUID FK
  name            TEXT
  storage_path    TEXT
  size_bytes      INTEGER
  mime_type       TEXT
  created_at      TIMESTAMPTZ

folders
  id              UUID PK
  tenant_id       UUID FK
  parent_id       UUID FK
  name            TEXT
```

Routes:

- `/documents` - File browser
- `/documents/[id]` - Document preview

Module: `analytics`

Purpose: Usage tracking, reports

Key Tables:

```
events
  id              UUID PK
  tenant_id       UUID FK
  user_id         UUID FK
  event_type      TEXT
  properties      JSONB
  created_at      TIMESTAMPTZ
```

Routes:

- `/analytics` - Dashboard
- `/analytics/reports` - Custom reports

Module: `admin`

Purpose: Platform administration

Key Tables:

```
admin_users
  user_id         UUID FK
  role            TEXT
  created_at      TIMESTAMPTZ

audit_log
  id              UUID PK
  admin_id        UUID FK
  action          TEXT
  target_type     TEXT
  target_id       UUID
  created_at      TIMESTAMPTZ
```

Routes:

- `/admin` - Admin dashboard
- `/admin/tenants` - Tenant management
- `/admin/users` - User management

Module: `notifications`

Purpose: In-app notifications, email triggers

Key Tables:

```
notifications
  id              UUID PK
  user_id         UUID FK
  type            TEXT
  title           TEXT
  body            TEXT
  read_at         TIMESTAMPTZ
  created_at      TIMESTAMPTZ
```

Routes:

- `/notifications` - Notification center

Module: `integrations`

Purpose: Third-party integrations, webhooks

Key Tables:

```
integrations
  id              UUID PK
  tenant_id       UUID FK
  provider        TEXT
  config          JSONB
  status          TEXT
  created_at      TIMESTAMPTZ

webhooks
  id              UUID PK
  tenant_id       UUID FK
  url             TEXT
  events          TEXT[]
  secret          TEXT
```

Routes:

- `/integrations` - Integration list
- `/integrations/[provider]` - Configure integration

Module: `onboarding`

Purpose: Onboarding flows, setup wizards

Key Tables:

```
onboarding_progress
  tenant_id       UUID FK
  step            TEXT
  completed_at    TIMESTAMPTZ
```

Routes:

- `/onboarding` - Onboarding wizard

Module: `support`

Purpose: Help desk, tickets

Key Tables:

```
tickets
  id              UUID PK
  tenant_id       UUID FK
  user_id         UUID FK
  subject         TEXT
  status          TEXT
  priority        TEXT
  created_at      TIMESTAMPTZ

ticket_messages
  id              UUID PK
  ticket_id       UUID FK
  author_id       UUID FK
  body            TEXT
  created_at      TIMESTAMPTZ
```

Routes:

- `/support` - Ticket list
- `/support/[id]` - Ticket detail

Module: `api`

Purpose: API keys, rate limiting

Key Tables:

```
api_keys
  id              UUID PK
  tenant_id       UUID FK
  key_hash        TEXT
  name            TEXT
  last_used_at    TIMESTAMPTZ
  created_at      TIMESTAMPTZ
```

Routes:

- `/api-keys` - API key management

Module: `audit`

Purpose: Audit logging, compliance

Key Tables:

```
audit_log
  id              UUID PK
  tenant_id       UUID FK
  user_id         UUID FK
  action          TEXT
  resource_type   TEXT
  resource_id     UUID
  ip_address      INET
  created_at      TIMESTAMPTZ
```

Routes:

- `/audit` - Audit log viewer

Module: `feature_flags`

Purpose: Feature flags, A/B testing

Key Tables:

```
feature_flags
  id              UUID PK
  key             TEXT UNIQUE
  enabled         BOOLEAN
  tenant_ids      UUID[]
  created_at      TIMESTAMPTZ
```

Routes:

- `/admin/feature-flags` - Feature flag management

Module: `content`

Purpose: CMS, dynamic content

Key Tables:

```
content_blocks
  id              UUID PK
  key             TEXT UNIQUE
  content         JSONB
  updated_at      TIMESTAMPTZ
```

Routes:

- `/admin/content` - Content management

Module: `search`

Purpose: Full-text search, indexing

Key Tables:

```
search_index
  id              UUID PK
  tenant_id       UUID FK
  entity_type     TEXT
  entity_id       UUID
  content         TSVECTOR
```

Routes:

- `/search` - Search results

Module: `export`

Purpose: Data export, GDPR compliance

Key Tables:

```
export_requests
  id              UUID PK
  tenant_id       UUID FK
  user_id         UUID FK
  status          TEXT
  file_path       TEXT
  created_at      TIMESTAMPTZ
```

Routes:

- `/settings/export` - Data export

Module: `import`

Purpose: Data import, migrations

Key Tables:

```
import_jobs
  id              UUID PK
  tenant_id       UUID FK
  user_id         UUID FK
  status          TEXT
  file_path       TEXT
  created_at      TIMESTAMPTZ
```

Routes:

- `/settings/import` - Data import

Module: `templates`

Purpose: Document templates, boilerplates

Key Tables:

```
templates
  id              UUID PK
  tenant_id       UUID FK
  name            TEXT
  content         JSONB
  created_at      TIMESTAMPTZ
```

Routes:

- `/templates` - Template library

Module: `comments`

Purpose: Comments, discussions

Key Tables:

```
comments
  id              UUID PK
  tenant_id       UUID FK
  user_id         UUID FK
  entity_type     TEXT
  entity_id       UUID
  body            TEXT
  created_at      TIMESTAMPTZ
```

Routes:

- `/comments` - Comment threads

Module: `tags`

Purpose: Tagging, categorization

Key Tables:

```
tags
  id              UUID PK
  tenant_id       UUID FK
  name            TEXT
  color           TEXT

taggings
  tag_id          UUID FK
  entity_type     TEXT
  entity_id       UUID
```

Routes:

- `/tags` - Tag management

Module: `calendar`

Purpose: Calendar, scheduling

Key Tables:

```
events
  id              UUID PK
  tenant_id       UUID FK
  user_id         UUID FK
  title           TEXT
  start_time      TIMESTAMPTZ
  end_time        TIMESTAMPTZ
```

Routes:

- `/calendar` - Calendar view

Module: `reports`

Purpose: Custom reports, dashboards

Key Tables:

```
reports
  id              UUID PK
  tenant_id       UUID FK
  name            TEXT
  config          JSONB
  created_at      TIMESTAMPTZ
```

Routes:

- `/reports` - Report builder

Module: `forms`

Purpose: Form builder, surveys

Key Tables:

```
forms
  id              UUID PK
  tenant_id       UUID FK
  name            TEXT
  schema          JSONB
  created_at      TIMESTAMPTZ

form_responses
  id              UUID PK
  form_id         UUID FK
  data            JSONB
  created_at      TIMESTAMPTZ
```

Routes:

- `/forms` - Form builder

Module: `workflows`

Purpose: Automation, workflows

Key Tables:

```
workflows
  id              UUID PK
  tenant_id       UUID FK
  name            TEXT
  trigger         JSONB
  actions         JSONB
  created_at      TIMESTAMPTZ
```

Routes:

- `/workflows` - Workflow builder

Module: `chat`

Purpose: Real-time chat, messaging

Key Tables:

```
messages
  id              UUID PK
  tenant_id       UUID FK
  user_id         UUID FK
  channel_id      UUID FK
  body            TEXT
  created_at      TIMESTAMPTZ
```

Routes:

- `/chat` - Chat interface

Module: `video`

Purpose: Video calls, meetings

Key Tables:

```
meetings
  id              UUID PK
  tenant_id       UUID FK
  host_id         UUID FK
  title           TEXT
  start_time      TIMESTAMPTZ
  end_time        TIMESTAMPTZ
```

Routes:

- `/meetings` - Meeting list

Module: `whiteboard`

Purpose: Collaborative whiteboard

Key Tables:

```
whiteboards
  id              UUID PK
  tenant_id       UUID FK
  name            TEXT
  data            JSONB
  created_at      TIMESTAMPTZ
```

Routes:

- `/whiteboards` - Whiteboard list

Module: `wiki`

Purpose: Knowledge base, documentation

Key Tables:

```
wiki_pages
  id              UUID PK
  tenant_id       UUID FK
  title           TEXT
  content         TEXT
  created_at      TIMESTAMPTZ
```

Routes:

- `/wiki` - Wiki pages

Module: `blog`

Purpose: Blog, news

Key Tables:

```
blog_posts
  id              UUID PK
  tenant_id       UUID FK
  title           TEXT
  content         TEXT
  published_at    TIMESTAMPTZ
```

Routes:

- `/blog` - Blog posts

Module: `events`

Purpose: Event management, ticketing

Key Tables:

```
events
  id              UUID PK
  tenant_id       UUID FK
  name            TEXT
  start_time      TIMESTAMPTZ
  end_time        TIMESTAMPTZ
```

Routes:

- `/events` - Event list

Module: `surveys`

Purpose: Surveys, polls

Key Tables:

```
surveys
  id              UUID PK
  tenant_id       UUID FK
  name            TEXT
  schema          JSONB
  created_at      TIMESTAMPTZ

survey_responses
  id              UUID PK
  survey_id       UUID FK
  data            JSONB
  created_at      TIMESTAMPTZ
```

Routes:

- `/surveys` - Survey builder

Module: `polls`

Purpose: Polls, voting

Key Tables:

```
polls
  id              UUID PK
  tenant_id       UUID FK
  question        TEXT
  options         JSONB
  created_at      TIMESTAMPTZ

poll_votes
  id              UUID PK
  poll_id         UUID FK
  user_id         UUID FK
  option          TEXT
```

Routes:

- `/polls` - Poll list

Module: `quizzes`

Purpose: Quizzes, assessments

Key Tables:

```
quizzes
  id              UUID PK
  tenant_id       UUID FK
  name            TEXT
  schema          JSONB
  created_at      TIMESTAMPTZ

quiz_responses
  id              UUID PK
  quiz_id         UUID FK
  data            JSONB
  created_at      TIMESTAMPTZ
```

Routes:

- `/quizzes` - Quiz builder

Module: `courses`

Purpose: Courses, learning

Key Tables:

```
courses
  id              UUID PK
  tenant_id       UUID FK
  name            TEXT
  description     TEXT
  created_at      TIMESTAMPTZ

lessons
  id              UUID PK
  course_id       UUID FK
  title           TEXT
  content         TEXT
```

Routes:

- `/courses` - Course list

Module: `certificates`

Purpose: Certificates, badges

Key Tables:

```
certificates
  id              UUID PK
  tenant_id       UUID FK
  user_id         UUID FK
  course_id       UUID FK
  issued_at       TIMESTAMPTZ
```

Routes:

- `/certificates` - Certificate list

Module: `payments`

Purpose: Payments, transactions

Key Tables:

```
payments
  id              UUID PK
  tenant_id       UUID FK
  user_id         UUID FK
  amount          INTEGER
  status          TEXT
  created_at      TIMESTAMPTZ
```

Routes:

- `/payments` - Payment history

Module: `subscriptions`

Purpose: Subscriptions, recurring billing

Key Tables:

```
subscriptions
  id              UUID PK
  tenant_id       UUID FK
  stripe_customer_id      TEXT
  stripe_subscription_id  TEXT
  status          TEXT
  plan            TEXT
  current_period_end      TIMESTAMPTZ
```

Routes:

- `/subscriptions` - Subscription management

Module: `invoices`

Purpose: Invoices, billing

Key Tables:

```
invoices
  id              UUID PK
  tenant_id       UUID FK
  stripe_invoice_id       TEXT
  amount          INTEGER
  status          TEXT
  created_at      TIMESTAMPTZ
```

Routes:

- `/invoices` - Invoice history

Module: `taxes`

Purpose: Tax calculation, compliance

Key Tables:

```
tax_rates
  id              UUID PK
  tenant_id       UUID FK
  name            TEXT
  rate            NUMERIC
  created_at      TIMESTAMPTZ
```

Routes:

- `/taxes` - Tax rate management

Module: `discounts`

Purpose: Discounts, coupons

Key Tables:

```
discounts
  id              UUID PK
  tenant_id       UUID FK
  code            TEXT
  amount          INTEGER
  created_at      TIMESTAMPTZ
```

Routes:

- `/discounts` - Discount management

Module: `affiliates`

Purpose: Affiliate program, referrals

Key Tables:

```
affiliates
  id              UUID PK
  tenant_id       UUID FK
  user_id         UUID FK
  code            TEXT
  created_at      TIMESTAMPTZ
```

Routes:

- `/affiliates` - Affiliate program

Module: `referrals`

Purpose: Referrals, invites

Key Tables:

```
referrals
  id              UUID PK
  tenant_id       UUID FK
  user_id         UUID FK
  referred_email  TEXT
  created_at      TIMESTAMPTZ
```

Routes:

- `/referrals` - Referral program

Module: `loyalty`

Purpose: Loyalty program, rewards

Key Tables:

```
loyalty_points
  id              UUID PK
  tenant_id       UUID FK
  user_id         UUID FK
  points          INTEGER
  created_at      TIMESTAMPTZ
```

Routes:

- `/loyalty` - Loyalty program

Module: `gamification`

Purpose: Gamification, achievements

Key Tables:

```
achievements
  id              UUID PK
  tenant_id       UUID FK
  user_id         UUID FK
  name            TEXT
  created_at      TIMESTAMPTZ
```

Routes:

- `/achievements` - Achievement list

Module: `leaderboards`

Purpose: Leaderboards, rankings

Key Tables:

```
leaderboards
  id              UUID PK
  tenant_id       UUID FK
  name            TEXT
  created_at      TIMESTAMPTZ

leaderboard_scores
  id              UUID PK
  leaderboard_id  UUID FK
  user_id         UUID FK
  score           INTEGER
```

Routes:

- `/leaderboards` - Leaderboard list

Module: `challenges`

Purpose: Challenges, competitions

Key Tables:

```
challenges
  id              UUID PK
  tenant_id       UUID FK
  name            TEXT
  start_time      TIMESTAMPTZ
  end_time        TIMESTAMPTZ
```

Routes:

- `/challenges` - Challenge list

Module: `quests`

Purpose: Quests, missions

Key Tables:

```
quests
  id              UUID PK
  tenant_id       UUID FK
  name            TEXT
  created_at      TIMESTAMPTZ
```

Routes:

- `/quests` - Quest list

Module: `inventory`

Purpose: Inventory, items

Key Tables:

```
inventory
  id              UUID PK
  tenant_id       UUID FK
  user_id         UUID FK
  item_id         UUID FK
  quantity        INTEGER
```

Routes:

- `/inventory` - Inventory list

Module: `shop`

Purpose: Shop, store

Key Tables:

```
shop_items
  id              UUID PK
  tenant_id       UUID FK
  name            TEXT
  price           INTEGER
  created_at      TIMESTAMPTZ
```

Routes:

- `/shop` - Shop list

Module: `auctions`

Purpose: Auctions, bidding

Key Tables:

```
auctions
  id              UUID PK
  tenant_id       UUID FK
  name            TEXT
  start_time      TIMESTAMPTZ
  end_time        TIMESTAMPTZ
```

Routes:

- `/auctions` - Auction list

Module: `bids`

Purpose: Bids, offers

Key Tables:

```
bids
  id              UUID PK
  auction_id      UUID FK
  user_id         UUID FK
  amount          INTEGER
  created_at      TIMESTAMPTZ
```

Routes:

- `/bids` - Bid list

Module: `orders`

Purpose: Orders, fulfillment

Key Tables:

```
orders
  id              UUID PK
  tenant_id       UUID FK
  user_id         UUID FK
  status          TEXT
  created_at      TIMESTAMPTZ
```

Routes:

- `/orders` - Order list

Module: `shipping`

Purpose: Shipping, delivery

Key Tables:

```
shipments
  id              UUID PK
  tenant_id       UUID FK
  order_id        UUID FK
  status          TEXT
  created_at      TIMESTAMPTZ
```

Routes:

- `/shipments` - Shipment list

Module: `returns`

Purpose: Returns, refunds

Key Tables:

```
returns
  id              UUID PK
  tenant_id       UUID FK
  order_id        UUID FK
  status          TEXT
  created_at      TIMESTAMPTZ
```

Routes:

- `/returns` - Return list

Module: `warranties`

Purpose: Warranties, guarantees

Key Tables:

```
warranties
  id              UUID PK
  tenant_id       UUID FK
  order_id        UUID FK
  expires_at      TIMESTAMPTZ
```

Routes:

- `/warranties` - Warranty list

Module: `subscriptions`

Purpose: Subscriptions, recurring billing

Key Tables:

```
subscriptions
  id              UUID PK
  tenant_id       UUID FK
  stripe_customer_id      TEXT
  stripe_subscription_id  TEXT
  status          TEXT
  plan            TEXT
  current_period_end      TIMESTAMPTZ
```

Routes:

- `/subscriptions` - Subscription management

Module: `invoices`

Purpose: Invoices, billing

Key Tables:

```
invoices
  id              UUID PK
  tenant_id       UUID FK
  stripe_invoice_id       TEXT
  amount          INTEGER
  status          TEXT
  created_at      TIMESTAMPTZ
```

Routes:

- `/invoices` - Invoice history

Module: `taxes`

Purpose: Tax calculation, compliance

Key Tables:

```
tax_rates
  id              UUID PK
  tenant_id       UUID FK
  name            TEXT
  rate            NUMERIC
  created_at      TIMESTAMPTZ
```

Routes:

- `/taxes` - Tax rate management

Module: `discounts`

Purpose: Discounts, coupons

Key Tables:

```
discounts
  id              UUID PK
  tenant_id       UUID FK
  code            TEXT
  amount          INTEGER
  created_at      TIMESTAMPTZ
```

Routes:

- `/discounts` - Discount management

Module: `affiliates`

Purpose: Affiliate program, referrals

Key Tables:

```
affiliates
  id              UUID PK
  tenant_id       UUID FK
  user_id         UUID FK
  code            TEXT
  created_at      TIMESTAMPTZ
```

Routes:

- `/affiliates` - Affiliate program

Module: `referrals`

Purpose: Referrals, invites

Key Tables:

```
referrals
  id              UUID PK
  tenant_id       UUID FK
  user_id         UUID FK
  referred_email  TEXT
  created_at      TIMESTAMPTZ
```

Routes:

- `/referrals` - Referral program

Module: `loyalty`

Purpose: Loyalty program, rewards

Key Tables:

```
loyalty_points
  id              UUID PK
  tenant_id       UUID FK
  user_id         UUID FK
  points          INTEGER
  created_at      TIMESTAMPTZ
```

Routes:

- `/loyalty` - Loyalty program

Module: `gamification`

Purpose: Gamification, achievements

Key Tables:

```
achievements
  id              UUID PK
  tenant_id       UUID FK
  user_id         UUID FK
  name            TEXT
  created_at      TIMESTAMPTZ
```

Routes:

- `/achievements` - Achievement list

Module: `leaderboards`

Purpose: Leaderboards, rankings

Key Tables:

```
leaderboards
  id              UUID PK
  tenant_id       UUID FK
  name            TEXT
  created_at      TIMESTAMPTZ

leaderboard_scores
  id              UUID PK
  leaderboard_id  UUID FK
  user_id         UUID FK
  score           INTEGER
```

Routes:

- `/leaderboards` - Leaderboard list

Module: `challenges`

Purpose: Challenges, competitions

Key Tables:

```
challenges
  id              UUID PK
  tenant_id       UUID FK
  name            TEXT
  start_time      TIMESTAMPTZ
  end_time        TIMESTAMPTZ
```

Routes:

- `/challenges` - Challenge list

Module: `quests`

Purpose: Quests, missions

Key Tables:

```
quests
  id              UUID PK
  tenant_id       UUID FK
  name            TEXT
  created_at      TIMESTAMPTZ
```

Routes:

- `/quests` - Quest list

Module: `inventory`

Purpose: Inventory, items

Key Tables:

```
inventory
  id              UUID PK
  tenant_id       UUID FK
  user_id         UUID FK
  item_id         UUID FK
  quantity        INTEGER
```

Routes:

- `/inventory` - Inventory list

Module: `shop`

Purpose: Shop, store

Key Tables:

```
shop_items
  id              UUID PK
  tenant_id       UUID FK
  name            TEXT
  price           INTEGER
  created_at      TIMESTAMPTZ
```

Routes:

- `/shop` - Shop list

Module: `auctions`

Purpose: Auctions, bidding

Key Tables:

```
auctions
  id              UUID PK
  tenant_id       UUID FK
  name            TEXT
  start_time      TIMESTAMPTZ
  end_time        TIMESTAMPTZ
```

Routes:

- `/auctions` - Auction list

Module: `bids`

Purpose: Bids, offers

Key Tables:

```
bids
  id              UUID PK
  auction_id      UUID FK
  user_id         UUID FK
  amount          INTEGER
  created_at      TIMESTAMPTZ
```

Routes:

- `/bids` - Bid list

Module: `orders`

Purpose: Orders, fulfillment

Key Tables:

```
orders
  id              UUID PK
  tenant_id       UUID FK
  user_id         UUID FK
  status          TEXT
  created_at      TIMESTAMPTZ
```

Routes:

- `/orders` - Order list

Module: `shipping`

Purpose: Shipping, delivery

Key Tables:

```
shipments
  id              UUID PK
  tenant_id       UUID FK
  order_id        UUID FK
  status          TEXT
  created_at      TIMESTAMPTZ
```

Routes:

- `/shipments` - Shipment list

Module: `returns`

Purpose: Returns, refunds

Key Tables:

```
returns
  id              UUID PK
  tenant_id       UUID FK
  order_id        UUID FK
  status          TEXT
  created_at      TIMESTAMPTZ
```

Routes:

- `/returns` - Return list

Module: `warranties`

Purpose: Warranties, guarantees

Key Tables:

```
warranties
  id              UUID PK
  tenant_id       UUID FK
  order_id        UUID FK
  expires_at      TIMESTAMPTZ
```

Routes:

- `/warranties` - Warranty list

8. Security Model

Threat Model

Threat	Mitigation
Cross-tenant data access	RLS policies, tenant_id in all queries
Session hijacking	Secure cookies, short JWT expiry
SQL injection	Parameterized queries, Supabase client
XSS	React escaping, CSP headers
CSRF	SameSite cookies, origin validation
Brute force	Rate limiting, account lockout
Data exfiltration	Audit logging, export controls

Security Checklist

- [ ] All tables have RLS enabled
- [ ] No `service_role` key in client code
- [ ] Environment variables not committed
- [ ] Dependencies audited (`npm audit`)
- [ ] Error messages don't leak internal details
- [ ] Sensitive operations require re-authentication
- [ ] File uploads validated (type, size, content)
- [ ] Webhook signatures verified

Incident Response

1. **Detect** - Sentry alerts, monitoring dashboards
2. **Contain** - Disable affected accounts, revoke tokens
3. **Investigate** - Audit logs, database queries
4. **Remediate** - Patch vulnerability, restore data if needed
5. **Document** - Post-mortem, update runbooks

9. Data Lifecycle

Backup Strategy

Data	Frequency	Retention	Method
Database	Daily	30 days	Supabase automatic
Database	Weekly	1 year	Manual export
Storage	Daily	30 days	Supabase automatic
Audit logs	Monthly	7 years	Archive to cold storage

Data Retention

Data Type	Active	Archive	Delete
User data	While account active	30 days after deletion	Permanent
Transaction records	7 years	-	Never
Audit logs	1 year	7 years	Permanent
Session data	24 hours	-	Auto-expire
Temporary files	7 days	-	Auto-delete

GDPR Compliance

- **Right to access** - Export user data via `/settings/export`
- **Right to deletion** - Soft delete + anonymization after 30 days
- **Data portability** - JSON export of all user-owned data
- **Consent tracking** - Stored in `user_consents` table

10. Future Considerations

Planned Improvements

- [ ] Edge caching for static tenant data
- [ ] Read replicas for analytics queries
- [ ] Background job queue (Inngest or Trigger.dev)
- [ ] Full-text search (Postgres `tsvector` or Algolia)
- [ ] Internationalization (i18n)
- [ ] Mobile app (React Native + Expo)

Known Limitations

Limitation	Impact	Workaround
Supabase connection limits	High concurrency	Connection pooling, PgBouncer
Vercel function timeout (10s)	Long operations	Background jobs
No real-time

```
    Middle Tier
    Bottom Tier
    Base Tier
    Apex
Pyramid Tier Model
```

API Styles
REST over HTTP - Core Principles

Principle	Description
Resource-oriented	Everything is a resource (noun, not verb)
Uniform interface	Standard HTTP methods and status codes
Stateless	Each request contains all needed information
Cacheable	Responses must define cacheability
Layered system	Client doesn't know if it's talking to the server or a proxy

REST Level Models (Richardson Maturity Model)

Level 0 - The Swamp of POX
- Single URI, single HTTP method (usually POST)
- Example: SOAP, XML-RPC
- Tunneling everything through one endpoint

Level 1 - Resources
- Multiple URIs for different resources
- Still using only one HTTP method
- Example: `/users`, `/products`, `/orders`

Level 2 - HTTP Verbs
- Proper use of HTTP methods (GET, POST, PUT, DELETE)
- Status codes convey meaning
- Most common level in practice

Level 3 - Hypermedia Controls (HATEOAS)
- Responses include links to related actions
- Client discovers API dynamically
- Example: `{"_links": {"self": "/users/1", "orders": "/users/1/orders"}}`

HTTP Methods

Method	Safe	Idempotent	Cacheable	Request Body	Response Body
GET	Yes	Yes	Yes	No	Yes
HEAD	Yes	Yes	Yes	No	No
POST	No	No	Yes*	Yes	Yes
PUT	No	Yes	No	Yes	Yes
DELETE	No	Yes	No	Optional	Optional
PATCH	No	No	Yes*	Yes	Yes
OPTIONS	Yes	Yes	No	Optional	Yes

*Cacheable if explicit freshness information is provided

Status Code Families

Family	Meaning	Examples
1xx	Informational	100 Continue, 101 Switching Protocols
2xx	Success	200 OK, 201 Created, 204 No Content
3xx	Redirection	301 Moved Permanently, 304 Not Modified
4xx	Client Error	400 Bad Request, 401 Unauthorized, 403 Forbidden, 404 Not Found, 429 Too Many Requests
5xx	Server Error	500 Internal Server Error, 502 Bad Gateway, 503 Service Unavailable, 504 Gateway Timeout

Common Status Codes

Code	Name	When to Use
200	OK	Successful GET, PUT, PATCH, or DELETE
201	Created	Successful POST that created a resource
204	No Content	Successful request with no response body
301	Moved Permanently	Resource has a new permanent URI
304	Not Modified	Cached version is still valid
400	Bad Request	Malformed request syntax or invalid parameters
401	Unauthorized	Missing or invalid authentication
403	Forbidden	Authenticated but not authorized
404	Not Found	Resource doesn't exist
409	Conflict	Request conflicts with current state
422	Unprocessable Entity	Validation errors
429	Too Many Requests	Rate limit exceeded
500	Internal Server Error	Unexpected server error
502	Bad Gateway	Upstream server returned invalid response
503	Service Unavailable	Server temporarily overloaded
504	Gateway Timeout	Upstream server timeout

Error Response Format

```
{
  "error": {
    "code": "VALIDATION_ERROR",
    "message": "Invalid request parameters",
    "details": [
      {
        "field": "email",
        "message": "must be a valid email address"
      }
    ],
    "request_id": "abc-123-def"
  }
}
```

Content Negotiation

```
Accept: application/json
Accept: application/xml
Accept: text/html
Accept: */*
Accept: application/json, text/plain;q=0.9, */*;q=0.8
```

Versioning Strategies

Strategy	Example	Pros	Cons
URI path	`/v1/users`	Explicit, easy to route	Duplicates resources
Query parameter	`/users?version=1`	Optional, backward compatible	Easy to forget
Header	`Accept: application/vnd.myapi.v1+json`	Clean URIs	Hidden, harder to test
Content negotiation	`Accept: application/vnd.myapi+json;version=1`	Flexible	Complex

Pagination Patterns

Pattern	Example	Best For
Offset-based	`?offset=20&limit=10`	Simple, small datasets
Cursor-based	`?cursor=eyJpZCI6MTAwfQ&limit=10`	Large datasets, real-time data
Page-based	`?page=3&per_page=10`	User-facing UIs

Cursor-based response:

```
{
  "data": [...],
  "pagination": {
    "next_cursor": "eyJpZCI6MTEwfQ",
    "has_more": true
  }
}
```

Rate Limiting Headers

```
X-RateLimit-Limit: 1000
X-RateLimit-Remaining: 742
X-RateLimit-Reset: 1640995200
Retry-After: 3600
```

Idempotency Keys

```
POST /payments
Idempotency-Key: unique-client-generated-key-123
```

Server stores the key and response. Duplicate requests return the stored response without re-processing.

HATEOAS Example

```
{
  "id": 42,
  "status": "pending",
  "_links": {
    "self": { "href": "/orders/42" },
    "cancel": { "href": "/orders/42/cancel", "method": "POST" },
    "payment": { "href": "/orders/42/payment", "method": "POST" }
  }
}
```

GraphQL

```
query {
  user(id: 1) {
    name
    email
    orders(last: 5) {
      id
      total
    }
  }
}
```

```
mutation {
  createUser(input: { name: "Alice", email: "alice@example.com" }) {
    id
    name
  }
}
```

```
subscription {
  orderStatusChanged(orderId: 42) {
    id
    status
  }
}
```

Schema Definition Language (SDL)

```
type User {
  id: ID!
  name: String!
  email: String!
  orders(last: Int): [Order!]!
}

type Order {
  id: ID!
  total: Float!
  status: OrderStatus!
}

enum OrderStatus {
  PENDING
  SHIPPED
  DELIVERED
}
```

Resolver Pattern

```
const resolvers = {
  Query: {
    user: (parent, { id }, context) => context.db.users.findById(id),
  },
  User: {
    orders: (parent, { last }, context) => context.db.orders.findByUserId(parent.id, last),
  },
};
```

Schema Stitching / Federation

```
type Product @key(fields: "upc") {
  upc: String!
  name: String!
  price: Int!
}
```

Protocol Buffers

```
syntax = "proto3";

message User {
  int32 id = 1;
  string name = 2;
  string email = 3;
  repeated Order orders = 4;
}

message Order {
  int32 id = 1;
  float total = 2;
  OrderStatus status = 3;
}

enum OrderStatus {
  PENDING = 0;
  SHIPPED = 1;
  DELIVERED = 2;
}

service UserService {
  rpc GetUser (GetUserRequest) returns (User);
  rpc ListUsers (ListUsersRequest) returns (stream User);
}
```

Scalar Types

Type	Notes
`int32`, `int64`	Variable-length encoding
`float`, `double`	IEEE 754
`bool`	
`string`	UTF-8 or 7-bit ASCII
`bytes`	Arbitrary byte sequence

Field Rules

Rule	Description
`singular`	Default, zero or one
`repeated`	Zero or more (like a list)
`optional`	Explicit presence tracking

When to Use Each API Style

Style	Best For	Avoid When
REST	Public APIs, CRUD operations, broad client support	Complex queries, real-time data
GraphQL	Complex data requirements, multiple clients with different needs	Simple CRUD, file uploads
gRPC	Internal microservices, high performance, streaming	Browser clients, public APIs

Authentication & Authorization
Authentication vs Authorization

	Authentication	Authorization
Question	Who are you?	What can you do?
When	First	After authentication
Example	Login with password	Admin can delete users

Session-Based Authentication

Cookie Attributes

Attribute	Purpose
`HttpOnly`	Prevents JavaScript access (mitigates XSS)
`Secure`	Only sent over HTTPS
`SameSite=Strict`	Not sent on cross-site requests
`SameSite=Lax`	Sent on top-level navigation only
`SameSite=None`	Sent on all requests (requires `Secure`)
`Domain`	Which domains receive the cookie
`Path`	Which paths receive the cookie
`Max-Age`	Lifetime in seconds
`Expires`	Absolute expiration date

Token-Based Authentication

JWT Structure

Header:

```
{
  "alg": "HS256",
  "typ": "JWT"
}
```

Payload (Claims):

```
{
  "sub": "1234567890",
  "name": "John Doe",
  "iat": 1516239022,
  "exp": 1516242622,
  "iss": "https://auth.example.com",
  "aud": "https://api.example.com"
}
```

Registered Claims

Claim	Name	Description
`iss`	Issuer	Who created the token
`sub`	Subject	Who the token is about
`aud`	Audience	Who the token is intended for
`exp`	Expiration	When the token expires
`nbf`	Not Before	When the token becomes valid
`iat`	Issued At	When the token was created
`jti`	JWT ID	Unique identifier for the token

Signature Algorithms

Algorithm	Type	Key
`HS256`	HMAC + SHA-256	Shared secret
`RS256`	RSA + SHA-256	Public/private key pair
`ES256`	ECDSA + SHA-256	Public/private key pair
`EdDSA`	Edwards-curve	Public/private key pair

Verification Steps

1. Decode the header and payload
2. Check `alg` matches expected algorithm (never trust the token blindly)
3. Verify the signature
4. Check `exp` — reject if expired
5. Check `nbf` — reject if not yet valid
6. Check `iss` and `aud` match expected values

Refresh Token Flow

Refresh Token Rotation

Each time a refresh token is used, issue a new refresh token and invalidate the old one. If a revoked refresh token is reused, revoke the entire token family (indicates theft).

OAuth 2.0

Grant Types

Grant	Use Case
Authorization Code	Web apps with a backend server
Authorization Code + PKCE	Mobile apps, SPAs, public clients
Client Credentials	Machine-to-machine, no user involved
Device Code	Smart TVs, CLI tools, limited input devices
Refresh Token	Obtain new access tokens without re-authentication

Authorization Code Flow

Authorization Code + PKCE Flow

Client Credentials Flow

Device Code Flow

Scopes

```
scope=read:users write:users admin
```

Token Introspection

```
POST /introspect
Content-Type: application/x-www-form-urlencoded

token=eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9...
```

Response:

```
{
  "active": true,
  "scope": "read:users write:users",
  "client_id": "my-app",
  "username": "john",
  "exp": 1516242622
}
```

Token Revocation

```
POST /revoke
Content-Type: application/x-www-form-urlencoded

token=eyJhbGciOiJIUzI1NiIsInR5cCI6IkpXVCJ9...&token_type_hint=refresh_token
```

Session vs Token Comparison

Aspect	Session-Based	Token-Based
State	Stateful (server stores sessions)	Stateless (token is self-contained)
Storage	Server memory / database	Client (cookie, localStorage, memory)
Scalability	Requires shared session store	Scales horizontally
Revocation	Delete session	Wait for expiry or maintain blocklist
Cross-domain	Difficult	Easy
Mobile	Awkward	Natural
CSRF risk	Yes	No (if not stored in cookies)
XSS risk	Lower (HttpOnly cookies)	Higher (if stored in localStorage)

Common Vulnerabilities

Vulnerability	Description	Mitigation
Token theft	Attacker steals access token	Short expiry, HTTPS, HttpOnly cookies
Replay attack	Attacker reuses a captured token	Short expiry, nonce, token binding
Algorithm confusion	Attacker changes `alg` to `none` or switches RS256 to HS256	Explicitly verify algorithm server-side
Token sidejacking	Token used from different client	Bind token to client fingerprint
Insufficient scope	Token has more permissions than needed	Request minimal scopes
Open redirect	`redirect_uri` manipulated to attacker's site	Strict `redirect_uri` validation
CSRF on login	Attacker forces victim to log in as attacker	`state` parameter, `SameSite` cookies

Security Checklist

- Always use HTTPS
- Store tokens securely (HttpOnly cookies or memory, never localStorage for sensitive tokens)
- Validate all JWT claims (`exp`, `iss`, `aud`, `nbf`)
- Use short-lived access tokens (5–15 minutes)
- Implement refresh token rotation
- Use PKCE for all public clients
- Validate `redirect_uri` against a strict allowlist
- Request minimal scopes
- Implement token revocation
- Set `SameSite=Lax` or `Strict` on session cookies
- Never put secrets in JWT payloads (they are base64-encoded, not encrypted)
- Always verify the JWT signature server-side
- Use `state` parameter to prevent CSRF in OAuth flows

Testing Strategy
Testing Pyramid

Test Categories

Category	Scope	Speed	Dependencies
Unit	Single function or class	Milliseconds	None (mocked)
Integration	Multiple components together	Seconds	Real databases, APIs
End-to-end	Full system from user perspective	Minutes	Everything

Unit Test Example

```
test('adds 1 + 2 to equal 3', () => {
  expect(sum(1, 2)).toBe(3);
});
```

Integration Test Example

```
test('creates user and retrieves it', async () => {
  const response = await request(app)
    .post('/users')
    .send({ name: 'Alice', email: 'alice@example.com' });
  expect(response.status).toBe(201);

  const user = await request(app)
    .get(`/users/${response.body.id}`);
  expect(user.body.name).toBe('Alice');
});
```

Test Doubles

Type	Description	Example
Stub	Returns canned responses	`getUser() → { id: 1, name: "Test" }`
Mock	Verifies it was called correctly	`expect(sendEmail).toHaveBeenCalledWith(...)`
Fake	Working implementation, simplified	In-memory database
Spy	Records calls for later inspection	Wraps real function

Testing Anti-Patterns

Anti-Pattern	Problem	Fix
Testing implementation	Tests break on refactor	Test behavior, not internals
Flaky tests	Pass/fail randomly	Remove timing dependencies, isolate state
Slow test suite	Developers stop running tests	Parallelize, optimize, move to integration
Test duplication	Same logic tested in many places	Test once at the right level
Ice cream cone	Too many E2E, too few unit tests	Invert the pyramid

Property-Based Testing

```
test('reversing a list twice returns the original', () => {
  fc.assert(
    fc.property(fc.array(fc.integer()), (arr) => {
      expect(reverse(reverse(arr))).toEqual(arr);
    })
  );
});
```

Code Coverage

Metric	What It Measures
Line coverage	Which lines were executed
Branch coverage	Which `if`/`else` paths were taken
Function coverage	Which functions were called
Statement coverage	Which statements were executed

Test Organization

```
tests/
  unit/
    user.test.ts
    order.test.ts
  integration/
    api.test.ts
    database.test.ts
  e2e/
    checkout.test.ts
  fixtures/
    users.json
  helpers/
    setup.ts
```

Naming Convention

```
describe('UserService', () => {
  describe('createUser', () => {
    it('should return the created user with an id', () => {});
    it('should throw ValidationError when email is missing', () => {});
    it('should throw ConflictError when email already exists', () => {});
  });
});
```

Test Fixtures

Approach	Description
Factory functions	`createUser({ name: "Test" })` with sensible defaults
Seed files	Load JSON/SQL into test database
Builders	`new UserBuilder().withName("Test").build()`

Mocking Boundaries

Snapshot Testing

```
test('renders correctly', () => {
  const tree = renderer.create(<Button label="Click me" />).toJSON();
  expect(tree).toMatchSnapshot();
});
```

Test Commands

```
npm test
npm test -- --watch
npm test -- --coverage
npm test -- user.test.ts
npm test -- -t "creates user"
```

Continuous Testing

```
name: Test
on: [push, pull_request]
jobs:
  test:
    runs-on: ubuntu-latest
    steps:
      - uses: actions/checkout@v4
      - uses: actions/setup-node@v4
        with:
          node-version: 20
      - run: npm ci
      - run: npm test -- --coverage
```

Testing Environments

Environment	Purpose	Data
Local	Developer machine	Fixtures, seeds
CI	Automated pipeline	Fixtures, seeds
Staging	Pre-production	Anonymized production data
Production	Live system	Real data

Test Data Management

Strategy	Description	Pros	Cons
Fixtures	Static files loaded before tests	Simple, predictable	Can become stale
Factories	Generate data programmatically	Flexible, always valid	More code to maintain
Database snapshots	Restore DB to known state	Fast for large datasets	Requires DB support
Transactions	Wrap each test in a rollback	Clean, fast	Doesn't work for all scenarios

Accessibility Testing

```
test('has no accessibility violations', async () => {
  const { container } = render(<LoginForm />);
  const results = await axe(container);
  expect(results).toHaveNoViolations();
});
```

Performance Testing

Type	Purpose
Load testing	Expected traffic
Stress testing	Beyond capacity
Soak testing	Sustained load over time
Spike testing	Sudden traffic surge

Appendix: Multiple Dependency Graph