

ASSIGNMENT

MACHINE LEARNING

Worksheet -2

1. Movie Recommendation systems are an example of:

- i) Classification
- ii) Clustering
- iii) Regression

Options:

- a) 2 Only
- b) 1 and 2
- c) 1 and 3
- d) 2 and 3

Answer:- d) 2 and 3

2. Sentiment Analysis is an example of:

- i) Regression
- ii) Classification
- iii) Clustering
- iv) Reinforcement

Options:

- a) 1 Only
- b) 1 and 2
- c) 1 and 3
- d) 1, 2 and 4

Answer:- All of the above

3. Can decision trees be used for performing clustering?

- a) True
- b) False

Answer:- a) True

4. Which of the following is the most appropriate strategy for data cleaning before performing clustering analysis, given less than desirable number of data points:

- i) Capping and flooring of variables
- ii) Removal of outliers

Options:

- a) 1 only
- b) 2 only
- c) 1 and 2
- d) None of the above

Answer:- a) 1 only

5. What is the minimum no. of variables/ features required to perform clustering?

- a) 0
- b) 1
- c) 2
- d) 3

Answer:- b) 1

6. For two runs of K-Mean clustering is it expected to get same clustering results?

- a) Yes
- b) No

Answer:- b) No

7. Is it possible that Assignment of observations to clusters does not change between successive iterations in K-Means?

- a) Yes
- b) No
- c) Can't say
- d) None of these

a) Yes

8. Which of the following can act as possible termination conditions in K-Means?

- i) For a fixed number of iterations.
- ii) Assignment of observations to clusters does not change between iterations. Except for cases with a bad local minimum.
- iii) Centroids do not change between successive iterations.
- iv) Terminate when RSS falls below a threshold.

Options:

- a) 1, 3 and 4
- b) 1, 2 and 3
- c) 1, 2 and 4
- d) All of the above

Answer:- d) All of the above

9. Which of the following algorithms is most sensitive to outliers?

- a) K-means clustering algorithm
- b) K-medians clustering algorithm
- c) K-modes clustering algorithm
- d) K-medoids clustering algorithm

Answer:- a) K-means clustering algorithm

10. How can Clustering (Unsupervised Learning) be used to improve the accuracy of Linear Regression model (Supervised Learning):

- i) Creating different models for different cluster groups.
- ii) Creating an input feature for cluster ids as an ordinal variable.
- iii) Creating an input feature for cluster centroids as a continuous variable.
- iv) Creating an input feature for cluster size as a continuous variable.

Options:

- a) 1 only
- b) 2 only
- c) 3 and
- 4 d) All of the above

Answer:- 4 d) All of the above

11. What could be the possible reason(s) for producing two different dendrograms using agglomerative clustering algorithms for the same dataset?

- a) Proximity function used
- b) of data points used
- c) of variables used
- d) All of the above

Answer: - d) All of the above

12. Is K sensitive to outliers?

Answer:- yes K is sensitive to outliers in detecting abnormal cases.

13. Why is K means better?

Answer:- K-means has been around since the 1970s and fares better than other clustering algorithms like density-based, expectation-maximisation. It is one of the most robust methods, especially for image segmentation and image annotation projects. K-means is very simple and easy to implement. However, it is unlikely to be the state-of-the-art, but for straightforward clustering, it is also a part of a larger data-processing pipeline.

14. Is K means a deterministic algorithm?

Answer:- No, It is not deterministic as running the algorithm several times on the same data, could give different results. However, to ensure consistent results, FCS Express performs *k*-means clustering using a deterministic method.