

# **Getting Started with the CLISP Common Lisp Interpreter**

# Getting Started with the CLISP Common Lisp Interpreter

- 

- 

- 

- 

-

## Getting Started with the CLISP Common Lisp Interpreter

- While logged in to **euclid** or **venus**, enter  
    `cl`  
    at the shell prompt to start the CLISP interpreter.

- 

- 


- 

-


## Getting Started with the CLISP Common Lisp Interpreter

- While logged in to **euclid** or **venus**, enter  
cl  
at the shell prompt to start the CLISP interpreter.
- CLISP's prompt is [*n*]> (e.g., [1]>, [2]>, [3]>, ...),  
where *n* is a count of the number of prompts that  
have been displayed so far.
- 
- 
-


## Getting Started with the CLISP Common Lisp Interpreter

- While logged in to **euclid** or **venus**, enter  
cl  
at the shell prompt to start the CLISP interpreter.
- CLISP's prompt is **[*n*]>** (e.g., **[1]>**, **[2]>**, **[3]>**, ...), where *n* is a count of the number of prompts that have been displayed so far.
- At any prompt, you can exit from CLISP by typing  **d** or by entering **(exit)** [including the parentheses!].
- 
-

## Getting Started with the CLISP Common Lisp Interpreter


- While logged in to **euclid** or **venus**, enter  
cl  
at the shell prompt to start the CLISP interpreter.
- CLISP's prompt is **[*n*]>** (e.g., **[1]>**, **[2]>**, **[3]>**, ...), where *n* is a count of the number of prompts that have been displayed so far.
- At any prompt, you can exit from CLISP by typing  **d** or by entering **(exit)** [including the parentheses!].
- At any prompt, you can enter a Lisp expression to be evaluated. Lisp will **read** in your expression, **evaluate** it, and then **print** the expression's value.
-

# Getting Started with the CLISP Common Lisp Interpreter

- While logged in to **euclid** or **venus**, enter  
cl  
at the shell prompt to start the CLISP interpreter.
- CLISP's prompt is [*n*]> (e.g., [1]>, [2]>, [3]>, ...), where *n* is a count of the number of prompts that have been displayed so far.
- At any prompt, you can exit from CLISP by typing d or by entering **(exit)** [*including* the parentheses!].
- At any prompt, you can enter a Lisp expression to be evaluated. Lisp will **read** in your expression, **evaluate** it, and then **print** the expression's value.
- Lisp expressions are written in a special notation:  


Java:	Lisp:
Java:	Lisp:
Java:	Lisp:

## Getting Started with the CLISP Common Lisp Interpreter


- While logged in to **euclid** or **venus**, enter  
    `cl`  
    at the shell prompt to start the CLISP interpreter.
- CLISP's prompt is `[n]>` (e.g., `[1]>`, `[2]>`, `[3]>`, ...), where *n* is a count of the number of prompts that have been displayed so far.
- At any prompt, you can exit from CLISP by typing  **d** or by entering **(exit)** [including the parentheses!].
- At any prompt, you can enter a Lisp expression to be evaluated. Lisp will **read** in your expression, **evaluate** it, and then **print** the expression's value.
- Lisp expressions are written in a special notation:  
    Java: 3 - 4.1                      Lisp: (- 3 4.1)  
    Java:                                Lisp:  
    Java:                                Lisp:



## Getting Started with the CLISP Common Lisp Interpreter

- While logged in to **euclid** or **venus**, enter  
    `cl`  
at the shell prompt to start the CLISP interpreter.
- CLISP's prompt is `[n]>` (e.g., `[1]>`, `[2]>`, `[3]>`, ...), where *n* is a count of the number of prompts that have been displayed so far.
- At any prompt, you can exit from CLISP by typing  **d** or by entering **(exit)** [including the parentheses!].
- At any prompt, you can enter a Lisp expression to be evaluated. Lisp will **read** in your expression, **evaluate** it, and then **print** the expression's value.
- Lisp expressions are written in a special notation:  
    Java: 3 - 4.1                      Lisp: (- 3 4.1)  
    Java: 3 - 4.1 + 2                  Lisp: (+ (- 3 4.1) 2)  
    Java:                                Lisp:

## Getting Started with the CLISP Common Lisp Interpreter

- While logged in to **euclid** or **venus**, enter  
    `cl`  
    at the shell prompt to start the CLISP interpreter.
- CLISP's prompt is `[n]>` (e.g., `[1]>`, `[2]>`, `[3]>`, ...), where *n* is a count of the number of prompts that have been displayed so far.
- At any prompt, you can exit from CLISP by typing  **d** or by entering **(exit)** [including the parentheses!].
- At any prompt, you can enter a Lisp expression to be evaluated. Lisp will **read** in your expression, **evaluate** it, and then **print** the expression's value.
- Lisp expressions are written in a special notation:

Java: <code>3 - 4.1</code>	Lisp: <code>(- 3 4.1)</code>
Java: <code>3 - 4.1 + 2</code>	Lisp: <code>(+ (- 3 4.1) 2)</code>
Java: <code>Math.sqrt(3*4.1)</code>	Lisp: <code>(sqrt (* 3 4.1))</code>

# Getting Started with the CLISP Common Lisp Interpreter

- At any prompt, you can enter a Lisp expression to be evaluated. Lisp will *read* in your expression, *evaluate* it, and then *print* the expression's value.
- Lisp expressions are written in a special notation:

Java: 3 - 4.1	Lisp: (- 3 4.1)
Java: 3 - 4.1 + 2	Lisp: (+ (- 3 4.1) 2)
Java: Math.sqrt(3*4.1)	Lisp: (sqrt (* 3 4.1))

## Getting Started with the CLISP Common Lisp Interpreter

- At any prompt, you can enter a Lisp expression to be evaluated. Lisp will *read* in your expression, *evaluate* it, and then *print* the expression's value.

- Lisp expressions are written in a special notation:

Java: 3 - 4.1	Lisp: (- 3 4.1)
Java: 3 - 4.1 + 2	Lisp: (+ (- 3 4.1) 2)
Java: Math.sqrt(3*4.1)	Lisp: (sqrt (* 3 4.1))


## Getting Started with the CLISP Common Lisp Interpreter

- At any prompt, you can enter a Lisp expression to be evaluated. Lisp will *read* in your expression, *evaluate* it, and then *print* the expression's value.
- Lisp expressions are written in a special notation:

Java: 3 - 4.1	Lisp: (- 3 4.1)
Java: 3 - 4.1 + 2	Lisp: (+ (- 3 4.1) 2)
Java: Math.sqrt(3*4.1)	Lisp: (sqrt (* 3 4.1))
- If an integer that is a perfect square (e.g., 9) is passed as argument to CLISP's sqrt, its *integer* square root is returned; in some other implementations of Common Lisp, a floating point result is returned.

## From p. 3 of Touretzky:

In this book we will work mostly with **integers**, which are whole numbers. Common Lisp provides many other kinds of numbers. One kind you should know about is **floating point** numbers. A floating point number is always written with a decimal point; for example, the number five would be written 5.0. The Sqrt function generally returns a floating point number as its result, even when its input is an integer.



**Note:** In Clisp, Sqrt returns an integer if its argument is a perfect square.

**Ratios** are yet another kind of number. On a pocket calculator, one-half must be written in floating point notation, as 0.5, but in Common Lisp we can also write one-half as the ratio 1/2. Common Lisp automatically simplifies ratios to use the smallest possible denominator; for example, the ratios 4/6, 6/9, and 10/15 would all be simplified to 2/3.

## Getting Started with the CLISP Common Lisp Interpreter

- At any prompt, you can enter a Lisp expression to be evaluated. Lisp will *read* in your expression, *evaluate* it, and then *print* the expression's value.
- Lisp expressions are written in a special notation:

Java: 3 - 4.1	Lisp: (- 3 4.1)
Java: 3 - 4.1 + 2	Lisp: (+ (- 3 4.1) 2)
Java: Math.sqrt(3*4.1)	Lisp: (sqrt (* 3 4.1))
- If an integer that is a perfect square (e.g., 9) is passed as argument to CLISP's sqrt, its *integer* square root is returned; in some other implementations of Common Lisp, a floating point result is returned.

## Getting Started with the CLISP Common Lisp Interpreter

- At any prompt, you can enter a Lisp expression to be evaluated. Lisp will *read* in your expression, *evaluate* it, and then *print* the expression's value.
- Lisp expressions are written in a special notation:

Java: 3 - 4.1	Lisp: (- 3 4.1)
Java: 3 - 4.1 + 2	Lisp: (+ (- 3 4.1) 2)
Java: Math.sqrt(3*4.1)	Lisp: (sqrt (* 3 4.1))
- If an integer that is a perfect square (e.g., 9) is passed as argument to CLISP's sqrt, its *integer* square root is returned; in some other implementations of Common Lisp, a floating point result is returned.
- If evaluation of an expression produces an error, then CLISP prints an error message followed by a **Break ... >** prompt:



## Getting Started with the CLISP Common Lisp Interpreter

- At any prompt, you can enter a Lisp expression to be evaluated. Lisp will *read* in your expression, *evaluate* it, and then *print* the expression's value.
- Lisp expressions are written in a special notation:

Java: 3 - 4.1	Lisp: (- 3 4.1)
Java: 3 - 4.1 + 2	Lisp: (+ (- 3 4.1) 2)
Java: Math.sqrt(3*4.1)	Lisp: (sqrt (* 3 4.1))
- If an integer that is a perfect square (e.g., 9) is passed as argument to CLISP's sqrt, its *integer* square root is returned; in some other implementations of Common Lisp, a floating point result is returned.
- If evaluation of an expression produces an error, then CLISP prints an error message followed by a **Break ... >** prompt: You can enter **:q** at a **Break ... >** prompt to get back to the regular **[n]>** prompt!

## Getting Started with the CLISP Common Lisp Interpreter

- At any prompt, you can enter a Lisp expression to be evaluated. Lisp will **read** in your expression, **evaluate** it, and then **print** the expression's value.
- Lisp expressions are written in a special notation:

Java: 3 - 4.1	Lisp: (- 3 4.1)
Java: 3 - 4.1 + 2	Lisp: (+ (- 3 4.1) 2)
Java: Math.sqrt(3*4.1)	Lisp: (sqrt (* 3 4.1))
- If an integer that is a perfect square (e.g., 9) is passed as argument to CLISP's sqrt, its **integer** square root is returned; in some other implementations of Common Lisp, a floating point result is returned.
- If evaluation of an expression produces an error, then CLISP prints an error message followed by a **Break ... >** prompt: You can enter **:q** at a **Break ... >** prompt to get back to the regular **[n]>** prompt!  
**Example:** The function sqrt expects just one argument, so evaluation of (sqrt 4 5) produces a **Break ... >**.

# **Assigning Values to Global Variables**

## Assigning Values to Global Variables

- **SETF** can be used to assign a value to a variable:

## Assigning Values to Global Variables

- **SETF** can be used to assign a value to a variable:

evaluation of `(setf x expr)` has the side-effect of **assigning *expr*'s value to the variable *x*.**

## Assigning Values to Global Variables

- **SETF** can be used to assign a value to a variable:  
The value of the Lisp expression `(setf x expr)` is the value of `expr`--e.g., the value of `(+ (setf x 3) 5)` is 8--but evaluation of `(setf x expr)` has the side-effect of assigning `expr`'s value to the variable `x`.

## Assigning Values to Global Variables

- **SETF** can be used to assign a value to a variable:  
The value of the Lisp expression `(setf x expr)` is the value of `expr`--e.g., the value of `(+ (setf x 3) 5)` is 8--but evaluation of `(setf x expr)` has the side-effect of assigning `expr`'s value to the variable `x`.
- Thus `(setf x ...)` is analogous to a C++ or Java expression of the form `(x = ...)`!

## Assigning Values to Global Variables

- **SETF** can be used to assign a value to a variable:  
The value of the Lisp expression `(setf x expr)` is the value of `expr`--e.g., the value of `(+ (setf x 3) 5)` is 8--but evaluation of `(setf x expr)` has the side-effect of assigning `expr`'s value to the variable `x`.
- Thus `(setf x ...)` is analogous to a C++ or Java expression of the form `(x = ...)`!
- Once a variable has been assigned a value, the variable can be used to represent that value in subsequent expressions.



## Assigning Values to Global Variables

- **SETF** can be used to assign a value to a variable:  
The value of the Lisp expression `(setf x expr)` is the value of `expr`--e.g., the value of `(+ (setf x 3) 5)` is 8--but evaluation of `(setf x expr)` has the side-effect of assigning `expr`'s value to the variable `x`.
- Thus `(setf x ...)` is analogous to a C++ or Java expression of the form `(x = ...)`!
- Once a variable has been assigned a value, the variable can be used to represent that value in subsequent expressions.
- **IMPORTANT**: SETF is not used in pure functional programming,

## Assigning Values to Global Variables

- **SETF** can be used to assign a value to a variable:  
The value of the Lisp expression `(setf x expr)` is the value of `expr`--e.g., the value of `(+ (setf x 3) 5)` is 8--but evaluation of `(setf x expr)` has the side-effect of assigning `expr`'s value to the variable `x`.
- Thus `(setf x ...)` is analogous to a C++ or Java expression of the form `(x = ...)`!
- Once a variable has been assigned a value, the variable can be used to represent that value in subsequent expressions.
- **IMPORTANT**: SETF is not used in pure functional programming, so the Lisp functions you write when doing programming assignments or answering exam questions must not use SETF!

## Assigning Values to Global Variables

- **SETF** can be used to assign a value to a variable:  
The value of the Lisp expression `(setf x expr)` is the value of `expr`--e.g., the value of `(+ (setf x 3) 5)` is 8--but evaluation of `(setf x expr)` has the side-effect of assigning `expr`'s value to the variable `x`.
- **IMPORTANT**: SETF is not used in pure functional programming, so the Lisp functions you write when doing programming assignments or answering exam questions must not use SETF!

## Assigning Values to Global Variables

- **SETF** can be used to assign a value to a variable:  
The value of the Lisp expression `(setf x expr)` is the value of `expr`--e.g., the value of `(+ (setf x 3) 5)` is 8--but evaluation of `(setf x expr)` has the side-effect of assigning `expr`'s value to the variable `x`.
- **IMPORTANT**: SETF is not used in pure functional programming, so the Lisp functions you write when doing programming assignments or answering exam questions must not use SETF!

## Assigning Values to Global Variables

- **SETF** can be used to assign a value to a variable:  
The value of the Lisp expression `(setf x expr)` is the value of `expr`--e.g., the value of `(+ (setf x 3) 5)` is 8--but evaluation of `(setf x expr)` has the side-effect of assigning `expr`'s value to the variable `x`.
- **IMPORTANT**: SETF is not used in pure functional programming, so the Lisp functions you write when doing programming assignments or answering exam questions must not use SETF!
- You may use SETF when testing your functions:

## Assigning Values to Global Variables

- **SETF** can be used to assign a value to a variable:  
The value of the Lisp expression `(setf x expr)` is the value of `expr`--e.g., the value of `(+ (setf x 3) 5)` is 8--but evaluation of `(setf x expr)` has the side-effect of assigning `expr`'s value to the variable `x`.
- **IMPORTANT**: SETF is not used in pure functional programming, so the Lisp functions you write when doing programming assignments or answering exam questions must not use SETF!
- You may use SETF when testing your functions:  
For example, if you plan to use  $2^{31} - 1$  as a test argument value several times, then you can use SETF to store  $2^{31} - 1$  in a variable that will be used as the actual argument each time.

# Ratios

## Ratios (a type of number that represents fractions)

- Unlike C++ and Java, Common Lisp has a built-in data type called ratio that represents (positive and negative, proper and improper) fractions *exactly*, with no rounding error. Examples:



## Ratios (a type of number that represents fractions)

- Unlike C++ and Java, Common Lisp has a built-in data type called ratio that represents (positive and negative, proper and improper) fractions *exactly*, with no rounding error. Examples:

6/8 represents the positive proper fraction  $\frac{6}{8} = \frac{3}{4}$ .

## Ratios (a type of number that represents fractions)

- Unlike C++ and Java, Common Lisp has a built-in data type called ratio that represents (positive and negative, proper and improper) fractions *exactly*, with no rounding error. Examples:

6/8 represents the positive proper fraction  $\frac{6}{8} = \frac{3}{4}$ .

-5/4 represents the negative improper fraction  $\frac{-5}{4}$ .

## Ratios (a type of number that represents fractions)

- Unlike C++ and Java, Common Lisp has a built-in data type called ratio that represents (positive and negative, proper and improper) fractions *exactly*, with no rounding error. Examples:

6/8 represents the positive proper fraction  $\frac{6}{8} = \frac{3}{4}$ .

-5/4 represents the negative improper fraction  $\frac{-5}{4}$ .

- Ratios are always *printed in lowest terms* (but they need not be written in lowest terms): You can write 6/8, but this ratio would be printed as 3/4.

## Ratios (a type of number that represents fractions)

- Unlike C++ and Java, Common Lisp has a built-in data type called ratio that represents (positive and negative, proper and improper) fractions *exactly*, with no rounding error. Examples:

6/8 represents the positive proper fraction  $\frac{6}{8} = \frac{3}{4}$ .

-5/4 represents the negative improper fraction  $\frac{-5}{4}$ .

- Ratios are always *printed in lowest terms* (but they need not be written in lowest terms): You can write 6/8, but this ratio would be printed as 3/4.
- If m and n are integers, n is not 0, and n does not divide m, then *the value of (/ m n) is a ratio*. For example, the value of (/ 12 9) is  $12/9 = 4/3$ .

## Ratios (a type of number that represents fractions)

- Unlike C++ and Java, Common Lisp has a built-in data type called ratio that represents (positive and negative, proper and improper) fractions *exactly*, with no rounding error. Examples:

6/8 represents the positive proper fraction  $\frac{6}{8} = \frac{3}{4}$ .

-5/4 represents the negative improper fraction  $\frac{-5}{4}$ .

- Ratios are always *printed in lowest terms* (but they need not be written in lowest terms): You can write 6/8, but this ratio would be printed as 3/4.
- If m and n are integers, n is not 0, and n does not divide m, then *the value of (/ m n) is a ratio*. For example, the value of (/ 12 9) is 12/9 = 4/3.
- There is *no space* before or after the / in a ratio: 5/7 cannot be written as 5 /7 or 5/ 7.

## Ratios (a type of number that represents fractions)

- Unlike C++ and Java, Common Lisp has a built-in data type called ratio that represents fractions *exactly*, with no rounding error.
- Ratios are always *printed in lowest terms* (but they need not be written in lowest terms): You can write 6/8, but this ratio would be printed as 3/4.
- If  $m$  and  $n$  are integers,  $n$  is not 0, and  $n$  does not divide  $m$ , then *the value of (`/ m n`) is a ratio*. For example, the value of (`/ 12 9`) is  $12/9 = 4/3$ .
- There is *no space* before or after the `/` in a ratio: 5/7 cannot be written as 5 /7 or 5/ 7.

## Ratios (a type of number that represents fractions)

- Unlike C++ and Java, Common Lisp has a built-in data type called ratio that represents fractions *exactly*, with no rounding error.
- Ratios are always *printed in lowest terms* (but they need not be written in lowest terms): You can write 6/8, but this ratio would be printed as 3/4.
- If m and n are integers, n is not 0, and n does not divide m, then *the value of (/ m n) is a ratio*. For example, the value of (/ 12 9) is 12/9 = 4/3.
- There is *no space* before or after the / in a ratio: 5/7 cannot be written as 5 /7 or 5/ 7.

## Ratios (a type of number that represents fractions)

- Unlike C++ and Java, Common Lisp has a built-in data type called ratio that represents fractions *exactly*, with no rounding error.
- Ratios are always *printed in lowest terms* (but they need not be written in lowest terms): You can write 6/8, but this ratio would be printed as 3/4.
- If m and n are integers, n is not 0, and n does not divide m, then *the value of (/ m n) is a ratio*. For example, the value of (/ 12 9) is  $12/9 = 4/3$ .
- There is *no space* before or after the / in a ratio: 5/7 cannot be written as 5 /7 or 5/ 7.



## Ratios (a type of number that represents fractions)

- Unlike C++ and Java, Common Lisp has a built-in data type called ratio that represents fractions *exactly*, with no rounding error.
- Ratios are always *printed in lowest terms* (but they need not be written in lowest terms): You can write 6/8, but this ratio would be printed as 3/4.
- If m and n are integers, n is not 0, and n does not divide m, then *the value of (/ m n) is a ratio*. For example, the value of (/ 12 9) is  $12/9 = 4/3$ .
- There is *no space* before or after the / in a ratio: 5/7 cannot be written as 5 /7 or 5/ 7.
- In Common Lisp, a number is said to be *rational* if it is either an integer or a ratio.

## Ratios (a type of number that represents fractions)

- Unlike C++ and Java, Common Lisp has a built-in data type called ratio that represents fractions *exactly*, with no rounding error.
- Ratios are always *printed in lowest terms* (but they need not be written in lowest terms): You can write 6/8, but this ratio would be printed as 3/4.
- If  $m$  and  $n$  are integers,  $n$  is not 0, and  $n$  does not divide  $m$ , then *the value of (`/ m n`) is a ratio*. For example, the value of (`/ 12 9`) is  $12/9 = 4/3$ .
- There is *no space* before or after the `/` in a ratio: `5/7` cannot be written as `5 /7` or `5/ 7`.
- In Common Lisp, a number is said to be *rational* if it is either an integer or a ratio.
- The functions `+`, `-`, `*`, and `/` accept rational and floating point argument values:

## Ratios (a type of number that represents fractions)

- Unlike C++ and Java, Common Lisp has a built-in data type called ratio that represents fractions *exactly*, with no rounding error.
- Ratios are always *printed in lowest terms* (but they need not be written in lowest terms): You can write 6/8, but this ratio would be printed as 3/4.
- If  $m$  and  $n$  are integers,  $n$  is not 0, and  $n$  does not divide  $m$ , then *the value of (/ m n) is a ratio*. For example, the value of (/ 12 9) is  $12/9 = 4/3$ .
- There is *no space* before or after the / in a ratio: 5/7 cannot be written as 5 /7 or 5/ 7.
- In Common Lisp, a number is said to be *rational* if it is either an integer or a ratio.
- The functions +, -, \*, and / accept rational and floating point argument values: If each argument value is rational, the returned result will also be rational; otherwise, the result will be a floating point number.