

Example Write a function **safe-sum** such that:

- If $L \Rightarrow$ a proper list of numbers, then
(safe-sum L) \Rightarrow the sum of the elements of that list.
- If $L \Rightarrow$ a proper list whose elements are not all numbers, then
(safe-sum L) \Rightarrow the symbol **ERR!**.

```
(defun safe-sum (L)
  (cond ((null L) 0)
        ((not (numberp (car L))) 'ERR!)
        (t (let ((X (safe-sum (cdr L))))
              (cond ((numberp X) (+ (car L) X))
                    (t 'ERR!))))))
```

2nd version
of the final
definition.

•

•

Example Write a function **safe-sum** such that:

- If $L \Rightarrow$ a proper list of numbers, then
 $(\text{safe-sum } L) \Rightarrow$ the sum of the elements of that list.
- If $L \Rightarrow$ a proper list whose elements are not all numbers, then
 $(\text{safe-sum } L) \Rightarrow$ the symbol **ERR!**.

```
(defun safe-sum (L)
  (cond ((null L) 0)
        ((not (numberp (car L))) 'ERR!)
        (t (let ((X (safe-sum (cdr L))))
              (cond ((numberp X) (+ (car L) X))
                    (t 'ERR!))))))
```

**2nd version
of the final
definition.**

- We didn't eliminate the LET, as its local variable X is used twice in the case where each of (car L) and X \Rightarrow a number.
-

Example Write a function **safe-sum** such that:

- *If $L \Rightarrow$ a proper list of numbers, then
 $(\text{safe-sum } L) \Rightarrow$ the sum of the elements of that list.*
- *If $L \Rightarrow$ a proper list whose elements are not all numbers, then
 $(\text{safe-sum } L) \Rightarrow$ the symbol **ERR!**.*

```
(defun safe-sum (L)
  (cond ((null L) 0)
        ((not (numberp (car L))) 'ERR!)
        (t (let ((X (safe-sum (cdr L))))
              (cond ((numberp X) (+ (car L) X))
                    (t 'ERR!))))))
```

**2nd version
of the final
definition.**

- We didn't eliminate the LET, as its local variable X is used twice in the case where each of (car L) and $X \Rightarrow$ a number.
- Eliminating the LET would produce the function on the next slide, or an equivalent function that uses COND instead of nested IFs. Those functions would be extremely inefficient when L is a list of numbers: Their running time grows exponentially with the length of the list.

- Eliminating LET from the 1st version of the definition gives:

```
(defun safe-sum (L) ; very inefficient!
```

```
  (if (null L)
```

```
      0
```

```
      (if (not (numberp (car L)))
```

```
          'ERR!
```

```
          let ((x (safe-sum (cdr L))))
```

```
            (if (numberp x (safe-sum (cdr L)))
```

```
                (+ (car L) x (safe-sum (cdr L)))
```

```
                'ERR!))))))
```

- Eliminating LET from the 1st version of the definition gives:

```
(defun safe-sum (L) ; very inefficient!
```

```
  (if (null L)
```

```
      0
```

```
      (if (not (numberp (car L)))
```

```
          'ERR!
```

```
          (if (numberp      (safe-sum (cdr L)))
```

```
              (+ (car L)      (safe-sum (cdr L)))
```

```
              'ERR!))))))
```

- Eliminating LET from the 1st version of the definition gives:

```
(defun safe-sum (L) ; very inefficient!
  (if (null L)
      0
      (if (not (numberp (car L)))
          'ERR!
          (if (numberp (safe-sum (cdr L)))
              (+ (car L) (safe-sum (cdr L)))
              'ERR!))))))
```

-

-

-

-

-

- Eliminating LET from the 1st version of the definition gives:

```
(defun safe-sum (L) ; very inefficient!
  (if (null L)
      0
      (if (not (numberp (car L)))
          'ERR!
          (if (numberp (safe-sum (cdr L)))
              (+ (car L) (safe-sum (cdr L)))
              'ERR!))))))
```

- Consider a call of safe-sum with argument value (0 1 2 ... 49).

-

-

-

-

- Eliminating LET from the 1st version of the definition gives:

```
(defun safe-sum (L) ; very inefficient!
  (if (null L)
      0
      (if (not (numberp (car L)))
          'ERR!
          (if (numberp (safe-sum (cdr L)))
              (+ (car L) (safe-sum (cdr L)))
              'ERR!))))))
```

- Consider a call of `safe-sum` with argument value `(0 1 2 ... 49)`.
- It makes $2=2^1$ recursive calls with argument value `(1 2 3 ... 49)`.

-

-

-

- Eliminating LET from the 1st version of the definition gives:

```
(defun safe-sum (L) ; very inefficient!
  (if (null L)
      0
      (if (not (numberp (car L)))
          'ERR!
          (if (numberp (safe-sum (cdr L)))
              (+ (car L) (safe-sum (cdr L)))
              'ERR!))))))
```

- Consider a call of `safe-sum` with argument value `(0 1 2 ... 49)`.
- It makes $2=2^1$ recursive calls with argument value `(1 2 3 ... 49)`.
- Each of those 2^1 calls makes 2 recursive calls with argument value `(2 3 4 ... 49)`, so there are a total of $2^1 \times 2 = 2^2$ recursive calls with argument value `(2 3 4 ... 49)`.

-

-

- Eliminating LET from the 1st version of the definition gives:

```
(defun safe-sum (L) ; very inefficient!
  (if (null L)
      0
      (if (not (numberp (car L)))
          'ERR!
          (if (numberp (safe-sum (cdr L)))
              (+ (car L) (safe-sum (cdr L)))
              'ERR!))))))
```

- Consider a call of `safe-sum` with argument value `(0 1 2 ... 49)`.
- It makes $2=2^1$ recursive calls with argument value `(1 2 3 ... 49)`.
- Each of those 2^1 calls makes 2 recursive calls with argument value `(2 3 4 ... 49)`, so there are a total of $2^1 \times 2 = 2^2$ recursive calls with argument value `(2 3 4 ... 49)`.
- Each of those 2^2 calls makes 2 recursive calls with argument value `(3 4 5 ... 49)`, so there are a total of $2^2 \times 2 = 2^3$ recursive calls with argument value `(3 4 5 ... 49)`.
-

- Eliminating LET from the 1st version of the definition gives:

```
(defun safe-sum (L) ; very inefficient!
  (if (null L)
      0
      (if (not (numberp (car L)))
          'ERR!
          (if (numberp (safe-sum (cdr L)))
              (+ (car L) (safe-sum (cdr L)))
              'ERR!))))))
```

- Consider a call of `safe-sum` with argument value `(0 1 2 ... 49)`.
- It makes $2=2^1$ recursive calls with argument value `(1 2 3 ... 49)`.
- Each of those 2^1 calls makes 2 recursive calls with argument value `(2 3 4 ... 49)`, so there are a total of $2^1 \times 2 = 2^2$ recursive calls with argument value `(2 3 4 ... 49)`.
- Each of those 2^2 calls makes 2 recursive calls with argument value `(3 4 5 ... 49)`, so there are a total of $2^2 \times 2 = 2^3$ recursive calls with argument value `(3 4 5 ... 49)`.
- For $0 \leq d \leq 50$, there are 2^d calls with argument value `(d ... 49)`.

- Eliminating LET from the 1st version of the definition gives:

```
(defun safe-sum (L) ; very inefficient!
  (if (null L)
      0
      (if (not (numberp (car L)))
          'ERR!
          (if (numberp (safe-sum (cdr L)))
              (+ (car L) (safe-sum (cdr L)))
              'ERR!))))))
```

- Consider a call of `safe-sum` with argument value `(0 1 2 ... 49)`.

- For $0 \leq d \leq 50$, there are 2^d calls with argument value `(d ... 49)`.

- Eliminating LET from the 1st version of the definition gives:

```
(defun safe-sum (L) ; very inefficient!
  (if (null L)
      0
      (if (not (numberp (car L)))
          'ERR!
          (if (numberp (safe-sum (cdr L)))
              (+ (car L) (safe-sum (cdr L)))
              'ERR!))))))
```

- Consider a call of `safe-sum` with argument value `(0 1 2 ... 49)`.
- For $0 \leq d \leq 50$, there are 2^d calls with argument value `(d ... 49)`.

-

-

- Eliminating LET from the 1st version of the definition gives:

```
(defun safe-sum (L) ; very inefficient!
  (if (null L)
      0
      (if (not (numberp (car L)))
          'ERR!
          (if (numberp (safe-sum (cdr L)))
              (+ (car L) (safe-sum (cdr L)))
              'ERR!))))))
```

- Consider a call of `safe-sum` with argument value `(0 1 2 ... 49)`.
- For $0 \leq d \leq 50$, there are 2^d calls with argument value `(d ... 49)`.
 \therefore the *total* no. of *recursive* calls is $2^1 + \dots + 2^{50} = 2^{51} - 2 > 2 \times 10^{15}$.

-

-

- Eliminating LET from the 1st version of the definition gives:

```
(defun safe-sum (L) ; very inefficient!
  (if (null L)
      0
      (if (not (numberp (car L)))
          'ERR!
          (if (numberp (safe-sum (cdr L)))
              (+ (car L) (safe-sum (cdr L)))
              'ERR!))))))
```

- Consider a call of **safe-sum** with argument value (0 1 2 ... 49).
- For $0 \leq d \leq 50$, there are 2^d calls with argument value ($d \dots 49$).
 \therefore the *total* no. of *recursive* calls is $2^1 + \dots + 2^{50} = 2^{51} - 2 > 2 \times 10^{15}$.
- **General Principle:** If a function f can make 2 or more direct recursive calls, then a single call of f might well produce 2^d or more recursive calls of f at recursion depth d .



- Eliminating LET from the 1st version of the definition gives:

```
(defun safe-sum (L) ; very inefficient!
  (if (null L)
      0
      (if (not (numberp (car L)))
          'ERR!
          (if (numberp (safe-sum (cdr L)))
              (+ (car L) (safe-sum (cdr L)))
              'ERR!))))))
```

- Consider a call of **safe-sum** with argument value (0 1 2 ... 49).
- For $0 \leq d \leq 50$, there are 2^d calls with argument value (d ... 49).
 \therefore the *total* no. of *recursive* calls is $2^1 + \dots + 2^{50} = 2^{51} - 2 > 2 \times 10^{15}$.
- **General Principle:** If a function f can make 2 or more direct recursive calls, then a single call of f might well produce 2^d or more recursive calls of f at recursion depth d .
- LET can be used to prevent a function from making 2 or more direct recursive calls with the very same argument values!

- **General Principle:** If a function f can make 2 or more direct recursive calls, then a single call of f might well produce 2^d or more recursive calls of f at recursion depth d .
- LET can be used to prevent a function from making 2 or more direct recursive calls *with the very same argument values!*

- **General Principle:** If a function f can make 2 or more direct recursive calls, then a single call of f might well produce 2^d or more recursive calls of f at recursion depth d .
- LET can be used to prevent a function from making 2 or more direct recursive calls *with the very same argument values!*

-

-

- **General Principle:** If a function *f* can make 2 or more direct recursive calls, then a single call of *f* might well produce 2^d or more recursive calls of *f* at recursion depth *d*.
- LET can be used to prevent a function from making 2 or more direct recursive calls with the very same argument values!
- The 1st and 2nd versions of `safe-sum` use LET in this way.

```
(defun safe-sum (L)
  (if (null L)
      0
      (if (not (numberp (car L)))
          'ERR!
          (let ((X (safe-sum (cdr L))))
            (if (numberp X)
                (+ (car L) X)
                'ERR!))))))
```

1st version
of the final
definition.

•

- **General Principle:** If a function `f` can make 2 or more direct recursive calls, then a single call of `f` might well produce 2^d or more recursive calls of `f` at recursion depth d .
- **LET can be used to prevent a function from making 2 or more direct recursive calls with the very same argument values!**
- The 1st and 2nd versions of `safe-sum` use `LET` in this way.

```
(defun safe-sum (L)
  (if (null L)
      0
      (if (not (numberp (car L)))
          'ERR!
          (let ((X (safe-sum (cdr L))))
            (if (numberp X)
                (+ (car L) X)
                'ERR!))))))
```

1st version
of the final
definition.

- These versions never make more than one direct recursive call, as a result of which `(safe-sum '(0 1 ... 49))` computes its result using **just 50** recursive calls rather than quadrillions!

Comments on Lisp Assignment 4

Problems 1–13 can be solved by starting with one of the templates below or a dual of the 2nd template in which the roles of e1 and e2 are switched. (These are just the templates presented earlier!)

Comments on Lisp Assignment 4

Problems 1–13 can be solved by starting with one of the templates below or a dual of the 2nd template in which the roles of e1 and e2 are switched. (These are just the templates presented earlier!)

```
(defun f (e)
  (if (null e) or (zerop e)
      value of (f nil) or (f 0)
      (let ((X (f (cdr e)) or (f (- e 1)))
            an expression that  $\Rightarrow$  value of (f e)
            and that involves X and, possibly, e))))
```

```
(defun f (e1 e2)
  (if (null e1) or (zerop e1)
      value of (f nil e2) or (f 0 e2)
      (let ((X (f (cdr e1) e2) or (f (- e1 1) e2))
            an expression that  $\Rightarrow$  value of (f e1 e2) and
            that involves X and, possibly, e1 and/or e2))))
```

Comments on Lisp Assignment 4

Problems 1–13 can be solved by starting with one of the templates above or a dual of the 2nd template in which the roles of e1 and e2 are switched. (These are just the templates presented earlier!)

Recall that:

-
-

Comments on Lisp Assignment 4

Problems 1–13 can be solved by starting with one of the templates above or a dual of the 2nd template in which the roles of e1 and e2 are switched. (These are just the templates presented earlier!)

Recall that:

- If there is no case in which **X** is used more than once, then *eliminate the LET*.
-

Comments on Lisp Assignment 4

Problems 1–13 can be solved by starting with one of the templates above or a dual of the 2nd template in which the roles of e1 and e2 are switched. (These are just the templates presented earlier!)

Recall that:

- If there is no case in which **X** is used more than once, then eliminate the LET.
- If the LET isn't eliminated, move any case in which **X** needn't be used out of the LET. If the LET is eliminated but there's a case where the recursive call's result isn't needed, deal with such cases as base cases--i.e., without making a recursive call.

Debugging Suggestions

For concreteness, let's assume you are writing a 2-argument function `f` such that, when `e1` \neq `NIL`, `(f e1 e2)` computes its result from `(f (cdr e1) e2)`.

-

-

-

Debugging Suggestions

For concreteness, let's assume you are writing a 2-argument function `f` such that, when `e1` \neq `NIL`, `(f e1 e2)` computes its result from `(f (cdr e1) e2)`.

- You can use an analogous approach in other cases.

-

-

Debugging Suggestions

For concreteness, let's assume you are writing a 2-argument function `f` such that, when `e1` \neq `NIL`, `(f e1 e2)` computes its result from `(f (cdr e1) e2)`.

- You can use an analogous approach in other cases.
- We will assume the definition of `f` has the following form:

```
(defun f (e1 e2)
  (if (null e1)
      value of (f nil e2)
      (let ((X (f (cdr e1) e2)))
        an expression that  $\Rightarrow$  value of (f e1 e2) and
        that involves X and, possibly, e1 and/or e2 ))))
```

-

Debugging Suggestions

For concreteness, let's assume you are writing a 2-argument function `f` such that, when `e1` \neq `NIL`, `(f e1 e2)` computes its result from `(f (cdr e1) e2)`.

- You can use an analogous approach in other cases.
- We will assume the definition of `f` has the following form:

```
(defun f (e1 e2)
  (if (null e1)
      value of (f nil e2)
      (let ((X (f (cdr e1) e2)))
        an expression that  $\Rightarrow$  value of (f e1 e2) and
        that involves X and, possibly, e1 and/or e2 ))))
```

- However, a similar debugging approach can be used if the definition of `f` does not use `LET` (e.g., because the `LET` has been eliminated) or the definition has more than one base case before the `LET`.

Debugging Suggestions

For concreteness, let's assume you are writing a 2-argument function `f` such that, when `e1` \neq `NIL`, `(f e1 e2)` computes its result from `(f (cdr e1) e2)`.

1.

2.

Debugging Suggestions

For concreteness, let's assume you are writing a 2-argument function `f` such that, when `e1` \neq `NIL`, `(f e1 e2)` computes its result from `(f (cdr e1) e2)`.

1. Make sure you know what the base case `(f nil e2)` *should* return; test `f` to check that `(f nil e2)` always returns the right result: If it doesn't, fix the definition of `f` so it does!
- 2.

Debugging Suggestions

For concreteness, let's assume you are writing a 2-argument function `f` such that, when `e1` \neq `NIL`, `(f e1 e2)` computes its result from `(f (cdr e1) e2)`.

1. Make sure you know what the base case `(f nil e2)` *should* return; test `f` to check that `(f nil e2)` always returns the right result: If it doesn't, fix the definition of `f` so it does!
2. Call `f` with different arguments. If for certain arguments *there's an evaluation error* or *f returns an incorrect result*, find arguments `e1` and `e2` such that:
 - (i) `(f e1 e2)` \neq the correct result,
 - but (ii) `(f (cdr e1) e2)` \Rightarrow the correct result.

Debugging Suggestions

For concreteness, let's assume you are writing a 2-argument function `f` such that, when `e1` \neq `NIL`, `(f e1 e2)` computes its result from `(f (cdr e1) e2)`.

1. Make sure you know what the base case `(f nil e2)` *should* return; test `f` to check that `(f nil e2)` always returns the right result: If it doesn't, fix the definition of `f` so it does!
2. Call `f` with different arguments. If for certain arguments *there's an evaluation error* or `f` returns an *incorrect result*, find arguments `e1` and `e2` such that:
 - (i) `(f e1 e2)` \neq the correct result,
but (ii) `(f (cdr e1) e2)` \Rightarrow the correct result.

(ii) implies `(let ((X (f (cdr e1) e2)))` gives `X` the correct value, whereas (i) implies *the* ... *expr* doesn't compute the correct result from `X`'s value!

Debugging Suggestions

For concreteness, let's assume you are writing a 2-argument function `f` such that, when `e1` \neq `NIL`, `(f e1 e2)` computes its result from `(f (cdr e1) e2)`.

1. Make sure you know what the base case `(f nil e2)` *should* return; test `f` to check that `(f nil e2)` always returns the right result: If it doesn't, fix the definition of `f` so it does!

2. Call `f` with different arguments. If for certain arguments *there's an evaluation error* or `f` returns an *incorrect result*, find arguments `e1` and `e2` such that:

(i) `(f e1 e2)` \neq the correct result,
but (ii) `(f (cdr e1) e2)` \Rightarrow the correct result.

(ii) implies `(let ((X (f (cdr e1) e2)))` gives `X` the correct value, whereas (i) implies *the* ... *expr* doesn't compute the correct result from `X`'s value!

When you find arguments `e1` and `e2` that satisfy (i) & (ii), fix the ... *expr* so `(f e1 e2)` \Rightarrow the **correct** result.

Debugging Suggestions

For concreteness, let's assume you are writing a 2-argument function `f` such that, when `e1` \neq `NIL`, `(f e1 e2)` computes its result from `(f (cdr e1) e2)`.

1. Make sure you know what the base case `(f nil e2)` *should* return; test `f` to check that `(f nil e2)` always returns the right result: If it doesn't, fix the definition of `f` so it does!

2. Call `f` with different arguments. If for certain arguments *there's an evaluation error* or `f` returns an *incorrect result*, find arguments `e1` and `e2` such that:

(i) `(f e1 e2)` \neq the correct result,
but (ii) `(f (cdr e1) e2)` \Rightarrow the correct result.

(ii) implies `(let ((X (f (cdr e1) e2)))` gives `X` the correct value, whereas (i) implies *the* ... *expr* doesn't compute the correct result from `X`'s value!

When you find arguments `e1` and `e2` that satisfy (i) & (ii), fix the ... *expr* so `(f e1 e2)` \Rightarrow the **correct** result.

Repeat step 2 until you think the definition of `f` is correct.

A Debugging Example Relating to Assignment 4

Problem 7 asks you to write a function PARTITION such that if $l \Rightarrow$ a proper list of real numbers and p is a real number, then (PARTITION l p) returns a list whose CAR is a list of those elements of the list given by l that are less than p , and whose CADR is a list of the other elements of the list given by l . So:

A Debugging Example Relating to Assignment 4

Problem 7 asks you to write a function PARTITION such that if $l \Rightarrow$ a proper list of real numbers and p is a real number, then (PARTITION l p) returns a list whose CAR is a list of those elements of the list given by l that are less than p , and whose CADR is a list of the other elements of the list given by l . So:

`(partition () 4) \Rightarrow (NIL NIL)` `(partition '(2 5 6 3) 5) \Rightarrow ((2 3) (5 6))`

A Debugging Example Relating to Assignment 4

Problem 7 asks you to write a function PARTITION such that if $l \Rightarrow$ a proper list of real numbers and p is a real number, then (PARTITION l p) returns a list whose CAR is a list of those elements of the list given by l that are less than p , and whose CADR is a list of the other elements of the list given by l . So:

`(partition () 4) \Rightarrow (NIL NIL)` `(partition '(2 5 6 3) 5) \Rightarrow ((2 3) (5 6))`

Here is an *incorrect* definition that needs debugging:

```
(defun partition (L p) ; Incorrect definition!
  (if (null L)
      '(()())
      (let ((X (partition (cdr L) p)))
        (cond ((> (car L) p) (list (car X) (cons (car L) (cadr X))))
              (t (list (cons (car L) (car X)) (cadr X)))))))
```

A Debugging Example Relating to Assignment 4

Problem 7 asks you to write a function `PARTITION` such that if $l \Rightarrow$ a proper list of real numbers and p is a real number, then `(PARTITION l p)` returns a list whose `CAR` is a list of those elements of the list given by l that are less than p , and whose `CADR` is a list of the other elements of the list given by l . So:

`(partition () 4) \Rightarrow (NIL NIL)` `(partition '(2 5 6 3) 5) \Rightarrow ((2 3) (5 6))`

Here is an *incorrect* definition that needs debugging:

```
(defun partition (L p) ; Incorrect definition!
  (if (null L)
      '(()())
      (let ((X (partition (cdr L) p)))
        (cond ((> (car L) p) (list (car X) (cons (car L) (cadr X))))
              (t (list (cons (car L) (car X)) (cadr X)))))))
```

On testing this function in *Clisp*, we find:

- `(partition () 4) \Rightarrow (NIL NIL)` **Correct!**
-
-
-

A Debugging Example Relating to Assignment 4

Problem 7 asks you to write a function `PARTITION` such that if $l \Rightarrow$ a proper list of real numbers and p is a real number, then `(PARTITION l p)` returns a list whose `CAR` is a list of those elements of the list given by l that are less than p , and whose `CADR` is a list of the other elements of the list given by l . So:

`(partition () 4) \Rightarrow (NIL NIL)` `(partition '(2 5 6 3) 5) \Rightarrow ((2 3) (5 6))`

Here is an *incorrect* definition that needs debugging:

```
(defun partition (L p) ; Incorrect definition!
  (if (null L)
      '(()())
      (let ((X (partition (cdr L) p)))
        (cond ((> (car L) p) (list (car X) (cons (car L) (cadr X))))
              (t (list (cons (car L) (car X)) (cadr X)))))))
```

On testing this function in *Clisp*, we find:

- `(partition () 4) \Rightarrow (NIL NIL)` **Correct!**
- `(partition '(2 5 6 3) 5) \Rightarrow ((2 5 3) (6))` **Wrong: should be**
-
-

A Debugging Example Relating to Assignment 4

Problem 7 asks you to write a function PARTITION such that if $l \Rightarrow$ a proper list of real numbers and p is a real number, then $(\text{PARTITION } l \ p)$ returns a list whose CAR is a list of those elements of the list given by l that are less than p , and whose CADR is a list of the other elements of the list given by l . So:

$(\text{partition } () \ 4) \Rightarrow (\text{NIL NIL})$ $(\text{partition } '(2 \ 5 \ 6 \ 3) \ 5) \Rightarrow ((2 \ 3) (5 \ 6))$

Here is an *incorrect* definition that needs debugging:

```
(defun partition (L p) ; Incorrect definition!
  (if (null L)
      '(()())
      (let ((X (partition (cdr L) p)))
        (cond ((> (car L) p) (list (car X) (cons (car L) (cadr X))))
              (t (list (cons (car L) (car X)) (cadr X)))))))
```

On testing this function in Clisp, we find:

- $(\text{partition } () \ 4) \Rightarrow (\text{NIL NIL})$ Correct!
- $(\text{partition } '(2 \ 5 \ 6 \ 3) \ 5) \Rightarrow ((2 \ 5 \ 3) (6))$ Wrong: should be
-
-

A Debugging Example Relating to Assignment 4

Problem 7 asks you to write a function `PARTITION` such that if $l \Rightarrow$ a proper list of real numbers and p is a real number, then `(PARTITION l p)` returns a list whose `CAR` is a list of those elements of the list given by l that are less than p , and whose `CADR` is a list of the other elements of the list given by l . So:

`(partition () 4) \Rightarrow (NIL NIL)` `(partition '(2 5 6 3) 5) \Rightarrow ((2 3) (5 6))`

Here is an *incorrect* definition that needs debugging:

```
(defun partition (L p) ; Incorrect definition!
  (if (null L)
      '(()())
      (let ((X (partition (cdr L) p)))
        (cond ((> (car L) p) (list (car X) (cons (car L) (cadr X))))
              (t (list (cons (car L) (car X)) (cadr X)))))))
```

On testing this function in *Clisp*, we find:

- `(partition () 4) \Rightarrow (NIL NIL)` Correct!
- `(partition '(2 5 6 3) 5) \Rightarrow ((2 5 3) (6))` Wrong: should be
- `(partition '(5 6 3) 5) \Rightarrow ((5 3) (6))` Wrong: should be
-

A Debugging Example Relating to Assignment 4

Problem 7 asks you to write a function `PARTITION` such that if $l \Rightarrow$ a proper list of real numbers and p is a real number, then $(\text{PARTITION } l \ p)$ returns a list whose `CAR` is a list of those elements of the list given by l that are less than p , and whose `CADR` is a list of the other elements of the list given by l . So:

`(partition () 4) \Rightarrow (NIL NIL)` `(partition '(2 5 6 3) 5) \Rightarrow ((2 3) (5 6))`

Here is an *incorrect* definition that needs debugging:

```
(defun partition (L p) ; Incorrect definition!
  (if (null L)
      '(()())
      (let ((X (partition (cdr L) p)))
        (cond ((> (car L) p) (list (car X) (cons (car L) (cadr X))))
              (t (list (cons (car L) (car X)) (cadr X)))))))
```

On testing this function in *Clisp*, we find:

- `(partition () 4) \Rightarrow (NIL NIL)` **Correct!**
- `(partition '(2 5 6 3) 5) \Rightarrow ((2 5 3) (6))` **Wrong: should be** ————— **((2 3) (5 6))**
- `(partition '(5 6 3) 5) \Rightarrow ((5 3) (6))` **Wrong: should be ((3) (5 6))**
-

A Debugging Example Relating to Assignment 4

Problem 7 asks you to write a function PARTITION such that if $l \Rightarrow$ a proper list of real numbers and p is a real number, then $(\text{PARTITION } l \ p)$ returns a list whose CAR is a list of those elements of the list given by l that are less than p , and whose CADR is a list of the other elements of the list given by l . So:

$(\text{partition } () \ 4) \Rightarrow (\text{NIL NIL})$ $(\text{partition } '(2 \ 5 \ 6 \ 3) \ 5) \Rightarrow ((2 \ 3) (5 \ 6))$

Here is an *incorrect* definition that needs debugging:

```
(defun partition (L p) ; Incorrect definition!
  (if (null L)
      '(()())
      (let ((X (partition (cdr L) p)))
        (cond ((> (car L) p) (list (car X) (cons (car L) (cadr X))))
              (t (list (cons (car L) (car X)) (cadr X)))))))
```

On testing this function in Clisp, we find:

- $(\text{partition } () \ 4) \Rightarrow (\text{NIL NIL})$ Correct!
- $(\text{partition } '(2 \ 5 \ 6 \ 3) \ 5) \Rightarrow ((2 \ 5 \ 3) (6))$ Wrong: should be —
- $(\text{partition } '(5 \ 6 \ 3) \ 5) \Rightarrow ((5 \ 3) (6))$ Wrong: should be $((3) (5 \ 6))$
- $(\text{partition } '(6 \ 3) \ 5) \Rightarrow ((3) (6))$ Correct!

A Debugging Example Relating to Assignment 4

Problem 7 asks you to write a function PARTITION such that if $l \Rightarrow$ a proper list of real numbers and p is a real number, then (PARTITION l p) returns a list whose CAR is a list of those elements of the list given by l that are less than p , and whose CADR is a list of the other elements of the list given by l . So:

`(partition () 4) \Rightarrow (NIL NIL)` `(partition '(2 5 6 3) 5) \Rightarrow ((2 3) (5 6))`

Here is an *incorrect* definition that needs debugging:

```
(defun partition (L p) ; Incorrect definition!
  (if (null L)
      '(()())
      (let ((X (partition (cdr L) p)))
        (cond ((> (car L) p) (list (car X) (cons (car L) (cadr X))))
              (t (list (cons (car L) (car X)) (cadr X)))))))
```

On testing this function in Clisp, we find:

- `(partition '(5 6 3) 5) \Rightarrow ((5 3) (6))` Wrong: should be `((3) (5 6))`
- `(partition '(6 3) 5) \Rightarrow ((3) (6))` Correct!

A Debugging Example Relating to Assignment 4

Problem 7 asks you to write a function `PARTITION` such that if $l \Rightarrow$ a proper list of real numbers and p is a real number, then `(PARTITION l p)` returns a list whose `CAR` is a list of those elements of the list given by l that are less than p , and whose `CADR` is a list of the other elements of the list given by l . So:

`(partition () 4) \Rightarrow (NIL NIL)` `(partition '(2 5 6 3) 5) \Rightarrow ((2 3) (5 6))`

Here is an *incorrect* definition that needs debugging:

```
(defun partition (L p) ; Incorrect definition!
  (if (null L)
      '(()())
      (let ((X (partition (cdr L) p)))
        (cond ((> (car L) p) (list (car X) (cons (car L) (cadr X))))
              (t (list (cons (car L) (car X)) (cadr X)))))))
```

On testing this function in *Clisp*, we find:

- `(partition '(5 6 3) 5) \Rightarrow ((5 3) (6))` Wrong: should be `((3) (5 6))`
- `(partition '(6 3) 5) \Rightarrow ((3) (6))` Correct!

A Debugging Example Relating to Assignment 4

Problem 7 asks you to write a function PARTITION such that if $l \Rightarrow$ a proper list of real numbers and p is a real number, then $(\text{PARTITION } l \ p)$ returns a list whose CAR is a list of those elements of the list given by l that are less than p , and whose CADR is a list of the other elements of the list given by l . So:

$(\text{partition } () \ 4) \Rightarrow (\text{NIL NIL})$ $(\text{partition } '(2 \ 5 \ 6 \ 3) \ 5) \Rightarrow ((2 \ 3) (5 \ 6))$

Here is an *incorrect* definition that needs debugging:

```
(defun partition (L p) ; Incorrect definition!
  (if (null L)
      '(()())
      (let ((X (partition (cdr L) p)))
        (cond ((> (car L) p) (list (car X) (cons (car L) (cadr X))))
              (t (list (cons (car L) (car X)) (cadr X)))))))
```

On testing this function in Clisp, we find:

- $(\text{partition } '(5 \ 6 \ 3) \ 5) \Rightarrow ((5 \ 3) (6))$ Wrong: should be $((3) (5 \ 6))$
- $(\text{partition } '(6 \ 3) \ 5) \Rightarrow ((3) (6))$ Correct!

When $L \Rightarrow (5 \ 6 \ 3)$ and $p \Rightarrow 5$, we have that $X \Rightarrow$: We must fix the ... expr so it \Rightarrow [instead of $((5 \ 3) (6))$].

A Debugging Example Relating to Assignment 4

Problem 7 asks you to write a function PARTITION such that if $L \Rightarrow$ a proper list of real numbers and p is a real number, then $(\text{PARTITION } L \ p)$ returns a list whose CAR is a list of those elements of the list given by L that are less than p , and whose CADR is a list of the other elements of the list given by L . So:

$(\text{partition } () \ 4) \Rightarrow (\text{NIL NIL})$ $(\text{partition } '(2 \ 5 \ 6 \ 3) \ 5) \Rightarrow ((2 \ 3) (5 \ 6))$

Here is an *incorrect* definition that needs debugging:

```
(defun partition (L p) ; Incorrect definition!
  (if (null L)
      '(()())
      (let ((X (partition (cdr L) p)))
        (cond ((> (car L) p) (list (car X) (cons (car L) (cadr X))))
              (t (list (cons (car L) (car X)) (cadr X)))))))
```

On testing this function in Clisp, we find:

- $(\text{partition } '(5 \ 6 \ 3) \ 5) \Rightarrow ((5 \ 3) (6))$ Wrong: should be $((3) (5 \ 6))$
- $(\text{partition } '(6 \ 3) \ 5) \Rightarrow ((3) (6))$ Correct!

When $L \Rightarrow (5 \ 6 \ 3)$ and $p \Rightarrow 5$, we have that $X \Rightarrow ((3) (6))$: We must fix the ... expr so it \Rightarrow [instead of $((5 \ 3) (6))$].

A Debugging Example Relating to Assignment 4

Problem 7 asks you to write a function PARTITION such that if $l \Rightarrow$ a proper list of real numbers and p is a real number, then $(\text{PARTITION } l \ p)$ returns a list whose CAR is a list of those elements of the list given by l that are less than p , and whose CADR is a list of the other elements of the list given by l . So:

$(\text{partition } () \ 4) \Rightarrow (\text{NIL NIL})$ $(\text{partition } '(2 \ 5 \ 6 \ 3) \ 5) \Rightarrow ((2 \ 3) (5 \ 6))$

Here is an *incorrect* definition that needs debugging:

```
(defun partition (L p) ; Incorrect definition!
  (if (null L)
      '(()())
      (let ((X (partition (cdr L) p)))
        (cond ((> (car L) p) (list (car X) (cons (car L) (cadr X))))
              (t (list (cons (car L) (car X)) (cadr X)))))))
```

On testing this function in Clisp, we find:

- $(\text{partition } '(5 \ 6 \ 3) \ 5) \Rightarrow ((5 \ 3) (6))$ Wrong: should be $((3) (5 \ 6))$
- $(\text{partition } '(6 \ 3) \ 5) \Rightarrow ((3) (6))$ Correct!

When $L \Rightarrow (5 \ 6 \ 3)$ and $p \Rightarrow 5$, we have that $X \Rightarrow ((3) (6))$: We must fix the ... expr so it $\Rightarrow ((3) (5 \ 6))$ [instead of $((5 \ 3) (6))$].

A Debugging Example Relating to Assignment 4

```
(let ((X (partition (cdr L) p)))  
  (cond ((> (car L) p) (list (car X) (cons (car L) (cadr X))))  
        (t (list (cons (car L) (car X)) (cadr X))))))
```

On testing this function in Clisp, we find:

- (partition '(5 6 3) 5) \Rightarrow ((5 3) (6)) **Wrong: should be ((3) (5 6))**
- (partition '(6 3) 5) \Rightarrow ((3) (6)) **Correct!**

When $L \Rightarrow (5\ 6\ 3)$ and $p \Rightarrow 5$, we have that $X \Rightarrow ((3)\ (6))$: *We must fix the ... expr so it $\Rightarrow ((3)\ (5\ 6))$ [instead of $((5\ 3)\ (6))$].*

A Debugging Example Relating to Assignment 4

```
(let ((X (partition (cdr L) p)))
```

```
(cond ((> (car L) p) (list (car X) (cons (car L) (cadr X))))  
      (t (list (cons (car L) (car X)) (cadr X))))))
```

On testing this function in Clisp, we find:

- (partition '(5 6 3) 5) \Rightarrow ((5 3) (6)) **Wrong: should be ((3) (5 6))**
- (partition '(6 3) 5) \Rightarrow ((3) (6)) **Correct!**

When $L \Rightarrow (5\ 6\ 3)$ and $p \Rightarrow 5$, we have that $X \Rightarrow ((3)\ (6))$: *We must fix the* ... *expr so it $\Rightarrow ((3)\ (5\ 6))$ [instead of ((5 3) (6))].*

A Debugging Example Relating to Assignment 4

```
(let ((X (partition (cdr L) p)))
```

```
(cond ((> (car L) p) (list (car X) (cons (car L) (cadr X))))  
      (t (list (cons (car L) (car X)) (cadr X))))))
```

On testing this function in Clisp, we find:

- (partition '(5 6 3) 5) \Rightarrow ((5 3) (6)) **Wrong: should be ((3) (5 6))**
- (partition '(6 3) 5) \Rightarrow ((3) (6)) **Correct!**

When $L \Rightarrow (5\ 6\ 3)$ and $p \Rightarrow 5$, we have that $X \Rightarrow ((3)\ (6))$: *We must fix the* ... *expr so it* $\Rightarrow ((3)\ (5\ 6))$ [instead of ((5 3) (6))].

Q. When $L \Rightarrow (5\ 6\ 3)$, $p \Rightarrow 5$, and $X \Rightarrow ((3)\ (6))$,
why does ... \Rightarrow the wrong result ((5 3) (6))?

A.

•

•

A Debugging Example Relating to Assignment 4

```
(let ((X (partition (cdr L) p)))  
  (cond ((> (car L) p) (list (car X) (cons (car L) (cadr X))))  
        (t (list (cons (car L) (car X)) (cadr X))))))
```

On testing this function in Clisp, we find:

- (partition '(5 6 3) 5) \Rightarrow ((5 3) (6)) **Wrong: should be ((3) (5 6))**
- (partition '(6 3) 5) \Rightarrow ((3) (6)) **Correct!**

When $L \Rightarrow (5\ 6\ 3)$ and $p \Rightarrow 5$, we have that $X \Rightarrow ((3)\ (6))$: *We must fix the ... expr so it $\Rightarrow ((3)\ (5\ 6))$ [instead of ((5 3) (6))].*

Q. When $L \Rightarrow (5\ 6\ 3)$, $p \Rightarrow 5$, and $X \Rightarrow ((3)\ (6))$,
why does ... \Rightarrow the wrong result ((5 3) (6))?

A. Because the $(> (\text{car } L) p)$ test of the 1st COND clause \Rightarrow NIL,
so the result is given by the **t** clause, whose consequent
form **(list (cons (car L) (car X)) (cadr X))** \Rightarrow ((5 3) (6)).

•

•

A Debugging Example Relating to Assignment 4

```
(let ((X (partition (cdr L) p)))  
  (cond ((> (car L) p) (list (car X) (cons (car L) (cadr X))))  
        (t (list (cons (car L) (car X)) (cadr X))))))
```

On testing this function in Clisp, we find:

- (partition '(5 6 3) 5) \Rightarrow ((5 3) (6)) **Wrong: should be ((3) (5 6))**
- (partition '(6 3) 5) \Rightarrow ((3) (6)) **Correct!**

When $L \Rightarrow (5\ 6\ 3)$ and $p \Rightarrow 5$, we have that $X \Rightarrow ((3)\ (6))$: *We must fix the ... expr so it $\Rightarrow ((3)\ (5\ 6))$ [instead of ((5 3) (6))].*

Q. When $L \Rightarrow (5\ 6\ 3)$, $p \Rightarrow 5$, and $X \Rightarrow ((3)\ (6))$,
why does ... \Rightarrow the wrong result ((5 3) (6))?

A. Because the $(> (\text{car } L) p)$ test of the 1st COND clause \Rightarrow NIL,
so the result is given by the **t** clause, whose consequent
form $(\text{list } (\text{cons } (\text{car } L) (\text{car } X)) (\text{cadr } X)) \Rightarrow ((5\ 3)\ (6))$.

- To get **((3) (5 6))** from $L \Rightarrow (5\ 6\ 3)$, $p \Rightarrow 5$, and $X \Rightarrow ((3)\ (6))$
(list _____ **)** would work.
-

A Debugging Example Relating to Assignment 4

```
(let ((X (partition (cdr L) p)))
```

```
(cond ((> (car L) p) (list (car X) (cons (car L) (cadr X))))  
      (t (list (cons (car L) (car X)) (cadr X))))))
```

On testing this function in Clisp, we find:

- (partition '(5 6 3) 5) \Rightarrow ((5 3) (6)) **Wrong: should be ((3) (5 6))**
- (partition '(6 3) 5) \Rightarrow ((3) (6)) **Correct!**

When $L \Rightarrow (5\ 6\ 3)$ and $p \Rightarrow 5$, we have that $X \Rightarrow ((3)\ (6))$: We must fix the ... expr so it $\Rightarrow ((3)\ (5\ 6))$ [instead of ((5 3) (6))].

Q. When $L \Rightarrow (5\ 6\ 3)$, $p \Rightarrow 5$, and $X \Rightarrow ((3)\ (6))$,
why does ... \Rightarrow the wrong result ((5 3) (6))?

A. Because the $(> (\text{car } L) p)$ test of the 1st COND clause \Rightarrow NIL,
so the result is given by the **t** clause, whose consequent
form $(\text{list } (\text{cons } (\text{car } L) (\text{car } X)) (\text{cadr } X)) \Rightarrow ((5\ 3)\ (6))$.

- To get **((3) (5 6))** from $L \Rightarrow (5\ 6\ 3)$, $p \Rightarrow 5$, and $X \Rightarrow ((3)\ (6))$
(list (car X) _____ **)** would work.
-

A Debugging Example Relating to Assignment 4

```
(let ((X (partition (cdr L) p)))
```

```
(cond ((> (car L) p) (list (car X) (cons (car L) (cadr X))))  
      (t (list (cons (car L) (car X)) (cadr X))))))
```

On testing this function in Clisp, we find:

- (partition '(5 6 3) 5) \Rightarrow ((5 3) (6)) **Wrong: should be ((3) (5 6))**
- (partition '(6 3) 5) \Rightarrow ((3) (6)) **Correct!**

When $L \Rightarrow (5\ 6\ 3)$ and $p \Rightarrow 5$, we have that $X \Rightarrow ((3)\ (6))$: *We must fix the ... expr so it $\Rightarrow ((3)\ (5\ 6))$ [instead of ((5 3) (6))].*

Q. When $L \Rightarrow (5\ 6\ 3)$, $p \Rightarrow 5$, and $X \Rightarrow ((3)\ (6))$,
why does ... \Rightarrow the wrong result ((5 3) (6))?

A. Because the $(> (\text{car } L) p)$ test of the 1st COND clause \Rightarrow NIL,
so the result is given by the **t** clause, whose consequent
form $(\text{list } (\text{cons } (\text{car } L) (\text{car } X)) (\text{cadr } X)) \Rightarrow ((5\ 3)\ (6))$.

- To get **((3) (5 6))** from $L \Rightarrow (5\ 6\ 3)$, $p \Rightarrow 5$, and $X \Rightarrow ((3)\ (6))$
(list (car X) (cons (car L) (cadr X))) would work.

•

A Debugging Example Relating to Assignment 4

```
(let ((X (partition (cdr L) p)))
```

```
(cond ((> (car L) p) (list (car X) (cons (car L) (cadr X))))  
      (t (list (cons (car L) (car X)) (cadr X))))))
```

On testing this function in Clisp, we find:

- (partition '(5 6 3) 5) \Rightarrow ((5 3) (6)) **Wrong: should be ((3) (5 6))**
- (partition '(6 3) 5) \Rightarrow ((3) (6)) **Correct!**

When $L \Rightarrow (5\ 6\ 3)$ and $p \Rightarrow 5$, we have that $X \Rightarrow ((3)\ (6))$: We must fix the ... expr so it $\Rightarrow ((3)\ (5\ 6))$ [instead of ((5 3) (6))].

Q. When $L \Rightarrow (5\ 6\ 3)$, $p \Rightarrow 5$, and $X \Rightarrow ((3)\ (6))$,
why does ... \Rightarrow the wrong result ((5 3) (6))?

A. Because the $(> (\text{car } L) p)$ test of the 1st COND clause \Rightarrow NIL, so the result is given by the t clause, whose consequent form $(\text{list } (\text{cons } (\text{car } L) (\text{car } X)) (\text{cadr } X)) \Rightarrow ((5\ 3)\ (6))$.

- To get **((3) (5 6))** from $L \Rightarrow (5\ 6\ 3)$, $p \Rightarrow 5$, and $X \Rightarrow ((3)\ (6))$ **(list (car X) (cons (car L) (cadr X)))** would work.
- This is just **the consequent form of the 1st COND clause**, so we can make ... $\Rightarrow ((3)\ (5\ 6))$ by fixing that clause's test.

Further Comments on Testing and Debugging Recursive Functions

-

-

Further Comments on Testing and Debugging Recursive Functions

- If p is a parameter of a recursive function f that has a smaller value in each recursive call than in the current call, then *a single call* of f that passes a large value to p will generally produce *many recursive calls* of f .
-

Further Comments on Testing and Debugging Recursive Functions

- If p is a parameter of a recursive function f that has a smaller value in each recursive call than in the current call, then *a single call* of f that passes a large value to p will generally produce *many recursive calls* of f .
- This can be viewed as an advantage of recursion that makes it easier to discover bugs by testing: A single test call of f can generate very many other (recursive) calls of f .

More Sophisticated Recursion

In the recursive function definitions that were given above:

-
-

In the recursive function definitions that were given above:

- In non-base cases the result is computed using just one recursive call, and it is the same recursive call in all non-base cases.
-

In the recursive function definitions that were given above:

- In non-base cases the result is computed using just one recursive call, and it is the same recursive call in all non-base cases.
- The function has a formal parameter `e` for which it passes the value of `(cdr e)` or `(- e 1)` to the same parameter of the recursive call in non-base cases.

○

In the recursive function definitions that were given above:

- In non-base cases the result is computed using just one recursive call, and it is the same recursive call in all non-base cases.
- The function has a formal parameter `e` for which it passes the value of `(cdr e)` or `(- e 1)` to the same parameter of the recursive call in non-base cases.
 - `e` may not be the only parameter, but the value of any other parameter is passed *without change* to the same parameter of the recursive call in non-base cases.

In the recursive function definitions that were given above:

- In non-base cases the result is computed using just one recursive call, and it is the same recursive call in all non-base cases.
- The function has a formal parameter `e` for which it passes the value of `(cdr e)` or `(- e 1)` to the same parameter of the recursive call in non-base cases.
 - `e` may not be the only parameter, but the value of any other parameter is passed *without change* to the same parameter of the recursive call in non-base cases.

All 13 problems in section 2 of Lisp Assignment 4 can be solved using recursive functions of this simple kind, *but when doing Lisp Assignment 5 you must be prepared to write recursive functions that work differently!*

In the recursive function definitions that were given above:

- In non-base cases the result is computed using just one recursive call, and it is the same recursive call in all non-base cases.
- The function has a formal parameter `e` for which it passes the value of `(cdr e)` or `(- e 1)` to the same parameter of the recursive call in non-base cases.
 - `e` may not be the only parameter, but the value of any other parameter is passed *without change* to the same parameter of the recursive call in non-base cases.

All 13 problems in section 2 of Lisp Assignment 4 can be solved using recursive functions of this simple kind, *but when doing Lisp Assignment 5 you must be prepared to write recursive functions that work differently!*

When a function makes a recursive call, there will often be a formal parameter `e` of the function for which the value passed to the same parameter of the recursive call is *smaller in size* than the value of `e`.

In the recursive function definitions that were given above:

- In non-base cases the result is computed using just one recursive call, and it is the same recursive call in all non-base cases.
- The function has a formal parameter `e` for which it passes the value of `(cdr e)` or `(- e 1)` to the same parameter of the recursive call in non-base cases.
 - `e` may not be the only parameter, but the value of any other parameter is passed *without change* to the same parameter of the recursive call in non-base cases.

All 13 problems in section 2 of Lisp Assignment 4 can be solved using recursive functions of this simple kind, *but when doing Lisp Assignment 5 you must be prepared to write recursive functions that work differently!*

When a function makes a recursive call, there will often be a formal parameter `e` of the function for which the value passed to the same parameter of the recursive call is smaller in size than the value of `e`.

`(cdr e)` and `(- e 1)` may be used to produce the value of smaller size. Other expressions that can be used to do that include:

When a function makes a recursive call, there will often be a formal parameter `e` of the function for which the value passed to the same parameter of the recursive call is *smaller in size* than the value of `e`.

`(cdr e)` and `(- e 1)` may be used to produce the value of smaller size. *Other* expressions that can be used to do that include:

When a function makes a recursive call, there will often be a formal parameter `e` of the function for which the value passed to the same parameter of the recursive call is *smaller in size* than the value of `e`.

`(cdr e)` and `(- e 1)` may be used to produce the value of smaller size. *Other* expressions that can be used to do that include:

-
-
-
-

When a function makes a recursive call, there will often be a formal parameter `e` of the function for which the value passed to the same parameter of the recursive call is *smaller in size* than the value of `e`.

`(cdr e)` and `(- e 1)` may be used to produce the value of smaller size. *Other* expressions that can be used to do that include:

- `(cddr e)` if `e` \Rightarrow a nonempty list.
-
-
-

When a function makes a recursive call, there will often be a formal parameter `e` of the function for which the value passed to the same parameter of the recursive call is *smaller in size* than the value of `e`.

`(cdr e)` and `(- e 1)` may be used to produce the value of smaller size. *Other* expressions that can be used to do that include:

- `(cddr e)` if `e` \Rightarrow a nonempty list.
- `(- e 2)` if `e` \Rightarrow an integer ≥ 2 .
-
-

When a function makes a recursive call, there will often be a formal parameter `e` of the function for which the value passed to the same parameter of the recursive call is *smaller in size* than the value of `e`.

`(cdr e)` and `(- e 1)` may be used to produce the value of smaller size. *Other* expressions that can be used to do that include:

- `(cddr e)` if `e` \Rightarrow a nonempty list.
- `(- e 2)` if `e` \Rightarrow an integer ≥ 2 .
- `(floor e 2)` if `e` \Rightarrow an integer other than 0 or -1.
 - `(floor e 2)` =
=
-

When a function makes a recursive call, there will often be a formal parameter `e` of the function for which the value passed to the same parameter of the recursive call is *smaller in size* than the value of `e`.

`(cdr e)` and `(- e 1)` may be used to produce the value of smaller size. *Other* expressions that can be used to do that include:

- `(cddr e)` if `e` \Rightarrow a nonempty list.
- `(- e 2)` if `e` \Rightarrow an integer ≥ 2 .
- `(floor e 2)` if `e` \Rightarrow an integer other than 0 or -1.
 - `(floor e 2)` = $\lfloor e/2 \rfloor$ = `e >> 1` in Java if `e` \Rightarrow an integer
= `e/2` in Java if `e` \Rightarrow a non-negative integer.
-

When a function makes a recursive call, there will often be a formal parameter `e` of the function for which the value passed to the same parameter of the recursive call is *smaller in size* than the value of `e`.

`(cdr e)` and `(- e 1)` may be used to produce the value of smaller size. *Other* expressions that can be used to do that include:

- `(cddr e)` if `e` \Rightarrow a nonempty list.
- `(- e 2)` if `e` \Rightarrow an integer ≥ 2 .
- `(floor e 2)` if `e` \Rightarrow an integer other than 0 or -1.
 - `(floor e 2) = $\lfloor e/2 \rfloor = e \gg 1$` in Java if `e` \Rightarrow an integer.
-

When a function makes a recursive call, there will often be a formal parameter `e` of the function for which the value passed to the same parameter of the recursive call is *smaller in size* than the value of `e`.

`(cdr e)` and `(- e 1)` may be used to produce the value of smaller size. *Other* expressions that can be used to do that include:

- `(cddr e)` if `e` \Rightarrow a nonempty list.
- `(- e 2)` if `e` \Rightarrow an integer ≥ 2 .
- `(floor e 2)` if `e` \Rightarrow an integer other than 0 or -1.
 - `(floor e 2) = $\lfloor e/2 \rfloor = e \gg 1$` in Java if `e` \Rightarrow an integer.
- `(/ e 2)` if `e` \Rightarrow an *even* integer other than 0.
-

When a function makes a recursive call, there will often be a formal parameter `e` of the function for which the value passed to the same parameter of the recursive call is *smaller in size* than the value of `e`.

`(cdr e)` and `(- e 1)` may be used to produce the value of smaller size. *Other* expressions that can be used to do that include:

- `(cddr e)` if `e` \Rightarrow a nonempty list.
- `(- e 2)` if `e` \Rightarrow an integer ≥ 2 .
- `(floor e 2)` if `e` \Rightarrow an integer other than 0 or -1.
 - `(floor e 2) = $\lfloor e/2 \rfloor = e \gg 1$` in Java if `e` \Rightarrow an integer.
- `(/ e 2)` if `e` \Rightarrow an *even* integer other than 0.
- `(cdr L1)` if `e` \Rightarrow a nonempty list;
here `L1` \Rightarrow a list, obtained by *transforming* the list given by `e` in some way, whose length is \leq the length of that list.

○

When a function makes a recursive call, there will often be a formal parameter `e` of the function for which the value passed to the same parameter of the recursive call is *smaller in size* than the value of `e`.

`(cdr e)` and `(- e 1)` may be used to produce the value of smaller size. *Other* expressions that can be used to do that include:

- `(cddr e)` if `e` \Rightarrow a nonempty list.
- `(- e 2)` if `e` \Rightarrow an integer ≥ 2 .
- `(floor e 2)` if `e` \Rightarrow an integer other than 0 or -1.
 - `(floor e 2) = [e/2] = e >> 1` in Java if `e` \Rightarrow an integer.
- `(/ e 2)` if `e` \Rightarrow an *even* integer other than 0.
- `(cdr L1)` if `e` \Rightarrow a nonempty list;
 - here `L1` \Rightarrow a list, obtained by *transforming* the list given by `e` in some way, whose length is \leq the length of that list.
- For Assignment 5, your function `SSORT` should use this kind of expression to produce the argument value for its recursive call.

Example of the Use of (caddr L) as a Recursive Call Argument

Recall from Assignment 4: If $L \Rightarrow$ a list then (SPLIT-LIST L) returns a list of two lists, in which the 1st list consists of the 1st, 3rd, 5th, ... elements of the list given by L, and the 2nd list consists of the 2nd, 4th, 6th, ... elements of the list given by L.

For example: (SPLIT-LIST ()) \Rightarrow (NIL NIL) (SPLIT-LIST '(B)) \Rightarrow ((B) NIL)
(SPLIT-LIST '(A B C D 1 2 3 4 5)) \Rightarrow ((A C 1 3 5) (B D 2 4))

Example of the Use of `(cddr L)` as a Recursive Call Argument

Recall from Assignment 4: If $L \Rightarrow$ a list then `(SPLIT-LIST L)` returns a list of two lists, in which the 1st list consists of the 1st, 3rd, 5th, ... elements of the list given by L , and the 2nd list consists of the 2nd, 4th, 6th, ... elements of the list given by L .

For example: `(SPLIT-LIST ())` \Rightarrow `(NIL NIL)` `(SPLIT-LIST '(B))` \Rightarrow `((B) NIL)`
`(SPLIT-LIST '(A B C D 1 2 3 4 5))` \Rightarrow `((A C 1 3 5) (B D 2 4))`

```
(defun split-list (L)
  (if (null L)
      '(()())
      (let ((X (split-list (cddr L))))
        an expression that  $\Rightarrow$  value of (split-list L)
        and that involves X and, possibly, L.
      )))
```

•

•

Example of the Use of `(cddr L)` as a Recursive Call Argument

Recall from Assignment 4: If $L \Rightarrow$ a list then `(SPLIT-LIST L)` returns a list of two lists, in which the 1st list consists of the 1st, 3rd, 5th, ... elements of the list given by L , and the 2nd list consists of the 2nd, 4th, 6th, ... elements of the list given by L .

For example: `(SPLIT-LIST ()) => (NIL NIL)` `(SPLIT-LIST '(B)) => ((B) NIL)`
`(SPLIT-LIST '(A B C D 1 2 3 4 5)) => ((A C 1 3 5) (B D 2 4))`

```
(defun split-list (L)
  (if (null L)
      '(()())
      (let ((X (split-list (cddr L))))
        an expression that  $\Rightarrow$  value of (split-list L)
        and that involves X and, possibly, L.
      )))
```

- To write the `...` expression, let's first consider *a possible value of L , the resulting value of X , and what `...`'s value should be for that value of L :*

-

Example of the Use of `(cddr L)` as a Recursive Call Argument

Recall from Assignment 4: If $L \Rightarrow$ a list then `(SPLIT-LIST L)` returns a list of two lists, in which the 1st list consists of the 1st, 3rd, 5th, ... elements of the list given by L , and the 2nd list consists of the 2nd, 4th, 6th, ... elements of the list given by L .

For example: `(SPLIT-LIST ())` \Rightarrow `(NIL NIL)` `(SPLIT-LIST '(B))` \Rightarrow `((B) NIL)`
`(SPLIT-LIST '(A B C D 1 2 3 4 5))` \Rightarrow `((A C 1 3 5) (B D 2 4))`

```
(defun split-list (L)
  (if (null L)
      '(()())
      (let ((X (split-list (cddr L))))
        an expression that  $\Rightarrow$  value of (split-list L)
        and that involves X and, possibly, L.
      )))
```

- To write the `...` expression, let's first consider *a possible value of L , the resulting value of X , and what `...`'s value should be for that value of L :*
- Let $L \Rightarrow$ `(A B C D 1 2 3 4 5)`, so `(cddr L)` \Rightarrow `(C D 1 2 3 4 5)`.
Then $X \Rightarrow$ `(B D 2 4)`
and `...` should \Rightarrow `((A C 1 3 5) (B D 2 4))`.

Example of the Use of `(cddr L)` as a Recursive Call Argument

Recall from Assignment 4: If $L \Rightarrow$ a list then `(SPLIT-LIST L)` returns a list of two lists, in which the 1st list consists of the 1st, 3rd, 5th, ... elements of the list given by L , and the 2nd list consists of the 2nd, 4th, 6th, ... elements of the list given by L .

For example: `(SPLIT-LIST ())` \Rightarrow `(NIL NIL)` `(SPLIT-LIST '(B))` \Rightarrow `((B) NIL)`
`(SPLIT-LIST '(A B C D 1 2 3 4 5))` \Rightarrow `((A C 1 3 5) (B D 2 4))`

```
(defun split-list (L)
  (if (null L)
      '(()())
      (let ((X (split-list (cddr L))))
        an expression that  $\Rightarrow$  value of (split-list L)
        and that involves X and, possibly, L.
      )))
```

- To write the `...` expression, let's first consider *a possible value of L , the resulting value of X , and what `...`'s value should be for that value of L :*
- Let $L \Rightarrow$ `(A B C D 1 2 3 4 5)`, so `(cddr L)` \Rightarrow `(C D 1 2 3 4 5)`.
Then $X \Rightarrow$ `((C 1 3 5) (D 2 4))`
and `...` should \Rightarrow .

Example of the Use of `(cddr L)` as a Recursive Call Argument

Recall from Assignment 4: If $L \Rightarrow$ a list then `(SPLIT-LIST L)` returns a list of two lists, in which the 1st list consists of the 1st, 3rd, 5th, ... elements of the list given by L , and the 2nd list consists of the 2nd, 4th, 6th, ... elements of the list given by L .

For example: `(SPLIT-LIST ())` \Rightarrow `(NIL NIL)` `(SPLIT-LIST '(B))` \Rightarrow `((B) NIL)`
`(SPLIT-LIST '(A B C D 1 2 3 4 5))` \Rightarrow `((A C 1 3 5) (B D 2 4))`

```
(defun split-list (L)
  (if (null L)
      '(()())
      (let ((X (split-list (cddr L))))
        an expression that  $\Rightarrow$  value of (split-list L)
        and that involves X and, possibly, L.))))
```

- To write the ... expression, let's first consider *a possible value of L , the resulting value of X , and what ...'s value should be for that value of L :*
- Let $L \Rightarrow (A\ B\ C\ D\ 1\ 2\ 3\ 4\ 5)$, so `(cddr L)` \Rightarrow `(C D 1 2 3 4 5)`.
Then $X \Rightarrow ((C\ 1\ 3\ 5)\ (D\ 2\ 4))$
and ... should $\Rightarrow ((A\ C\ 1\ 3\ 5)\ (B\ D\ 2\ 4))$.

Example of the Use of `(cddr L)` as a Recursive Call Argument

Recall from Assignment 4: If $L \Rightarrow$ a list then `(SPLIT-LIST L)` returns a list of two lists, in which the 1st list consists of the 1st, 3rd, 5th, ... elements of the list given by L , and the 2nd list consists of the 2nd, 4th, 6th, ... elements of the list given by L .

For example: `(SPLIT-LIST ())` \Rightarrow `(NIL NIL)` `(SPLIT-LIST '(B))` \Rightarrow `((B) NIL)`
`(SPLIT-LIST '(A B C D 1 2 3 4 5))` \Rightarrow `((A C 1 3 5) (B D 2 4))`

```
(defun split-list (L)
  (if (null L)
      '(()())
      (let ((X (split-list (cddr L))))
        an expression that  $\Rightarrow$  value of (split-list L)
        and that involves X and, possibly, L.
      )))
```

- Let $L \Rightarrow (A B C D 1 2 3 4 5)$, so `(cddr L)` $\Rightarrow (C D 1 2 3 4 5)$.
Then `X` $\Rightarrow ((C 1 3 5) (D 2 4))$
and `...` should $\Rightarrow ((A C 1 3 5) (B D 2 4))$.

Example of the Use of `(caddr L)` as a Recursive Call Argument

Recall from Assignment 4: If $L \Rightarrow$ a list then `(SPLIT-LIST L)` returns a list of two lists, in which the 1st list consists of the 1st, 3rd, 5th, ... elements of the list given by L , and the 2nd list consists of the 2nd, 4th, 6th, ... elements of the list given by L .

For example: `(SPLIT-LIST ())` \Rightarrow `(NIL NIL)` `(SPLIT-LIST '(B))` \Rightarrow `((B) NIL)`
`(SPLIT-LIST '(A B C D 1 2 3 4 5))` \Rightarrow `((A C 1 3 5) (B D 2 4))`

```
(defun split-list (L)
  (if (null L)
      '(()())
      (let ((X (split-list (caddr L))))
        an expression that  $\Rightarrow$  value of (split-list L)
        and that involves X and, possibly, L.
      )))
```

- Let $L \Rightarrow (A B C D 1 2 3 4 5)$, so `(caddr L)` $\Rightarrow (C D 1 2 3 4 5)$.
Then `X` $\Rightarrow ((C 1 3 5) (D 2 4))$
and `...` should $\Rightarrow ((A C 1 3 5) (B D 2 4))$.

•

Example of the Use of `(cddr L)` as a Recursive Call Argument

Recall from Assignment 4: If $L \Rightarrow$ a list then `(SPLIT-LIST L)` returns a list of two lists, in which the 1st list consists of the 1st, 3rd, 5th, ... elements of the list given by L , and the 2nd list consists of the 2nd, 4th, 6th, ... elements of the list given by L .

For example: `(SPLIT-LIST ())` \Rightarrow `(NIL NIL)` `(SPLIT-LIST '(B))` \Rightarrow `((B) NIL)`
`(SPLIT-LIST '(A B C D 1 2 3 4 5))` \Rightarrow `((A C 1 3 5) (B D 2 4))`

```
(defun split-list (L)
  (if (null L)
      '(()())
      (let ((X (split-list (cddr L))))
        an expression that  $\Rightarrow$  value of (split-list L)
        and that involves X and, possibly, L.
      )))
```

- Let $L \Rightarrow (A B C D 1 2 3 4 5)$, so `(cddr L)` $\Rightarrow (C D 1 2 3 4 5)$.
Then `X` $\Rightarrow ((C 1 3 5) (D 2 4))$
and `...` should $\Rightarrow ((A C 1 3 5) (B D 2 4))$.
- Q. What is a good `...` expression in this case?
A.

Example of the Use of `(cddr L)` as a Recursive Call Argument

Recall from Assignment 4: If $L \Rightarrow$ a list then `(SPLIT-LIST L)` returns a list of two lists, in which the 1st list consists of the 1st, 3rd, 5th, ... elements of the list given by L , and the 2nd list consists of the 2nd, 4th, 6th, ... elements of the list given by L .

For example: `(SPLIT-LIST ())` \Rightarrow `(NIL NIL)` `(SPLIT-LIST '(B))` \Rightarrow `((B) NIL)`
`(SPLIT-LIST '(A B C D 1 2 3 4 5))` \Rightarrow `((A C 1 3 5) (B D 2 4))`

```
(defun split-list (L)
  (if (null L)
      '(()())
      (let ((X (split-list (cddr L))))
        an expression that  $\Rightarrow$  value of (split-list L)
        and that involves X and, possibly, L.
      )))
```

- Let $L \Rightarrow (A B C D 1 2 3 4 5)$, so `(cddr L)` $\Rightarrow (C D 1 2 3 4 5)$.
Then $X \Rightarrow ((C 1 3 5) (D 2 4))$
and `...` should $\Rightarrow ((A C 1 3 5) (B D 2 4))$.
- Q. What is a good `...` expression in this case?
A. `(list (cons (car L) (car X)) (cons (cadr L) (cadr X)))`
- Q.

Example of the Use of `(cddr L)` as a Recursive Call Argument

Recall from Assignment 4: If $L \Rightarrow$ a list then `(SPLIT-LIST L)` returns a list of two lists, in which the 1st list consists of the 1st, 3rd, 5th, ... elements of the list given by L , and the 2nd list consists of the 2nd, 4th, 6th, ... elements of the list given by L .

For example: `(SPLIT-LIST ()) => (NIL NIL)` `(SPLIT-LIST '(B)) => ((B) NIL)`
`(SPLIT-LIST '(A B C D 1 2 3 4 5)) => ((A C 1 3 5) (B D 2 4))`

```
(defun split-list (L)
  (if (null L)
      '(()())
      (let ((X (split-list (cddr L))))
        an expression that  $\Rightarrow$  value of (split-list L)
        and that involves X and, possibly, L.
      )))
```

- Let $L \Rightarrow (A B C D 1 2 3 4 5)$, so `(cddr L)` $\Rightarrow (C D 1 2 3 4 5)$.
Then $X \Rightarrow ((C 1 3 5) (D 2 4))$
and `...` should $\Rightarrow ((A C 1 3 5) (B D 2 4))$.
- Q. What is a good `...` expression in this case?
A. `(list (cons (car L) (car X)) (cons (cadr L) (cadr X)))`
- Q. For what non-null values of L is this not a good `...`?

Example of the Use of `(cddr L)` as a Recursive Call Argument

`(SPLIT-LIST '(A B C D 1 2 3 4 5)) => ((A C 1 3 5) (B D 2 4))`

```
(defun split-list (L)
  (if (null L)
      '(()())
      (let ((X (split-list (cddr L))))
        an expression that => value of (split-list L)
        and that involves X and, possibly, L.
      )))
```

- Let $L \Rightarrow (A\ B\ C\ D\ 1\ 2\ 3\ 4\ 5)$, so $(cddr\ L) \Rightarrow (C\ D\ 1\ 2\ 3\ 4\ 5)$.
Then $X \Rightarrow ((C\ 1\ 3\ 5)\ (D\ 2\ 4))$
and `...` should $\Rightarrow ((A\ C\ 1\ 3\ 5)\ (B\ D\ 2\ 4))$.
- Q. What is a good `...` expression in this case?
A. `(list (cons (car L) (car X)) (cons (cadr L) (cadr X)))`
- Q. For what non-null values of L is this not a good `...`?

Example of the Use of `(cddr L)` as a Recursive Call Argument

We want: `(SPLIT-LIST '(A B C D 1 2 3 4 5)) => ((A C 1 3 5) (B D 2 4))`

```
(defun split-list (L)
  (if (null L)
      '(()())
      (let ((X (split-list (cddr L))))
        an expression that => value of (split-list L)
        and that involves X and, possibly, L.
      )))
```

- Let $L \Rightarrow (A\ B\ C\ D\ 1\ 2\ 3\ 4\ 5)$, so $(cddr\ L) \Rightarrow (C\ D\ 1\ 2\ 3\ 4\ 5)$.
Then $X \Rightarrow ((C\ 1\ 3\ 5)\ (D\ 2\ 4))$
and `...` should $\Rightarrow ((A\ C\ 1\ 3\ 5)\ (B\ D\ 2\ 4))$.
- Q. What is a good `...` expression in this case?
A. `(list (cons (car L) (car X)) (cons (cadr L) (cadr X)))`
- Q. For what non-null values of L is this not a good `...`?
A.

Example of the Use of (cddr L) as a Recursive Call Argument

We want: (SPLIT-LIST '(A B C D 1 2 3 4 5)) => ((A C 1 3 5) (B D 2 4))

```
(defun split-list (L)
  (if (null L)
      '(()())
      (let ((X (split-list (cddr L))))
        an expression that => value of (split-list L)
        and that involves X and, possibly, L.
      )))
```

- Let $L \Rightarrow (A\ B\ C\ D\ 1\ 2\ 3\ 4\ 5)$, so $(\text{cddr } L) \Rightarrow (C\ D\ 1\ 2\ 3\ 4\ 5)$.
Then $X \Rightarrow ((C\ 1\ 3\ 5)\ (D\ 2\ 4))$
and \dots should $\Rightarrow ((A\ C\ 1\ 3\ 5)\ (B\ D\ 2\ 4))$.
- Q. What is a good \dots expression in this case?
A. $(\text{list } (\text{cons } (\text{car } L) (\text{car } X)) (\text{cons } (\text{cadr } L) (\text{cadr } X)))$
- Q. For what non-null values of L is this not a good \dots ?
A. It's not good if $L \Rightarrow$ a list of length 1--e.g., $L \Rightarrow (B)$:

Example of the Use of (cddr L) as a Recursive Call Argument

We want: (SPLIT-LIST '(A B C D 1 2 3 4 5)) \Rightarrow ((A C 1 3 5) (B D 2 4))

```
(defun split-list (L)
  (if (null L)
      '(()())
      (let ((X (split-list (cddr L))))
        an expression that  $\Rightarrow$  value of (split-list L)
        and that involves X and, possibly, L.
      )))
```

- Let $L \Rightarrow (A B C D 1 2 3 4 5)$, so $(cddr L) \Rightarrow (C D 1 2 3 4 5)$.
Then $X \Rightarrow ((C 1 3 5) (D 2 4))$
and ... should $\Rightarrow ((A C 1 3 5) (B D 2 4))$.
- Q. What is a good ... expression in this case?
A. (list (cons (car L) (car X)) (cons (cadr L) (cadr X)))
- Q. For what non-null values of L is this not a good ...?
A. It's not good if $L \Rightarrow$ a list of length 1--e.g., $L \Rightarrow (B)$:
If $L \Rightarrow (B)$, we want (split-list L) $\Rightarrow ((B) NIL)$ but
(list ... (cons (cadr L) (cadr X)))
 \Rightarrow a list whose 2nd element is a CONS!

Example of the Use of (cddr L) as a Recursive Call Argument

We want: (SPLIT-LIST '(A B C D 1 2 3 4 5)) => ((A C 1 3 5) (B D 2 4))

```
(defun split-list (L)
  (if (null L)
      '(()())
      (let ((X (split-list (cddr L))))
        an expression that => value of (split-list L)
        and that involves X and, possibly, L.
      )))
```

- Let $L \Rightarrow (A\ B\ C\ D\ 1\ 2\ 3\ 4\ 5)$, so $(\text{cddr } L) \Rightarrow (C\ D\ 1\ 2\ 3\ 4\ 5)$.
Then $X \Rightarrow ((C\ 1\ 3\ 5)\ (D\ 2\ 4))$
and \dots should $\Rightarrow ((A\ C\ 1\ 3\ 5)\ (B\ D\ 2\ 4))$.
- Q. What is a good \dots expression in this case?
A. $(\text{list } (\text{cons } (\text{car } L) (\text{car } X)) (\text{cons } (\text{cadr } L) (\text{cadr } X)))$
- Q. For what non-null values of L is this not a good \dots ?
A. It's not good if $L \Rightarrow$ a list of length 1--e.g., $L \Rightarrow (B)$.

Example of the Use of (caddr L) as a Recursive Call Argument

We want: (SPLIT-LIST '(A B C D 1 2 3 4 5)) \Rightarrow ((A C 1 3 5) (B D 2 4))

```
(defun split-list (L)
```

```
  (if (null L)
```

```
      '(()())
```

```
      (let ((X (split-list (caddr L))))
```

an expression that \Rightarrow value of (split-list L)
and that involves X and, possibly, L.

```
      )))
```

- Let $L \Rightarrow (A B C D 1 2 3 4 5)$, so $(caddr L) \Rightarrow (C D 1 2 3 4 5)$.
Then $X \Rightarrow ((C 1 3 5) (D 2 4))$
and ... should $\Rightarrow ((A C 1 3 5) (B D 2 4))$.
- Q. What is a good ... expression in this case?
A. (list (cons (car L) (car X)) (cons (cadr L) (cadr X)))
- Q. For what non-null values of L is this not a good ...?
A. It's not good if $L \Rightarrow$ a list of length 1--e.g., $L \Rightarrow (B)$.
- Q. What is a good ... expression in that case?
Recall: The expression must $\Rightarrow ((B) \text{NIL})$.

A.

Example of the Use of (caddr L) as a Recursive Call Argument

We want: (SPLIT-LIST '(A B C D 1 2 3 4 5)) \Rightarrow ((A C 1 3 5) (B D 2 4))

```
(defun split-list (L)
  (if (null L)
      '(()())
      (let ((X (split-list (caddr L))))
        an expression that  $\Rightarrow$  value of (split-list L)
        and that involves X and, possibly, L.
      )))
```

- Let $L \Rightarrow (A B C D 1 2 3 4 5)$, so $(caddr L) \Rightarrow (C D 1 2 3 4 5)$.
Then $X \Rightarrow ((C 1 3 5) (D 2 4))$
and ... should $\Rightarrow ((A C 1 3 5) (B D 2 4))$.
- Q. What is a good ... expression in this case?
A. (list (cons (car L) (car X)) (cons (cadr L) (cadr X)))
- Q. For what non-null values of L is this not a good ...?
A. It's not good if $L \Rightarrow$ a list of length 1--e.g., $L \Rightarrow (B)$.
- Q. What is a good ... expression in that case?
Recall: The expression must $\Rightarrow ((B) \text{NIL})$.
A. (list L ())

Example of the Use of `(cddr L)` as a Recursive Call Argument

```
(defun split-list (L)
  (if (null L)
      '(()())
      (let ((X (split-list (cddr L))))
        an expression that  $\Rightarrow$  value of (split-list L)
        and that involves X and, possibly, L.
      )))
```

- Let $L \Rightarrow (A\ B\ C\ D\ 1\ 2\ 3\ 4\ 5)$, so $(cddr\ L) \Rightarrow (C\ D\ 1\ 2\ 3\ 4\ 5)$.
Then $X \Rightarrow ((C\ 1\ 3\ 5)\ (D\ 2\ 4))$
and `...` should $\Rightarrow ((A\ C\ 1\ 3\ 5)\ (B\ D\ 2\ 4))$.
- Q. What is a good `...` expression in this case?
A. `(list (cons (car L) (car X)) (cons (cadr L) (cadr X)))`
- Q. For what non-null values of L is this not a good `...`?
A. It's not good if $L \Rightarrow$ a list of length 1--e.g., $L \Rightarrow (B)$.
- Q. What is a good `...` expression in that case?
A. `(list L ())`

Example of the Use of (caddr L) as a Recursive Call Argument

```
(defun split-list (L)
  (if (null L)
      '(()())
      (let ((X (split-list (caddr L))))
        an expression that  $\Rightarrow$  value of (split-list L)
        and that involves X and, possibly, L.
      )))
```

- Let $L \Rightarrow (A\ B\ C\ D\ 1\ 2\ 3\ 4\ 5)$, so $(caddr\ L) \Rightarrow (C\ D\ 1\ 2\ 3\ 4\ 5)$.
Then $X \Rightarrow ((C\ 1\ 3\ 5)\ (D\ 2\ 4))$
and \dots should $\Rightarrow ((A\ C\ 1\ 3\ 5)\ (B\ D\ 2\ 4))$.
- Q. What is a good \dots expression in this case?
A. $(list\ (cons\ (car\ L)\ (car\ X))\ (cons\ (cadr\ L)\ (cadr\ X)))$
- Q. For what non-null values of L is this not a good \dots ?
A. It's not good if $L \Rightarrow$ a list of length 1--e.g., $L \Rightarrow (B)$.
- Q. What is a good \dots expression in that case?
A. $(list\ L\ ())$

Example of the Use of `(cddr L)` as a Recursive Call Argument

```
(defun split-list (L)
  (if (null L)
      '(()())
      (let ((X (split-list (cddr L))))
        an expression that  $\Rightarrow$  value of (split-list L)
        and that involves X and, possibly, L.))))
```

- Let $L \Rightarrow (A\ B\ C\ D\ 1\ 2\ 3\ 4\ 5)$, so $(cddr\ L) \Rightarrow (C\ D\ 1\ 2\ 3\ 4\ 5)$.
Then $X \Rightarrow ((C\ 1\ 3\ 5)\ (D\ 2\ 4))$
and `...` should $\Rightarrow ((A\ C\ 1\ 3\ 5)\ (B\ D\ 2\ 4))$.
- Q. What is a good `...` expression in this case?
A. `(list (cons (car L) (car X)) (cons (cadr L) (cadr X)))`
- Q. For what non-null values of L is this not a good `...`?
A. It's not good if $L \Rightarrow$ a list of length 1--e.g., $L \Rightarrow (B)$.
- Q. What is a good `...` expression in that case?
A. `(list L ())`

So `...` can
be written:

```
(cond ((null (cdr L)) (list L ()))
      (t (list (cons (car L) (car X))
                (cons (cadr L) (cadr X))))))
```

Example of the Use of (cddr L) as a Recursive Call Argument

```
(defun split-list (L)
  (if (null L)
      '(()())
      (let ((X (split-list (cddr L))))
        )))
```

So ... can
be written:

```
(cond ((null (cddr L)) (list L ()))
      (t (list (cons (car L) (car X))
                 (cons (cadr L) (cadr X))))))
```

Example of the Use of (cddr L) as a Recursive Call Argument

```
(defun split-list (L)
  (if (null L)
      '(()())
      (let ((X (split-list (cddr L))))
        (cond ((null (cdr L)) (list L ()))
              (t (list (cons (car L) (car X))
                        (cons (cadr L) (cadr X)))))))))
```

•

•

•

Example of the Use of (cddr L) as a Recursive Call Argument

```
(defun split-list (L)
  (if (null L)
      '(()())
      (let ((X (split-list (cddr L))))
        (cond ((null (cdr L)) (list L ()))
              (t (list (cons (car L) (car X))
                        (cons (cadr L) (cadr X)))))))))
```

- As X is used twice in the t case, we must not eliminate the LET: The function would be very inefficient if it called (split-list (cddr L)) twice!

-

-

Example of the Use of (cddr L) as a Recursive Call Argument

```
(defun split-list (L)
  (if (null L)
      '(()())
      (let ((X (split-list (cddr L))))
        (cond ((null (cdr L)) (list L ()))
              (t (list (cons (car L) (car X))
                        (cons (cadr L) (cadr X)))))))))
```

- As **X** is used twice in the **t** case, we must not eliminate the LET: The function would be very inefficient if it called (split-list (cddr L)) twice!
- As **X** is not used in the (null (cdr L)) case, it's good to move that case out of the LET.
-

Example of the Use of (cddr L) as a Recursive Call Argument

```
(defun split-list (L)
  (if (null L)
      '(()())
      (let ((X (split-list (cddr L))))
        (cond ((null (cdr L)) (list L ()))
              (t (list (cons (car L) (car X))
                        (cons (cadr L) (cadr X)))))))))
```

- As **X** is used twice in the **t** case, we must not eliminate the LET: The function would be very inefficient if it called (split-list (cddr L)) twice!
- As **X** is not used in the (null (cdr L)) case, it's good to move that case out of the LET.
- After that case is moved out of the LET, it can be combined with the (null L) base case, because (list L ()) is a good value to return in both cases.

Example of the Use of `(cddr L)` as a Recursive Call Argument

```
(defun split-list (L)
  (if (null L)
      '(()())
      (let ((X (split-list (cddr L))))
        (cond ((null (cdr L)) (list L ()))
              (t (list (cons (car L) (car X))
                        (cons (cadr L) (cadr X)))))))))
```

- As `X` is not used in the `(null (cdr L))` case, it's good to move that case out of the LET.
- After that case is moved out of the LET, it can be combined with the `(null L)` base case, because `(list L ())` is a good value to return in both cases.

Example of the Use of `(cddr L)` as a Recursive Call Argument

```
(defun split-list (L)
  (if (null L)
      '(()())
      (let ((X (split-list (cddr L))))
        (cond ((null (cdr L)) (list L ()))
              (t (list (cons (car L) (car X))
                        (cons (cadr L) (cadr X))))))))
```

- As `X` is not used in the `(null (cdr L))` case, it's good to move that case out of the LET.
- After that case is moved out of the LET, it can be combined with the `(null L)` base case, because `(list L ())` is a good value to return in both cases.

Final version:

Example of the Use of (cddr L) as a Recursive Call Argument

```
(defun split-list (L)
  (if (null L)
      '(()())
      (let ((X (split-list (cddr L))))
        (cond ((null (cdr L)) (list L ()))
              (t (list (cons (car L) (car X))
                        (cons (cadr L) (cadr X))))))))
```

- As **X** is not used in the (null (cdr L)) case, it's good to move that case out of the LET.
- After that case is moved out of the LET, it can be combined with the (null L) base case, because (list L ()) is a good value to return in both cases.

Final version: (defun split-list (L)

Note that calling (if (null (cdr L))
 (split-list (cddr L))
instead of
 (split-list (cdr L))
reduces the depth
of recursion.

```
                          (list L ())  
                          (let ((X (split-list (cddr L))))  
                              (list (cons (car L) (car X))  
                                     (cons (cadr L) (cadr X)))))
```

Example of the Use of $(\text{floor } n^2)$ as a Recursive Call Argument
 e (i.e., the base of natural logs) is one of the best known constants. How can we calculate e very accurately?

Example of the Use of **(floor n 2)** as a Recursive Call Argument


e (i.e., the base of natural logs) is one of the best known constants. How can we calculate e very accurately? To be concrete, let's say we want to find a number y such that:

[illegible]

graph of e and $(1+1/x)^{x+1}$ and $(1+1/x)^x$ from 1 to 1000

 Extended Keyboard


 Upload

 Examples

Input interpretation:

	e	
plot	$\left(1 + \frac{1}{x}\right)^{x+1}$	$x = 1 \text{ to } 1000$
	$\left(1 + \frac{1}{x}\right)^x$	

Plot:



e (i.e., the base of natural logs) is one of the best known constants. How can we calculate e very accurately? To be concrete, let's say we want to find a number y such that:

One way is to use the following fact (which we'll assume is true but isn't very hard to prove if you know enough calculus):

When $n = 10^{25}$, this fact says that (\clubsuit) holds when y is
 $(1 + 10^{-25})^{10^{25}} = 1.\underbrace{000000000000000000000000}_{25 \text{ zeros}}1\underbrace{000000000000000000000000}_{25 \text{ zeros}}$

(power z n) $\Rightarrow z^n$ if $z \Rightarrow$ a number & $n \Rightarrow$ an integer ≥ 0

54

Example of the Use of **(floor n 2)** as a Recursive Call Argument

e (i.e., the base of natural logs) is one of the best known constants. How can we calculate e very accurately? To be concrete, let's say we want to find a number y such that:

[illegible]

(♣) holds when y is

$$(1 + 10^{-25})^{10^{25}} = 1.\underbrace{000000000000000000000000}_{\text{25 zeros}}0\underbrace{1000000000000000000000000}_{\text{25 ones}}$$

Q. How can we write a recursive function **power** such that

(power z n) $\Rightarrow z^n$ if $z \Rightarrow$ a number & $n \Rightarrow$ an integer ≥ 0

that can be used to compute $(1 + 10^{-25})^{10^{25}}$?

e (i.e., the base of natural logs) is one of the best known constants. How can we calculate e very accurately? To be concrete, let's say we want to find a number y such that:

[illegible]

(power z n) $\Rightarrow z^n$ if $z \Rightarrow$ a number & $n \Rightarrow$ an integer ≥ 0

that can be used to compute $(1 + 10^{-25})^{10^{25}}$?

- ```
(defun power (z n) ; far too inefficient!
 (cond ((= n 0) 1)
 (t (* z (power z (- n 1))))))
```

58







## Example of the Use of (floor n 2) as a Recursive Call Argument

$e$  (i.e., the base of natural logs) is one of the best known constants. How can we calculate  $e$  very accurately? To be concrete, let's say we want to find a number  $y$  such that:

[illegible]

It can be shown using calculus that ( $\clubsuit$ ) holds when  $y$  is  $(1 + 10^{-25})^{10^{25}} = 1.\underbrace{000000000000000000000000}_{\text{25 zeros}}1^{\underbrace{1000000000000000000000000}_{\text{25 zeros}}}$

Q. How can we write a recursive function **power** such that

(power z n)  $\Rightarrow z^n$  if  $z \Rightarrow$  a number &  $n \Rightarrow$  an integer  $\geq 0$

that can be used to compute  $(1 + 10^{-25})^{10^{25}}$ ?

- A solution is given by the function below, which is based on:

$$z^n = (z^{\lfloor n/2 \rfloor})^2 \text{ if } n \text{ is } \underline{\text{even}}; \quad z^n = z * (z^{\lfloor n/2 \rfloor})^2 \text{ if } n \text{ is } \underline{\text{odd}}.$$

**Examples:**  $z^{12} = (z^6)^2$  and  $z^{11} = z^*(z^5)^2$ .







## Example of the Use of (floor n 2) as a Recursive Call Argument

We want to find a number  $y$  such that:

$$y < e < 1.\underbrace{000000000000000000000000}_{\text{25 zeros}}1 \, y = (1 + 10^{-25}) y \quad (\clubsuit)$$

It can be shown using calculus that (♣) holds when  $y$  is

$$(1 + 10^{-25})^{10^{25}} = 1.\underbrace{000000000000000000000000}_{25 \text{ zeros}}1^{\underbrace{1000000000000000000000000}_{25 \text{ zeros}}}$$

Q. How can we write a recursive function **power** such that

(power z n)  $\Rightarrow z^n$  if  $z \Rightarrow$  a number &  $n \Rightarrow$  an integer  $\geq 0$

that can be used to compute  $(1 + 10^{-25})^{10^{25}}$ ?

- A solution is given by the function below:

```
(defun power (z n)
 (cond ((zerop n) 1)
 (t (let ((X (power z (floor n 2))))
 (cond ((evenp n) (* X X))
 (t (* z X X)))))))
```

- We get  $\lfloor n/2 \rfloor$  by chopping off the rightmost bit of  $n$ .

●



