

Syntax of Programming Languages

Syntax and Semantics of Expressions

Loosely speaking:

- *Syntax* means “form”.
- *Semantics* means “meaning”.

In the context of programming languages:

Loosely speaking:

- ***Syntax*** means “form”.
- ***Semantics*** means “meaning”.

In the context of programming languages:

- The Java expressions **a - 3 - b** and **u - 7 - v** have the *same syntax*, but *different semantics*.

Loosely speaking:

- ***Syntax*** means “form”.
- ***Semantics*** means “meaning”.

In the context of programming languages:

- The Java expressions $a - 3 - b$ and $u - 7 - v$ have the *same syntax*, but *different semantics*.
- The Java expressions $a - 3 - b$ and $((a - 3) - b)$ have the *same semantics*, but *different syntax*.

Loosely speaking:

- **Syntax** means “form”.
- **Semantics** means “meaning”.

In the context of programming languages:

- The Java expressions $a - 3 - b$ and $u - 7 - v$ have the *same syntax*, but *different semantics*.
- The Java expressions $a - 3 - b$ and $((a - 3) - b)$ have the *same semantics*, but *different syntax*.
- The Lisp expression $(- (- 2 3) 4)$ and the Java expression $2 - 3 - 4$ have the *same semantics* but have *different syntax*.

Operators, Arities, and Operands

An *operator of arity k* , also called a *k -ary operator*, is a symbol that represents a function of k arguments.

Operators, Arities, and Operands

An *operator of arity k* , also called a *k -ary operator*, is a symbol that represents a function of k arguments.

- *Binary* means 2-ary.
- *Unary* means 1-ary.
- *Ternary* means 3-ary.

Operators, Arities, and Operands

An *operator of arity k* , also called a *k -ary operator*, is a symbol that represents a function of k arguments.

- *Binary* means 2-ary.
- *Unary* means 1-ary.
- *Ternary* means 3-ary.

When a k -ary operator appears in an expression, each of the k subexpressions whose values are the k arguments of the function it represents is called an *operand* of the operator.

Examples

Operators, Arities, and Operands

An *operator of arity k* , also called a *k -ary operator*, is a symbol that represents a function of k arguments.

- *Binary* means 2-ary.
- *Unary* means 1-ary.
- *Ternary* means 3-ary.

When a k -ary operator appears in an expression, each of the k subexpressions whose values are the k arguments of the function it represents is called an *operand* of the operator.

Examples

In a Java or C++ expression $x - y + z$

- $+$ is a binary operator whose operands are $x - y$ and z .
- $-$ is a binary operator whose operands are x and y .

Operators, Arities, and Operands

An *operator of arity k* , also called a *k -ary operator*, is a symbol that represents a function of k arguments.

- *Binary* means 2-ary.
- *Unary* means 1-ary.
- *Ternary* means 3-ary.

When a k -ary operator appears in an expression, each of the k subexpressions whose values are the k arguments of the function it represents is called an *operand* of the operator.

Examples

In a Java or C++ expression $x - y + z$

- $+$ is a binary operator whose operands are $x - y$ and z .
- $-$ is a binary operator whose operands are x and y .

In the Lisp expression $(+ (- x y) 3 (* z z))$

- $+$ is a ternary operator whose operands are $(- x y)$, 3 , and $(* z z)$.

Overview of Some Expression Notations

We will say that two expressions are *equivalent* if they have the same semantics.

Overview of Some Expression Notations

We will say that two expressions are equivalent if they have the same semantics.

Here is a Java expression: `f(g(h(1,2), f(3,4)), 5)`

We will now write equivalent expressions in:

Overview of Some Expression Notations

We will say that two expressions are equivalent if they have the same semantics.

Here is a Java expression: `f(g(h(1,2), f(3,4)), 5)`

We will now write equivalent expressions in:

- Infix notation, not making use of precedence classes
- Infix notation, making use of precedence classes
- Lisp notation
- Prefix notation
- Postfix notation (also called **Reverse Polish Notation**)

Overview of Some Expression Notations

We will say that two expressions are equivalent if they have the same semantics.

Here is a Java expression: `f(g(h(1,2), f(3,4)), 5)`

We will now write equivalent expressions in:

- Infix notation, not making use of precedence classes
- Infix notation, making use of precedence classes
- Lisp notation
- Prefix notation
- Postfix notation (also called **Reverse Polish Notation**)

Infix Notation

In infix notation, we write binary operators *between* their operands--e.g., `f(3,4)` would be written `3 f 4`.

So the above Java expression is equivalent to the following infix expression:

Overview of Some Expression Notations

We will say that two expressions are equivalent if they have the same semantics.

Here is a Java expression: `f(g(h(1,2), f(3,4)), 5)`

We will now write equivalent expressions in:

- Infix notation, not making use of precedence classes
- Infix notation, making use of precedence classes
- Lisp notation
- Prefix notation
- Postfix notation (also called **Reverse Polish Notation**)

Infix Notation

In infix notation, we write binary operators *between* their operands--e.g., `f(3,4)` would be written `3 f 4`.

So the above Java expression is equivalent to the following infix expression: `((1 h 2) g (3 f 4)) f 5`

The designer of an infix notation will usually give *precedence and associativity rules* for the operators, to reduce the need for parentheses.

Suppose the notation designer specifies that:

The designer of an infix notation will usually give *precedence and associativity rules* for the operators, to reduce the need for parentheses.

Suppose the notation designer specifies that:

- f and g belong to the *same* precedence class, and that precedence class is *left-associative*.
- h belongs a *higher* precedence class than f and g.

Now the above infix expression $((1\ h\ 2)\ g\ (3\ f\ 4))\ f\ 5$ is equivalent to:

The designer of an infix notation will usually give *precedence and associativity rules* for the operators, to reduce the need for parentheses.

Suppose the notation designer specifies that:

- f and g belong to the *same* precedence class, and that precedence class is *left-associative*.
- h belongs a *higher* precedence class than f and g.

Now the above infix expression $((1\ h\ 2)\ g\ (3\ f\ 4))\ f\ 5$
is equivalent to: $1\ h\ 2\ g\ (3\ f\ 4)\ f\ 5$

The designer of an infix notation will usually give *precedence and associativity rules* for the operators, to reduce the need for parentheses.

Suppose the notation designer specifies that:

- f and g belong to the *same* precedence class, and that precedence class is *left-associative*.
- h belongs a *higher* precedence class than f and g.

Now the above infix expression $((1\ h\ 2)\ g\ (3\ f\ 4))\ f\ 5$ is equivalent to:

$1\ h\ 2\ g\ (3\ f\ 4)\ f\ 5$

An Analogous Example

In ordinary infix arithmetic notation:

- + and - belong to the same precedence class, and that precedence class is left-associative.
- * belongs to a higher precedence class than + and -.

Thus the infix expression $((1\ *\ 2) - (3 + 4)) + 5$ is equivalent to:

The designer of an infix notation will usually give ***precedence and associativity rules*** for the operators, to reduce the need for parentheses.

Suppose the notation designer specifies that:

- f and g belong to the ***same*** precedence class, and that precedence class is ***left-associative***.
- h belongs a ***higher*** precedence class than f and g.

Now the above infix expression $((1\ h\ 2)\ g\ (3\ f\ 4))\ f\ 5$ is equivalent to:

$1\ h\ 2\ g\ (3\ f\ 4)\ f\ 5$

An Analogous Example

In ordinary infix arithmetic notation:

- + and - belong to the same precedence class, and that precedence class is left-associative.
- * belongs to a higher precedence class than + and -.

Thus the infix expression $((1\ *\ 2) - (3 + 4)) + 5$ is equivalent to:

$1\ *\ 2 - (3 + 4) + 5$

Lisp Notation and Prefix Notation

The above Java expression `f(g(h(1,2), f(3,4)), 5)` is equivalent to the following Lisp expression:

Lisp Notation and Prefix Notation

The above Java expression `f(g(h(1,2), f(3,4)), 5)`
is equivalent to the
following Lisp expression: `(f (g (h 1 2) (f 3 4)) 5)`

Lisp Notation and Prefix Notation

The above Java expression `f(g(h(1,2), f(3,4)), 5)` is equivalent to the following Lisp expression: `(f (g (h 1 2) (f 3 4)) 5)`

Prefix notation is *Lisp notation without parentheses*. Thus the above Java expression is equivalent to the following prefix expression:

Lisp Notation and Prefix Notation

The above Java expression `f(g(h(1,2), f(3,4)), 5)` is equivalent to the following Lisp expression: `(f (g (h 1 2) (f 3 4)) 5)`

Prefix notation is *Lisp notation without parentheses*.

Thus the above Java expression is equivalent to the following prefix expression: `f g h 1 2 f 3 4 5`

Lisp Notation and Prefix Notation

The above Java expression `f(g(h(1,2), f(3,4)), 5)` is equivalent to the following Lisp expression: `(f (g (h 1 2) (f 3 4)) 5)`

Prefix notation is *Lisp notation without parentheses*.

Thus the above Java expression is equivalent to the following prefix expression: `f g h 1 2 f 3 4 5`

Prefix notation is not ambiguous **if we know the arity of every operator**: Then we can “put parentheses back” to produce an equivalent Lisp expression.

If we do not know the arities of operators, then prefix notation can be ambiguous.

For example,

Lisp Notation and Prefix Notation

The above Java expression `f(g(h(1,2), f(3,4)), 5)` is equivalent to the following Lisp expression: `(f (g (h 1 2) (f 3 4)) 5)`

Prefix notation is *Lisp notation without parentheses*.

Thus the above Java expression is equivalent to the following prefix expression: `f g h 1 2 f 3 4 5`

Prefix notation is not ambiguous **if we know the arity of every operator**: Then we can “put parentheses back” to produce an equivalent Lisp expression.

If we do not know the arities of operators, then prefix notation can be ambiguous.

For example, if `+` and `-` are binary then `+ 1 - 2 3` is equivalent to

Lisp Notation and Prefix Notation

The above Java expression `f(g(h(1,2), f(3,4)), 5)` is equivalent to the following Lisp expression: `(f (g (h 1 2) (f 3 4)) 5)`

Prefix notation is *Lisp notation without parentheses*.

Thus the above Java expression is equivalent to the following prefix expression: `f g h 1 2 f 3 4 5`

Prefix notation is not ambiguous **if we know the arity of every operator**: Then we can “put parentheses back” to produce an equivalent Lisp expression.

If we do not know the arities of operators, then prefix notation can be ambiguous.

For example, if `+` and `-` are binary then `+ 1 - 2 3` is equivalent to `(+ 1 (- 2 3))`,

Lisp Notation and Prefix Notation

The above Java expression `f(g(h(1,2), f(3,4)), 5)` is equivalent to the following Lisp expression: `(f (g (h 1 2) (f 3 4)) 5)`

Prefix notation is *Lisp notation without parentheses*.

Thus the above Java expression is equivalent to the following prefix expression: `f g h 1 2 f 3 4 5`

Prefix notation is not ambiguous if we know the arity of every operator: Then we can “put parentheses back” to produce an equivalent Lisp expression.

If we do not know the arities of operators, then prefix notation can be ambiguous.

For example, if `+` and `-` are binary then `+ 1 - 2 3` is equivalent to `(+ 1 (- 2 3))`, but if `+` is ternary and `-` is unary then `+ 1 - 2 3` is equivalent to

Lisp Notation and Prefix Notation

The above Java expression `f(g(h(1,2), f(3,4)), 5)` is equivalent to the following Lisp expression: `(f (g (h 1 2) (f 3 4)) 5)`

Prefix notation is *Lisp notation without parentheses*.

Thus the above Java expression is equivalent to the following prefix expression: `f g h 1 2 f 3 4 5`

Prefix notation is not ambiguous if we know the arity of every operator: Then we can “put parentheses back” to produce an equivalent Lisp expression.

If we do not know the arities of operators, then prefix notation can be ambiguous.

For example, if `+` and `-` are binary then `+ 1 - 2 3` is equivalent to `(+ 1 (- 2 3))`, but if `+` is ternary and `-` is unary then `+ 1 - 2 3` is equivalent to `(+ 1 (- 2) 3)`.

“RpnLisp” Notation and Postfix Notation

In Lisp, a function call is written as a list whose first element is the function name.

Now consider a notation we’ll call *rpnLisp* that’s the same as Lisp except in that a function call is written as a list whose last element is the function name.

“RpnLisp” Notation and Postfix Notation

In Lisp, a function call is written as a list whose first element is the function name.

Now consider a notation we’ll call *rpnLisp* that’s the same as Lisp except in that a function call is written as a list whose last element is the function name.

Thus the Lisp expression `(+ (- 1 2) (* 3 4 5) 6)` is equivalent to the following *rpnLisp* expression:

“RpnLisp” Notation and Postfix Notation

In Lisp, a function call is written as a list whose first element is the function name.

Now consider a notation we’ll call *rpnLisp* that’s the same as Lisp except in that a function call is written as a list whose Last element is the function name.

Thus the Lisp expression `(+ (- 1 2) (* 3 4 5) 6)` is equivalent to the following *rpnLisp* expression: `((1 2 -) (3 4 5 *) 6 +)`

“RpnLisp” Notation and Postfix Notation

In Lisp, a function call is written as a list whose first element is the function name.

Now consider a notation we’ll call *rpnLisp* that’s the same as Lisp except in that a function call is written as a list whose Last element is the function name.

Thus the Lisp expression `(+ (- 1 2) (* 3 4 5) 6)` is equivalent to the following *rpnLisp* expression: `((1 2 -) (3 4 5 *) 6 +)`

Just as prefix notation is “Lisp notation without parentheses”, postfix notation is “*rpnLisp notation without parentheses*”.

So the above expressions are equivalent to this postfix expression:

“RpnLisp” Notation and Postfix Notation

In Lisp, a function call is written as a list whose first element is the function name.

Now consider a notation we’ll call *rpnLisp* that’s the same as Lisp except in that a function call is written as a list whose Last element is the function name.

Thus the Lisp expression `(+ (- 1 2) (* 3 4 5) 6)` is equivalent to the following *rpnLisp* expression: `((1 2 -) (3 4 5 *) 6 +)`

Just as prefix notation is “Lisp notation without parentheses”, postfix notation is “*rpnLisp notation without parentheses*”.

So the above expressions are equivalent to this postfix expression: `1 2 - 3 4 5 * 6 +`

“RpnLisp” Notation and Postfix Notation

In Lisp, a function call is written as a list whose first element is the function name.

Now consider a notation we’ll call *rpnLisp* that’s the same as Lisp except in that a function call is written as a list whose last element is the function name.

Thus the Lisp expression `(+ (- 1 2) (* 3 4 5) 6)` is equivalent to the following *rpnLisp* expression: `((1 2 -) (3 4 5 *) 6 +)`

Just as prefix notation is “Lisp notation without parentheses”, postfix notation is “*rpnLisp notation without parentheses*”.

So the above expressions are equivalent to this postfix expression: `1 2 - 3 4 5 * 6 +`

In *rpnLisp*, *rpn* stands for “reverse polish notation”.

The above Java expression
is equivalent to the
Lisp expression
and this rpnLisp expression:

`f(g(h(1,2), f(3,4)), 5)`
`(f (g (h 1 2) (f 3 4)) 5)`

The above Java expression
is equivalent to the

Lisp expression

and this rpnLisp expression:

`f(g(h(1,2), f(3,4)), 5)`

`(f (g (h 1 2) (f 3 4)) 5)`

`((1 2 h) (3 4 f) g) 5 f)`

The above Java expression `f(g(h(1,2), f(3,4)), 5)`
is equivalent to the
Lisp expression `(f (g (h 1 2) (f 3 4)) 5)`
and this rpnLisp expression: `((1 2 h) (3 4 f) g) 5 f)`
Thus the expression is equivalent
to this *postfix* expression: `1 2 h 3 4 f g 5 f`

The above Java expression `f(g(h(1,2), f(3,4)), 5)`
is equivalent to the
Lisp expression `(f (g (h 1 2) (f 3 4)) 5)`
and this rpnLisp expression: `((1 2 h) (3 4 f) g) 5 f)`

Thus the expression is equivalent
to this postfix expression: `1 2 h 3 4 f g 5 f`

As is the case with prefix notation, postfix notation
isn't ambiguous if we know the arity of each operator:

If we do not know the arities of operators, then
postfix notation can be ambiguous.

For example:

The above Java expression `f(g(h(1,2), f(3,4)), 5)`
 is equivalent to the
 Lisp expression `(f (g (h 1 2) (f 3 4)) 5)`
 and this rpnLisp expression: `((1 2 h) (3 4 f) g) 5 f)`

Thus the expression is equivalent
 to this postfix expression: `1 2 h 3 4 f g 5 f`

As is the case with prefix notation, postfix notation
 isn't ambiguous if we know the arity of each operator:

If we do not know the arities of operators, then
 postfix notation can be ambiguous.

For example:

- If + and - are binary, the postfix expression `1 2 3 + -`
 is equivalent to the rpnLisp expression `(1 (2 3 +) -)`

The above Java expression `f(g(h(1,2), f(3,4)), 5)`
is equivalent to the
Lisp expression `(f (g (h 1 2) (f 3 4)) 5)`
and this rpnLisp expression: `((1 2 h) (3 4 f) g) 5 f)`

Thus the expression is equivalent
to this postfix expression: `1 2 h 3 4 f g 5 f`

As is the case with prefix notation, postfix notation
isn't ambiguous if we know the arity of each operator:

If we do not know the arities of operators, then
postfix notation can be ambiguous.

For example:

- If + and - are binary, the postfix expression `1 2 3 + -`
is equivalent to the rpnLisp expression `(1 (2 3 +) -)`
and equivalent to the Lisp expression `(- 1 (+ 2 3)) => -4.`

The above Java expression `f(g(h(1,2), f(3,4)), 5)`
 is equivalent to the
 Lisp expression `(f (g (h 1 2) (f 3 4)) 5)`
 and this rpnLisp expression: `((1 2 h) (3 4 f) g) 5 f)`

Thus the expression is equivalent
 to this **postfix** expression: `1 2 h 3 4 f g 5 f`

As is the case with prefix notation, postfix notation
 isn't ambiguous **if we know the arity of each operator**:

If we do not know the arities of operators, then
 postfix notation can be ambiguous.

For example:

- If + and - are binary, the postfix expression `1 2 3 + -`
 is equivalent to the rpnLisp expression `(1 (2 3 +) -)`
 and equivalent to the Lisp expression `(- 1 (+ 2 3)) => -4.`
- If + is ternary and - is unary, the expression `1 2 3 + -`
 is equivalent to the rpnLisp expression `((1 2 3 +) -)`
 and equivalent to the Lisp expression

The above Java expression `f(g(h(1,2), f(3,4)), 5)`
is equivalent to the
Lisp expression `(f (g (h 1 2) (f 3 4)) 5)`
and this rpnLisp expression: `((1 2 h) (3 4 f) g) 5 f)`

Thus the expression is equivalent
to this postfix expression: `1 2 h 3 4 f g 5 f`

As is the case with prefix notation, postfix notation
isn't ambiguous if we know the arity of each operator:

If we do not know the arities of operators, then
postfix notation can be ambiguous.

For example:

- If + and - are binary, the postfix expression `1 2 3 + -`
is equivalent to the rpnLisp expression `(1 (2 3 +) -)`
and equivalent to the Lisp expression `(- 1 (+ 2 3)) => -4.`
- If + is ternary and - is unary, the expression `1 2 3 + -`
is equivalent to the rpnLisp expression `((1 2 3 +) -)`
and equivalent to the Lisp expression `(- (+ 1 2 3)) => -6.`

More on Infix Notation

Infix notation allows unary and binary operators, but does *not* allow operators of arity > 2 .

Binary operators are written between their operands.

More on Infix Notation

Infix notation allows unary and binary operators, but does not allow operators of arity > 2 .

Binary operators are written between their operands.

The designer of an infix notation must specify, for each *unary* operator the notation allows, whether that unary operator is to be written as a ***prefix operator*** or is to be written as a ***postfix operator***:

More on Infix Notation

Infix notation allows unary and binary operators, but does **not** allow operators of arity > 2 .

Binary operators are written between their operands.

The designer of an infix notation must specify, for each *unary* operator the notation allows, whether that unary operator is to be written as a ***prefix operator*** or is to be written as a ***postfix operator***:

- Prefix operators are written *before* their operands.

- **Examples:**

- Postfix operators are written *after* their operands.

- **Example:**

More on Infix Notation

Infix notation allows unary and binary operators, but does not allow operators of arity > 2 .

Binary operators are written between their operands.

The designer of an infix notation must specify, for each *unary* operator the notation allows, whether that unary operator is to be written as a ***prefix operator*** or is to be written as a ***postfix operator***:

- Prefix operators are written *before* their operands.
 - **Examples:** `-` in a Java or C++ expression `-x`
`++` in a Java or C++ expression `++i`
`*` in a C++ expression `*ptr`
- Postfix operators are written *after* their operands.
 - **Example:**

More on Infix Notation

Infix notation allows unary and binary operators, but does not allow operators of arity > 2.

Binary operators are written between their operands.

The designer of an infix notation must specify, for each *unary* operator the notation allows, whether that unary operator is to be written as a ***prefix operator*** or is to be written as a ***postfix operator***:

- Prefix operators are written *before* their operands.
 - **Examples:** `-` in a Java or C++ expression `-x`
`++` in a Java or C++ expression `++i`
`*` in a C++ expression `*ptr`
- Postfix operators are written *after* their operands.
 - **Example:** `++` in a Java or C++ expression `i++`

Syntactically Valid Infix Expressions

An expression e is a *syntactically valid infix expression* (*s.v.i.e.*) if one of the following is true:

Syntactically Valid Infix Expressions

An expression e is a *syntactically valid infix expression* (*s.v.i.e.*) if one of the following is true:

1. e is a literal constant or an identifier.

Syntactically Valid Infix Expressions

An expression e is a *syntactically valid infix expression* (s.v.i.e.) if one of the following is true:

1. e is a literal constant or an identifier.
2. $e = (e_1)$, where e_1 is an s.v.i.e.

Syntactically Valid Infix Expressions

An expression e is a *syntactically valid infix expression* (*s.v.i.e.*) if one of the following is true:

1. e is a literal constant or an identifier.
2. $e = (e_1)$, where e_1 is an s.v.i.e.
3. $e = e_1 \text{ op } e_2$ where each of e_1 and e_2 is an s.v.i.e. and **op** is a binary operator.

Syntactically Valid Infix Expressions

An expression e is a *syntactically valid infix expression* (*s.v.i.e.*) if one of the following is true:

1. e is a literal constant or an identifier.
2. $e = (e_1)$, where e_1 is an s.v.i.e.
3. $e = e_1 \text{ op } e_2$ where each of e_1 and e_2 is an s.v.i.e. and **op** is a binary operator.
4. $e = \text{op } e_1$ where e_1 is an s.v.i.e. and **op** is a prefix unary operator.

Syntactically Valid Infix Expressions

An expression e is a *syntactically valid infix expression* (*s.v.i.e.*) if one of the following is true:

1. e is a literal constant or an identifier.
2. $e = (e_1)$, where e_1 is an s.v.i.e.
3. $e = e_1 \text{ op } e_2$ where each of e_1 and e_2 is an s.v.i.e. and **op** is a binary operator.
4. $e = \text{op } e_1$ where e_1 is an s.v.i.e. and **op** is a prefix unary operator.
5. $e = e_1 \text{ op}$ where e_1 is an s.v.i.e. and **op** is a postfix unary operator.

Syntactically Valid Infix Expressions

An expression e is a *syntactically valid infix expression* (*s.v.i.e.*) if one of the following is true:

1. e is a literal constant or an identifier.
2. $e = (e_1)$, where e_1 is an s.v.i.e.
3. $e = e_1 \text{ op } e_2$ where each of e_1 and e_2 is an s.v.i.e. and **op** is a binary operator.
4. $e = \text{op } e_1$ where e_1 is an s.v.i.e. and **op** is a prefix unary operator.
5. $e = e_1 \text{ op}$ where e_1 is an s.v.i.e. and **op** is a postfix unary operator.

Rules 2 – 5 give decompositions of e into two (rules 4 & 5) or three (rule 2 & 3) substructures, but

Syntactically Valid Infix Expressions

An expression e is a *syntactically valid infix expression* (*s.v.i.e.*) if one of the following is true:

1. e is a literal constant or an identifier.
2. $e = (e_1)$, where e_1 is an s.v.i.e.
3. $e = e_1 \text{ op } e_2$ where each of e_1 and e_2 is an s.v.i.e. and **op** is a binary operator.
4. $e = \text{op } e_1$ where e_1 is an s.v.i.e. and **op** is a prefix unary operator.
5. $e = e_1 \text{ op}$ where e_1 is an s.v.i.e. and **op** is a postfix unary operator.

Rules 2 – 5 give decompositions of e into two (rules 4 & 5) or three (rule 2 & 3) substructures, but some of these decompositions may *violate* the following important principle of syntax specification:

- *The semantics of a structure should be easily definable in terms of the semantics of its syntactic substructures.*

Example of How the Principle May be Violated

Recall that the principle is:

- *The semantics of a structure should be easily definable in terms of the semantics of its syntactic substructures.*

Example of How the Principle May be Violated

Recall that the principle is:

- *The semantics of a structure should be easily definable in terms of the semantics of its syntactic substructures.*

Let e be the following Java expression: $x - y * z + w$

Then 3. $e = e_1 \text{ op } e_2$ where each of e_1 and e_2 is an s.v.i.e. and op is a binary operator.

gives the following decompositions of e :

Example of How the Principle May be Violated

Recall that the principle is:

- *The semantics of a structure should be easily definable in terms of the semantics of its syntactic substructures.*

Let e be the following Java expression: $x - y * z + w$

Then 3. $e = e_1 \text{ op } e_2$ where each of e_1 and e_2 is an s.v.i.e. and op is a binary operator.

gives the following decompositions of e :

$$(i) \quad e_1 = x \qquad \text{op} = - \qquad e_2 = y * z + w$$

Example of How the Principle May be Violated

Recall that the principle is:

- *The semantics of a structure should be easily definable in terms of the semantics of its syntactic substructures.*

Let e be the following Java expression: $x - y * z + w$

Then 3. $e = e_1 \text{ op } e_2$ where each of e_1 and e_2 is an s.v.i.e. and op is a binary operator.

gives the following decompositions of e :

(i)	$e_1 = x$	$\text{op} = -$	$e_2 = y * z + w$
(ii)	$e_1 = x - y$	$\text{op} = *$	$e_2 = z + w$

Example of How the Principle May be Violated

Recall that the principle is:

- *The semantics of a structure should be easily definable in terms of the semantics of its syntactic substructures.*

Let e be the following Java expression: $x - y * z + w$

Then 3. $e = e_1 \text{ op } e_2$ where each of e_1 and e_2 is an s.v.i.e. and op is a binary operator.

gives the following decompositions of e :

- | | | | |
|-------|-------------------|-----------------|-------------------|
| (i) | $e_1 = x$ | $\text{op} = -$ | $e_2 = y * z + w$ |
| (ii) | $e_1 = x - y$ | $\text{op} = *$ | $e_2 = z + w$ |
| (iii) | $e_1 = x - y * z$ | $\text{op} = +$ | $e_2 = w$ |

Example of How the Principle May be Violated

Recall that the principle is:

- *The semantics of a structure should be easily definable in terms of the semantics of its syntactic substructures.*

Let e be the following Java expression: $x - y * z + w$

Then 3. $e = e_1 \text{ op } e_2$ where each of e_1 and e_2 is an s.v.i.e. and op is a binary operator.

gives the following decompositions of e :

- | | | | |
|-------|-------------------|-----------------|-------------------|
| (i) | $e_1 = x$ | $\text{op} = -$ | $e_2 = y * z + w$ |
| (ii) | $e_1 = x - y$ | $\text{op} = *$ | $e_2 = z + w$ |
| (iii) | $e_1 = x - y * z$ | $\text{op} = +$ | $e_2 = w$ |

But decompositions (i) and (ii) both violate the above principle, because (based on the semantics of Java), e is equivalent to: $(x - y * z) + w$

Example of How the Principle May be Violated

Recall that the principle is:

- *The semantics of a structure should be easily definable in terms of the semantics of its syntactic substructures.*

Let e be the following Java expression: $x - y * z + w$

Then 3. $e = e_1 \text{ op } e_2$ where each of e_1 and e_2 is an s.v.i.e. and op is a binary operator.

gives the following decompositions of e :

- | | | | |
|-------|-------------------|-----------------|-------------------|
| (i) | $e_1 = x$ | $\text{op} = -$ | $e_2 = y * z + w$ |
| (ii) | $e_1 = x - y$ | $\text{op} = *$ | $e_2 = z + w$ |
| (iii) | $e_1 = x - y * z$ | $\text{op} = +$ | $e_2 = w$ |

But decompositions (i) and (ii) both violate the above principle, because (based on the semantics of Java), e is equivalent to: $(x - y * z) + w$

- Sec. 2.5 of Sethi (assigned reading after Exam 1) gives another way to specify syntactically valid infix expressions *that does not have this drawback.*

Semantics of an Infix Expression e

The semantics of e tells you how e can be evaluated.

Semantics of an Infix Expression e

The semantics of e tells you how e can be evaluated.

Let $e.value$ denote the value of e . Then:

Semantics of an Infix Expression e

The semantics of e tells you how e can be evaluated.

Let $e.value$ denote the value of e . Then:

1. If e is an identifier or a literal constant,
 $e.value = \text{the value of the identifier / constant.}$

Semantics of an Infix Expression e

The semantics of e tells you how e can be evaluated.

Let $e.value$ denote the value of e . Then:

1. If e is an identifier or a literal constant,
 $e.value = \text{the value of the identifier / constant.}$
2. If $e = (e_1)$,
 $e.value = e_1.value.$

Semantics of an Infix Expression e

The semantics of e tells you how e can be evaluated.

Let $e.value$ denote the value of e . Then:

1. If e is an identifier or a literal constant,
 $e.value = \text{the value of the identifier / constant.}$
2. If $e = (e_1)$,
 $e.value = e_1.value.$

Otherwise, *Let op be the operator of e that should be applied Last.* Then:

Semantics of an Infix Expression e

The semantics of e tells you how e can be evaluated.

Let $e.value$ denote the value of e . Then:

1. If e is an identifier or a literal constant,
 $e.value = \text{the value of the identifier / constant.}$
2. If $e = (e_1)$,
 $e.value = e_1.value.$

Otherwise, *Let op be the operator of e that should be applied Last.* Then:

- If e is $e_1 \text{ } op \text{ } e_2$,
 $e.value = \text{result of applying } op \text{ with } e_1.value \text{ and } e_2.value \text{ as the 1st and 2nd arguments.}$

Semantics of an Infix Expression e

The semantics of e tells you how e can be evaluated.

Let $e.value$ denote the value of e . Then:

1. If e is an identifier or a literal constant,
 $e.value = \text{the value of the identifier / constant.}$
2. If $e = (e_1)$,
 $e.value = e_1.value.$

Otherwise, *Let op be the operator of e that should be applied Last.* Then:

- If e is $e_1 \text{ } op \text{ } e_2$,
 $e.value = \text{result of applying } op \text{ with } e_1.value \text{ and } e_2.value \text{ as the 1st and 2nd arguments.}$
- If e is $op \text{ } e_1$ or e is $e_1 \text{ } op$
 $e.value = \text{result of applying } op \text{ to } e_1.value.$

Semantics of an Infix Expression e

The semantics of e tells you how e can be evaluated.

Let $e.value$ denote the value of e . Then:

1. If e is an identifier or a literal constant,
 $e.value = \text{the value of the identifier / constant.}$
2. If $e = (e_1)$,
 $e.value = e_1.value.$

Otherwise, *Let op be the operator of e that should be applied Last.* Then:

- If e is $e_1 \text{ } op \text{ } e_2$,
 $e.value = \text{result of applying } op \text{ with } e_1.value \text{ and } e_2.value \text{ as the 1st and 2nd arguments.}$
- If e is $op \text{ } e_1$ or e is $e_1 \text{ } op$
 $e.value = \text{result of applying } op \text{ to } e_1.value.$

Key Question: How can we determine which operator of e should be applied last?

How to Determine Which Operator of an Infix Expression e Should be Applied Last

We'll say an operator op is *top-level* in e if

(a) op is not a binary operator \circ such that $e = (e_1 \circ e_2)$ and

(b) op is not a unary operator u such that $e = u(e_1)$ and

(c) op is not a binary operator \circ such that $e = (e_1 \circ e_2)$ and

How to Determine Which Operator of an Infix Expression *e* Should be Applied Last

We'll say an operator *op* is *top-level* in *e* if

- (a) *op* is not surrounded by parentheses in *e*, and
- (b) *op* is not a prefix unary operator that is immediately after another operator in *e*, and
- (c) *op* is not a postfix unary operator that is immediately before another operator in *e*.

Example:

How to Determine Which Operator of an Infix Expression e Should be Applied Last

We'll say an operator op is *top-level* in e if

- (a) op is not surrounded by parentheses in e , and
- (b) op is not a prefix unary operator that is immediately after another operator in e , and
- (c) op is not a postfix unary operator that is immediately before another operator in e .

Example: The top-level operators in the C++ expression

$-x / -(y + (z - 3) - 2) * w ++ \% v ++$

are

How to Determine Which Operator of an Infix Expression e Should be Applied Last

We'll say an operator op is *top-level* in e if

- (a) op is not surrounded by parentheses in e , and
- (b) op is not a prefix unary operator that is immediately after another operator in e , and
- (c) op is not a postfix unary operator that is immediately before another operator in e .

Example: The top-level operators in the C++ expression

$-x / -(y + (z - 3) - 2) * w ++ \% v ++$

are the *1st unary -*,

How to Determine Which Operator of an Infix Expression e Should be Applied Last

We'll say an operator op is *top-level* in e if

- (a) op is not surrounded by parentheses in e , and
- (b) op is not a prefix unary operator that is immediately after another operator in e , and
- (c) op is not a postfix unary operator that is immediately before another operator in e .

Example: The top-level operators in the C++ expression

$-x / -(y + (z - 3) - 2) * w ++ \% v ++$

are the *1st unary* $-$, $/$,

How to Determine Which Operator of an Infix Expression e Should be Applied Last

We'll say an operator op is **top-level** in e if

- (a) op is not surrounded by parentheses in e , and
- (b) op is not a prefix unary operator that is immediately after another operator in e , and
- (c) op is not a postfix unary operator that is immediately before another operator in e .

Example: The top-level operators in the C++ expression

$-x / -(y + (z - 3) - 2) * w ++ \% v ++$

are the **1st unary** $-$, $/$, $*$,

How to Determine Which Operator of an Infix Expression e Should be Applied Last

We'll say an operator op is **top-level** in e if

- (a) op is not surrounded by parentheses in e , and
- (b) op is not a prefix unary operator that is immediately after another operator in e , and
- (c) op is not a postfix unary operator that is immediately before another operator in e .

Example: The top-level operators in the C++ expression

$-x / -(y + (z - 3) - 2) * w ++ \% v ++$

are the **1st unary** $-$, $/$, $*$, $\%$,

How to Determine Which Operator of an Infix Expression e Should be Applied Last

We'll say an operator op is *top-level* in e if

- (a) op is not surrounded by parentheses in e , and
- (b) op is not a prefix unary operator that is immediately after another operator in e , and
- (c) op is not a postfix unary operator that is immediately before another operator in e .

Example: The top-level operators in the C++ expression

$-x / -(y + (z - 3) - 2) * w ++ \% v ++$

are the *1st unary* $-$, $/$, $*$, $\%$, and the *2nd* $++$.

How to Determine Which Operator of an Infix Expression e Should be Applied Last

We'll say an operator op is **top-level** in e if

- (a) op is not surrounded by parentheses in e , and
- (b) op is not a prefix unary operator that is immediately after another operator in e , and
- (c) op is not a postfix unary operator that is immediately before another operator in e .

Example: The top-level operators in the C++ expression

$-x / -(y + (z - 3) - 2) * w ++ \% v ++$

are the **1st** unary $-$, $/$, $*$, $\%$, and the **2nd** $++$.

The three operators in $(y + (z - 3) - 2)$ are not top-level: They violate (a).

How to Determine Which Operator of an Infix Expression e Should be Applied Last

We'll say an operator op is **top-level** in e if

- (a) op is not surrounded by parentheses in e , and
- (b) op is not a prefix unary operator that is immediately after another operator in e , and
- (c) op is not a postfix unary operator that is immediately before another operator in e .

Example: The top-level operators in the C++ expression

$-x / -(y + (z - 3) - 2) * w ++ \% v ++$

are the **1st unary** $-$, $/$, $*$, $\%$, and the **2nd** $++$.

The three operators in $(y + (z - 3) - 2)$ are not top-level: They violate (a).

The **2nd unary** $-$ is not top-level: It violates (b).

How to Determine Which Operator of an Infix Expression e Should be Applied Last

We'll say an operator op is **top-level** in e if

- (a) op is not surrounded by parentheses in e , and
- (b) op is not a prefix unary operator that is immediately after another operator in e , and
- (c) op is not a postfix unary operator that is immediately before another operator in e .

Example: The top-level operators in the C++ expression

$-x / -(y + (z - 3) - 2) * w ++ \% v ++$

are the **1st unary** $-$, $/$, $*$, $\%$, and the **2nd** $++$.

The three operators in $(y + (z - 3) - 2)$ are not top-level: They violate (a).

The **2nd** unary $-$ is not top-level: It violates (b).

The **1st** $++$ is not top-level: It violates (c).

**How to Determine Which Operator of an Infix Expression
e Should be Applied Last (Continued)**

How to Determine Which Operator of an Infix Expression **e** Should be Applied Last (Continued)

If no precedence and associativity rules for the operators have been given, then when an expression has more than one top level operator it will **not** be possible to uniquely determine which operator should be applied last!

How to Determine Which Operator of an Infix Expression **e** Should be Applied Last (Continued)

If no precedence and associativity rules for the operators have been given, then when an expression has more than one top level operator it will **not** be possible to uniquely determine which operator should be applied last!

However, the designer of an infix notation will usually give ***precedence and associativity rules*** for the operators that:

(i)

(ii)

How to Determine Which Operator of an Infix Expression **e** Should be Applied Last (Continued)

If no precedence and associativity rules for the operators have been given, then when an expression has more than one top level operator it will **not** be possible to uniquely determine which operator should be applied last!

However, the designer of an infix notation will usually give ***precedence and associativity rules*** for the operators that:

- (i) partition the operators into ***ranked precedence classes***, and
- (ii)

How to Determine Which Operator of an Infix Expression **e** Should be Applied Last (Continued)

If no precedence and associativity rules for the operators have been given, then when an expression has more than one top level operator it will not be possible to uniquely determine which operator should be applied last!

However, the designer of an infix notation will usually give **precedence and associativity rules** for the operators that:

- (i) partition the operators into **ranked precedence classes**, and
- (ii) specify, for each class, whether the class is **left**-associative (= **left-to-right** associative) or **right**-associative (= **right-to-left** associative).

An example of precedence and associativity rules (from the course reader).

assignment	=
logical or	
logical and	&&
inclusive or	
exclusive or	^
and	&
equality	== !=
relational	< <= >= >
shift	<< >>
additive	+ -
multiplicative	* / %

Figure 2.9 A partial table of binary operators in C, in order of increasing precedence; that is, the assignment operator = has the lowest precedence and the multiplicative operators *, /, and % have the highest precedence. All operators on the same line have the same precedence and associativity. The assignment operator is right associative; all the other operators are left associative.

How to Determine Which Operator of an Infix Expression **e** Should be Applied Last (Continued)

If no precedence and associativity rules for the operators have been given, then when an expression has more than one top level operator it will **not** be possible to uniquely determine which operator should be applied last!

However, the designer of an infix notation will usually give **precedence and associativity rules** for the operators that:

- (i) partition the operators into **ranked precedence classes**, and
- (ii) specify, for each class, whether the class is **left**-associative (= **left-to-right** associative) or **right**-associative (= **right-to-left** associative).

How to Determine Which Operator of an Infix Expression **e** Should be Applied Last (Continued)

If no precedence and associativity rules for the operators have been given, then when an expression has more than one top level operator it will not be possible to uniquely determine which operator should be applied last!

However, the designer of an infix notation will usually give **precedence and associativity rules** for the operators that:

- (i) partition the operators into **ranked precedence classes**, and
- (ii) specify, for each class, whether the class is **left**-associative (= **left-to-right** associative) or **right**-associative (= **right-to-left** associative).

Using these rules, *we can find the operator of **e** that should be applied last as follows:*

Follow These Steps to Determine Which Operator of an Infix Expression e Should be Applied Last:

1.

2.

2.1

2.2

2.3

Follow These Steps to Determine Which Operator of an Infix Expression e Should be Applied Last:

1. If e is of the form (e') , then the operator that should be applied last in e' is also the operator that should be applied last in e .

2.

2.1

2.2

2.3

Follow These Steps to Determine Which Operator of an Infix Expression e Should be Applied Last:

1. If e is of the form (e') , then the operator that should be applied last in e' is also the operator that should be applied last in e .
2. Otherwise, the operator that should be applied last in e can be found by doing 2.1 – 2.3 below.

2.1

2.2

2.3

Follow These Steps to Determine Which Operator of an Infix Expression e Should be Applied Last:

1. If e is of the form (e') , then the operator that should be applied last in e' is also the operator that should be applied last in e .
2. Otherwise, the operator that should be applied last in e can be found by doing 2.1 – 2.3 below.
 - 2.1 Find the top-level operators of lowest precedence rank in e .
 - 2.2
 - 2.3

Follow These Steps to Determine Which Operator of an Infix Expression e Should be Applied Last:

1. If e is of the form (e') , then the operator that should be applied last in e' is also the operator that should be applied last in e .
2. Otherwise, the operator that should be applied last in e can be found by doing 2.1 – 2.3 below.
 - 2.1 Find the top-level operators of lowest precedence rank in e .
 - 2.2 If just one operator is found by step 2.1, then that is the operator that should be applied last.
 - 2.3

Follow These Steps to Determine Which Operator of an Infix Expression e Should be Applied Last:

1. If e is of the form (e') , then the operator that should be applied last in e' is also the operator that should be applied last in e .
2. Otherwise, the operator that should be applied last in e can be found by doing 2.1 – 2.3 below.
 - 2.1 Find the top-level operators of lowest precedence rank in e .
 - 2.2 If just one operator is found by step 2.1, then that is the operator that should be applied last.
 - 2.3 If more than one operator is found by step 2.1, then the operator that should be applied last is the rightmost of the operators found by 2.1 if their precedence class is left-associative, **but**

Follow These Steps to Determine Which Operator of an Infix Expression e Should be Applied Last:

1. If e is of the form (e') , then the operator that should be applied last in e' is also the operator that should be applied last in e .
2. Otherwise, the operator that should be applied last in e can be found by doing 2.1 – 2.3 below.
 - 2.1 Find the top-level operators of Lowest precedence rank in e .
 - 2.2 If just one operator is found by step 2.1, then that is the operator that should be applied last.
 - 2.3 If more than one operator is found by step 2.1, then the operator that should be applied last is the rightmost of the operators found by 2.1 if their precedence class is Left-associative, *but* is the Leftmost of the operators found by 2.1 if their precedence class is right-associative.

- 2.1 Find the top-level operators of Lowest precedence rank in **e**.
- 2.2 If just one operator is found by step 2.1, then that is the operator that should be applied last.
- 2.3 If more than one operator is found by step 2.1, then the operator that should be applied last is the rightmost of the operators found by 2.1 if their precedence class is left-associative, **but** is the leftmost of the operators found by 2.1 if their precedence class is right-associative.

- 2.1 Find the top-level operators of Lowest precedence rank in **e**.
- 2.2 If just one operator is found by step 2.1, then that is the operator that should be applied last.
- 2.3 If more than one operator is found by step 2.1, then the operator that should be applied last is the rightmost of the operators found by 2.1 if their precedence class is Left-associative, **but** is the leftmost of the operators found by 2.1 if their precedence class is right-associative.

- 2.1 Find the top-level operators of lowest precedence rank in **e**.
- 2.2 If just one operator is found by step 2.1, then that is the operator that should be applied last.
- 2.3 If more than one operator is found by step 2.1, then the operator that should be applied last is the rightmost of the operators found by 2.1 if their precedence class is Left-associative, **but** is the leftmost of the operators found by 2.1 if their precedence class is right-associative.

- 2.1 Find the top-level operators of lowest precedence rank in **e**.
- 2.2 If just one operator is found by step 2.1, then that is the operator that should be applied last.
- 2.3 If more than one operator is found by step 2.1, then the operator that should be applied last is the rightmost of the operators found by 2.1 if their precedence class is Left-associative, **but** is the leftmost of the operators found by 2.1 if their precedence class is right-associative.

Example: Find the operator that should be applied last in this C expression:

$x * (y + (z + 3) - 2) + w - u / t$

Solution:

- 2.1 Find the top-level operators of lowest precedence rank in **e**.
- 2.2 If just one operator is found by step 2.1, then that is the operator that should be applied last.
- 2.3 If more than one operator is found by step 2.1, then the operator that should be applied last is the rightmost of the operators found by 2.1 if their precedence class is Left-associative, **but** is the leftmost of the operators found by 2.1 if their precedence class is right-associative.

Example: Find the operator that should be applied last in this C expression:

$x * (y + (z + 3) - 2) + w - u / t$

Solution: There are 4 top-level operators, namely the 4 **black** operators in:

$x * (y + (z + 3) - 2) + w - u / t$

Step 2.1:

Step 2.3:

assignment	=	From the course reader.
logical or		
logical and	&&	
inclusive or		
exclusive or	^	
and	&	
equality	== !=	
relational	< <= >= >	
shift	<< >>	
additive	+ -	
multiplicative	* / %	

Figure 2.9 A partial table of binary operators in C, in order of increasing precedence; that is, the assignment operator = has the lowest precedence and the multiplicative operators *, /, and % have the highest precedence. All operators on the same line have the same precedence and associativity. The assignment operator is right associative; all the other operators are left associative.

- 2.1 Find the top-level operators of lowest precedence rank in **e**.
- 2.2 If just one operator is found by step 2.1, then that is the operator that should be applied last.
- 2.3 If two or more operators are found by step 2.1, then the operator that should be applied last is the rightmost of the operators found by 2.1 if their precedence class is Left-associative, **but** is the leftmost of the operators found by 2.1 if their precedence class is right-associative.

Example: Find the operator that should be applied last in this C expression:

$x * (y + (z + 3) - 2) + w - u / t$

Solution: There are 4 top-level operators, namely the 4 **black** operators in:

$x * (y + (z + 3) - 2) + w - u / t$

Step 2.1:

Step 2.3:

- 2.1 Find the top-level operators of Lowest precedence rank in **e**.
- 2.2 If just one operator is found by step 2.1, then that is the operator that should be applied last.
- 2.3 If two or more operators are found by step 2.1, then the operator that should be applied last is the rightmost of the operators found by 2.1 if their precedence class is Left-associative, **but** is the leftmost of the operators found by 2.1 if their precedence class is right-associative.

Example: Find the operator that should be applied last in this C expression:

$x * (y + (z + 3) - 2) + w - u / t$

Solution: There are 4 top-level operators, namely the 4 **black** operators in:

$x * (y + (z + 3) - 2) + w - u / t$

Step 2.1: The top-level operators of Lowest precedence are the 2 **blue** operators in:

$x * (y + (z + 3) - 2) + w - u / t$

Step 2.3:

- 2.1 Find the top-level operators of Lowest precedence rank in **e**.
- 2.2 If just one operator is found by step 2.1, then that is the operator that should be applied last.
- 2.3 If two or more operators are found by step 2.1, then the operator that should be applied last is the rightmost of the operators found by 2.1 if their precedence class is Left-associative, **but** is the leftmost of the operators found by 2.1 if their precedence class is right-associative.

Example: Find the operator that should be applied last in this C expression:

$x * (y + (z + 3) - 2) + w - u / t$

Solution: There are 4 top-level operators, namely the 4 **black** operators in:

$x * (y + (z + 3) - 2) + w - u / t$

Step 2.1: The top-level operators of Lowest precedence are the 2 **blue** operators in: $x * (y + (z + 3) - 2) + w - u / t$

Step 2.3: These 2 operators **+** and **-** belong to a Left-associative precedence class, so the rightmost of them (i.e., **-**) must be applied last.

Precedence & Associativity Rules Might Not Uniquely Determine Which Operator Should be Applied First

Precedence & Associativity Rules Might Not Uniquely Determine Which Operator Should be Applied First

Consider this C/C++ expression: $y / 2 * --y$

$/$ and $*$ belong to a *left-associative* precedence class, so the operator that should be applied last is: $*$

Precedence & Associativity Rules Might Not Uniquely Determine Which Operator Should be Applied First

Consider this C/C++ expression: $y / 2 * --y$

$/$ and $*$ belong to a *left-associative* precedence class, so the operator that should be applied last is: $*$

But a C or C++ compiler is free to generate code that applies $--$ first or applies $/$ first!

Precedence & Associativity Rules Might Not Uniquely Determine Which Operator Should be Applied First

Consider this C/C++ expression: $y / 2 * --y$

$/$ and $*$ belong to a *left-associative* precedence class, so the operator that should be applied last is: $*$

But a C or C++ compiler is free to generate code that applies $--$ first or applies $/$ first!

Note: In addition to precedence & associativity rules, a language may have *other* rules that govern the order in which operators in infix expressions are applied!

Example:

Precedence & Associativity Rules Might Not Uniquely Determine Which Operator Should be Applied First

Consider this C/C++ expression: $y / 2 * --y$

$/$ and $*$ belong to a *left-associative* precedence class, so the operator that should be applied last is: $*$

But a C or C++ compiler is free to generate code that applies $--$ first or applies $/$ first!

Note: In addition to precedence & associativity rules, a language may have *other* rules that govern the order in which operators in infix expressions are applied!

Example: In Java, arguments of functions or operators are evaluated in left-to-right order, so $/$ is applied before $--$ when evaluating the above expression. Thus

Precedence & Associativity Rules Might Not Uniquely Determine Which Operator Should be Applied First

Consider this C/C++ expression: `y / 2 * --y`

`/` and `*` belong to a *left-associative* precedence class, so the operator that should be applied last is: `*`

But a C or C++ compiler is free to generate code that applies `--` first or applies `/` first!

Note: In addition to precedence & associativity rules, a language may have *other* rules that govern the order in which operators in infix expressions are applied!

Example: In Java, arguments of functions or operators are evaluated in left-to-right order, so `/` is applied before `--` when evaluating the above expression. Thus

```
int y = 4; System.out.println(y / 2 * --y);
```

prints 6 (not 3).

Precedence & Associativity Rules Might Not Uniquely Determine Which Operator Should be Applied First

Consider this C/C++ expression: `y / 2 * --y`

`/` and `*` belong to a *left-associative* precedence class, so the operator that should be applied last is: `*`

But a C or C++ compiler is free to generate code that applies `--` first or applies `/` first!

Note: In addition to precedence & associativity rules, a language may have *other* rules that govern the order in which operators in infix expressions are applied!

Example: In Java, arguments of functions or operators are evaluated in left-to-right order, so `/` is applied before `--` when evaluating the above expression. Thus

`int y = 4; System.out.println(y / 2 * --y);`
prints 6 (not 3). In C++ there's no left-to-right rule, so `int y = 4; cout << y / 2 * --y;` may print 3 or 6.