

Context-Free Grammars

Grammars were invented by Chomsky in the mid-1950s for describing natural languages. In the late 1950s, one of Chomsky's types of grammar (Type 2 or *context-free* grammar) was reinvented by Backus and proposed as a way to specify the syntax of the new language Algol.

Context-Free Grammars

Grammars were invented by Chomsky in the mid-1950s for describing natural languages. In the late 1950s, one of Chomsky's types of grammar (Type 2 or context-free grammar) was reinvented by Backus and proposed as a way to specify the syntax of the new language Algol.

This proposal was adopted in the **Algol 60 Report** (edited by Naur), an influential document considered to have done an excellent job of specifying Algol 60.

Context-Free Grammars

Grammars were invented by Chomsky in the mid-1950s for describing natural languages. In the late 1950s, one of Chomsky's types of grammar (Type 2 or **context-free** grammar) was reinvented by Backus and proposed as a way to specify the syntax of the new language Algol.

This proposal was adopted in the **Algol 60 Report** (edited by Naur), an influential document considered to have done an excellent job of specifying Algol 60.

The grammar notation used in the Algol 60 Report is now called "Backus Naur Form" or **BNF**.

Context-Free Grammars

Grammars were invented by Chomsky in the mid-1950s for describing natural languages. In the late 1950s, one of Chomsky's types of grammar (Type 2 or *context-free* grammar) was reinvented by Backus and proposed as a way to specify the syntax of the new language Algol.

This proposal was adopted in the **Algol 60 Report** (edited by Naur), an influential document considered to have done an excellent job of specifying Algol 60.

The grammar notation used in the Algol 60 Report is now called "Backus Naur Form" or **BNF**.

Like many authors (but unlike Sethi), we use the term **BNF** more loosely, to simply mean "*a commonly used notation for writing context-free grammars*"; we refer to grammars written in such a notation as **BNF specifications**.

A grammar written in BNF notation on p. 46 of Sethi (p. 47 in the course reader).

On p. 42, Sethi gives this equivalent grammar that is written in a similar notation. *We will consider this notation to be BNF,*

```

<expression> ::= <expression> + <term>
               | <expression> - <term>
               | <term>
<term> ::= <term> * <factor>
          | <term> / <factor>
          | <factor>
<factor> ::= number
           | name
           | ( <expression> )

```

A grammar written in BNF notation on p. 46 of Sethi (p. 47 in the course reader).

Figure 2.10 BNF syntactic rules for arithmetic expressions.

On p. 42, Sethi gives this equivalent grammar that is written in a similar notation. We will consider this notation to be BNF,

```

E ::= E + T | E - T | T
T ::= T * F | T / F | F
F ::= number | name | ( E )

```

Figure 2.6 A grammar for arithmetic expressions.

```

<expression> ::= <expression> + <term>
               | <expression> - <term>
               | <term>
<term> ::= <term> * <factor>
          | <term> / <factor>
          | <factor>
<factor> ::= number
           | name
           | ( <expression> )

```

A grammar written in BNF notation on p. 46 of Sethi (p. 47 in the course reader).

Figure 2.10 BNF syntactic rules for arithmetic expressions.

On p. 42, Sethi gives this equivalent grammar that is written in a similar notation. We will consider this notation to be BNF, even though it isn't exactly the same as the notation used in the Algol 60 Report and so Sethi does not call it BNF.

```

E ::= E + T | E - T | T
T ::= T * F | T / F | F
F ::= number | name | ( E )

```

Figure 2.6 A grammar for arithmetic expressions.

We will use the term grammar to mean "context-free grammar"; we will not use other types of grammar.

-

-

-

-

We will use the term grammar to mean "context-free grammar"; we will not use other types of grammar.

- A grammar is a relatively concise way to precisely specify certain (possibly infinite) *sets of finite sequences of symbols*; those symbols are referred to as *terminals* of the grammar.

-

-

-

We will use the term grammar to mean "context-free grammar"; we will not use other types of grammar.

- A grammar is a relatively concise way to precisely specify certain (possibly infinite) *sets of finite sequences of symbols*; those symbols are referred to as *terminals* of the grammar.
- Each of the specified *sets of finite sequences of terminals* is denoted by a *nonterminal* of the grammar.
-

-

We will use the term grammar to mean "context-free grammar"; we will not use other types of grammar.

- A grammar is a relatively concise way to precisely specify certain (possibly infinite) *sets of finite sequences of symbols*; those symbols are referred to as *terminals* of the grammar.
- Each of the specified *sets of finite sequences of terminals* is denoted by a *nonterminal* of the grammar.
- One of the nonterminals is regarded as the “most important”: It is called the *starting nonterminal* (or *start symbol* or *sentence symbol*);

•

We will use the term grammar to mean "context-free grammar"; we will not use other types of grammar.

- A grammar is a relatively concise way to precisely specify certain (possibly infinite) *sets of finite sequences of symbols*; those symbols are referred to as ***terminals*** of the grammar.
- Each of the specified *sets of finite sequences of terminals* is denoted by a ***nonterminal*** of the grammar.
- One of the nonterminals is regarded as the “most important”: It is called the ***starting nonterminal*** (or *start symbol* or *sentence symbol*); the set of sequences of terminals it denotes is called the ***language generated by*** (or *language of*) the grammar.
-

We will use the term grammar to mean "context-free grammar"; we will not use other types of grammar.

- A grammar is a relatively concise way to precisely specify certain (possibly infinite) *sets of finite sequences of symbols*; those symbols are referred to as ***terminals*** of the grammar.
- Each of the specified *sets of finite sequences of terminals* is denoted by a ***nonterminal*** of the grammar.
- One of the nonterminals is regarded as the “most important”: It is called the ***starting nonterminal*** (or *start symbol* or *sentence symbol*); the set of sequences of terminals it denotes is called the ***Language generated by*** (or *Language of*) the grammar.
- We commonly think of the other nonterminals as auxiliary nonterminals that are defined for use in defining the starting nonterminal.

$\langle \text{real-number} \rangle ::= \langle \text{integer-part} \rangle . \langle \text{fraction} \rangle$
 $\langle \text{integer-part} \rangle ::= \langle \text{digit} \rangle \mid \langle \text{integer-part} \rangle \langle \text{digit} \rangle$
 $\langle \text{fraction} \rangle ::= \langle \text{digit} \rangle \mid \langle \text{digit} \rangle \langle \text{fraction} \rangle$
 $\langle \text{digit} \rangle ::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9$

A grammar given by Sethi to specify unsigned floating point literals in a simple language.

Figure 2.3 BNF rules for real numbers.

In the above grammar:

$$\begin{aligned}
\langle \text{real-number} \rangle &::= \langle \text{integer-part} \rangle . \langle \text{fraction} \rangle \\
\langle \text{integer-part} \rangle &::= \langle \text{digit} \rangle \mid \langle \text{integer-part} \rangle \langle \text{digit} \rangle \\
\langle \text{fraction} \rangle &::= \langle \text{digit} \rangle \mid \langle \text{digit} \rangle \langle \text{fraction} \rangle \\
\langle \text{digit} \rangle &::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9
\end{aligned}$$

A grammar given by Sethi to specify unsigned floating point literals in a simple language.

Figure 2.3 BNF rules for real numbers.

In the above grammar:

The following characters are the 11 *terminals*:

. 0 1 2 3 4 5 6 7 8 9

A *terminal* of a grammar is a constant symbol that is *not* defined by the grammar.

```

<real-number> ::= <integer-part> . <fraction>
<integer-part> ::= <digit> | <integer-part> <digit>
<fraction> ::= <digit> | <digit> <fraction>
<digit> ::= 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9

```

A grammar given by Sethi to specify unsigned floating point literals in a simple language.

Figure 2.3 BNF rules for real numbers.

In the above grammar:

The following characters are the 11 ***terminals***:

. 0 1 2 3 4 5 6 7 8 9

A **terminal** of a grammar is a constant symbol that is **not** defined by the grammar.

The following are the 4 ***nonterminals***:

<real-number> <integer-part> <fraction> <digit>

A **nonterminal** of a grammar is a variable that denotes a set of finite sequences of terminals. For example, <digit> denotes


```

<real-number> ::= <integer-part> . <fraction>
<integer-part> ::= <digit> | <integer-part> <digit>
<fraction> ::= <digit> | <digit> <fraction>
<digit> ::= 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9

```

A grammar given by Sethi to specify unsigned floating point literals in a simple language.

Figure 2.3 BNF rules for real numbers.

In the above grammar:

The following characters are the 11 *terminals*:

. 0 1 2 3 4 5 6 7 8 9

A *terminal* of a grammar is a constant symbol that is *not* defined by the grammar.

The following are the 4 *nonterminals*:

<real-number> <integer-part> <fraction> <digit>

A *nonterminal* of a grammar is a variable that denotes a set of finite sequences of terminals. For example, <digit> denotes the set {0, 1, 2, 3, 4, 5, 6, 7, 8, 9}.

$\langle \text{real-number} \rangle ::= \langle \text{integer-part} \rangle . \langle \text{fraction} \rangle$
 $\langle \text{integer-part} \rangle ::= \langle \text{digit} \rangle \mid \langle \text{integer-part} \rangle \langle \text{digit} \rangle$
 $\langle \text{fraction} \rangle ::= \langle \text{digit} \rangle \mid \langle \text{digit} \rangle \langle \text{fraction} \rangle$
 $\langle \text{digit} \rangle ::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9$

A grammar given by Sethi to specify unsigned floating point literals in a simple language.

Figure 2.3 BNF rules for real numbers.

In the above grammar:

$$\begin{aligned}
\langle \text{real-number} \rangle &::= \langle \text{integer-part} \rangle . \langle \text{fraction} \rangle \\
\langle \text{integer-part} \rangle &::= \langle \text{digit} \rangle \mid \langle \text{integer-part} \rangle \langle \text{digit} \rangle \\
\langle \text{fraction} \rangle &::= \langle \text{digit} \rangle \mid \langle \text{digit} \rangle \langle \text{fraction} \rangle \\
\langle \text{digit} \rangle &::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9
\end{aligned}$$

A grammar given by Sethi to specify unsigned floating point literals in a simple language.

Figure 2.3 BNF rules for real numbers.

In the above grammar:

There are 15 rules called ***productions***. Each production:

- has a left side that is a *single nonterminal*, and
- has a right side that is a *sequence of 0 or more terminals and/or nonterminals*.

The “vertical bar” symbol \mid means:

$$\begin{aligned}
\langle \text{real-number} \rangle &::= \langle \text{integer-part} \rangle . \langle \text{fraction} \rangle \\
\langle \text{integer-part} \rangle &::= \langle \text{digit} \rangle \mid \langle \text{integer-part} \rangle \langle \text{digit} \rangle \\
\langle \text{fraction} \rangle &::= \langle \text{digit} \rangle \mid \langle \text{digit} \rangle \langle \text{fraction} \rangle \\
\langle \text{digit} \rangle &::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9
\end{aligned}$$

A grammar given by Sethi to specify unsigned floating point literals in a simple language.

Figure 2.3 BNF rules for real numbers.

In the above grammar:

There are 15 rules called ***productions***. Each production:

- has a left side that is a *single nonterminal*, and
- has a right side that is a *sequence of 0 or more terminals and/or nonterminals*.

The “vertical bar” symbol \mid means:

*The left side of this production is the same as the left side of the **previous** production.*

Example: The 3rd production of the above grammar is

$$\begin{aligned}
\langle \text{real-number} \rangle &::= \langle \text{integer-part} \rangle . \langle \text{fraction} \rangle \\
\langle \text{integer-part} \rangle &::= \langle \text{digit} \rangle \mid \langle \text{integer-part} \rangle \langle \text{digit} \rangle \\
\langle \text{fraction} \rangle &::= \langle \text{digit} \rangle \mid \langle \text{digit} \rangle \langle \text{fraction} \rangle \\
\langle \text{digit} \rangle &::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9
\end{aligned}$$

A grammar given by Sethi to specify unsigned floating point literals in a simple language.

Figure 2.3 BNF rules for real numbers.

In the above grammar:

There are 15 rules called ***productions***. Each production:

- has a left side that is a *single nonterminal*, and
- has a right side that is a *sequence of 0 or more terminals and/or nonterminals*.

The “vertical bar” symbol \mid means:

*The left side of this production is the same as the left side of the **previous** production.*

Example: The 3rd production of the above grammar is

$$\langle \text{integer-part} \rangle ::= \langle \text{integer-part} \rangle \langle \text{digit} \rangle$$

$\langle \text{real-number} \rangle ::= \langle \text{integer-part} \rangle . \langle \text{fraction} \rangle$
 $\langle \text{integer-part} \rangle ::= \langle \text{digit} \rangle \mid \langle \text{integer-part} \rangle \langle \text{digit} \rangle$
 $\langle \text{fraction} \rangle ::= \langle \text{digit} \rangle \mid \langle \text{digit} \rangle \langle \text{fraction} \rangle$
 $\langle \text{digit} \rangle ::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9$

A grammar given by Sethi to specify unsigned floating point literals in a simple language.

Figure 2.3 BNF rules for real numbers.

```

<real-number> ::= <integer-part> . <fraction>
<integer-part> ::= <digit> | <integer-part> <digit>
<fraction> ::= <digit> | <digit> <fraction>
<digit> ::= 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9

```

A grammar given by Sethi to specify unsigned floating point literals in a simple language.

Figure 2.3 BNF rules for real numbers.

Grammar notation is “free format”: We can insert whitespace characters, *including newlines*, between symbols without changing the specified grammar!

For example, the 2nd and 3rd productions

`<integer-part> ::= <digit> | <integer-part> <digit>`

of the above grammar could be rewritten as:

```

<real-number> ::= <integer-part> . <fraction>
<integer-part> ::= <digit> | <integer-part> <digit>
<fraction> ::= <digit> | <digit> <fraction>
<digit> ::= 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9

```

A grammar given by Sethi to specify unsigned floating point literals in a simple language.

Figure 2.3 BNF rules for real numbers.

Grammar notation is “free format”: We can insert whitespace characters, *including newlines*, between symbols without changing the specified grammar!

For example, the 2nd and 3rd productions

```

<integer-part> ::= <digit> | <integer-part> <digit>

```

of the above grammar could be rewritten as:

```

<integer-part> ::= <digit>
                  | <integer-part> <digit>

```



```

<real-number> ::= <integer-part> . <fraction>
<integer-part> ::= <digit> | <integer-part> <digit>
<fraction> ::= <digit> | <digit> <fraction>
<digit> ::= 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9

```

A grammar given by Sethi to specify unsigned floating point literals in a simple language.

Figure 2.3 BNF rules for real numbers.

Grammar notation is “free format”: We can insert whitespace characters, *including newlines*, between symbols without changing the specified grammar!

For example, the 2nd and 3rd productions

```

<integer-part> ::= <digit> | <integer-part> <digit>

```

of the above grammar could be rewritten as:

```

<integer-part> ::= <digit>
                  | <integer-part> <digit>

```

Intuitively, a production $N ::= \dots$ means “any \dots is an N ”.

$\langle \text{real-number} \rangle ::= \langle \text{integer-part} \rangle . \langle \text{fraction} \rangle$
 $\langle \text{integer-part} \rangle ::= \langle \text{digit} \rangle \mid \langle \text{integer-part} \rangle \langle \text{digit} \rangle$
 $\langle \text{fraction} \rangle ::= \langle \text{digit} \rangle \mid \langle \text{digit} \rangle \langle \text{fraction} \rangle$
 $\langle \text{digit} \rangle ::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9$

Figure 2.3 BNF rules for real numbers.

A grammar given by Sethi to specify unsigned floating point literals in a simple language.

$$\begin{aligned}
\langle \text{real-number} \rangle &::= \langle \text{integer-part} \rangle . \langle \text{fraction} \rangle \\
\langle \text{integer-part} \rangle &::= \langle \text{digit} \rangle \mid \langle \text{integer-part} \rangle \langle \text{digit} \rangle \\
\langle \text{fraction} \rangle &::= \langle \text{digit} \rangle \mid \langle \text{digit} \rangle \langle \text{fraction} \rangle \\
\langle \text{digit} \rangle &::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9
\end{aligned}$$

A grammar given by Sethi to specify unsigned floating point literals in a simple language.

Figure 2.3 BNF rules for real numbers.

$\langle \text{real-number} \rangle$ is the *starting nonterminal* of the above grammar.

In this course, we use the convention that *unless otherwise indicated*, the starting nonterminal of a grammar is ...

$$\begin{aligned}
\langle \text{real-number} \rangle &::= \langle \text{integer-part} \rangle . \langle \text{fraction} \rangle \\
\langle \text{integer-part} \rangle &::= \langle \text{digit} \rangle \mid \langle \text{integer-part} \rangle \langle \text{digit} \rangle \\
\langle \text{fraction} \rangle &::= \langle \text{digit} \rangle \mid \langle \text{digit} \rangle \langle \text{fraction} \rangle \\
\langle \text{digit} \rangle &::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9
\end{aligned}$$

A grammar given by Sethi to specify unsigned floating point literals in a simple language.

Figure 2.3 BNF rules for real numbers.

$\langle \text{real-number} \rangle$ is the *starting nonterminal* of the above grammar.

In this course, we use the convention that *unless otherwise indicated*, the starting nonterminal of a grammar is the nonterminal on the left side of the *first* production:

$$\begin{aligned}
\langle \text{real-number} \rangle &::= \langle \text{integer-part} \rangle . \langle \text{fraction} \rangle \\
\langle \text{integer-part} \rangle &::= \langle \text{digit} \rangle \mid \langle \text{integer-part} \rangle \langle \text{digit} \rangle \\
\langle \text{fraction} \rangle &::= \langle \text{digit} \rangle \mid \langle \text{digit} \rangle \langle \text{fraction} \rangle \\
\langle \text{digit} \rangle &::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9
\end{aligned}$$

A grammar given by Sethi to specify unsigned floating point literals in a simple language.

Figure 2.3 BNF rules for real numbers.

$\langle \text{real-number} \rangle$ is the *starting nonterminal* of the above grammar.

In this course, we use the convention that *unless otherwise indicated*, the starting nonterminal of a grammar is the nonterminal on the left side of the *first* production:

If you write a grammar and want *some other* nonterminal to be its starting nonterminal, then

$$\begin{aligned}
\langle \text{real-number} \rangle &::= \langle \text{integer-part} \rangle . \langle \text{fraction} \rangle \\
\langle \text{integer-part} \rangle &::= \langle \text{digit} \rangle \mid \langle \text{integer-part} \rangle \langle \text{digit} \rangle \\
\langle \text{fraction} \rangle &::= \langle \text{digit} \rangle \mid \langle \text{digit} \rangle \langle \text{fraction} \rangle \\
\langle \text{digit} \rangle &::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9
\end{aligned}$$

A grammar given by Sethi to specify unsigned floating point literals in a simple language.

Figure 2.3 BNF rules for real numbers.

$\langle \text{real-number} \rangle$ is the *starting nonterminal* of the above grammar.

In this course, we use the convention that *unless otherwise indicated*, the starting nonterminal of a grammar is the nonterminal on the left side of the *first* production:

If you write a grammar and want *some other* nonterminal to be its starting nonterminal, then you must *explicitly indicate* which nonterminal is the starting nonterminal!

$\langle \text{real-number} \rangle ::= \langle \text{integer-part} \rangle . \langle \text{fraction} \rangle$
 $\langle \text{integer-part} \rangle ::= \langle \text{digit} \rangle \mid \langle \text{integer-part} \rangle \langle \text{digit} \rangle$
 $\langle \text{fraction} \rangle ::= \langle \text{digit} \rangle \mid \langle \text{digit} \rangle \langle \text{fraction} \rangle$
 $\langle \text{digit} \rangle ::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9$

A grammar given
by Sethi to
specify unsigned
floating point
literals in a
simple language.

Figure 2.3 BNF rules for real numbers.

$\langle \text{real-number} \rangle ::= \langle \text{integer-part} \rangle . \langle \text{fraction} \rangle$
 $\langle \text{integer-part} \rangle ::= \langle \text{digit} \rangle \mid \langle \text{integer-part} \rangle \langle \text{digit} \rangle$
 $\langle \text{fraction} \rangle ::= \langle \text{digit} \rangle \mid \langle \text{digit} \rangle \langle \text{fraction} \rangle$
 $\langle \text{digit} \rangle ::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9$

A grammar given
by Sethi to
specify unsigned
floating point
literals in a
simple language.

Figure 2.3 BNF rules for real numbers.

$\langle \text{empty} \rangle$ denotes the empty string; other people write ϵ or λ to denote the empty string.

Example:

$\langle \text{real-number} \rangle ::= \langle \text{integer-part} \rangle . \langle \text{fraction} \rangle$
 $\langle \text{integer-part} \rangle ::= \langle \text{digit} \rangle \mid \langle \text{integer-part} \rangle \langle \text{digit} \rangle$
 $\langle \text{fraction} \rangle ::= \langle \text{digit} \rangle \mid \langle \text{digit} \rangle \langle \text{fraction} \rangle$
 $\langle \text{digit} \rangle ::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9$

A grammar given by Sethi to specify unsigned floating point literals in a simple language.

Figure 2.3 BNF rules for real numbers.

$\langle \text{empty} \rangle$ denotes the empty string; other people write ϵ or λ to denote the empty string.

Example: Changing the 2nd production above from $\langle \text{integer-part} \rangle ::= \langle \text{digit} \rangle$ to $\langle \text{integer-part} \rangle ::= \langle \text{empty} \rangle$ will allow a number with *no digits before the point* (e.g., .213) to belong to the language of the grammar.

Note that $\langle \text{empty} \rangle$ is neither a terminal nor a nonterminal!

Parse Trees

Q. Exactly which sequences of terminals belong to the set of sequences of terminals that is denoted by a given nonterminal N of a grammar?

Parse Trees

- Q.** Exactly which sequences of terminals belong to the set of sequences of terminals that is denoted by a given nonterminal N of a grammar?
- A.** A sequence of terminals $t_1 \dots t_k$ belongs to the set of sequences denoted by a nonterminal N *if and only if* ...

Parse Trees

- Q. Exactly which sequences of terminals belong to the set of sequences of terminals that is denoted by a given nonterminal N of a grammar?
- A. A sequence of terminals $t_1 \dots t_k$ belongs to the set of sequences denoted by a nonterminal N *if and only if* there is a **parse tree with root N that generates $t_1 \dots t_k$.**

Parse Trees

Q. Exactly which sequences of terminals belong to the set of sequences of terminals that is denoted by a given nonterminal N of a grammar?

A. A sequence of terminals $t_1 \dots t_k$ belongs to the set of sequences denoted by a nonterminal N *if and only if* there is a **parse tree with root N that generates $t_1 \dots t_k$.**

Unless otherwise indicated, the term **parse tree** means **parse tree whose root is the starting nonterminal**.

So we can say that a sequence of terminals $t_1 \dots t_k$ belongs to the language of a grammar *if and only if* there is a **parse tree that generates $t_1 \dots t_k$.**

Comment:

Parse Trees

Q. Exactly which sequences of terminals belong to the set of sequences of terminals that is denoted by a given nonterminal N of a grammar?

A. A sequence of terminals $t_1 \dots t_k$ belongs to the set of sequences denoted by a nonterminal N *if and only if* there is a **parse tree with root N that generates $t_1 \dots t_k$.**

Unless otherwise indicated, the term **parse tree** means parse tree whose root is the starting nonterminal.

So we can say that a sequence of terminals $t_1 \dots t_k$ belongs to the language of a grammar *if and only if* there is a **parse tree that generates $t_1 \dots t_k$.**


Comment: Instead of using parse trees, we can also answer the above question using the concept of a **derivation** that is introduced on pp. 40 – 41 of Sethi.

Below is a parse tree, whose root is $\langle integer-part \rangle$, that shows **282** belongs to the set of sequences denoted by $\langle integer-part \rangle$ in the following grammar:

$$\begin{aligned}\langle real-number \rangle &::= \langle integer-part \rangle . \langle fraction \rangle \\ \langle integer-part \rangle &::= \langle empty \rangle \mid \langle integer-part \rangle \langle digit \rangle \\ \langle fraction \rangle &::= \langle digit \rangle \mid \langle digit \rangle \langle fraction \rangle \\ \langle digit \rangle &::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9\end{aligned}$$

Below is a parse tree, whose root is $\langle \text{integer-part} \rangle$, that shows **282** belongs to the set of sequences denoted by $\langle \text{integer-part} \rangle$ in the following grammar:

$\langle \text{real-number} \rangle ::= \langle \text{integer-part} \rangle . \langle \text{fraction} \rangle$
 $\langle \text{integer-part} \rangle ::= \langle \text{empty} \rangle \mid \langle \text{integer-part} \rangle \langle \text{digit} \rangle$
 $\langle \text{fraction} \rangle ::= \langle \text{digit} \rangle \mid \langle \text{digit} \rangle \langle \text{fraction} \rangle$
 $\langle \text{digit} \rangle ::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9$



Note: This is just a picture to show what parse trees look like.

A precise definition of a parse tree will be given below.

Below is a parse tree that shows 282.83 belongs to the language of the same grammar:


```
<real-number> ::= <integer-part> . <fraction>
<integer-part> ::= <empty> | <integer-part> <digit>
<fraction> ::= <digit> | <digit> <fraction>
<digit> ::= 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9
```

Below is a parse tree that shows **282.83** belongs to the language of the same grammar:

$\langle \text{real-number} \rangle ::= \langle \text{integer-part} \rangle . \langle \text{fraction} \rangle$
 $\langle \text{integer-part} \rangle ::= \langle \text{empty} \rangle \mid \langle \text{integer-part} \rangle \langle \text{digit} \rangle$
 $\langle \text{fraction} \rangle ::= \langle \text{digit} \rangle \mid \langle \text{digit} \rangle \langle \text{fraction} \rangle$
 $\langle \text{digit} \rangle ::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9$

This is just a picture to show what parse trees look like.

A precise definition of a parse tree will be given below.



Given a nonterminal N and a *parse tree with root N* is an ordered rooted tree with the following properties:

1.

2.

3.

4.

Given a nonterminal N and a parse tree with root N is an ordered rooted tree with the following properties:

1. The **root** is N .
2. Each **leaf** either is a terminal symbol or is a nonterminal symbol; moreover, if a leaf is a nonterminal symbol, then it is N .
3. Each **internal node** is N .
4. The left-to-right sequence of children of any internal node M is the sequence of nonterminals in the yield of the subtree rooted at M .

Given a nonterminal N and a *parse tree with root N* is an ordered rooted tree with the following properties:

1. The **root** is **the nonterminal N** .
2. Each **leaf** either is ϵ or is a terminal symbol; moreover, if a is a terminal symbol, then a is the label of the leaf.
3. Each **internal node** is a nonterminal symbol.
4. The left-to-right sequence of children of any internal node M is the sequence of nonterminals in the right-hand side of the production rule for M .

Given a nonterminal N and a parse tree with root N is an ordered rooted tree with the following properties:

1. The **root** is **the nonterminal N** .
2. Each **leaf** either is **a terminal** or is **<empty>**;
moreover, .
3. Each **internal node** is .
4. The left-to-right sequence of children of any
internal node M is .

Given a nonterminal N and a *parse tree with root N* is an ordered rooted tree with the following properties:

1. The **root** is **the nonterminal N** .
2. Each **leaf** either is **a terminal** or is **$\langle empty \rangle$** ; moreover, **a leaf that is $\langle empty \rangle$ has no sibling**.
3. Each **internal node** is .
4. The left-to-right sequence of children of any internal node M is .

Given a nonterminal N and a *parse tree with root N* is an ordered rooted tree with the following properties:

1. The **root** is **the nonterminal N** .
2. Each **leaf** either is **a terminal** or is **$\langle empty \rangle$** ; moreover, **a leaf that is $\langle empty \rangle$ has no sibling**.
3. Each **internal node** is **a nonterminal**.
4. The left-to-right sequence of children of any internal node M is

.

Given a nonterminal N and a parse tree with root N is an ordered rooted tree with the following properties:

1. The root is the nonterminal N .
2. Each leaf either is a terminal or is $\langle \text{empty} \rangle$; moreover, a leaf that is $\langle \text{empty} \rangle$ has no sibling.
3. Each internal node is a nonterminal.
4. The left-to-right sequence of children of any internal node M is the right side of a production whose left side is the nonterminal M .

Given a nonterminal N and a *parse tree with root N* is an ordered rooted tree with the following properties:

1. The **root** is the nonterminal N .
2. Each **leaf** either is a terminal or is $\langle \text{empty} \rangle$; moreover, a leaf that is $\langle \text{empty} \rangle$ has no sibling.
3. Each **internal node** is a nonterminal.
4. The left-to-right sequence of children of any internal node M is the right side of a production whose left side is the nonterminal M .

Unless otherwise indicated, the term *parse tree* means *parse tree whose root is the starting nonterminal*.

Given a nonterminal N and a *parse tree with root N* is an ordered rooted tree with the following properties:

1. The **root** is the nonterminal N .
2. Each **leaf** either is a terminal or is $\langle \text{empty} \rangle$; moreover, a leaf that is $\langle \text{empty} \rangle$ has no sibling.
3. Each **internal node** is a nonterminal.
4. The left-to-right sequence of children of any internal node M is the right side of a production whose left side is the nonterminal M .

Unless otherwise indicated, the term *parse tree* means *parse tree whose root is the starting nonterminal*.

Given terminals t_1, \dots, t_k , a *parse tree with root N that generates $t_1 \dots t_k$* (or *parse tree with root N of $t_1 \dots t_k$*) is a parse tree with root N for which ...

Given a nonterminal N and a **parse tree with root N** is an ordered rooted tree with the following properties:

1. The **root** is the nonterminal N .
2. Each **leaf** either is a terminal or is $\langle \text{empty} \rangle$; moreover, a leaf that is $\langle \text{empty} \rangle$ has no sibling.
3. Each **internal node** is a nonterminal.
4. The left-to-right sequence of children of any internal node M is the right side of a production whose left side is the nonterminal M .

Unless otherwise indicated, the term **parse tree** means **parse tree whose root is the starting nonterminal**.

Given terminals t_1, \dots, t_k , a **parse tree with root N that generates $t_1 \dots t_k$** (or **parse tree with root N of $t_1 \dots t_k$**) is a parse tree with root N for which **the left-to-right sequence of leaves that are not $\langle \text{empty} \rangle$ is t_1, \dots, t_k** .

RECALL:

Q. Exactly which sequences of terminals belong to the set of sequences of terminals that is denoted by a given nonterminal N of a grammar?

A.

RECALL:

- Q. Exactly which sequences of terminals belong to the set of sequences of terminals that is denoted by a given nonterminal N of a grammar?
- A. A sequence of terminals $t_1 \dots t_k$ belongs to the set of sequences denoted by a nonterminal N *if and only if* ...

RECALL:

- Q. Exactly which sequences of terminals belong to the set of sequences of terminals that is denoted by a given nonterminal N of a grammar?
- A. A sequence of terminals $t_1 \dots t_k$ belongs to the set of sequences denoted by a nonterminal N *if and only if* there is a **parse tree with root N that generates $t_1 \dots t_k$.**

Let's draw a parse tree, whose root is $\langle integer-part \rangle$, that shows 282 belongs to the set of sequences denoted by $\langle integer-part \rangle$ in the following grammar:

Let's draw a parse tree, whose root is $\langle integer-part \rangle$, that shows **282** belongs to the set of sequences denoted by $\langle integer-part \rangle$ in the following grammar:

$$\begin{aligned}\langle real-number \rangle &::= \langle integer-part \rangle . \langle fraction \rangle \\ \langle integer-part \rangle &::= \langle empty \rangle \mid \langle integer-part \rangle \langle digit \rangle \\ \langle fraction \rangle &::= \langle digit \rangle \mid \langle digit \rangle \langle fraction \rangle \\ \langle digit \rangle &::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9\end{aligned}$$

Let's draw a parse tree, whose root is *<integer-part>*, that shows **282** belongs to the set of sequences denoted by *<integer-part>* in the following grammar:

<real-number> ::= *<integer-part>* . *<fraction>*
<integer-part> ::= *<empty>* | *<integer-part>* *<digit>*
<fraction> ::= *<digit>* | *<digit>* *<fraction>*
<digit> ::= 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9

The root of this parse tree
is *<integer-part>*.

<integer-part>


Let's draw a parse tree, whose root is $\langle integer-part \rangle$, that shows 282 belongs to the set of sequences denoted by $\langle integer-part \rangle$ in the following grammar:

$\langle real-number \rangle ::= \langle integer-part \rangle . \langle fraction \rangle$
 $\langle integer-part \rangle ::= \langle empty \rangle \mid \langle integer-part \rangle \langle digit \rangle$
 $\langle fraction \rangle ::= \langle digit \rangle \mid \langle digit \rangle \langle fraction \rangle$
 $\langle digit \rangle ::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9$

The left-to-right sequence of children of any internal node M is the right side of a production whose left side is the nonterminal M.

Using production:

$\langle integer-part \rangle ::= \langle integer-part \rangle \langle digit \rangle$




Let's draw a parse tree, whose root is $\langle integer-part \rangle$, that shows 282 belongs to the set of sequences denoted by $\langle integer-part \rangle$ in the following grammar:

$\langle real-number \rangle ::= \langle integer-part \rangle . \langle fraction \rangle$
 $\langle integer-part \rangle ::= \langle empty \rangle \mid \langle integer-part \rangle \langle digit \rangle$
 $\langle fraction \rangle ::= \langle digit \rangle \mid \langle digit \rangle \langle fraction \rangle$
 $\langle digit \rangle ::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9$

The left-to-right sequence of children of any internal node M is the right side of a production whose left side is the nonterminal M.

Re-using production:

$\langle integer-part \rangle ::= \langle integer-part \rangle \langle digit \rangle$




Let's draw a parse tree, whose root is $\langle \text{integer-part} \rangle$, that shows **282** belongs to the set of sequences denoted by $\langle \text{integer-part} \rangle$ in the following grammar:

$\langle \text{real-number} \rangle ::= \langle \text{integer-part} \rangle . \langle \text{fraction} \rangle$
 $\langle \text{integer-part} \rangle ::= \langle \text{empty} \rangle \mid \langle \text{integer-part} \rangle \langle \text{digit} \rangle$
 $\langle \text{fraction} \rangle ::= \langle \text{digit} \rangle \mid \langle \text{digit} \rangle \langle \text{fraction} \rangle$
 $\langle \text{digit} \rangle ::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9$

The left-to-right sequence of children of any internal node M is the right side of a production whose left side is the nonterminal M.

Using production:
 $\langle \text{digit} \rangle ::= 2$




Let's draw a parse tree, whose root is $\langle \text{integer-part} \rangle$, that shows **282** belongs to the set of sequences denoted by $\langle \text{integer-part} \rangle$ in the following grammar:

$\langle \text{real-number} \rangle ::= \langle \text{integer-part} \rangle . \langle \text{fraction} \rangle$
 $\langle \text{integer-part} \rangle ::= \langle \text{empty} \rangle \mid \langle \text{integer-part} \rangle \langle \text{digit} \rangle$
 $\langle \text{fraction} \rangle ::= \langle \text{digit} \rangle \mid \langle \text{digit} \rangle \langle \text{fraction} \rangle$
 $\langle \text{digit} \rangle ::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9$

The left-to-right sequence of children of any internal node M is the right side of a production whose left side is the nonterminal M.

Using production:
 $\langle \text{digit} \rangle ::= 8$




Let's draw a parse tree, whose root is $\langle integer-part \rangle$, that shows 282 belongs to the set of sequences denoted by $\langle integer-part \rangle$ in the following grammar:

$\langle real-number \rangle ::= \langle integer-part \rangle . \langle fraction \rangle$
 $\langle integer-part \rangle ::= \langle empty \rangle \mid \langle integer-part \rangle \langle digit \rangle$
 $\langle fraction \rangle ::= \langle digit \rangle \mid \langle digit \rangle \langle fraction \rangle$
 $\langle digit \rangle ::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9$

The left-to-right sequence of children of any internal node M is the right side of a production whose left side is the nonterminal M.

Using production:

$\langle integer-part \rangle ::= \langle integer-part \rangle \langle digit \rangle$




Let's draw a parse tree, whose root is $\langle integer-part \rangle$, that shows **282** belongs to the set of sequences denoted by $\langle integer-part \rangle$ in the following grammar:

$\langle real-number \rangle ::= \langle integer-part \rangle . \langle fraction \rangle$
 $\langle integer-part \rangle ::= \langle empty \rangle \mid \langle integer-part \rangle \langle digit \rangle$
 $\langle fraction \rangle ::= \langle digit \rangle \mid \langle digit \rangle \langle fraction \rangle$
 $\langle digit \rangle ::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9$

The left-to-right sequence of children of any internal node M is the right side of a production whose left side is the nonterminal M.

Using production:

$\langle integer-part \rangle ::= \langle empty \rangle$




Let's draw a parse tree, whose root is $\langle integer-part \rangle$, that shows **282** belongs to the set of sequences denoted by $\langle integer-part \rangle$ in the following grammar:

$\langle real-number \rangle ::= \langle integer-part \rangle . \langle fraction \rangle$
 $\langle integer-part \rangle ::= \langle empty \rangle \mid \langle integer-part \rangle \langle digit \rangle$
 $\langle fraction \rangle ::= \langle digit \rangle \mid \langle digit \rangle \langle fraction \rangle$
 $\langle digit \rangle ::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9$

The left-to-right sequence of children of any internal node M is the right side of a production whose left side is the nonterminal M.

Using production:
 $\langle digit \rangle ::= 2$



Let's draw a parse tree, whose root is $\langle integer-part \rangle$, that shows **282** belongs to the set of sequences denoted by $\langle integer-part \rangle$ in the following grammar:

$\langle real-number \rangle ::= \langle integer-part \rangle . \langle fraction \rangle$
 $\langle integer-part \rangle ::= \langle empty \rangle \mid \langle integer-part \rangle \langle digit \rangle$
 $\langle fraction \rangle ::= \langle digit \rangle \mid \langle digit \rangle \langle fraction \rangle$
 $\langle digit \rangle ::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9$


The left-to-right sequence of children of any internal node M is the right side of a production whose left side is the nonterminal M .

Using production:

$\langle digit \rangle ::= 2$

The left-to-right sequence of leaves that are not $\langle empty \rangle$ is 282, as required.

So the parse tree is complete!



RECALL:

The set of sequences of terminals denoted by the **starting nonterminal** of a grammar is called the *Language generated by* (or *Language of*) that grammar.

So a sequence of terminals $t_1 \dots t_k$ belongs to the language of a grammar *if and only if* ...

RECALL:

The set of sequences of terminals denoted by the **starting nonterminal** of a grammar is called the *Language generated by* (or *Language of*) that grammar.

So a sequence of terminals $t_1 \dots t_k$ belongs to the language of a grammar *if and only if* there is a **parse tree**, whose root is the **starting nonterminal**, that generates $t_1 \dots t_k$.

RECALL:

The set of sequences of terminals denoted by the **starting nonterminal** of a grammar is called the *language generated by* (or *language of*) that grammar.

So a sequence of terminals $t_1 \dots t_k$ belongs to the language of a grammar *if and only if* there is a **parse tree**, whose root is the **starting nonterminal**, that generates $t_1 \dots t_k$.

Unless otherwise indicated, the term *parse tree* means *parse tree whose root is the starting nonterminal*.

So we can simply say:

RECALL:

The set of sequences of terminals denoted by the **starting nonterminal** of a grammar is called the *language generated by* (or *language of*) that grammar.

So a sequence of terminals $t_1 \dots t_k$ belongs to the language of a grammar *if and only if* there is a **parse tree**, whose root is the **starting nonterminal**, that generates $t_1 \dots t_k$.

Unless otherwise indicated, the term *parse tree* means *parse tree whose root is the starting nonterminal*.

So we can simply say:

- A sequence of terminals $t_1 \dots t_k$ belongs to the language of a grammar *if and only if* there is a **parse tree** that generates $t_1 \dots t_k$.

Below is a parse tree that shows **282.83** belongs to the language of this grammar:

```
<real-number> ::= <integer-part> . <fraction>
<integer-part> ::= <empty> | <integer-part> <digit>
<fraction> ::= <digit> | <digit> <fraction>
<digit> ::= 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9
```

Below is a parse tree that shows **282.83** belongs to the language of this grammar:

$\langle \text{real-number} \rangle ::= \langle \text{integer-part} \rangle . \langle \text{fraction} \rangle$
 $\langle \text{integer-part} \rangle ::= \langle \text{empty} \rangle \mid \langle \text{integer-part} \rangle \langle \text{digit} \rangle$
 $\langle \text{fraction} \rangle ::= \langle \text{digit} \rangle \mid \langle \text{digit} \rangle \langle \text{fraction} \rangle$
 $\langle \text{digit} \rangle ::= 0 \mid 1 \mid 2 \mid 3 \mid 4 \mid 5 \mid 6 \mid 7 \mid 8 \mid 9$

