

## Lab: 使用 systemctl 管理服务

觀察服務狀況, 啟用服務

```
# systemctl status rsyncd
```

<請觀察相關資訊>

```
# systemctl start rsyncd
```

```
# systemctl status rsyncd
```

<請觀察相關資訊>

觀察開機是否啟用服務

```
# systemctl is-enabled rsyncd
```

<請觀察相關資訊>

```
# find /etc/systemd -name "*rsync*"
```

<請觀察相關資訊>

```
# find /usr/lib/systemd/ -name "*rsync*"
```

<請觀察相關資訊>

設定開機啟用服務

```
# systemctl enable rsyncd
```

```
# systemctl is-enabled rsyncd
```

<請觀察相關資訊>

```
# find /etc/systemd -name "*rsync*"
```

<請觀察相關資訊>

```
# find /usr/lib/systemd/ -name "*rsync*"
```

<請觀察相關資訊>

## Lab: 修改預設的target

```
# ls -l /etc/systemd/system/default.target
```

<請觀察相關資訊>

更改為文字介面開機

```
# systemctl set-default multi-user
```

```
# ls -l /etc/systemd/system/default.target
```

<請觀察相關資訊>

修改回圖形介面開機

```
# systemctl set-default graphical
```

```
# ls -l /etc/systemd/system/default.target
```

<請觀察相關資訊>