http://poloclub.gatech.edu/cse6242

CSE6242 / CX4242: Data & Visual Analytics

Graphs / Networks

Centrality measures, algorithms, interactive applications

Duen Horng (Polo) Chau
Assistant Professor
Associate Director, MS Analytics
Georgia Tech

Partly based on materials by
Professors Guy Lebanon, Jeffrey Heer, John Stasko, Christos Faloutsos, Parishit Ram (GT PhD alum; SkyTree), Alex Gray

Centrality

= “Importance”

Why Node Centrality?

What can we do if we can rank all the nodes in a graph (e.g., Facebook, LinkedIn, Twitter)?

Why Node Centrality?

What can we do if we can rank all the nodes in a graph (e.g., Facebook, LinkedIn, Twitter)?

- Find **celebrities** or influential people in a social network (Twitter)
- Find "**gatekeepers**" who connect communities (headhunters love to find them on LinkedIn)
- What else?



Why Node Centrality?

Helps **graph analysis, visualization, understanding**, e.g.,

- Let us **rank** nodes, group or study them by centrality
- Only show subgraph formed by the **top 100 nodes**, out of the millions in the full graph
  - **Similar to google search results** (ranked, and they only show you 10 per page)
- Most graph analysis packages already have centrality algorithms implemented. **Use them!**

Can also compute edge centrality.
Here we focus on node centrality.

Degree Centrality (easiest)



Degree = number of neighbors

- For directed graphs
  - **In degree** = No. of incoming edges
  - **Out degree** = No. of outgoing edges
- For undirected graphs, **only degree is defined**.
- Algorithms?
  - Sequential scan through edge list
  - What about for a graph stored in SQLite?

1, 2
1, 3
2, 4
3, 2

Computing Degrees using SQL

Recall simplest way to store a graph in SQLite:

```
edges(source_id, target_id)
```

1, 2
1, 3
2, 4
3, 2

1. If slow, first create index for each column

2. Use **group by** statement to find **out degrees**

```
select count(*) from edges group by source_id;
```

Betweenness Centrality



High betweenness = "gatekeeper"

Betweenness of a node v

$$= \sum_{s \neq v \neq t \in V} \frac{\sigma_{st}(v)}{\sigma_{st}}$$

Number of shortest paths between s and t that **goes through v**

Number of shortest paths between s and t

= how often a node serves as the "bridge" that connects two other nodes.

Betweenness is very well studied. http://en.wikipedia.org/wiki/Centrality#Betweenness_centrality

(Local) Clustering Coefficient

A node's clustering coefficient is a measure of how close the node's neighbors are from forming a clique.



c = 1

1 = neighbors form a clique

0 = No edges among neighbors



c = 1/3

(Assuming undirected graph)

"Local" means it's for a node; can also compute a graph's "global" coefficient



c = 0

Image source: http://en.wikipedia.org/wiki/Clustering_coefficient

Computing Clustering Coefficients...

Requires **triangle counting**

Real social networks have a lot of triangles

- Friends of friends are friends



Triangles are **expensive** to compute

(neighborhood intersections; several approx. algos)

Can we do that quickly?

Algorithm details:
Faster Clustering Coefficient Using Vertex Covers
http://www.cc.gatech.edu/~ogreen3/_docs/2013VertexCoverClusteringCoefficients.pdf

details

Super Fast Triangle Counting
[Tsourakakis ICDM 2008]

But: triangles are expensive to compute
(3-way join; several approx. algos)
Q: Can we do that quickly?
A: Yes!

#triangles = 1/6 Sum (λ_i^3)

(and, because of skewness,
we only need the top few eigenvalues!

Power Law in Eigenvalues of Adjacency Matrix





1000x+ speed-up, >90% accuracy

More Centrality Measures…

- Degree
- Betweenness
- Closeness, by computing
  - Shortest paths
  - "**Proximity**" (usually via *random walks*) — **used successfully in a lot of applications**
- Eigenvector
- …

PageRank (Google)

Larry Page

Sergey Brin

Brin, Sergey and Lawrence Page (1998). *Anatomy of a Large-Scale Hypertextual Web Search Engine*. 7th Intl World Wide Web Conf.

PageRank: Problem

Given a directed graph, find its most interesting/central node



A node is important, if it is connected with important nodes (recursive, but OK!)

PageRank: Solution

Given a directed graph, find its most interesting/central node

Proposed solution:
use **random walk**; spot most "popular" node (-> steady state probability (ssp))



"state" = webpage

A node has high ssp, if it is connected with high ssp nodes (recursive, but OK!)

(Simplified) PageRank

Let **B** be the transition matrix:
transposed, column-normalized



From

To

B

		1		
1			1	
	1/2			1/2
				1/2
	1/2			

p1
p2
p3
p4
p5

=

p1
p2
p3
p4
p5

(Simplified) PageRank

B p = p

B p = p



		1		
1			1	
	1/2			1/2
				1/2
	1/2			

p1
p2
p3
p4
p5

=

p1
p2
p3
p4
p5

How to compute SSP:

https://fenix.tecnico.ulisboa.pt/downloadFile/377957968847 3/6.3.pdf

http://www.sosmath.com/matrix/markov/markov.html

(Simplified) PageRank

- **B p = 1 * p**
- Thus, **p** is the **eigenvector** that corresponds to the highest eigenvalue (=1, since the matrix is column-normalized)
- Why does such a **p** exist?
  - **p** exists if **B** is nxn, nonnegative, irreducible [Perron–Frobenius theorem]

(Simplified) PageRank

- In short: imagine a particle/person randomly moving along the edges/links
- Compute its steady-state probability (ssp)

Full version of algorithm:

With occasional random jumps to any nodes

Why? To make the matrix **irreducible.**

Irreducible = from any state (node), there's non-zero probability to reach any other state (node)

Full Algorithm

With probability 1-c, fly-out to a random node

Then, we have

$$\mathbf{p} = c\,\mathbf{B}\,\mathbf{p} + \frac{(1-c)}{n}\,\mathbf{1}$$

$$\mathbf{p} = \frac{(1-c)}{n}\,[\mathbf{I} - c\,\mathbf{B}]^{-1}\,\mathbf{1}$$





How to compute PageRank for huge matrix?



Use the power iteration method

http://en.wikipedia.org/wiki/Power_iteration

$$\mathbf{p} = c\,\mathbf{B}\,\mathbf{p} + \frac{(1-c)}{n}\,\mathbf{1}$$

p’ **B** **p**

$$\begin{bmatrix} p1 \\ p2 \\ p3 \\ p4 \\ p5 \end{bmatrix} = c \begin{bmatrix} & & 1 & & \\ 1 & & & 1 & \\ & 1/2 & & & 1/2 \\ & & & & 1/2 \\ & 1/2 & & & \end{bmatrix} \begin{bmatrix} p1 \\ p2 \\ p3 \\ p4 \\ p5 \end{bmatrix} + \frac{(1-c)}{n} \begin{bmatrix} 1 \\ 1 \\ \cdots \\ 1 \end{bmatrix}$$

Can initialize this vector to any non-zero vector, e.g., all “1”s

PageRank Explained with Javascript



Also great for checking the correctness of your PageRank Implementation.

http://www.cs.duke.edu/csed/principles/pagerank/

PageRank for graphs (generally)

You can run PageRank on **any graphs**

- All you need are the graph edges!

Should be in your algorithm “toolbox”

- Better than degree centrality
- Fast to compute for large graphs, runtime linear in the number of edges, O(E)

But can be “misled” (Google Bomb)

- How?

Personalized PageRank

Intuition: not all pages are equal, some more relevant to some people

Goal: rank pages in a way that those more relevant to you will be ranked higher

How? Make just **one** small change to PageRank

Personalized PageRank

With probability 1-c, fly-out to
~~a random node~~ **some preferred nodes**

$$\mathbf{p}' = c\,\mathbf{B}\,\mathbf{p} + \frac{(1-c)}{n}\mathbf{1}$$



Why Learn Personalized PageRank?

For **recommendation**

- If I like webpage A, what else do I like?
- If I bought product A, what other products would I also buy?

Visualizing and interacting with large graphs

- Instead of visualizing every single nodes, visualize the **most important ones**

Very flexible — works on any graph

Related "guilt-by-association" / diffusion techniques

- **Personalized PageRank**
  (= Random Walk with Restart)
- "Spreading activation" or "degree of interest" in Human-Computer Interaction (HCI)
- Belief Propagation
  (powerful inference algorithm, for fraud detection, image segmentation, error-correcting codes, etc.)

Why are these algorithms popular?

- **Intuitive to interpret**
  uses “network effect”, homophily
- **Easy to implement**
  math is relatively simple (mainly matrix-vector multiplication)
- **Fast**
  run time linear to #edges, or better
- **Probabilistic** meaning

Human-In-The-Loop Graph Mining

Apolo:

Machine Learning + Visualization

CHI 2011

Apolo: Making Sense of Large Network Data by Combining Rich User Interaction and Machine Learning

Finding More Relevant Nodes

HCI
Paper



Data Mining
Paper

Citation network

Finding More Relevant Nodes



Citation network

Finding More Relevant Nodes



Citation network

Apolo uses **guilt-by-association**
(Belief Propagation, similar to personalized PageRank)

Demo: Mapping the Sensemaking Literature

Nodes: 80k papers from Google Scholar (node size: #citation)
Edges: 150k citations



Search | Suggestions

For **The cost structure of sensemaking**

The information visualizer, an inf...	1991	
Card, S.K. and Robertson, G.G. and Macki...	532	
The WebBook and the Web Forag...	1996	
Card, S.K. and Robertson, G.G. and York, W.	403	
LyberWorld—a visualization user...	1994	
Hemmje, M. and Kunkel, C. and Willett, A.	223	
The structure of the information...	1997	
Card, S.K. and Mackinlay, J.	198	
Information visualization	2009	
Card, S. and Mackinlay, JD and Shneiderm...	180	
"I"ll get that off the audio": a cas...	1997	
Moran, T.P. and Palen, L. and Harrison, S....	143	
An organic user interface for sear...	1995	
Mackinlay, J.D. and Rao, R. and Card, S.K.	123	
Using a landscape metaphor to re...	1993	
Chalmers, M.	122	
Personal information management	2007	
Jones, W.P. and Teevan, J.	109	
SearchTogether: an interface for c...	2007	
Morris, M.R. and Horvitz, E.	108	
Information foraging theory: Ada...	2007	
Pirolli, P.	107	
Investigating behavioral variabilit...	2007	
White, R.W. and Drucker, S.M.	79	
Jigsaw: Supporting investigative...	2008	
Stasko, J. and Görg, C. and Liu, Z.	71	
The cost-of-knowledge character...	1994	
Card, S.K. and Pirolli, P. and Mackinlay, J.D.	54	
Collaborative conceptual design:...	1996	
Potts, C. and Catledge, L.	45	

The cost structure of sen...

The cost structure of sensemaking PDF 1993

Russell, D.M. and Stefik, M.J. and Pirolli, P. and Card, S.K.

245 citations 8 versions

googlescholar.db

Search | Suggestions

For **The cost structure of sensemaking**

The information visualizer, an inf...	1991	
Card, S.K. and Robertson, G.G. and Macki...	532	
The WebBook and the Web Forag...	1996	
Card, S.K. and Robertson, G.G. and York, W.	403	
LyberWorld—a visualization user...	1994	
Hemmje, M. and Kunkel, C. and Willett, A.	223	
The structure of the information...	1997	
Card, S.K. and Mackinlay, J.	198	
Information visualization	2009	
Card, S. and Mackinlay, JD and Shneiderm...	180	
"I"ll get that off the audio": a cas...	1997	
Moran, T.P. and Palen, L. and Harrison, S....	143	
An organic user interface for sear...	1995	
Mackinlay, J.D. and Rao, R. and Card, S.K.	123	
Using a landscape metaphor to re...	1993	
Chalmers, M.	122	
Personal information management	2007	
Jones, W.P. and Teevan, J.	109	
SearchTogether: an interface for c...	2007	
Morris, M.R. and Horvitz, E.	108	
Information foraging theory: Ada...	2007	
Pirolli, P.	107	
Investigating behavioral variabilit...	2007	
White, R.W. and Drucker, S.M.	79	
Jigsaw: Supporting investigative...	2008	
Stasko, J. and Görg, C. and Liu, Z.	71	
The cost-of-knowledge character...	1994	
Card, S.K. and Pirolli, P. and Mackinlay, J.D.	54	
Collaborative conceptual design:...	1996	
Potts, C. and Catledge, L.	45	

The cost structure of sen...

The cost structure of sensemaking PDF 1993

Russell, D.M. and Stefik, M.J. and Pirolli, P. and Card, S.K.

245 citations 8 versions

googlescholar.db

Key Ideas (Recap)

Specify exemplars

Find other relevant nodes (BP)



Apolo's Contributions

1 Human + Machine

It was like having a **partnership** with the machine.

2 Personalized Landscape

Apolo 2009

Cluster Data
Add Group
Recommendations:
End User Programming
End users creating effective softw...
End user software engineering: chi...
Invited research overview: end-us...
Brad A. Myers
Margaret M. Burnett
Mary Beth Rosson
Andrew Jensen Ko
Alan F. Blackwell
Show: All
Not Interested
Automatically generating user inte...
Decision-Theoretic User Interface ...
Daniel S. Weld
Krzysztof Z. Gajos
Automatically generating
Exploring the design spac
Predictability and accuracy
Planning-Based Control of
Brad
Brad A. Myers
The garnet user interface developm...
Using HCI Techniques to Design a M...
Creating charts by demonstration.
The Amulet User Interface Developm...
Easily Adding Animations to Interfac...
Simplifying video editng using metad...
SILVER: simplifying video editing wit...
Text Entry
In-stroke word completion.
Integrating isometric joysticks into...
Eyes on the road, hands on the whe...
An alternative to push, press, and t...
Maximizing the guessability of symb...
Few-key text entry revisited: mnem...
Text entry from power wheelchairs: ...
Joystick text entry with date stamp, ...
Show: Papers
Interface Generation
Huddle: automatically generating i...
UNIFORM: automatically generatin...
Demonstrating the viability of auto...
Jeffrey Nichols
Brandon Rothrock
Duen Horng Chau

Apolo 2010


Shiftr
Data
Save/Load
Export
Search
sense
103 matches
all
title
authors
Title
Cites
Authors
Year
The cost structure of sensemaking 188 Russell, D 1993
Table lens as a tool for making sens 37 Pirolli, P. 1996
Sensemaking of evolving web sites 22 Chi, EH a 1999
Sources of structure in sensemaking 19 Qu, Y. ar 2005
A sensemaking-supporting informa 11 Qu, Y. 2003
PIM
Collab search
InfoVis
Sensemaking
Title
Cit...
Authors
Year
SenseMaker: an information-explor 155 Baldonad 1997
Sources of structure in sensemakin 19 Qu, Y. an 2005
The cost structure of sensemaking 188 Russell, D 1993
Inferring web communities from li 663 Gibson, D 1998
Sensemaking for Topic Compreher 0 Ryder, B. 0
A sensemaking-supporting inform 11 Qu, Y. 2003
Model-driven formative evaluation 6 Qu, Y. an 2008
The digital library integrated task e 85 Cousins, 1997
CiteSense: supporting sensemaking 0 Zhang, X. 2008
An informal information-seeking e 53 Hendry, I 1997
An empirical evaluation of user int 35 Amento, 1999
The effectiveness of automatically 19 Gon{\c{c 2004
The microstructures of social taggi 3 Fu, W.T. 2008
Sensemaking: Bringing theories an 0 Sharma, I 2006
Data manipulation services in the I 7 Asdonia 1998
Considerations for information en 78 Fumas, G 1998
Improve results
Pin
Select neighbors
Pause layout
Results:
18
Change in representations
Sources of structure in sensemaking
CiteSense: supporting
SearchTogether: an interface
Evaluating Collaborative Information Seeking Interfaces
The cost structure of sensemaking
Presto: an experimental architecture for
Personal Information management
Information visualization
INFORMATION VISUALIZATION
Cat-a-Cone:
Understanding Users'
17 nodes selected
1993
The cost structure of sensemaking
Russell, D.M., Stefik, M.J., Pirolli, P., Card, S.K.
Cited by 188
booktitle
Proceedings of the INTERACT'93 and CHI'93 con
Change in representations
Change in Representations
No. of seeds
0
1
2
3
4
5
6
7
8
9

Apolo 2011

22,000 lines of code. Java 1.6. Swing.
Uses SQLite3 to store graph on disk



User Study

Used citation network

Task: Find related papers for 2 sections in a survey paper on *user interface*

- Model-based generation of UI
- Rapid prototyping tools



Past, Present and Future of User Interface Software Tools

Brad Myers, Scott E. Hudson, and Randy Pausch

Human Computer Interaction Institute
School of Computer Science
Carnegie Mellon University

Between subjects design

Participants: **grad student** or **research staff**


Apolo
Google Scholar
“Model-based”
“Prototyping”
10 papers for each section


Apolo
Google Scholar
"Model-based"
"Prototyping"
10 papers for each section
Expert judges rated papers
1 + 0 = 1
1 + 1 = 2
0 + 0 = 0

Judges' Scores



Higher is better.
Apolo wins.

** Statistically significant, by two-tailed t test, p <0.05*

Practitioners' guide to building (interactive) applications

What kinds of **prototypes**?

- Paper prototype, lo-fi prototype, high-fi prototype

Important to involve **REAL users** as early as possible

- Recruit your friends to try your tools
- Lab study (controlled, as in Apolo)
- Longitudinal study (usage over months)
- Deploy it and see the world's reaction!

- To learn more:
  - CS 6750 Human-Computer Interaction
  - CS 6455 User Interface Design and Evaluation

Practitioners' guide to building (interactive) applications

Think about scalability early

- Identify candidate scalable algorithms early on

Use **iterative** design approach, as in Apolo and industry

- Why? It's hard to get it right the first time
- Create prototype, evaluate, modify prototype, evaluate, ...
- Quick evaluation helps you identify **important fixes early — save you a lot of time overall**

Waterfall model (software engineering)



If you want to know more about people…

http://amzn.com/0321767535