

THIS DOCUMENT CONTAINS VALUABLE PROPRIETARY TO RAFAEL. THE RECIPIENTS OF THIS DOCUMENT SHALL NOT DISCLOSE ITS CONTENTS IN WHOLE OR IN PART TO ANY THIRD PARTY UNLESS OTHERWISE AGREED BY RAFAEL.		UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN MILLIMETERS. INTERPRET DRAWING ACCORDING TO RAFAEL PROCEDURE 18.00.10		
REVISIONS				
REV	DESCRIPTION	ECN	ID	DATE
F	UPDATE DRAWING	ECN361996	ronav	16-Mar-2025

ח"ג:שלנו
עד:34ש
140X

PRODUCTION ROUTING CHART					OPER	DATE
No.	DESCRIPTION					
10	GENERAL INSTRUCTIONS					
10.1	THIS DRAWING SHALL BE USED WITH ITS MODEL FOR COMPLETE PRODUCT DEFINITION					
20	MATERIAL					
	DESCRIPTION	CAT.NO.	QTY	UM		
20.1	STAINLESS STEEL 304L-ANNEALED SEAMLESS TUBE L=6000. OD=33. W.T=6.35 MM AIRCRAFT, GEN_1111-1, ASTM A312	5100577733	0.274	M		
30	UNLESS OTHERWISE SPECIFIED (WHEN IN CONFLICT, THIS PARA. OVERRIDES TITLE BLOCK REQ.):					
30.1	IN-PROCESS PRESERVATION PER PS-38-576104					
30.2	BREAK SHARP EDGES ~0.2X45 °, EXTERNAL EDGES MAY BE PERFORMED AS R0.2 +0.2					
30.3	INTERNAL RADIUS R 0.3 MAX.					
40	PRODUCTION SEQUENCE:					
40.1	MACHINING					
40.2	MARKING: LETTER DEPTH 0.2mm MAX. HEIGHT 3mm					
50	MANUFACTURER INSPECTION REQUIREMENTS:					
50.1	100% VISUAL INSPECTION					
50.2	SAMPLING METHOD FOR ALL OTHER DIMENSIONS & REQUIREMENTS: ZO SQUEGLIA, INDEX VALUE 2.5%. PER PS-TILDOCS#172373. ACCEPTANCE CRITERIA: ZERO NONCONFORMITY.					
50.3	100% INSPECTION OF * MARKED DIMENSIONS AND/OR PARAMETERS.					
50.4	NUMBER OF * MARKED DIMENSIONS AND/OR PARAMETERS IS:4					
60	INSPECTION VERIFICATION BY CUSTOMER'S REPRESENTATIVE					
70	SURFACE TREATMENT:					
70.1	STAINLESS STEEL PASSIVATION TREATMENT PER PS-111.21 (RAFDQCS-434847)					
80	PAINTING					
80.1	DO NOT PAINT THE MARKED (— — — — —) SURFACES					
80.2	PRIMER PAINTING APPLY 1 LAYER OF PRIMER COAT-EPOGAL COATING, EPOXY PRIMER FOR GALVANIZED STEEL, TAMBOUR CODE No. 649-050 OR EQUIVALENT PRIMER COATING APPROVED BY RAFAEL POC.					
80.3	INTERMEDIATE COAT PAINTING APPLY TWO LAYERS OF COATING OF EPOXY POLYAMIDE ACCORDING TO MIL-PRF-22750					
80.4	TOP COAT PAINTING APPLY TWO LAYERS OF POLYURETHANE TOP COAT ACCORDING TO MIL-C-83286 OR MIL-PRF-85285. TOP COAT COLOUR ACCORDING TO FED-STD-595C-36081					
80.5	TOTAL PAINT THICKNESS TOTAL THICKNESS OF DRY COAT OF PAINT: 150-230 MICRON					
90	INSPECTION VERIFICATION BY CUSTOMER'S REPRESENTATIVE					
100	ATTACHMENT OF C.O.C AND OTHER DOCUMENTS SPECIFIED IN THE PURCHASE ORDER					
110	PACKING FOR SHIPMENT PER PS-38-576104					

TOLERANCES UNLESS OTHERWISE SPECIFIED		CAGE CODE 1931A	ID	SIGNATURE	RAFAEL  COPYRIGHT PROTECTED © TITLE DESICCANT BODY PN RZIC9301A SEE EDR 1 1 DRAWING NO 30-044515 SIZE A2 REV F		
OVER	INCL	DESIGNED	n6nm	DIGITALLY SIGNED DATE: 2025-03-20 RELEASED FOR PRODUCTION			
0	6 ±0.1	DESIGNED					
6	30 ±0.2	CHECKED	n6aw				
30	120 ±0.3	CHECKED	n6mo				
120	315 ±0.5	APPROVED					
315	1000 ±0.8	APPROVED	n6mo				
Angles ±1°							
SURFACE TEXTURE  Ra3.2		SCALE 1:2	CLASS Unclassified				

