

A

B

C

D

ח"ג:שלנו
עד:

4X
32X
32X
32X
1ש
3ש
6ש
10ש

BLACK-T COATING ACC TO RC50.2

מחיר בי טי אי
1.375" * 75ממ 20 *
שח ליח 90

ציפוי

SCALE 1:1

SCALE 1:1

MARKING ACC TO RC60

מחיר ציפוי אגמים:
פסיבציה+מיסוך+קסילן 1427 מחיר יחידה 95 ש"ח ליח

THIS DOCUMENT CONTAINS VALUABLE PROPRIETARY TO RAFAEL.
THE RECIPIENTS OF THIS DOCUMENT SHALL NOT DISCLOSE ITS CONTENTS IN
WHOLE OR IN PART TO ANY THIRD PARTY UNLESS OTHERWISE AGREED BY RAFAEL.

UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS
ARE IN MILLIMETERS. INTERPRET DRAWING
ACCORDING TO RAFAEL PROCEDURE 18.00.10

REVISIONS			
REV	DESCRIPTION	ECN	ID
A	RELEASED		shayre
			24-Dec-2025

PRODUCTION ROUTING CHART				
No.	DESCRIPTION	OPER DATE		
10	GENERAL INSTRUCTIONS			
10.1	THIS DRAWING SHALL BE USED WITH ITS MODEL FOR COMPLETE PRODUCT DEFINITION			
10.2	DIMENSIONAL LIMITS APPLY AFTER SURFACE TREATMENT UNLESS OTHERWISE SPECIFIED			
20	MATERIAL			
	DESCRIPTION	CAT.NO.	QTY	UM
20.1	STAINLESS STEEL PH15-5-SOL. H.T ROUND ROD L=144. D=1.25 INCH AIRCRAFT, GEN_1111-1, AMS 5659	5101586192	0.432	KG
20.2	OPTIONAL MATERIAL: STAINLESS STEEL PH15-5-SOL. H.T ROUND ROD L=144. D=1.5 INCH AIRCRAFT, GEN_1111-1, AMS 5659	5101586040	0	KG
20.3	OTHER SIZE AND/OR SHAPE OF SAME MATERIAL, GRADE AND THERMAL CONDITION IS APPROVED			
30	HEAT TREATMENT			
30.1	FINAL CONDITION H1025, PER PS 111.24 (RAFD0CS-14125690)			
40	MACHINING			
40.1	REMOVE BURRS ~0.3, UNLESS OTHERWISE SPECIFIED			
40.2	INNER RADII ~0.3, UNLESS OTHERWISE SPECIFIED			
50	SURFACE TREATMENT			
50.1	STAINLESS STEEL PASSIVATION TREATMENT PER PS-111.21 (RAFD0CS-434847)			
50.2	MASK SURFACES ACC. TO DRAWING			
50.3	PROPRIETARY CORROSION RESISTANCE ORGANIC COATING (BLACK T/KAL GARD) 8-12 μm THICK PER PS-111.22 (RAFD0CS-10844074)			
60	MARKING			
60.1	PART MARKING, METHOD: LASER, CHARACTERS HEIGHT: 5 mm			
60.2	Z= FIRST LETTER OF THE MANUFACTURER CODE, YYYY-WW= YEAR-WEEK, LXX= LOT NUMBER, CHARACTERS HEIGHT: 5 mm			
60.3	ANY OTHER MARKING METHOD IS APPROVED SUBJECTED TO CUSTOMER APPROVAL			
70	INSPECTION			
70.1	VISUAL INSPECTION			
70.2	100% INSPECTION OF ALL DIMENSIONS			
70.3	ACTUAL RESULTS TO BE REPORTED			
80	FINAL APPROVAL			
80.1	VISUAL INSPECTION & VERIFICATION OF DOCUMENTS			
80.2	SERVICEABILITY TAG			
90	PACKING			
90.1	PACKING SHALL PREVENT CORROSION AND PHYSICAL DAMAGE DURING PROCESS, STORAGE AND SHIPMENT			

TOLERANCES UNLESS OTHERWISE SPECIFIED	CAGE CODE 1931A	ID	SIGNATURE	RAFAEL COPYRIGHT PROTECTED ©		
HOLES POSITION ⌀0.20 A B C	DESIGNED	ROEIDE	DIGITALLY SIGNED DATE: 2025-12-24 RELEASED FOR PRODUCTION	TITLE		
SURFACE PROFILE 0.3 A B C	DESIGNED			FFT TIGHT GIG LOCK		
HOLES +0.10 -0.03	CHECKED	baumd		PN	SEE EDR	SHT OF
	CHECKED			BP26371A		1 1
	APPROVED					
	APPROVED	shayre				
SURFACE TEXTURE Ra1.6	SCALE 2:1	CLASS Unclassified		DRAWING NO BP26371A	SIZE A3	REV A