

KNUST Research Proposal 2026 Final

Job #: PF-2026-000481 • Customer: Dr. Michael Adjei

PRINT OPERATOR PRE-FLIGHT SPECIFICATIONS

Paper Size: A4 | Color Mode: COLOR | Sidedness: double-sided
Binding: SPIRAL | Copies: 3 | Order Total: GHS 168.00



1. Document Overview & Pre-Print Requirements

- This document has been verified for production printing through the PrintFlow platform.
- Please verify margins, typography baseline alignments, and graphic asset color reproduction.
- Digital high-speed laser printing requires adequate binding gutters (minimum 12mm on inner binding edge).
- Operators can inspect this preview in both full-color and grayscale monochrome laser simulation.
- Ensure that paper stock, weight (e.g. 80gsm bond), and finishing machine are loaded before starting job.

Safe Spine Gutter

Section 2: Content Verification & Production Details

Certified Template & Layout Proofing (Page 2 of 8)

The operational parameters specified for this document order mandate rigorous consistency across all 8 pages.

Every page layout has been formatted with standard ISO 216 A4 boundaries (210mm x 297mm).

Digital rasterization guarantees that vector artwork, mathematical typography, and photographic figures remain sharp.

Quality assurance verification confirms that double-sided duplex page numbering alternates correctly.

Ensure that the high-speed laser toner density is calibrated to prevent bleed-through on lightweight stock.

Pre-flight Verification Parameter Table

Resolution: 600 DPI Vector | Toner: CMYK High Contrast | Finishing: Heat Press Bonded

Section 3: Content Verification & Production Details

Certified Template & Layout Proofing (Page 3 of 8)

The operational parameters specified for this document order mandate rigorous consistency across all 8 pages.

Every page layout has been formatted with standard ISO 216 A4 boundaries (210mm x 297mm).

Digital rasterization guarantees that vector artwork, mathematical typography, and photographic figures remain sharp.

Quality assurance verification confirms that double-sided duplex page numbering alternates correctly.

Ensure that the high-speed laser toner density is calibrated to prevent bleed-through on lightweight stock.

Pre-flight Verification Parameter Table

Resolution: 600 DPI Vector | Toner: CMYK High Contrast | Finishing: Heat Press Bonded

Section 4: Content Verification & Production Details

Certified Template & Layout Proofing (Page 4 of 8)

The operational parameters specified for this document order mandate rigorous consistency across all 8 pages.

Every page layout has been formatted with standard ISO 216 A4 boundaries (210mm x 297mm).

Digital rasterization guarantees that vector artwork, mathematical typography, and photographic figures remain sharp.

Quality assurance verification confirms that double-sided duplex page numbering alternates correctly.

Ensure that the high-speed laser toner density is calibrated to prevent bleed-through on lightweight stock.

Pre-flight Verification Parameter Table

Resolution: 600 DPI Vector | Toner: CMYK High Contrast | Finishing: Heat Press Bonded

Section 5: Content Verification & Production Details

Certified Template & Layout Proofing (Page 5 of 8)

The operational parameters specified for this document order mandate rigorous consistency across all 8 pages.

Every page layout has been formatted with standard ISO 216 A4 boundaries (210mm x 297mm).

Digital rasterization guarantees that vector artwork, mathematical typography, and photographic figures remain sharp.

Quality assurance verification confirms that double-sided duplex page numbering alternates correctly.

Ensure that the high-speed laser toner density is calibrated to prevent bleed-through on lightweight stock.

Pre-flight Verification Parameter Table

Resolution: 600 DPI Vector | Toner: CMYK High Contrast | Finishing: Heat Press Bonded

Section 6: Content Verification & Production Details

Certified Template & Layout Proofing (Page 6 of 8)

The operational parameters specified for this document order mandate rigorous consistency across all 8 pages.

Every page layout has been formatted with standard ISO 216 A4 boundaries (210mm x 297mm).

Digital rasterization guarantees that vector artwork, mathematical typography, and photographic figures remain sharp.

Quality assurance verification confirms that double-sided duplex page numbering alternates correctly.

Ensure that the high-speed laser toner density is calibrated to prevent bleed-through on lightweight stock.

Pre-flight Verification Parameter Table

Resolution: 600 DPI Vector | Toner: CMYK High Contrast | Finishing: Heat Press Bonded

Section 7: Content Verification & Production Details

Certified Template & Layout Proofing (Page 7 of 8)

The operational parameters specified for this document order mandate rigorous consistency across all 8 pages.

Every page layout has been formatted with standard ISO 216 A4 boundaries (210mm x 297mm).

Digital rasterization guarantees that vector artwork, mathematical typography, and photographic figures remain sharp.

Quality assurance verification confirms that double-sided duplex page numbering alternates correctly.

Ensure that the high-speed laser toner density is calibrated to prevent bleed-through on lightweight stock.

Pre-flight Verification Parameter Table

Resolution: 600 DPI Vector | Toner: CMYK High Contrast | Finishing: Heat Press Bonded

Section 8: Content Verification & Production Details

Certified Template & Layout Proofing (Page 8 of 8)

The operational parameters specified for this document order mandate rigorous consistency across all 8 pages.

Every page layout has been formatted with standard ISO 216 A4 boundaries (210mm x 297mm).

Digital rasterization guarantees that vector artwork, mathematical typography, and photographic figures remain sharp.

Quality assurance verification confirms that double-sided duplex page numbering alternates correctly.

Ensure that the high-speed laser toner density is calibrated to prevent bleed-through on lightweight stock.

Pre-flight Verification Parameter Table

Resolution: 600 DPI Vector | Toner: CMYK High Contrast | Finishing: Heat Press Bonded